



CERAMIC TILE INSTALLATION PRODUCT GUIDE



SURFACE PREPARATION

MEMBRANES

THIN SETS/MORTARS

ADHESIVES/MASTICS

GROUTS/EPOXIES

ADMIXTURES

SPECIALTY ITEMS



LEED® Compliant Products



Performance.



It starts with installation. In the flooring industry complete satisfaction is the sum of many parts, but integrity and quality will always shoulder a majority of the burden. By using Bostik's Durabond products you're well on your way to ensuring your customers' satisfaction. The rest is up to you.



Each product displaying Bostik's Blockade™ antimicrobial protection logo contains an agent which inhibits the growth of bacteria, mold, or mildew on the surface of the dried adhesive/membrane; the dried adhesive/membrane resists stains caused by mold. To obtain specific test information by product, please contact Bostik's Technical Service Department at 1-800-523-6530.




TABLE OF CONTENTS

Surface Preparation	2
Membranes	3
Thin Sets/Mortars	4-7
Mastics	8
Grout/Epoxies.....	9-11
Admixtures/Specialty	11
Accessories/Displays	12
Warranty	IBC



Our Green Mission

As a global leader in adhesives, coatings and sealant technologies, Bostik continuously strives to commercialize products that minimize environmental impact and promote the health and well being of our customers. Bostik shall demonstrate these objectives by achieving compliance with the most rigorous standards set forth by industry recognized green building authorities.

Many of the products featured in this catalog are LEED® compliant.

For a complete list of Bostik Construction Products that

could contribute to LEED credits, email us at

contactus@bostik-us.com - Subject: VOC Product Portfolio

or visit us at www.greenmission.bostik-us.com.



Bostik is a global company with over 4,000 employees and 48 production facilities across five continents. Bostik's parent company is Total, a 193 billion dollar multi-national company.

SURFACE PREPARATION



DURALEVEL® 83P

SELF LEVELING
UNDERLAYMENT



DURALEVEL® 83P is a high compressive strength, self-leveling, cement-based underlayment used to repair, smooth and level concrete as well as existing ceramic, terrazzo, or approved plywood sub floors prior to the installation of carpet, vinyl, VCT, laminate, solid and engineered hardwood flooring, ceramic or natural stone. DURALEVEL 83P is suitable for thicknesses from featheredge to 1" thick, or up to 5" thick when mixed as designed with pea gravel. Use on, above or below grade. Use DURALEVEL 83P in smaller installations where it may be mixed by hand, or underlayment pump to quickly cover large jobs.

Packaging:

50 lb. bags, Item #D63210-83P,

UPC#747224631206

Volatile Organic Compounds: 0 g/l



WEBCRETE® 98

PREMIUM PORTLAND
CEMENT PATCH



WEBCRETE® 98 is a premium fast-setting, latex-fortified Portland cement patch for interior use. WEBCRETE 98 may be used to skim coat or feather edge finishes up to 1/2" deep in one application. Floor covering can be installed in as little as an hour after application. WEBCRETE 98 is extremely flexible and resilient for use to patch and smooth floors prior to the installation of ceramic tile, carpet, resilient and wood flooring. The high concentration of polymer in Webcrete 98, enables the use of this product as an embossing leveler when mixed only with water.

Packaging:

25# bags, Item# D63158-952, UPC#74722463189

Volatile Organic Compounds: 0 g/l



WEBCRETE® 95

PORTLAND CEMENT
PATCH



WEBCRETE® 95 is a fast-setting, latex-fortified Portland cement patch for interior use. WEBCRETE 95 may be used to skim coat or feather edge finishes up to 1/2" deep in one application. Floor covering can be installed in as little as an hour after application. WEBCRETE 95 is extremely flexible and resilient for use to patch and smooth floors prior to the installation of ceramic tile, carpet, resilient and wood flooring. When mixed with DL-16 instead of water, not only is the performance and flexibility improved, but WEBCRETE® 95 can also be used as an embossing leveler.

Packaging:

25# bags, Item# D63168-952, UPC#747224630506

40 lb. Pail, Item#D63170, UPC# 747224631701

Volatile Organic Compounds: 0 g/l



ULTRAFINISH™

PREMIUM PORTLAND
CEMENT PATCH



Bostik ULTRAFINISH™ is a fast-setting, latex-fortified, Portland cement-based patch for interior use. This product may be used to skim coat or feather-edge up to 1" deep in one application. Floor Covering can be installed typically in as little as 15-20 minutes over concrete, wood, ceramic, and quarry tile without the requirement of priming or the use of a liquid additive. When mixed with Durabond D-L16 High Strength Additive instead of water, ULTRAFINISH can be used as an embossing leveler.

Packaging:

10# bags, Item# D00130, UPC#747224001306

Volatile Organic Compounds: 0 g/l



Product	Description	Substrates
D-222 DuraGuard™	Antifracture and Waterproofing Membrane	1,2,3,4,5,9
83P DuraLevel®	Self Leveling Underlayment	1,2,4,5,7
Webcrete® 95	Portland Cement Patch	1,2,4,5,6,7
Webcrete® 98	Portland Cement Patch	1,2,4,5,6,7
UltraFinish	Portland Cement Patch	1,2,4,5,6,7

Legend: Substrates

1. Plywood
2. Concrete
3. Gypsum Wallboard
4. Cementitious Backer Units
5. Properly Prepared Ceramic Tile

6. Properly Prepared Vinyl/VCT tile
7. Cutback Residue (interior dry only)
8. Clean Steel
9. Mortar Beds

UNIVERSAL PRIMER

PRIMER




Universal Primer is designed for use with DURALEVEL 83P Self Leveling Underlayment. Use over concrete, approved plywood substrates, cement backer board, ceramic tile, marble, granite and terrazzo.

Packaging:

20# bags, Item# D00130, UPC#747224001306

Volatile Organic Compounds: 0 g/l

WATERPROOFING /ANTI-FRACTURE MEMBRANES



WALL CONSTRUCTED OF CEMENT BOARD/GYPSUM BOARD/CEMENT BLOCK

D-222 DURAGUARD™ MEMBRANE

LATEX ANTI-FRACTURE & WATERPROOFING MEMBRANE

D-222 DuraGuard™ is a ready to use, latex waterproofing and antifracture membrane for use beneath thin set ceramic tile installations on vertical and horizontal surfaces. Use D-222 DuraGuard in commercial or residential applications. Apply over concrete, cement block walls, cement backer board, gypsum board, exterior grade plywood (interior, dry installations only) and mortar beds. Dries in one to three hours. Cleans up with water.

Packaging:

3.5 gallon pails, Item # D08800-KH, UPC#747224088031

4 x 1 gallon pails, Item # D08800-KL, UPC#747224088017

Volatile Organic Compounds: 12.5 g/l



ANSI A118.10

ANSI A118.12



THIN SET/MORTARS



NEW! D-65™ High Performance & Non-Sag Mortar

- Excellent for large bodied tile and stone in vertical applications
- Exceeds ALL Requirements on ANSI A118.1, A118.4, and A118.11
- Excellent for use on all approved floors and walls
- For interior and exterior jobs
- High compressive strengths for extra heavy service

Product	Description	Tile Types
<i>D-70™ ProFlex</i>	High Performance	ABCDEFH
<i>D-65™ High Performance & Non Sag</i>	High Performance & Non-Sag	ABCDEFH
<i>D-60™ Medium Set</i>	Premium Latex Modified Medium Set	ABCDEFH
<i>D-55™ Fast Set</i>	Premium Latex-Modified Fast Setting	ABCDEFH
<i>D-50™ Flexible</i>	Premium Latex-Modified	ABCDEFH
<i>D-40™ DuraFlex</i>	Multi-Purpose Latex Modified	ABCDEFH
<i>D-25™ Ditra-Set</i>	Premium Thin Set	ABCDEFH
<i>D-20™ Porcelain Set</i>	Porcelain Set	ABCDEFH
<i>D-5™ Premium</i>	mixed with DL-16	ABCDEFH
	mixed with water	ABCDEFH
<i>D-2™ Floor Grade</i>	mixed with DL-16	ABCDEFH
	mixed with water	ABCDEFH

Durabond® brand latex-modified thin set mortars incorporate state-of-the-art dry polymers and adhesion promoting agents for outstanding bonds with virtually all ceramic and natural stone tile. Just add water and mix. All Durabond® latex mortars are recommended for interior/exterior use over a wide variety of substrates.

D-70™ PROFLEX® HIGH PERFORMANCE MORTAR

D-70™ Proflex Mortar is a high performance, extremely flexible, multipurpose latex-modified thin set mortar, used for interior or exterior installations to set porcelain, glass, ceramic, granite, slate, marble, limestone and dimension stone tiles. Use over properly prepared concrete; structurally-sound, exterior grade plywood (interior/dry use only); cementitious backer board; DURABOND® D-222 DuraGurad™; existing well-bonded vinyl/VCT or ceramic tile; cutback adhesive residue (dry only) and floors equipped with radiant heat.

- Excellent non sag working characteristics for vertical jobs
- Can withstand deflection up to L/240.

Packaging: 50 lb. bags

White: Item# D07010-7F2, UPC#747224070104

Gray: Item# D07020-7F2, UPC#747224070203

Volitile Organic Compounds: 0 g/L



D-65™ HIGH PERFORMANCE & NON-SAG MORTAR

D-65™ is for interior or exterior, commercial or residential installations to set all types of porcelain, Saltillo, ceramic, granite, slate, marble, limestone, dimension stone and glass tiles. D-65 is formulated to prevent large bodied ceramic, porcelain and stone tiles from slipping in vertical applications. D-65 is also suitable for installing floor tiles. Use over properly prepared concrete; structurally-sound, exterior grade plywood (interior/dry use only); cementitious backer board; DURABOND D-222™; existing well-bonded vinyl/VCT or ceramic tile; cutback adhesive residue (dry only) and floors equipped with radiant heat.

- Excellent non sag working characteristics for vertical jobs
- Can withstand deflection up to L/240.

Packaging: 50 lb. bags

White: Item# D06500, UPC#747224065001

Volitile Organic Compounds: 0 g/L

ANSI A118.4
ANSI A118.11



ANSI A118.4
ANSI A118.11



Substrates	Final Set	Porcelain Tile	Glazed Wall Tile	Quarry Tile	Quarry Tile/ Wood	28 Day Compressive Strength	Specifications
1,2,3,4,5,6,7	10-15 Hours	576 psi	560 psi	425 psi	300 psi	3600 psi	ANSI A118.4 & A118.11
1,2,3,4,5,6,7	10-15 Hours	575 psi	550 psi	425 psi	300 psi	3403 psi	ANSI A118.4 & A118.11
1,2,3,4,5,6,7	10-15 Hours	375 psi	557 psi	300 psi	250 psi	3400 psi	ANSI A118.4 & A118.11
1,2,3,4,5,6,7	60-90 Minutes	490 psi	500 psi	400 psi	250 psi	3100 psi	ANSI A118.4 & A118.11
1,2,3,4,5,6,7	15 Hours	450 psi	450 psi	440 psi	250 psi	3450 psi	ANSI A118.4 & A118.11
1,2,3,4,5,6,7	15 Hours	400 psi	443 psi	300 psi	200 psi	3000 psi	ANSI A118.4 & A118.11
1,2,3,4,5,6	12 Hours	250 psi	300 psi	225 psi	N/A	3200 psi	ANSI A118.1, A118.4* & A118.11*
2,4	12 Hours	250 psi	300 psi	225 psi	N/A	3200 psi	ANSI A118.1 & ANSI A118.4
1,2,3,4,5,6	9 Hours	470 psi	504 psi	370 psi	175 psi	3300 psi	ANSI A118.1, A118.4 & A118.11
1,2,3,4,5,6	12 Hours	200 psi	300 psi	225 psi	N/A	3200 psi	A118.1
1,2,3,4,5,6	9 Hours	420 psi	515 psi	400 psi	175 psi	3200 psi	ANSI A118.1, A118.4 & A118.11
1,2,3,4,5,6	12 Hours	200 psi	280 psi	215 psi	N/A	3100 psi	A118.1

Legend: Tile Types

- A. Non-Vitreous
- B. Semi-Vitreous
- C. Vitreous
- D. Impervious/Porcelain
- E. White Translucent Marble
- F. Granite, Sable Stones, Slate

- G. Moisture Sensitive Stone (i.e. Russo LeVanto and Nero Marquina Marble or Green Marble and their Agglomerates.
- H. Large Ceramic Tile, Stable Stone and Granite

Legend: Substrates

- 1. Plywood
- 2. Concrete
- 3. Gypsum Wallboard
- 4. Cementitious Backer Units
- 5. Properly Prepared Ceramic Tile
- 6. Properly Prepared Vinyl/VCT tile

- 7. Cutback Residue (interior dry only)
- 8. Clean Steel

*when mixed with Durabond D-L16 High Performance Admixture

D-60™ MEDIUM SET

PREMIUM LATEX-MODIFIED MORTAR

60™ Medium-Set is a premium latex-modified, medium-set mortar used for interior or exterior installations to set all large-sized ceramic, porcelain, granite, slate, marble, limestone, and dimension stone tiles. Use over properly prepared concrete; structurally-sound, exterior grade plywood (interior/dry use only); cementitious backer board; D-222™; and existing, well-bonded vinyl/VCT or ceramic tile.



- Helps prevent lippage between large tiles
- Use from 1/8" to 3/4" thick
- Use for all tile and stone (except moisture sensitive marble)

Packaging: 50 lb. bags.

White: Item# D70050-UT2, UPC# 747224700506

Gray: Item# D70040-UT2, UPC# 747224700407

Volatile Organic Compounds: 0 g/l

ANSI A118.4
ANSI A118.11



D-55™ FAST SET

PREMIUM LATEX-MODIFIED MORTAR

D-55 Fast-Set is a premium, latex-modified, fast-setting mortar used for interior or exterior installations to set ceramic, porcelain, granite, slate, marble, limestone, and dimension stone tiles. Use over properly prepared concrete; structurally-sound exterior grade plywood (interior/dry use only); cementitious backer board; D-222™ Duraguard; and existing, well-bonded vinyl/VCT or ceramic tile.



- Use where down time must be minimized
- Use as a fast-setting "thin set" or "medium-bed"
- Set and Grout in the same day
- Mix with D-L16 for premium setting characteristics

Packaging: 50 lb. bags.

White: Item# D63176-UT6, UPC#747224631763

Gray: Item# D63178-UT6, UPC#747224631787

Volatile Organic Compounds: 0g/l

ANSI A118.4
ANSI A118.11



THIN SET/MORTARS

Latex Modified Thin Sets (add water only)

D-50™ FLEXIBLE

PREMIUM LATEX-MODIFIED MORTAR

D-50™ is used for interior or exterior installations to set ceramic, porcelain, granite, slate, marble, limestone, and dimension stone tiles. Use over properly prepared concrete; structurally-sound, exterior grade plywood (interior/dry use only); cementitious backer board; D-222™ Duraguard; and existing, well-bonded vinyl/VCT or ceramic tile.

- Excellent open time and workability

Packaging: 50 lb. bags

White: Item# D63141-UT6, UPC# 747224631411

Gray: Item# D63140-UT6, UPC# 747224631404

Volatile Organic Compounds: 0 g/l

ANSI A118.4
ANSI A118.11



D-40 DURAFLEX™

MULTI-PURPOSE LATEX-MODIFIED MORTAR

40™ DuraFlex™ is a multi-purpose latex-modified mortar used for interior or exterior installations to set ceramic, porcelain, granite, slate, marble, limestone, and dimension stone tiles. Use over properly prepared concrete; structurally-sound, exterior grade plywood (interior/dry use only); cementitious backer board; D-222™ Duraguard and existing, well-bonded vinyl/VCT or ceramic tile.

Packaging: 50 lb. bags

White: Item# D62884-UT4, UPC# 747224628848

Gray: Item# D62889-UT4, UPC# 747224628893

Volatile Organic Compounds: 0 g/l

ANSI A118.4
ANSI A118.11



Durabond® brand thin set mortars are designed for basic tile installations. When used with a Durabond® D-L16 High Performance latex mortar additive, provide enhanced bond strength to meet ANSI A118.4 specifications.

D-25 DITRA-SET™

PREMIUM THIN SET


D-25 DitraSet™ Thin-Set Mortar is composed of select, proprietary chemicals, carefully graded aggregates, inorganic adhesion promoters, and purified cements. It provides outstanding workability, excellent durability, and superior bond strengths in interior and exterior applications when used in conjunction with the Schluter®-DITRA uncoupling membrane and Schluter®-KERDI waterproofing membrane. Use D-25 DitraSet™ to install the membranes over substrates approved by Schluter®-Systems and to set ceramic, porcelain, and stone tile over Schluter®-DITRA and Schluter®-KERDI.

Packaging: 50 lb. bags

White: Item# D62825-D25, UPC# 747224628251

Volatile Organic Compounds: 0 g/l

ANSI A118.1
ANSI A118.4
ANSI A118.11



D-20™ PORCELAIN SET

MORTAR

D-20™ Porcelain Set is for interior or exterior installations to set all types of ceramic, porcelain, granite, slate, marble, limestone, and dimension stone tiles. Use over properly prepared concrete, cement backer board, cured mortar beds, brick cement block and D-222 Duraguard.



- Excellent open time and workability
- Use for porcelain, ceramic or stone tile

Packaging: 50 lb. bags.

White: Item# D01769-D20, UPC# 747224019691

Gray: Item# D01969-D20, UPC# 747224019697

Volatile Organic Compounds: 0 g/l

ANSI A118.4
ANSI A118.11



D-5™ PREMIUM

MORTAR

D-5 Premium Thin Set Mortar is for interior or exterior installations to set all types of ceramic, porcelain, granite, slate, marble, limestone, and dimension stone tiles. Use over properly prepared concrete, structurally-sound exterior grade plywood (interior/dry use only); cementitious backer board; Durabond D-222™* and existing, well bonded vinyl/VCT or ceramic tile.



- Suitable for exterior when mixed with D-L16™ Admixture.

Packaging: 50 lb. bags.

White: Item# D63292-UT3, UPC# 747224632920

Gray: Item# D63296-UT3, UPC# 747224632968

Volatile Organic Compounds: 0 g/l

* D-5 used over D-222™ must be mixed with D-L16™

ANSI A118.1
ANSI A118.4
ANSI A118.11



D-2™ FLOOR GRADE

MORTAR

D-2™ Floor Grade Thin-Set Mortar is for interior or exterior installations to set all types of ceramic, porcelain, granite, slate, marble, limestone, and dimension stone tiles. Use over properly prepared concrete, structurally-sound, exterior grade plywood (interior/dry use only); cementitious backer board, D-222™* and existing, well-bonded vinyl/VCT or ceramic tile.



Packaging: 50 lb. bags.

White: Item# D63270-UT7, UPC# 747224632708

Gray: Item# D63275-UT7, UPC# 747224632753

Volatile Organic Compounds: 0 g/l

* D-2 used over D-222™ must be mixed with D-L16™

ANSI A118.1
ANSI A118.4
ANSI A118.11



MASTIC/ADHESIVES



Durabond® brand adhesives are advanced formulations that provide superior bondstrength. For residential to commercial applications, Durabond "Type 1" tile adhesives can handle the demands of even large, heavy tile and stone. Applications include most any interior wall or ceiling surface subjected to limited water exposure, such as tub surrounds, bathrooms, and tile walls.



D-2001™ MULTI-PURPOSE

America's #1, superior performance, contractor preferred, "RED BUCKET" mastic. Use for installations of ceramic tile and natural stone tile on interior walls and floors. Best performing on areas with intermittent water exposure.

- Excellent sag resistance
- Easy to trowel
- For residential and commercial construction as well as intermittent water exposure
- Use for large red & white body ceramic tiles
- Excellent for most marble

Packaging:

3.5 gallon - Item# D60483, UPC# 747224604835

4 x 1 gallon containers- Item# D60396, UPC# 747224606968

6 x 1 quart containers - Item# D60483, UPC# 747224603258

Volatile Organic Compounds: 123 g/l

ANSI A136.1



D-1001™ FLOOR & WALL

Use for installation of ceramic tile and natural stone tile on interior walls and floors.

- Excellent sag resistance
- Easy to trowel
- For residential and commercial construction as well as intermittent water exposure
- Use for large red & white body ceramic tiles
- Excellent for most marble

Packaging:

3.5 gallon - Item# 60658, UPC# 747224606587

4 x 1 gallon containers- Item# D60656, UPC# 747224606563

12 x 1 quart containers - Item# D60654, UPC# 747224606549

Volatile Organic Compounds: 123 g/l

ANSI A136.1



D-501™ PROFESSIONAL GRADE

Use for installations of ceramic tile, and natural stone tile on interior walls and floors.

- Excellent sag resistance
- Easy to trowel
- For residential and commercial construction as well as intermittent water exposure

Packaging:

3.5 gallon - Item# 60282, UPC# 747224602824

Volatile Organic Compounds: 123 g/l

ANSI A136.1



GROUTS/EPOXIES



**Consistent
Color
Every Time**

**Crack
Resistant
Flexibility**

**No Sealing
Ever**

Ready to Use

TRUCOLOR™ PRE-MIXED GROUT

Bostik TruColor™ Pre-Mixed Grout is a patented, water-based, urethane grout offering the ultimate in color accuracy, stain protection and crack resistance for residential and commercial tile installations. This breakthrough formulation installs up to 50% faster than traditional grouts, and never needs to be sealed. Its perfect balance of flexibility and toughness enables it to exhibit unmatched performance and crack resistance. TruColor exceeds the grout-relevant portion of the ANSI A118.3 epoxy standard (modified ANSI 118.3-UG)

Available colors: White D-G01, Bone D-G19, Birch D-G50, Oyster D-G03, Biscuit D-G14, Driftwood DG-16, Coffee D-G28, Haystack D-G07, Sycamore D-G45, Camel D-G21, Walnut D-G15, Sandcastle D-G04, Acorn D-G47, Chocolate D-G10, Steel D-G22, Natural D-G02, Ocean Gray D-G05, Cobblestone D-G44, Storm Gray D-G06, Jet Black D-G08

(see previous page for color reference)

ANSI A118.3 UG



Packaging: 18 lb. & 9 lb. Pails

Volatile Organic Compounds: 35 g/l

Tile Size (inches)	Joint width					
	1/16"	1/8"	3/16"	1/4"	3/8"	1/2"
1" x 1" x 1/4"	63	32	-	-	-	-
2" x 2" x 1/4"	126	63	-	-	-	-
4 1/4" x 4 1/4" x 3/16"	214	107	71	54	36	27
4" x 8" x 1/2"	168	84	56	42	28	21
6" x 6" x 1/2"	189	95	63	47	32	24
8" x 8" x 3/8"	337	168	112	84	56	42
12" x 12" x 3/8"	505	253	168	126	84	63
13" x 13" x 3/8"	547	274	182	137	91	68
16" x 16" x 3/8"	673	337	224	168	112	84
18" x 18" x 3/8"	758	379	253	189	126	95
24" x 24" x 3/8"	1010	505	337	253	168	126

Tile Size (inches)	Joint width					
	1/16"	1/8"	3/16"	1/4"	3/8"	1/2"
1" x 1" x 1/4"	32	16	-	-	-	-
2" x 2" x 1/4"	63	32	-	-	-	-
4 1/4" x 4 1/4" x 3/16"	107	54	36	27	18	13
4" x 8" x 1/2"	84	42	28	21	14	11
6" x 6" x 1/2"	95	47	32	24	16	12
8" x 8" x 3/8"	168	84	56	42	28	21
12" x 12" x 3/8"	253	126	84	63	42	32
13" x 13" x 3/8"	274	137	91	68	46	34
16" x 16" x 3/8"	337	168	112	84	56	42
18" x 18" x 3/8"	379	189	126	95	63	47
24" x 24" x 3/8"	505	253	198	126	84	63

EzPox [™] Grout Coverage					
Tile Size	Pounds per 100 Square Feet				
	Joint Width				
	1/16"	1/8"	1/4"	3/8"	1/2"
1" x 1" x 1/4"	28	50	85	110	130
2" x 1" x 1/4"	21	39	67	90	109
2" x 2" x 1/4"	14	26	50	68	85
3" x 3" x 1/4"	10	19	35	50	62
4" x 4" x 1/4"	8	14	26	39	50
4" x 4" x 3/8"	11	21	41	57	74
4" x 4" x 1/2"	14	28	54	77	109
4" x 8" x 3/8"	9	17	31	44	57
4" x 8" x 1/2"	11	21	41	59	77
4" x 8" x 1 3/8"	28	50	85	110	130
6" x 6" x 3/8"	8	14	28	41	52
6" x 6" x 1/2"	10	19	36	55	69
6" x 6" x 3/8"	6	11	21	31	40
6" x 6" x 3/4"	14	29	55	80	103
8" x 8" x 1/4"	4	8	14	21	26
8" x 8" x 3/8"	6	11	21	31	40
8" x 8" x 1/2"	8	14	29	51	54
10" x 10" x 3/8"	4	9	18	25	33
12" x 12" x 1/4"	3	6	10	14	19
12" x 12" x 3/8"	4	8	14	21	28
12" x 12" x 1/2"	6	10	19	29	37



**Easy to Apply!
Simple to Clean!**



EZPOXY™

100% SOLIDS EPOXY MORTAR & GROUT

EzPoxy™ is for interior or exterior, vertical or horizontal installations. Typical applications include commercial and residential kitchens, lobbies, bathrooms, fast food restaurants, breweries, wineries, factories, shopping malls, meat processors, and distilleries.

Available colors: Sycamore D-G45, Driftwood D-G16, Steel D-G22, Chocolate D-G10, Oyster D-G03, Platinum D-G23, Quarry Red D-G32, Jet Black D-G08, Storm Gray D-G06

(see previous page for color reference)

Packaging:

14 lb. Kit - Item# D60483, UPC# 747224604835

Volatile Organic Compounds: 0 g/l

ANSI A118.3



FORTIFIED TILE GROUT

SANDED

Use DURABOND Fortified Tile Grout (Sanded) for all types of ceramic mosaics, porcelain, granite, cultured marble, dimension stone and structural glazed tile where joint width is 1/8" to 1 1/2". Fortified Tile Grout is available in 40 popular colors.

- Exceeds ANSI A118.6 requirements
- Heavy duty, High compressive strength
- Latex fortified
- Fast-setting
- No shrinkage



Packaging: 25 lb bags and 4 x 9 lb bags

Volatile Organic Compounds: 0 g/l

FORTIFIED TILE GROUT

UNSANDED

Designed for grouting any type of tile or natural stone with joints up to 1/8". Fortified Tile Grout is available in 40 popular colors and is complimented by Ceramaseal Colored Tub and Tile Acrylic Latex Caulks (sanded & unsanded) as well as Grout Stain.

- Exceeds ANSI A118.6 requirements
- Interior/Exterior
- Fast setting
- Excellent Workability



Packaging: 25 lb bags and 6 x 5 lb bags

Volatile Organic Compounds: 0 g/l

FORTIFIED TILE GROUT /D-190 EPOXY						FORTIFIED TILE GROUT UNSANDED		
Tile Size	Pounds per 100 Square Feet						Joint Width	
	Joint Width						Joint Width	
	1/8"	3/16"	1/4"	3/8"	1/2"		1/16"	1/8"
1" x 1" x 1/4"	58	84	110	-	-		29	57
2" x 1" x 1/4"	44	67	83	-	-		22	43
2" x 2" x 1/4"	30	44	58	-	-		15	29
3" x 3" x 1/4"	20	30	39	-	-		10	20
4" x 4" x 1/4"	15	23	30	44	58		8	15
4 1/4" X 4 1/4" X 1/4	-	-	-	-	-		7	14
4" x 4" x 3/8"	-	-	-	-	-		11	22
4" x 4" x 1/2"	31	45	60	89	116		15	30
4" x 4" x 3/4	45	68	89	133	173		-	-
4" x 8" x 3/8"	17	26	34	50	65		9	17
4" x 8" x 1/2"	23	34	45	66	88		11	22
4" x 8" x 1 1/8"	-	-	-	-	-		26	50
4" x 8" x 1 3/8"	63	84	123	184	241		-	-
6" x 6" x 3/8"	15	23	30	45	59		8	15
6" x 6" x 1/2"	20	31	40	60	79		10	20
6" x 6" x 3/4"	31	46	60	91	118		15	30
8" x 8" x 1/4"	8	11	15	22	30		-	-
8" x 8" x 3/8"	11	17	23	34	45		6	11
8" x 8" x 1/2"	15	23	31	45	60		8	15
10" x 10" x 3/8"	9	14	18	27	36		4	9
12" x 12" x 1/4"	5	8	10	15	20		8	15
12" x 12" x 3/8"	8	11	15	23	31		-	-
12" x 12" x 1/2"	10	15	20	31	40		5	10
12" x 12" x 3/4"	-	-	-	-	-		8	15
16" X 16" X 1/2"	8	11	15	23	31		4	8
18" X 18" X 3/8"	-	-	-	-	-		3	5
18" X 18" X 1/2"	7	10	14	20	27		3	7
24" X 24" X 1/2"	5	8	10	15	20		3	5
24" x 24" x 3/8"	-	-	-	-	-		2	3

Complement your choice in tile or stone with Durabond Fortified Tile Grout (sanded and unsanded formulas).

Experience the Beauty of Durabond Grout

Complementary colors also available in CermaSeal® Tub & Tile Caulk & Grout Stain



White	D-021
Platinum	D-023
Wedgewood	D-027
Deep Blue	D-034
Blue Bayou	D-031
Castel Blue	D-033
Ocean Gray	D-088
Steel	D-023
Cobblestone	D-044
Storm Gray	D-086
Jet Black	D-088
Bone	D-019
Seashore	D-026
Adobe	D-048
Birch	D-050
Niccol	D-014
Driftwood	D-016
Oyster	D-083
Coffee	D-028
Sundance	D-048
Soapstone	D-048
Hazelnut	D-087
Sandcastle	D-084
Caramel	D-021
Acorn	D-047
Chocolate	D-016
Querry Red	D-033
Walnut	D-015
Natural	D-083
Mint	D-035
Reveries	D-038
Ginkgo	D-038
Buckskin	D-038
Forest Hills	D-043
Timber	D-024
Spencere	D-045
Chaparral	D-041
Reiter	D-040
Carnation	D-017
Rose Rouge	D-042

DURABOND®

D-190 DURAPOXY™

EPOXY MODIFIED GROUT AND MORTAR & ADMIXTURES

D-190 DuraPoxy™ Epoxy Modified Grout and Mortar Admixture when mixed with Durabond Fortified Tile Grout (sanded only), is for interior and exterior installations to set and/or grout all ceramic, porcelain, quarry, granite, slate, marble, limestone, and dimension stone tiles. Exceeds ANSI A118.8.

Packaging:

2 part kits containing Part A Resin and Part B Hardener

Item# D60658, UPC# 747224606587

Volatile Organic Compounds: 0 g/l



D-L16™

ACRYLIC LATEX ADMIXTURE

Designed as an admixture used instead of water for thin set and cement grouts. Provides improved shear bonds and compressive strengths, frost resistance and stain resistance. Use with Durabond® D-20, Durabond®, D-25 Durabond®, D-5 and Durabond® D-2 Thin Set Mortars for exterior installations, porcelain tile, over plywood sub floors or over D-222 Duraguard. Use with Fortified Tile Grouts to improve bond to porcelain tile, add flexibility as well as for installations in freeze thaw environments. D-L16 may also be used to prepare Portland cement bondcoats and mortar beds.

Packaging:

4 x 1 gallon jugs, Item# D60555-8K UPC#747224605559

Case UPC# 10747224605556

5 gallon pails Item# D60663-6C UPC#747224606634

Volatile Organic Compounds: 0 g/l



SPECIALTY

GROUT STAIN

This oil-based stain is used to restore the color of grout. Grout stain is also an excellent grout sealer. CeramaSeal Grout Stain is extremely durable product with excellent hiding power. Grout stain is available in all Durabond Colors (except Natural).

Packaging:

Pint Containers.

Volatile Organic Compounds: 541 g/l



TUB & TILE CAULK

This water cleanable caulking is available in sanded and unsanded formulas to complement most all Durabond Fortified Tile Grouts. Use in tub surrounds, countertops, walls, floors. Interior applications only.

Packaging:

12 x 10.1 oz cartridges

Volatile Organic Compounds: 20.8 g/l



PURE SILICONE CAULK

Pure Silicone Caulking from Bostik is a 100% RTV Curing Silicone Caulking which is waterproof and permanently flexible. Use Pure Silicone Caulking in tub surrounds to set drains, fixtures, and plumbing penetrations. Use as an adhesive or bedding compound for countertops, soap dishes and thresholds. Pure Silicone Caulking is highly chemical resistant and can withstand temperatures to 400° F.

Packaging:

12 x 10.1 oz cartridges

Clear: Item# G93201, UPC# Each - 747224932013, Case - 10747224932010

White: Item# G93202, UPC# Each - 747224932020, Case - 10747224932027

Volatile Organic Compounds: 32 g/l





DURABOND GROUT KITS: This display showcases the 40 vivid colors of Fortified Tile Grouts offered by Durabond in both sanded and unsanded formulas as well as 9 colors offered in Bostik EzPoxy™ 100% Solids Epoxy Grout & Mortar and 20 TruColor Pre-Mixed Grout* Colors. To obtain a Durabond® grout kit please contact us at 1-888-592-8558.

DURABOND GROUT DISPLAY BOX: This Counter Top, Point of Purchase Display Box, is designed to showcase the 40 vivid colors available in the Durabond Grout Line for both sanded/unsanded Fortified Tile Grout, 9 colors available in the EzPoxy™ 100% Solids Epoxy Grout series as well as the 20 colors offered in the TruColor™ Pre-Mixed Grout* line. Each slot holds 20 plastic channels for each grout color as well as 25 Durabond Grout Selector Cards. Great for dealer and distributor Showrooms. For more information on obtaining a Display Box contact your local Durabond Ceramic Territory Sales Manager.

* TruColor Grout Kits and Display boxes can be obtained by contacting your Bostik Sales Representative.



DURABOND CERAMIC INSTALLATION PRODUCTS DISPLAY BOARD:

This Point of Purchase Display Board is designed as a visual guide and offers product suggestions for common tile installations, applications and warranties. For more information on obtaining a Durabond Installation Display Board please contact us at 888-592-8558.

Durabond Ceramic Installation Products literature can be obtained by visiting us on the web at www.bostik-us.com and clicking on any one of the "ORDER LITERATURE" links or got to <http://bostik.doublediamondsoftware.com>.

DURABOND CERAMIC TILE INSTALLATION SYSTEM WARRANTY

Bostik, Inc. warrants the Durabond Ceramic Tile Installation System¹ will perform according to published specifications for period equal to “the flooring manufacturer’s product warranty” being installed on a prorated basis from date of substantial completion, not to exceed 10 years.

This warranty is exclusive to the purchaser of the products, may not be assigned, and is contingent upon the following:

- The evaluation of a potential claim by a Bostik, Inc. representative in advance of any replacement work.
- Products must be installed in accordance with applicable ANSI specifications and the most recent Durabond published literature.
- Submittal of flooring manufacturer’s warranty information, when applicable.

In the event of a valid claim under this warranty, Bostik, Inc. will pay material and labor for the costs associated with repairing or replacing the portion of the installation that is proven to be defective on a prorated, per square foot basis. Bostik, Inc. is not responsible for workmanship not in accordance with Durabond’s most recent published literature, damages due to hydrostatic head, losses due to delays or other consequential damages.

¹Durabond Ceramic Tile Installation System” includes the proper use of any of the following products:

Surface Preparation:	D-222 DuraGuard™, Webcrete® 95, Bostik UltraFinish, Duralevel® 83P/ Universal Primer
Mortars:	D-70 ProFlex™, D-60™ Medium Set, D-65™ High Performance & Non-Sag Mortar, D-55™ Fast Set, D-50™ Flexible Thin Set, D-40™ DuraFlex, D-25™ DitraSet, D-20™ Porcelain Set, D-5™ Premium, D-2™ Floor Grade
Admixtures:	D-L16™
Grouts:	Fortified Tile Grout (sanded), Fortified Tile Grout (unsanded), D-190 DuraPoxy™, Bostik® EzPoxy™, Bostik TruColor™ Pre-Mixed Grout



Your Partner in Flooring System Solutions



No sealing. No problem!

TruColor™ Grout, our premium, ready-to-use, pre-mixed product, is improving the quality and longevity of tile installations worldwide. It resists all types of stains including coffee, red wine, oil, and yes, even tomato sauce. TruColor Grout surpasses the performance of epoxy and cement-based grouts, while being easier and faster to install. For superior color consistency, stain resistance and flexibility, use TruColor Grout on your next installation.



See Video Demo at
www.bostik-us.com/our-brands/trucolor/default.html

www.bostik-us.com

- Consistent Color Every Time
- Crack Resistant Flexibility
- No Sealing Ever
- Ready to Use
- UV Resistant
- Fast, Easy Installation
- Chemical & Stain Resistant

TruColor
by Bostik

1-800-7BOSTIK

Bostik

The Adhesive Company

WEBSITE
CUSTOMER SERVICE

www.bostik-us.com
www.greenmission.bostik-us.com

TECHNICAL SERVICE

800.7.BOSTIK
Fax: 978.750.7306
Mon-Fri. 8am-6pm EST

800.523.2678
Mon-Fri, 8am-6pm EST

CORRESPONDENCE

Bostik, Inc. | C&I Headquarters
211 Boston Street | Middleton, MA 01949
800.7.BOSTIK | contactus@bostik-us.com

TDS / MSDS REQUESTS

To obtain a TDS / MSDS for any Bostik product, please consult our website. For 24-hour MSDS information, call 800.227-0332.

**AUTHORIZED BOSTIK
DISTRIBUTOR PRICING**

Please contact your sales representative or Customer Service for up-to-date product pricing.