



Product No. **Size** **Description**

Ctn. Qty. **Back Pressure P.S.I.** **Feet of Head**

SINGLE-SIZE TEST-BALL® PLUGS

- Made of natural rubber for excellent expansion and memory
- Seals both round and out-of-round pipe
- Zinc-plated steel chain and ring handle acts as an anchor to prevent plug from sliding down a line

- Fits easily through test tees, sanitary tees, floor drains, and other "tight" situations
- Broader expansion range than mechanical plugs

270 008	3/4"-1-1/4"	Test-Ball® Plug	6	17 PSI	40 FT
270 016	1-1/4"-1-1/2"	Test-Ball® Plug	6	13 PSI	30 FT
270 024	2"	Test-Ball® Plug	6	13 PSI	30 FT
270 108	2-1/2"	Test-Ball® Plug	6	13 PSI	30 FT
270 032	3"	Test-Ball® Plug	6	13 PSI	30 FT
270 040	4"	Test-Ball® Plug	6	13 PSI	30 FT
270 059	5"	Test-Ball® Plug	6	13 PSI	30 FT
270 067	6"	Test-Ball® Plug	6	13 PSI	30 FT



BULK TEST-BALL® PLUGS – INDIVIDUAL DISPLAY BAGS*

- Same great Test-Ball® plug in bulk packaging

- Preprinted bag designed for use with peg hook displays

240 018	1-1/4"-1-1/2"	Test-Ball® Plug	24	13 PSI	30 FT
240 028	2"	Test-Ball® Plug	24	13 PSI	30 FT
240 038	3"	Test-Ball® Plug	24	13 PSI	30 FT
240 048	4"	Test-Ball® Plug	24	13 PSI	30 FT

* Bulk Test-Ball® Plugs MUST be ordered in quantities of 24 plugs.



SINGLE-SIZE TEST-BALL® PLUGS (UNDERGROUND)

- Designed to block sewer flow or for use as a back plug for sewer air testing
- Natural rubber material for excellent expansion and memory
- Seals both round and out-of-round pipe

- Removable inflation valve can be replaced if damaged or replaced with quick disconnect fitting
- Features an eye-bolt for use with a poly-lift line

041 386	8"	Test-Ball® Plug	1	17 PSI	40 FT
041 394	10"	Test-Ball® Plug	1	17 PSI	40 FT
041 408	12"	Test-Ball® Plug	1	17 PSI	40 FT



MULTI-SIZE TEST-BALL® PLUGS

- One size fits multiple pipe diameters, doing the job of 2+ single-size plugs
- Seals both round and out-of-round pipe

- Use to block flow (water DWV test) or as a back plug for sewer air testing
- Zinc-plated steel chain and ring handle acts as an anchor to prevent plug from sliding down a line

276 128	1-1/4"-2"	Test-Ball® Plug	6	17 PSI	40 FT
276 238	2"- 3"	Test-Ball® Plug	6	17 PSI	40 FT
276 348	3"- 4"	Test-Ball® Plug	6	17 PSI	40 FT
276 468	4"- 6"	Test-Ball® Plug	6	17 PSI	40 FT



MULTI-SIZE TEST-BALL® PLUGS (UNDERGROUND)

- One plug fits multiple pipe diameters
- Made of natural rubber for excellent expansion and memory
- Seals both round and out-of-round pipe

- Removable inflation valve can be replaced if damaged or replaced with quick disconnect fitting
- Use to block flow or as a back plug for sewer air testing

275 048	4"- 6"	Test-Ball® Plug	1	17 PSI	40 FT
275 058	6"- 8"	Test-Ball® Plug	1	17 PSI	40 FT
395 128	6"- 12"	Test-Ball® Plug	1	13 PSI	30 FT
275 088	8"- 12"	Test-Ball® Plug	1	11 PSI	25 FT
275 128	12"- 18"	Test-Ball® Plug	1	11 PSI	25 FT
395 248	12"- 24"	Test-Ball® Plug	1	13 PSI	30 FT



CLEAN-SEAL® PLUGS

- Threads into test tee, eliminating water back splash
- Removable sniffer valve inflation fitting is replaceable

- Made from long-lasting natural rubber
- Seals both cast-iron and plastic pipe

271 508	1-1/2"	Clean-Seal® Plug	6	13 PSI	30 FT
271 705	2"	Clean-Seal® Plug	6	13 PSI	30 FT
271 713	3"	Clean-Seal® Plug	6	13 PSI	30 FT
271 721	4"	Clean-Seal® Plug	6	13 PSI	30 FT
271 758	6"	Clean-Seal® Plug	1	13 PSI	30 FT



LONG TEST-BALL® PLUGS

- Designed for waste stack testing from floor drain to sewer pipe
- Includes 3' extension hose
- Long enough to seal wye vertical riser and sewer run
- Ring and chain assembly prevents plug from sliding down a line

271 020	2"	Long Test-Ball® Plug	1	13 PSI	30 FT
271 039	3"	Long Test-Ball® Plug	1	13 PSI	30 FT
271 047	4"	Long Test-Ball® Plug	1	13 PSI	30 FT
271 055	5"	Long Test-Ball® Plug	1	13 PSI	30 FT
271 063	6"	Long Test-Ball® Plug	1	13 PSI	30 FT
271 098	4"- 6"	Long Test-Ball® Plug	1	13 PSI	30 FT

Product No.	Size	Description	Ctn. Qty.	Back Pressure P.S.I.	Feet of Head
-------------	------	-------------	-----------	----------------------	--------------

MS2® LONG TEST-BALL® PLUGS

- Designed for waste stack testing from floor drain to sewer pipe
- Multi-stage deflation eliminates backplash
- Pressure relief valve to safeguard against over-inflation
- Long enough to seal wye vertical riser and sewer run
- Works in multiple pipe diameters
- Nylon strap and safety handle prevents plug from sliding down a line

274 518	2"- 3"	MS2® Plug	1	13 PSI	30 FT
274 526	3"- 4"	MS2® Plug	1	13 PSI	30 FT
274 534	4"- 6"	MS2® Plug	1	13 PSI	30 FT



SINGLE-SIZE MUNI-BALL® PLUGS (UNDERGROUND)

- Works in all types of pipe
- Durable natural rubber construction seals the roughest of surfaces
- Threaded aluminum bypass
- Easily converts to an air test plug with use of a conversion kit
- 8", 10", 12" and 15" plugs include two port plug for easy use in sewer air tests

262 008	1-1/2"	Muni-Ball® Plug	1/8" Bypass	1	22 PSI	50FT
262 010	2"	Muni-Ball® Plug	1/8" Bypass	1	22 PSI	50FT
262 021	3"	Muni-Ball® Plug	3/4" Bypass	1	22 PSI	50FT
262 048	4"	Muni-Ball® Plug	3/4" Bypass	1	22 PSI	50FT
262 064	6"	Muni-Ball® Plug	1-1/2" Bypass	1	13 PSI	30FT
262 080	8"	Muni-Ball® Plug	3" Bypass	1	13 PSI	30FT
262 110	10"	Muni-Ball® Plug	3" Bypass	1	13 PSI	30FT
262 129	12"	Muni-Ball® Plug	3" Bypass	1	13 PSI	30FT
262 137	15"-16"	Muni-Ball® Plug	3" Bypass	1	13 PSI	30FT
262 188	18"	Muni-Ball® Plug	4" Bypass	1	13 PSI	30FT
262 218	21"	Muni-Ball® Plug	4" Bypass	1	13 PSI	30FT
262 242	24"	Muni-Ball® Plug	4" Bypass	1	13 PSI	30FT



MULTI-SIZE MUNI-BALL® PLUGS (UNDERGROUND)

- Work in all types of pipe
- Durable natural rubber construction seals the roughest of surfaces
- Threaded aluminum bypass
- Easily converts to an air test plug with the use of a conversion kit
- One plug fits multiple pipe diameters

265 048	4"- 6"	Muni-Ball® Plug	3/4" Bypass	1	17 PSI	40FT
265 068	6"- 8"	Muni-Ball® Plug	1-1/2" Bypass	1	17 PSI	40FT
355 128	6"- 12"	Muni-Ball® Plug	1" Bypass	1	13 PSI	30FT
265 078	8"- 10"	Muni-Ball® Plug	2" Bypass	1	17 PSI	40FT
265 098	8"- 12"	Muni-Ball® Plug	2" Bypass	1	17 PSI	40FT
265 128	12"- 18"	Muni-Ball® Plug	4" Bypass	1	13 PSI	30FT
355 248	12"- 24"	Muni-Ball® Plug	2" Bypass	1	13 PSI	30FT



REPLACEMENT RING & CHAIN ASSEMBLIES

- Replacement assemblies for Test-Ball plugs
- Rings prevent test plugs from sliding down a line
- Includes a safety tag

059 708	2"	Ring with 12" Chain	1
059 718	3"	Ring with 12" Chain	1
059 728	4"	Ring with 12" Chain	1
059 738	5"	Ring with 12" Chain	1
059 748	6"	Ring with 12" Chain	1
059 758	2"	Ring with 24" Chain	1
059 768	3"	Ring with 24" Chain	1
059 778	4"	Ring with 24" Chain	1
059 788	5"	Ring with 24" Chain	1
059 798	6"	Ring with 24" Chain	1



ECON-O-PUMP™ TEST PUMP

- Low cost version for the infrequent user
- 0-140 PSI gauge
- Traditional thumb lock
- All metal construction

273 888	Econ-O-Pump™ Test Pump	1
---------	------------------------	---





Product No.	Size	Description	Ctn. Qty.	Back Pressure P.S.I.	Feet of Head
-------------	------	-------------	-----------	----------------------	--------------

AIR- MAX™ TEST PUMPS

- Gauge raised from base for protection
- Durable steel barrel
- Textured steel base prevents feet from slipping
- Durable, no-kink hose

273 958		Air-Max® Test Pump	1		
034 588		Replacement Hose Assembly w/ Thumb Lock	1		

AIR- MAX™ PRO HV TEST PUMPS

- Large barrel for maximum volume means fewer strokes to inflate plug
- 0-60 PSI gauge for most accurate plug pressure readings
- All-metal thumb lock for durability
- Hose strain relief to transfer tension from hose to the barrel
- Forged steel barrel for extra toughness
- Large, three-point base for maximum stability
- Rubber cover to protect gauge from damage
- Solid wood handle for greater comfort and durability
- Durable, no-kink hose

273 968		Air-Max® Pro HV Test Pump	1		
055 728		Replacement Hose Assembly w/ Thumb Lock	1		

EXTENSION HOSES

- Recommended for use with plugs up to 15" in diameter
- Ideal for plumbing applications
- Standard tire fitting connections
- 3/16" ID hose

274 011	2'	Extension Hose	6		
274 038	3'	Extension Hose	6		
274 054	5'	Extension Hose	6		
274 100	10'	Extension Hose	1		
274 208	20'	Extension Hose	1		

055 816		Deflator with Clamp (Female Replacement End)	1		
055 808		Inflator with Clamp (Male Replacement End)	1		

274 218	5'	Extension Hose w/ Gauge	1		
274 228	10'	Extension Hose w/ Gauge	1		
274 238	20'	Extension Hose w/ Gauge	1		

POLY-LIFT LINE WITH GAUGE

- Dump valve for quick deflation
- Utilizes quick disconnects
- Poly rope designed for raising and lowering plug
- Ideal for plugs 8" and larger in diameter
- Dampened gauge protects against "peg out"
- 3/8" ID hose for quicker inflation and deflation
- Snap hook connects to plug eyebolt

261 398	20'	Poly-Lift Line / Inflation Hose w/ Gauge	1		
261 408	30'	Poly-Lift Line / Inflation Hose w/ Gauge	1		
261 418	40'	Poly-Lift Line / Inflation Hose w/ Gauge	1		
048 468	0-160 PSI	Dampened Gauge w/ Cover	1		
053 458	0-160 PSI	Dampened Gauge	1		

POLY-LIFT LINE

- Standard tire fitting connections
- Poly rope designed for raising and lowering plug
- Ideal for plugs 8" and up
- 3/16" ID hose
- Snap hook connects to plug eyebolt

261 084	20'	Poly-Lift Line / Inflation Hose	1		
261 106	30'	Poly-Lift Line / Inflation Hose	1		
261 114	40'	Poly-Lift Line / Inflation Hose	1		

TEST GAUGES

- Features 2" unbreakable plastic face
- All connections constructed of high-quality brass
- Inflator valve is replaceable

000 698	0-15 psi w/out test body	1			
000 628	0-30 psi w/out test body	1			
000 638	0-60 psi w/out test body	1			
000 648	0-100 psi w/out test body	1			

024 568	0-15 psi w/ hex test body	1			
019 698	0-30 psi w/ hex test body	1			
019 708	0-60 psi w/ hex test body	1			
019 718	0-100 psi w/ hex test body	1			

000 658	Hex Test Body, 1/8th Tap	1			
068 527	Replacement Sniffer Valve 1/8"	1			



Product No.	Size	Description	Ctn. Qty.	Back Pressure P.S.I.	Feet of Head
-------------	------	-------------	-----------	----------------------	--------------

GRIPPER® MECHANICAL PLUGS

- Ideal for plumbing system tests
- Easy to install with extra-large wing nut
- Inside of pipe seals inside pipe as far as needed
- Made with glass-reinforced ABS plastic
- End-of-pipe seals only at the end of a pipe, preventing plug from falling into stack

270 210	1-1/2"	End of Pipe Gripper® Plug	10	17 PSI	40FT
270 229	2"	End of Pipe Gripper® Plug	10	17 PSI	40FT
270 237	3"	End of Pipe Gripper® Plug	10	17 PSI	40FT
270 245	4"	End of Pipe Gripper® Plug	10	17 PSI	40FT
270 261	6"	End of Pipe Gripper® Plug	5	17 PSI	40FT
270 270	8"	End of Pipe Gripper® Plug	1	17 PSI	40FT
270 296	4"	Inside of Pipe Gripper® Plug	10	17 PSI	40FT
270 253	6"	Inside of Pipe Gripper® Plug	5	17 PSI	40FT
270 288	8"	Inside of Pipe Gripper® Plug	1	17 PSI	40FT



HUB-FIT GRIPPER® PLUGS

- Ideal for use in hub fittings and in bell-end pipe
- Pressure rated for conducting DWV tests
- Yellow color enhances visibility in pipe
- Made with glass-reinforced ABS plastic and natural rubber O-ring

270 528	2"	Hub-Fit Gripper® Plug	10	13 PSI	30FT
270 538	3"	Hub-Fit Gripper® Plug	10	13 PSI	30FT
270 548	4"	Hub-Fit Gripper® Plug	10	13 PSI	30FT



CLEAN-OUT GRIPPER® PLUGS

- Threaded O-ring ensures airtight seal
- Stainless steel hardware prevents corrosion
- Black color blends well with cast-iron pipe
- NPT-sized, including hard-to-find 3-1/2"
- Guaranteed to seal all damaged threads
- Made with glass-reinforced ABS plastic and natural rubber O-ring

270 168	2"	Plug seals 2-1/2" threaded opening	10	17 PSI	40FT
270 178	3"	Plug seals 3-1/2" threaded opening	10	17 PSI	40FT
270 138	3-1/2"	Plug seals 4" threaded opening	10	17 PSI	40FT
270 188	4"	Plug seals 4-1/2" threaded opening	10	17 PSI	40FT



T-HANDLE ALUMINUM GRIPPER® PLUGS (UNDERGROUND)

- Can be used in long-term applications
- Chemical-resistant neoprene O-ring
- Made of heavy-duty aluminum
- Bypass can be used to conduct sewer air pressure test

272 949	6"	Gripper® Plug 1/4" Bypass	1	17 PSI	40FT
272 957	8"	Gripper® Plug 3/4" Bypass	1	17 PSI	40FT
272 965	10"	Gripper® Plug 3/4" Bypass	1	17 PSI	40FT
272 973	12"	Gripper® Plug 3/4" Bypass	1	13 PSI	30FT
272 981	15"	Gripper® Plug 3/4" Bypass*	1	13 PSI	30FT
272 998	18"	Gripper® Plug 3/4" Bypass*	1	8.7 PSI	20FT

*Concrete and clay pipe sizes only.



T-HANDLE ALUMINUM GRIPPER® PLUGS (UNDERGROUND)

- Can be used in long-term applications
- Chemical-resistant neoprene O-ring
- Made of heavy-duty aluminum

272 892	6"	Gripper® Plug (Non By-Pass)	1	17 PSI	40FT
272 906	8"	Gripper® Plug (Non By-Pass)	1	17 PSI	40FT
272 914	10"	Gripper® Plug (Non By-Pass)	1	17 PSI	40FT
272 922	12"	Gripper® Plug (Non By-Pass)	1	13 PSI	30FT
272 930	15"	Gripper® Plug (Non By-Pass)*	1	13 PSI	30FT
272 888	18"	Gripper® Plug (Non By-Pass)*	1	8.7 PSI	20FT

*Concrete and clay pipe sizes only.



Cherne manufactures plugs to 96" in diameter, hydrostatic test pumps, along with a complete line of sewer testing equipment. Go to www.cherneind.com for our complete offering or contact customer service for a full line catalog

**Product
No.****Size****Description****Ctn.
Qty.****Back Pressure
P.S.I.****Feet
of Head****IRON GRIP™ MECHANICAL BY-PASS PLUGS**

- Wing-nut design allows for easy installation without tools
- Can be used as a permanent or temporary plug
- Cast-iron bypass design can be used for water test or sewer air testing

268 028	2"	Iron Grip™ Plug	3/8" Bypass	1	13 PSI	30FT
268 038	3"	Iron Grip™ Plug	1/2" Bypass	1	11 PSI	25FT
268 048	4"	Iron Grip™ Plug	1/2" Bypass	1	8.7 PSI	20FT
268 068	6"	Iron Grip™ Plug	1/2" Bypass	1	4.3 PSI	10FT
268 088	8"	Iron Grip™ Plug	1/2" Bypass	1	4.3 PSI	10FT
268 108	10"	Iron Grip™ Plug	1/2" Bypass	1	3.5 PSI	8FT
268 128	12"	Iron Grip™ Plug	1" Bypass	1	2.6 PSI	6FT

**ECON-O-GRIP® PLUGS**

- Cost-effective method for plugging open-ended pipe
- Natural rubber O-ring
- Effective pipe dust cover
- Not recommended for pressure tests

271 519	1-1/2"	Econ-O-Grip® Plug		10	2 PSI	5FT
271 527	2"	Econ-O-Grip® Plug		10	2 PSI	5FT
271 535	3"	Econ-O-Grip® Plug		10	2 PSI	5FT
271 543	4"	Econ-O-Grip® Plug		10	2 PSI	5FT
271 551	5"	Econ-O-Grip® Plug		5	1 PSI	2FT
271 578	6"	Econ-O-Grip® Plug		5	1 PSI	2FT

**PETRO ECON-O-GRIP® PLUGS (CHEMICAL RESISTANT)**

- Chemical-resistant Nitrile rubber and stainless steel hardware
- Not recommended for pressure tests

273 318	1-1/2"	Stainless Steel Econ-O-Grip® Plug		2	2 PSI	5FT
273 328	2"	Stainless Steel Econ-O-Grip® Plug		2	2 PSI	5FT
273 338	3"	Stainless Steel Econ-O-Grip® Plug		2	2 PSI	5FT
273 348	4"	Stainless Steel Econ-O-Grip® Plug		2	2 PSI	5FT
273 358	5"	Stainless Steel Econ-O-Grip® Plug		1	1 PSI	2FT
273 368	6"	Stainless Steel Econ-O-Grip® Plug		1	1 PSI	2FT

**SURE-GRIP® PLUGS**

- Polypropylene construction with natural rubber O-ring
- Can be used as a permanent or temporary plug
- Fits all type of pipe at nominal sizes

271 158	1-1/2"	Sure-Grip® Plug		10	22 PSI	50FT
271 208	2"	Sure-Grip® Plug		10	22 PSI	50FT
271 308	3"	Sure-Grip® Plug		10	13 PSI	30FT
271 408	4"	Sure-Grip® Plug		10	13 PSI	30FT

**KWIK 'N SURE® PLUGS**

- Works in all types of pipe
- Wing nut on 3/8" – 1-1/4" sizes
- Hex nut on 1.5" through 5" sizes
- Works well for plugging water line stub-outs
- Natural rubber O-ring

269 832	0.39"	Kwik 'n Sure Plug		10	185 PSI	428FT
269 840	1/2"	Kwik 'n Sure Plug		10	180 PSI	415FT
269 867	3/4"	Kwik 'n Sure Plug		10	180 PSI	415FT
269 875	1"	Kwik 'n Sure Plug		10	40 PSI	92FT
269 883	1-1/4"	Kwik 'n Sure Plug		10	112 PSI	258FT
269 891	1-1/2"	Kwik 'n Sure Plug		10	88 PSI	203FT
269 905	2"	Kwik 'n Sure Plug		5	112 PSI	258FT
269 913	2-1/2"	Kwik 'n Sure Plug		5	72 PSI	166FT
269 921	3"	Kwik 'n Sure Plug		5	28 PSI	65FT
269 948	4"	Kwik 'n Sure Plug		5	24 PSI	55FT
269 956	5"	Kwik 'n Sure Plug		5	8 PSI	18FT

**MONITOR WELL™ LOCKING PLUGS**

- Designed to seal monitor wells
- Sized to seal schedule 40 piping
- 2" and 4" sizes can also seal schedule 5 plastic and stainless steel pipe
- Yellow chromate-coated locking latch accepts Cherne's solid brass padlock or No. 2 Master®, padlock
- Meets all EPA requirements for locking plugs
- Made with chemical-/petroleum-resistant Estaloc® plastic top/bottom plates and Nitrile sealing O-ring
- Comes with stainless steel carriage bolt

271 648	1"-1-1/4"	Monitor Well™ Locking Plug		12	6.5 PSI	15FT
271 675	2"	Monitor Well™ Locking Plug		50	6.5 PSI	15FT
271 669	3"	Monitor Well™ Locking Plug		75	6.5 PSI	15FT
271 683	4"	Monitor Well™ Locking Plug		25	6.5 PSI	15FT
271 691	6"	Monitor Well™ Locking Plug		8	6.5 PSI	15FT
271 735	8"	Monitor Well™ Locking Plug		1	6.5 PSI	15FT
112 941		Padlock with Key		1	6.5 PSI	15FT



Product No.	Size	Description	Ctn. Qty.	Back Pressure P.S.I.	Feet of Head
-------------	------	-------------	-----------	----------------------	--------------

PLASTIC TEST CAPS

- Seal pipe ends economically

- For use on schedule 40 ABS and PVC DWV pipe

Group A

238 701	1-1/2"	Knock-Out™ Test Cap	100/1500	4.3 PSI	10FT
238 702	2"	Knock-Out™ Test Cap	100/1200	4.3 PSI	10FT
238 703	3"	Knock-Out™ Test Cap	50/500	4.3 PSI	10FT
238 704	4"	Knock-Out™ Test Cap	25/300	4.3 PSI	10FT

Group B

228 108	1-1/2"	Push-Cap™ Test Cap	50/250	4.3 PSI	10FT
228 208	2"	Push-Cap™ Test Cap	25/150	4.3 PSI	10FT
228 308	3"	Push-Cap™ Test Cap	10/100	4.3 PSI	10FT
228 408	4"	Push-Cap™ Test Cap	10/50	4.3 PSI	10FT

Group C

238 108	1-1/2"	End-Cap™ Test Cap	100/1000	17 PSI	40FT
238 208	2"	End-Cap™ Test Cap	100/800	17 PSI	40FT
238 308	3"	End-Cap™ Test Cap	50/400	17 PSI	40FT
238 408	4"	End-Cap™ Test Cap	20/200	17 PSI	40FT

Group D

238 128	1-1/2"-2"	MS End-Cap™ Test Cap	50/500	17 PSI	40FT
238 348	3"-4"	MS End-Cap™ Test Cap	25/200	17 PSI	40FT



PVC TEST-KAP™ PLUGS

- Stainless steel hose clamp won't corrode
- For use on plastic, steel, copper and cast-iron pipe

- Reinforced cross-molded top increases strength
- Tighten clamp with torque wrench or screwdriver to 60 inch pounds

270 725	1-1/2"	Test-Kap® Plug	10	13 PSI	30FT
270 733	2"	Test-Kap® Plug	10	13 PSI	30FT
270 741	3"	Test-Kap® Plug	10	13 PSI	30FT
270 768	4"	Test-Kap® Plug	10	13 PSI	30FT
270 776	5"	Test-Kap® Plug	5	13 PSI	30FT
270 784	6"	Test-Kap® Plug	5	13 PSI	30FT



TUB WASTE & OVERFLOW PLUGS

- Used to isolate bath wastes for air/water testing
- Natural rubber gasket creates air-tight seal
- 3/8" Drain thread

- Yellow ABS plastic ensures easy job site recognition
- For use on center hole drains overflow
- 1/4" Overflow thread

012 678	Tub Plug Set (overflow & drain)	12
---------	---------------------------------	----

MANOMETER

- Used for final test of DWV pipe and to test gas lines
- Reads in 1/10" increments

- Measures water columns from 0" to 16"

010 205	Manometer	1
---------	-----------	---



CLOG BUSTER™ DRAIN FLUSHER

- Unclogs drain pipes in seconds
- Simply remove aerator from faucet spigot and attach faucet adapter to garden hose

- Attaches to standard garden hose fitting
- Natural rubber body provides excellent seal

303 127	1"-2"	Drain Flusher	1
303 135	1-1/2"-3"	Drain Flusher	1
303 143	4"- 6"	Drain Flusher	1
006 193		Faucet Adapter	1



Cherne manufactures plugs to 96" in diameter, hydrostatic test pumps, along with a complete line of sewer testing equipment. Go to www.cherneind.com for our complete offering or contact customer service for a full line catalog