

CST/berger™

No One Measures Up... Worldwide

Product Catalog

- Laser & Optical Tools
- Measuring Devices
- Accessories



**CONSTRUCTION SITE
TOUGH**

THE BRAND FOUND ON MORE JOBSITES... PERIOD.

ROTARY LASERS

CST/berger Brands can be found anywhere construction, surveying, leveling, and layout work is being performed. We are customer driven and committed to providing quality laser products and superior service. CST/berger offers a comprehensive line of rotating laser tools.

CONSTRUCTION SITE
TOUGH

57-ALHVD ALHV Package

Hard Shell
Carrying Case

V-Mount
for Drop Ceilings
#57-VMOUNT



ALGR Grade Control-Dual Dial-In Through Multi-Function LCD Display



Set dual axis grade ($\pm 10\%$), Sweep "Chalkline", Point-to-Point, and Spot modes allow you to adapt the ALGR Control Grade Through The Multi-Function LCD

CST/berger



Model	ALGR	ALHV	ALHV-G	ALH	LM800	LM800GR	LMH600
Horizontal Accuracy @ 100 ft	1/16 in (1.6mm)	1/16 in (1.6mm)	1/16 in (1.6mm)	1/16 in (1.6mm)	1/16 in (1.6mm)	1/16 in (1.6mm)	3/32 in (2.4mm)
Rotation Rate (Preset Speeds)	0-1000 RPM	Variable (3)	Variable (3)	600 RPM	Variable (3)	600 RPM	Variable (3)
Range Indoors	660-ft (200m)	660-ft (200m)	820-ft (250m)	-	660-ft (200m)	-	330-ft (100m)
Range Exterior with Detector	2800-ft (850m)	2800-ft (850m)	1312-ft (400m)	2800-ft (850m)	2800-ft (850m)	2800-ft (850m)	2000-ft (610m)
Leveling Type (Degrees)	Electronic ($\pm 5^\circ$)	Electronic ($\pm 5^\circ$)	Electronic ($\pm 5^\circ$)	Electronic ($\pm 5^\circ$)	Electronic ($\pm 5^\circ$)	Electronic ($\pm 5^\circ$)	Electronic ($\pm 5^\circ$)
Beam Rating	635nm	635nm	532nm	650nm	635nm	650nm	635nm
Scanning w/ Spot Mode	Yes	Yes	Yes		Yes		Yes
Vertical Accuracy @ 100 ft	1/8 in (3.2mm)	1/8 in (3.2mm)	1/8 in (3.2mm)		1/8 in (3.2mm)		1/8 in (3.2mm)
Laydown Beam Positioning	Yes	Yes	Yes		Yes		Yes
Slope/Grade Capability ($\pm 10\%$)	Dual Dial-In	Dual	Dual	Single	Dual w/Remote	Dual	Dual
Battery Type	4-"D" Cell	4-"D" Cell	NiMH	4-"D" Cell	NiMH	NiMH	4-"D" Cell
Water/Dust Protection	IP67	IP67	IP67	IP67	IP67	IP67	IP54
Warranty	3 Year	3 Year	3 Year	3 Year	3 Year	3 Year	2 Year

Available Packages:



Complete Package Contents:

57-ALGRPCKG
Remote, LD440 Detector w/Clamp, Glasses, (2) Magnetic Targets, V-Mount, Tripod, 8-ft Rod, Batteries, Case

57-ALHVPCKG
Remote, LD440 Detector w/Clamp, Glasses, (2) Magnetic Targets, V-Mount, Tripod, 8-ft Rod, Batteries, Case

n/a

57-ALHPCKG
LD440 Detector w/Clamp, Tripod, 8-ft Rod, Batteries, Case

57-LM800PKG
Remote, LD400 Det. w/Clamp, Tripod, 8-ft Rod, NiMH Battery Pack/Charger, Case

57-LM800GRPKG
LD400 Detector w/Clamp, Tripod, 8-ft Rod, NiMH Battery Pack and Charger, Case

57-LMH600PKG
Remote, Glasses, Magnetic Target, V-Mount, LD400 Detector w/Clamp, Batteries, Tripod, 8-ft Rod, Case

Detector Package Contents:

57-ALGRD
Remote, LD440 w/clamp, Batteries, Case

57-ALHVD
Remote, LD440 Detector w/Clamp, Glasses, (2) Magnetic Targets, V-Mount, Batteries, Case

57-ALHVG
Remote, LD440G Detector w/Clamp, Glasses, Magnetic Target, V-Mount, NiMH Rechargeable Batteries, Case

57-ALH
LD440 Detector w/Clamp, Batteries, Case

57-LM800D
Remote, LD400 Detector w/Clamp, NiMH Battery Pack and Charger, Case

57-LM800GR
Remote, LD400 Detector w/Clamp, NiMH Battery Pack and Charger, Case

57-LMH600D
Remote, LD400 Detector w/Clamp, Batteries, Case

Interior Package Contents:

n/a

57-ALHV
Remote, Glasses, (2) Magnetic Targets, V-Mount, Batteries, Case

57-ALHVG
Remote, Glasses, Magnetic Target, V-Mount, NiMH Rechargeable Batteries, Case

n/a

57-LM800I
Remote, Glasses, (2) Magnetic Targets, V-Mount, NiMH Battery Pack and Charger, Case

n/a

57-LMH600I
Remote, Glasses, Magnetic Target, V-Mount, Batteries, Case

Other Package Contents:

57-LM800DI
Same as #57-LM800I with LD400 detector

57-LM800GRPKG-3
Same as #57-LM800GRPKG 3-in-1 Tricase

57-LMH600
Remote, Batteries, Case

DETECTORS— ROTARY LASER



Lay-Down Beam Positioning

Position beam automatically (90° vertical) over a reference point.



Vertical Self-Leveling

Vertical self-leveling allows interior rotary lasers to be positioned in laydown for vertical applications.

CST/berger.



STANLEY



Model	LD500	LD440G Green Beam	LD440	LD400	LD120	LD100N	LD90	RLD1
Range	600-ft (180m)	1400-ft (425m)	1400-ft (425m)	1400-ft (425m)	1000-ft (305m)	1000-ft (305m)	400-ft (120m)	1400-ft (425m)
Bandwidth (mm)	5/10/25	.75/1.5/3.0	.75/1.5/3.0	.75/1.5/3.0	1.5/3.0	1.5/3.0	1.5/3.0	.75/1.5/3.0
LCD Display(s)	1-Side	2-Sides	2-Sides	2-Sides	2-Sides	1-Side	-	2-Sides
Visual LED's	Yes	Yes	Yes	-	-	-	Yes	-
Audible	med/high	med/high	med/high	med/high	on/off	on/off	on/off	med/high
Display Channels	7	7	7	7	3	3	-	7
Strobe Shield™	Yes	Yes	Yes	-	-	-	-	-
Contents:	57-LD500 HD Rod Bracket, Pin, Case	57-LD440G HD Rod Bracket	57-LD440 HD Rod Bracket	57-LD400 HD Rod Bracket	57-LD120 Rod Bracket	57-LD100N Rod Bracket	57-LD90 Rod Bracket	77-169 HD Rod Bracket

CST/berger.

**LMH-CU****LM1000X****LM30**

STANLEY

**RL350GL****RL350****RL250GL****RL250GR****RL100**

3/32 in (2.4mm)	1/8 in (3.2mm)	1/4 in (6.4mm)	1/16 in (1.6mm)	1/8 in (3.2mm)	1/16 in (1.6mm)	3/32 in (2.4mm)	1/4 in (6.4mm)
600 RPM	Variable (4)	Variable (2)	Variable (3)	Variable (3)	600 RPM	600 RPM	(2) Variable
-	200-ft (60m)	200-ft (60m)	200-ft (60m)	200-ft (60m)	-	-	200-ft (60m)
2000-ft (610m)	1000-ft (305m)	800-ft (240m)	2300-ft (700m)	2000-ft (610m)	2300-ft (700m)	2000-ft (610m)	800-ft (240m)
Electronic (±3°)	Electronic (±5°)	Manual	Electronic (±5°)	Electronic (±5°)	Electronic (±5°)	Electronic (±5°)	Manual
650nm	635nm	635nm	635nm	635nm	650nm	650nm	635nm
	Yes	Yes	Yes		Yes		Yes
	1/8 in (3.2mm)	1/4 in (6.4mm)	1/8 in (3.2mm)	1/8 in (3.2mm)			1/4 in (6.4mm)
Manual			Single	Single	Single	Single	
4-"D" Cell	NiMH	4-"C" Cell	NiMH	NiMH	NiMH	NiMH	4-"C" Cell
IP54	IP54		IP67	IP54	IP67	IP54	
2 Year	1 Year	1 Year	2 Year	1 Year	2 Year	1 Year	1 Year

EXTERIOR

INTERIOR
EXTERIORINTERIOR
EXTERIORINTERIOR
EXTERIORINTERIOR
EXTERIOR

EXTERIOR

EXTERIOR

INTERIOR
EXTERIOR

57-LMHCUPK
LD400 Detector
w/Clamp, Tripod, 8-ft
Rod, Batteries, Tripod,
8-ft Rod, Case

57-LM1000XPKG
Remote, Glasses,
Magnetic Target,
V-Mount, LD120 Det.
w/Clamp, NiMH Bat-
tery Pack and Charger,
Tripod, 8-ft Rod, Case

57-LM30PKG
Glasses, Magnetic
Target, Wiz-Mount,
LD100N Detector
w/Clamp, Batteries,
Tripod, 8-ft Rod, Case

77-228
Remote, Laser Detec-
tor w/Clamp, Glasses,
Magnetic Target (2),
V-Mount, NiMH Bat-
tery Pack and Charger,
Tripod, 8-ft Rod, Case

77-230
Laser Detector
w/Clamp, Tripod,
8-ft Rod, NiMH Battery
Pack and Charger,
Tripod, 8-ft Rod, Case

77-224
Remote, Laser Detec-
tor w/Clamp, Glasses,
Magnetic Target (2),
V-Mount, NiMH Bat-
tery Pack and Charger,
Tripod, 8-ft Rod, Case

77-223
Laser Detector
w/Clamp, Tripod,
8-ft Rod, NiMH Battery
Pack and Charger,
Tripod, 8-ft Rod, Case

57-LMH-CU
LD400 Detector
w/Clamp, Batteries,
Case

57-LM1000XE
LD120 Detector
w/Clamp, NiMH Bat-
tery Pack and Charger,
Tripod, 8-ft Rod, Case

57-LM30D
LD100N Det.w/Clamp,
Batteries, Case
57-LM30DUI
Same as #57-LM30I
plus LD400 Det.

77-229
Laser Detector
w/Clamp, NiMH Bat-
tery Pack and Charger,
Case

77-196
Laser Detector
w/Clamp, NiMH Bat-
tery Pack and Charger,
Case

77-156
Remote, Wall-Mount
Bracket, Magnetic
Target, Glasses, Case

57-LM1000X
Remote, Glasses,
Magnetic Target,
V-Mount, LD120
Detector w/Clamp,
NiMH Battery Pack
and Charger, Case

57-LM30I
Remote, Target, Wiz-
Mount, Batteries, Case
57-LM30
Batteries, Case

77-227
Remote, Glasses,
Magnetic Target (2),
V-Mount, NiMH Bat-
tery Pack and Charger,
Case

77-197
Remote, Glasses,
Magnetic Target (2),
V-Mount, NiMH Bat-
tery Pack and Charger,
Case

57-LMHCUPK-3
Same as
#57-LMHCUPK
3-in-1 Tricase

57-LM30PKG-3
Same as
#57-LM30PKG
3-in-1 Tricase

77-230-3
Same as
#77-230
3-in-1 Tricase

77-223-3
Same as
#77-223
3-in-1 Tricase



LINE LAYOUT LASERS

CST/berger offers a diverse range of line layout lasers for construction, squaring, alignment, leveling, and layout work. We are customer driven and develop products that fit your needs.

CST/berger.

CONSTRUCTION SITE
TOUGH



Model	LM-54	XLP-34	ILM-XTG	ILM-XT	ILM	LM2
Diode (#)	635nm (5)	635nm (3)	532nm (2)	635nm (2)	635nm (2)	635nm (2)
Down Plumb Beam	650nm (1)	650nm (1)	-	-	-	-
Accuracy Up To ±	3/8 in @ 100-ft (3mm @ 30m)	1/8 in @ 100-ft (3.3mm @ 30m)	3/32 in @ 30-ft (2.4mm @ 9m)	3/32 in @ 30-ft (2.4mm @ 9m)	1/4 in @ 30-ft (6mm @ 9m)	1/4 in @ 60-ft (6mm @ 18m)
Range (Interior)	75-ft (15m)	100-ft (30m)	100-ft (30m)	100-ft (30m)	32-ft (10m)	100-ft (30m)
Range (Exterior w/Detector)	100-ft (30m)	300-ft	-	100-ft (30m)	-	-
Leveling Type	Electronic, ±5°	Electronic, ±5°	Self-Leveling, ±5°	Self-Leveling, ±5°	Self-Leveling, ±4°	Manual-Vials (Adj. Feet)
Laser Cross	4	3	1	1	1	1
Battery Type	3- NiMH "C"	3-"AA"	3- NiMH "AA"	3-"AA"	3-"AA"	3-"AA"
Warranty	1 Year	1 Year	1 Year	2 Years	1 Year	1 Year
Available Packages:						
Interior Package Contents:	58-LM54 Trivet, Glasses, Target, NiMH Rechargeable Batteries, Case	58-XLP34 Magnetic Laser Tripod, 2-Magnetic Targets, Laser Glasses, Batteries, Case	58-ILM-XTG Magnetic Laser Tripod, Rechargeable Batteries/Charger Pack, Case	58-ILM-XT Magnetic Laser Tripod, 3-"AA" Alkaline Batteries, Case	58-ILM Magnetic Laser Tripod, Target, Batteries, Case	58-LM2 2-Magnetic Targets, Batteries, Case
Exterior Package Contents:	58-LM54E LLD2 Detector, Trivet, Glasses, Target, NiMH Rechargeable Batteries, Case	58-XLP34PKG XLD-2 Detector, B-Mount, Magnetic Laser Tripod, 2-Magnetic Targets, Glasses, Batteries, Case	Summer 2008	58-ILM-XTE Magnetic Laser Tripod, LLD-20 Detector, Batteries, Case		



DOT LASERS

CST/berger Dot Lasers are great tools to increase productivity when 90° squaring, aligning and transferring points, as well as leveling.

CST/berger.

STANLEY.



Model	XP5	MP5	MP3	MP5	PB2	SP1X
Diode (#)	635nm (5)	635nm (5)	532nm (3)	635nm (5)	635nm (3)	635nm (1)
Accuracy ±	3/16 in @ 100-ft (4.8mm @ 30m)	1/4 in @ 100-ft (6.4mm @ 30m)	1/4 in @ 100-ft (6.4mm @ 30m)	1/4 in @ 100-ft (6.4mm @ 30m)	1/4 in @ 100-ft (6.4mm @ 30m)	1/4 in @ 50-ft (6.4mm @ 15m)
Range (Interior)	100-ft (30m)	100-ft (30m)	100-ft (30m)	100-ft (30m)	100-ft (30m)	50-ft (10m)
Leveling Type	Self-Leveling	Self-Leveling	Self-Leveling	Self-Leveling	Self-Leveling	Manual
Leveling Range	±5°	±5°	±5°	±5°	±5°	-
Battery Type	3-"AA"	3-"AA"	3-"AA"	3-"AA"	3-"AA"	3-"AA"
Warranty	2 Years	1 Year	1 Year	1 Year	1 Year	-
Available Packages:						
Standard Package Contents:	58-XP5 Multi-Mount, Trivet, Target, Strap, Batteries, Soft Case and Hard Case	58-MP5 Multi-Mount, Strap, Target, Trivet, Batteries, Case	58-MP3 Multi-Mount, Strap, Target, Trivet, Batteries, Case	77-154 Multi-Mount, Strap, Target, Trivet, Batteries, Case	77-189 Batteries, Case	77-190 Magnetic Laser Tripod, Beam Splitter-90°, Laser Chalkline Adapter, Batteries, Case

STANLEY

MATRIX XT

CL2XT

CL2

CLL

S2XL

S2

635nm (5) 650nm (1)	635nm (2)	635nm (2)	635nm (2)	635nm (2)	635nm (2)
3/8 in @ 100-ft (3mm @ 30m)	3/32 in @ 30-ft (2.4mm @ 9m)	5/32 in @ 30-ft (4mm @ 9m)	1/4 in @ 30-ft (6mm @ 9m)	1/4 in @ 60-ft (6mm @ 18m)	1/2 in @ 30-ft (13mm @ 18m)
75-ft (22.9m)	100-ft (30m)	32-ft (10m)	32-ft (10m)	100-ft (30m)	30-ft (10m)
100-ft (30m)	100-ft (30m)	-	-	-	-
Electronic, ±5°	Self-Leveling, ±4°	Self-Leveling, ±4°	Self-Leveling, ±4°	Manual-Vials	Manual-Vials
4	1	1	1	1	1
3- NiMH "C"	3-"AA"	3-"AA"	3-"AA"	3-"AA"	3-"AA"
1 Year	1 Year	1 Year	1 Year	1 Year	1 Year



77-204
Trivet, Glasses, Target,
NiMH Rechargeable
Batteries, Case

LLD1 Line Laser
Detector (77-213)
Sold Separately



77-215
Magnetic Laser
Tripod, 3-"AA" Alkaline
Batteries, Case

77-222
Magnetic Laser Tri-
pod, LLD-20 Detector,
Batteries, Case



77-153
Magnetic Laser
Tripod, Target, Batter-
ies, Case



77-214
9-ft Laser Pole with
Platform, 3-"AA"
Batteries, Case



77-198
Adhesive Strips,
Target, Case



77-188
Adhesive Strips

Accessories

LP12-UM

12-ft Laser Pole Platform System.

Cat. #	Description
58-LP12-UM	12-ft Pole System

LLD-20

Laser Line Detector

Cat. #	Description
58-LLD20	Electronic Line Detector

MINIT

Magnetic Mini-Laser Tripod

Cat. #	Description
58-MINIT	Fits both 5/8-11 & 1/4-20

LASER DISTANCE MEASURERS

Tru laser measuring for when it has to be accurate. Just point the laser, press a button, and measure. Ideal for appraisers, carpenters, technicians, floor and tile layers, and painters.

CST/berger.
STANLEY

Model
LT-160

Available Jun '08


TLM300

TLM200

TLM100

**Available Mar '08

Laser Diode	635nm	635nm	635nm	635nm
Range	195-ft (60m)	600-ft (200m)	165-ft (50m)	100-ft (30m)
Accuracy Up to ±	1/16 in (1.5mm)	1/16 in (1.5mm)	1/8" (3.0mm)	**1/8 in (3.0mm)
Calculate Area	Yes	Yes	Yes	Yes
Calculate Volume	Yes	Yes	Yes	Yes
Total Room Data	-	Yes	-	-
Memory	Yes	Yes	Yes	10 values
Pythagoras Measuring	Simple	Advanced	Simple	**Simple
Trapezium	-	Yes	-	-
Battery Type	2-"AAA"	2-"AA"	2-"AAA"	**2-"AAA"
Warranty	1 Year	1 Year	1 Year	1 Year

Available Packages:



Package
Contents: **58-LT160**
Batteries, Case



77-930
Batteries, Case



77-920
Batteries, Case



77-910
Batteries, Case

PIPE LASER

Electronic pipe laser is designed with strength, accuracy, and reliability to operate on the most demanding jobsite conditions.

CST/berger.

Two-way RF control gives real-time data between remote and pipelaser. Rugged, waterproof housing.


Model
LMPL20

Diode (#)	635nm (5)
Accuracy ±	±1 arc sec.
Range	800-ft (243m)
Grade Range	-15%, ~ +40%
Line Range	±15%
Cross Axis Leveling	Yes
Auto Line Centering	Yes
Battery Type	NiMH
Warranty	2 Year

Available Packages:

Package
Contents: **59-LMPL20**
Remote, Target Set, NiMH
Bat. Pack/Charger, Alka-
line Battery Pack, 12V
Cord, Leg Set (3), Case

59-RC20

59-PLMHT

59-BLOWER

OPTICAL INSTRUMENTS

Levels and Transit-Levels

Berger has been building quality, reliability, and value into their instruments since 1871.



Features:

- Built-in sunshade
- Large coated achromatic lens
- Rubber eyepiece cap
- 4ft. (1.2m) short focus
- High precision glass level vials
- Dust protected eyepiece with fixed cross hairs
- Powder coated safety yellow paint
- Includes custom hard-shell carrying case, plumb bob (not included with Econo-Series).



CST/berger.

Model

300LP
Magnum Series**300B**
Magnum Series**200B**
Speed-Series**190B**
Speed-Series**140B**
Speed-Series**136**
Econo-Series**135**
Econo-Series

Magnification

22X

22X

20X

20X

20X

20X

20X

Leveling Accuracy @ 100-ft

1/8 in (3.2mm)

1/8 in (3.2mm)

1/4 in (6.4mm)

1/4 in (6.4mm)

1/4 in (6.4mm)

1/4 in (6.4mm)

1/4 in (6.4mm)

Horizontal Angle

5'

5'

15'

15'

15'

n/a

15'

Vertical Angle

1°

1°

1°

n/a

n/a

n/a

n/a

Working Range

250-ft (76.2m)

250-ft (76.2m)

200-ft (60m)

200-ft (60m)

200-ft (60m)

200-ft (60m)

200-ft (60m)

Thread Tripod Base

5/8-11

3 1/2-8

5/8-11

5/8-11

5/8-11

5/8-11

5/8-11

Warranty

1 Year

1 Year

1 Year

1 Year

1 Year

1 Year

1 Year

Available Packages:

Complete Package Contents:

n/a

54-300K
Plumb Bob, Adjustment Tools, Case, Tripod, 8-ft Rod**54-200K**
Plumb Bob, Adjustment Tools, Case, Tripod, 8-ft Rod**54-190K**
Plumb Bob, Adjustment Tools, Case, Tripod, 8-ft Rod**54-140K**
Plumb Bob, Adjustment Tools, Case, Tripod, 8-ft Rod**54-136K**
Adjustment Tools, Case, Tripod, 8-ft Rod**54-135K**
Adjustment Tools, Case, Tripod, 8-ft Rod

Standard Package Contents:

54-300LP
Laser Plummet built into base, Plumb Bob, Adjustment tools, Case**54-300B**
Plumb Bob, Adjustment Tools, Case**54-200B**
Plumb Bob, Adjustment Tools, Case**54-190B**
Plumb Bob, Adjustment Tools, Case**54-140B**
Plumb Bob, Adjustment Tools, Case

n/a

54-135
Adjustment Tools, Case

Automatic Levels

CST/berger.

Model

SAL32'N'**SAL28'N'****PAL 26X****SAL24'N'****PAL 24X****PAL 22X****SAL20'N'**

Magnification

32X

28X

26X

24X

24X

22X

20X

Leveling Accuracy

1/16 in @ 250-ft
(1.6mm @ 76.2m)1/16 in @ 200-ft
(1.6mm @ 60m)1/16 in @ 200-ft
(1.6mm @ 60m)±1/16 in @ 150-ft
(1.6mm @ 45.7m)±1/16 in @ 150-ft
(1.6mm @ 45.7m)±3/32 in @ 150-ft
(2.4mm @ 45.7m)1/8 in @ 100-ft
(3.3mm @ 30m)

Angular Accuracy

1°/1gon

1°/1gon

1°/1gon

1°/1gon

1°/1gon

1°/1gon

1°/1gon

Comp Setting

±0.3"

±0.5"

±0.5°

±0.8"

±0.8°

±0.8°

±0.8"

Working Range

400'

350'

325'

300'

300'

250'

200'

Warranty

5 Years

5 Years

5 Years

5 Years

5 Years

5 Years

5 Years

Available Packages:

Complete Kit Contents:

55-SLVP32N
Lens Cover, Plumb Bob, Adjustment Tools, Case, Tripod, 8-ft Rod**55-SLVP28N**
Lens Cover, Plumb Bob, Adjustment Tools, Case, Tripod, 8-ft Rod**55-PLVP26N**
Lens Cover, Plumb Bob, Adjustment Tools, Case, Tripod, 8-ft Rod**55-SLVP24N**
Lens Cover, Plumb Bob, Adjustment Tools, Case, Tripod, 8-ft Rod**55-PLVP24D**
Lens Cover, Plumb Bob, Adjustment Tools, Case, Tripod, 8-ft Rod**55-PLVP22N**
Lens Cover, Plumb Bob, Adjustment Tools, Case, Tripod, 8-ft Rod**55-SLVP20N**
Lens Cover, Plumb Bob, Adjustment Tools, Case, Tripod, 8-ft Rod

Standard Package Contents:

55-SAL32N
Lens Cover, Plumb Bob, Adjustment Tools, Case**55-SAL28N**
Lens Cover, Plumb Bob, Adjustment Tools, Case**55-PAL26N**
Lens Cover, Plumb Bob, Adjustment Tools, Case**55-SAL24N**
Lens Cover, Plumb Bob, Adjustment Tools, Case**55-PAL24D**
Lens Cover, Plumb Bob, Adjustment Tools, Case**55-PAL22N**
Lens Cover, Plumb Bob, Adjustment Tools, Case**55-SAL20N**
Lens Cover, Plumb Bob, Adjustment Tools, Case

Other Package Contents:

NOTE: When ordering autolevels, please add "D" for Degrees of "G" for "Gons". PAL24X is only available in Degrees.**55-SLVP24N**

Lens Cover, Plumb Bob, Adjustment Tools, 3-in-1 Tricase, Tripod, 8-ft Rod

ELECTRONIC TOTAL STATIONS AND THEODOLITES

CST/berger.



Model	CST-202 Total Station	CST-205 Total Station	DGT-02 Theodolite	DGT-10 Theodolite
Magnification	30X	30X	30X	30X
Resolving Power	4.0"	4.0"	3.5"	3.5"
Field of View	1°30'	1°30'	1°30'	1°30'
Minimum Focus	4.92' (1.5m)	4.92' (1.5m)	4.27' (1.3m)	4.27' (1.3m)
Distance Measurement Single Prism	5,249-ft (1,600m)	5,249-ft (1,600m)	n/a	n/a
Angular Accuracy	2 Sec.	5 Sec.	2 Sec.	5 Sec.
Internal Memory	15,000 Points	15,000 Points	-	-
Tripod Thread	5/8-11	5/8-11	5/8-11	5/8-11

Available Packages:


Standard Package Contents:	56-CST202 2 Ni-MH Rechargeable Batteries w/ Charger, Software, Cable, Tool Kit, Sun Shade, Rain Cover, Plumb Bob, Case	56-CST205 2 Ni-MH Rechargeable Batteries w/ Charger, Software, CABLE, Tool Kit, Sun Shade, Rain Cover, Plumb Bob, Case	56-DGT02 Batteries, Sunshade, Tool Kit, Rain Cover, Drying Cloth, Plumb Bob, Case	56-DGT10 Batteries, Sunshade, Tool Kit, Rain Cover, Drying Cloth, Plumb Bob, Case
----------------------------	--	--	---	---




3-D Coordinates




Resection




Distance Offset



Horizontal Angle Offset



Setting Out


CST/berger.
STANLEY

CAL 26

AL24D

26X	24X
±1/16 in @ 150-ft (1.6mm @ 45.7m)	±1/16 in @ 150-ft (1.6mm @ 45.7m)
1°/1gon	1°
±0.8°	±0.8°
150'	300'
1 Year	5 Years

55-CAL26
Lens Cover, Plumb Bob, Adjustment Tools, Case

77-183
Lens Cover, Plumb Bob, Adjustment Tools, Case

77-159
Lens Cover, Plumb Bob, Adjustment Tools, Case, Tripod, 16-ft Rod

Automatic Level Tri-Case All-in-One Carrying Case

55-TRCS Tri-Case All-in-one Carrying Case
Carries Automatic Level, Tripod, Rod


- Protects Instruments from Damage
- Stores Instruments in One Place
- Easy to Transport

Level & Transit-Level Kits

Level and transit-level kits include the instrument with case and accessories, an aluminum quick clamp tripod, and a 8-ft telescoping aluminum rod.

54-200K
Transit-Level Kit


Automatic Level Kits

Automatic Level Kits include the instrument with case and accessories, an aluminum quick clamp tripod, and a telescoping aluminum rod.

When ordering Automatic Levels add "D" for Degrees or "G" for Gons and/or "M" for Metric Kits (Example 55-SLVP24ND)

55-SLVP24ND
Automatic Level Kit

TRIPODS

Quick Clamp

Positive quick clamp locking clamps.



Wing Screw

CST's traditional wing screw clamping tripods offer quick and secure clamping for budget-minded users.



Hand Hold

Easily carry tripod with hand hold in one leg of the CST Wood Tripods (WDW Tripods).



CST/berger.

Heavy-Duty Tripods - Aluminum

Lightweight, heavy gauge aluminum and the added stability of double banded legs put this extension leg tripod "head and shoulders" above other aluminum tripods.

Quick-Clamp

Cat. #	Extended	Closed	Net Wt	Head	Fastener
60-ALQR20	65" (165cm)	42" (107cm)	12lb (5.5kg)	FLAT	5/8-11
60-ALQRI20	65" (165cm)	42" (107cm)	12lb (5.5kg)	FLAT	5/8-11
60-ALQR25	65" (165cm)	42" (107cm)	12lb (5.5kg)	FLAT	3 1/2-8
60-ALQR40	65" (165cm)	42" (107cm)	12lb (5.5kg)	DOME	5/8-11
60-ALQRI40	65" (165cm)	42" (107cm)	12lb (5.5kg)	DOME	5/8-11

Wing Screw

Cat. #	Extended	Closed	Net Wt	Head	Fastener
60-ALW10	49" (124cm)	25" (64cm)	9lb (4.1kg)	FLAT	5/8-11
60-ALW20	65" (165cm)	42" (107cm)	13lb (5.5kg)	FLAT	5/8-11
60-ALWI20	65" (165cm)	42" (107cm)	13lb (5.5kg)	FLAT	5/8-11
60-ALW25	65" (165cm)	42" (107cm)	13lb (5.5kg)	FLAT	3 1/2-8
60-ALW30	97" (246cm)	59" (150cm)	14lb (5.5kg)	FLAT	5/8-11

CST/berger.

Heavy-Duty Tripods Wood/Fiberglass

Quick-Clamp, Flat Head

Cat.#	Extended	Closed	Net Wt	Fastener
60-WDF20	72" (183cm)	42" (107cm)	16lb (7.2kg)	5/8-11
60-WDF20X	72" (183cm)	42" (107cm)	16lb (7.2kg)	5/8-11
60-WDF25	72" (183cm)	42" (107cm)	16lb (7.2kg)	3 1/2-8
60-FGHD20*	72" (183cm)	42" (107cm)	16lb (7.2kg)	5/8-11

*All Fiberglass



CST/berger.

Heavy-Duty Elevator Tripods

The adjustable column has a height adjustment range of 12" (305mm) and improved gear system for smooth continuous motion.

Cat.#	Type	Extended	Closed	Net Wt	Fastener
60-ALW30ELAZ	Aluminum	128" (325cm)	68" (173cm)	21lb (9.5kg)	5/8-11
60-WDW30ELAZ	Wood	128" (325cm)	68" (173cm)	27lb (12.2kg)	5/8-11
60-WDW20ELAZ	Wood	94" (239cm)	49" (124cm)	18lb (8.2kg)	5/8-11
60-WDF20ELAZ	Wood/Fbgls	94" (239cm)	49" (124cm)	18lb (8.2kg)	5/8-11
60-ALW20ELAZ	Aluminum	88" (224cm)	48" (122cm)	15lb (6.8kg)	5/8-11
60-ALW10ELAZ	Aluminum	46" (117cm)	25" (64cm)	13lb (5.9kg)	5/8-11

60-IOFOOT
Indoor/Outdoor Rubber Shoe.
All-surface rubber feet with retractable sharp metal points



CST/berger.

Contractor's Tripods - Aluminum

Our popular Contractor's Tripods offer a positive locking quick clamp or wing screw style clamp. The Price Is Right! Our aluminum tripod has value written all over it. This tripod is stronger and more rigid than comparable tripods.

Quick-Clamp

Cat. #	Extended	Closed	Net Wt	Head	Fastener
60-ALQC20	63" (160cm)	38" (97cm)	9lb (4.1kg)	FLAT	5/8-11
60-ALQCI21	63" (160cm)	38" (97cm)	9lb (4.1kg)	FLAT	1/2-20, 1/4-20
60-ALQC25	63" (160cm)	38" (97cm)	9lb (4.1kg)	FLAT	3 1/2-8
60-ALQC40	63" (160cm)	38" (97cm)	9lb (4.1kg)	DOME	5/8-11
60-ALQCI20	63" (160cm)	38" (97cm)	9lb (4.1kg)	FLAT	5/8-11
60-ALQCI40	63" (160cm)	38" (97cm)	9lb (4.1kg)	DOME	5/8-11

Wing Screw

Cat. #	Extended	Closed	Net Wt	Head	Fastener
60-ALC20	63" (160cm)	38" (97cm)	9lb (4.1kg)	FLAT	5/8-11
60-ALC40	63" (160cm)	38" (97cm)	9lb (4.1kg)	DOME	5/8-11

CST/berger.

Heavy-Duty Tripods - Wood

Wing Screw, Flat Head

Cat.#	Extended	Closed	Net Wt	Fastener
60-WDW10HV	25" (64cm)	19" (48cm)	12lb (5.5kg)	5/8-11
60-WDW20HV	72" (183cm)	42" (107cm)	16lb (7.2kg)	5/8-11
60-WDWI20	72" (183cm)	42" (107cm)	16lb (7.2kg)	5/8-11
60-WDW30HV	97" (246cm)	59" (150cm)	21lb (9.5kg)	5/8-11

CST/berger.

Contractor's Elevator Tripods

Cat.#	Type	Extended	Closed	Net Wt	Fastener
60-ALELT20	Aluminum	72" (183cm)	72" (183cm)	12lb (5.5kg)	5/8-11
60-ALQRI20ELAZ	Aluminum	88" (224cm)	48" (122cm)	16lb (7.2kg)	5/8-11

Elevator Columns

Cat.#	Fastener	Adj. Height
60-ELAZ20	5/8-11	17" (432mm)
60-ELAZ25	3 1/2-8	17" (432mm)
60-ELAZ30	5/8-11	34" (864mm)
60-ELAZ35	3 1/2-8	34" (864mm)



CST/berger.

Robotics Tripods

Aluminum

Cat.#	Type	Extended	Closed	Net Wt	Fastener
60-RT20ALW	Aluminum	63" (160cm)	38" (97cm)	-	5/8-11
60-RT20WDF	Composite	71"	46" (117cm)	-	5/8-11
60-RT20FG	Composite/Wood	71"	46" (117cm)	-	5/8-11

GPS Receiver Tripod

Mast Height: 84" (213cm). Total Extension Height Open: 10'-5" (317cm)

Cat.#	Extended	Closed	Net Wt	Fastener
60-WDF20MST	72" (183cm)	42" (107cm)	17lb (7.8kg)	5/8-11

Machine Control Tripods

Elevator column allows a height adjustment range of 17" (43cm)

Cat.#	Extended	Closed	Net Wt	Fastener
60-MCT	135" (343cm)	72" (183cm)	29lb (13kg)	5/8-11
60-MCTE	171" (434cm)	84" (213cm)	34lb (15.4kg)	5/8-11

NOTE: All MCT Tripods include Heavy Duty Points as well as industrial grade casters for interior applications.



60-MCTE Tripod



60-RT20ALW Tripod

TRIPOD ACCESSORIES

Cat.#	Description
60-TFG20	Tripod Floor Guide
60-BAG20	Tripod Carrying Bag fits tripods up to 45" (114cm) in closed length.
61-2512	Universal Plastic Tripod Cap, 5/8-11 thread



60-TFG20 Floor Guide

CST/berger.

Tripod Adapters

Easily adapt a tripod to fit your instrument.



Cat.#	Tripod Fastener	Adapts to Instrument Size
61-2506	5/8-11	11/16 X 20
61-2507	1/2-20	11/16 X 20
61-2508	1/2-20	5/8 X11
61-2509	5/8-11	1/2-20
61-2510	5/8-11	3 1/2-8
61-2510A	3 1/2-8	5/8-11
61-2516	1/4-20	1/4-20
61-2517	5/8-11	1/4-20

CST/berger.

RODS

Telescoping Rods

Cat.#	Length	UOM	Type	Section
06-805MC	16-ft/5m	Metric Ft/in/8ths	Aluminum	5
06-805MT	16-ft/5m	Metric Ft/in/100ths	Aluminum	5
06-808A	8-ft	Feet/10ths/100ths	Aluminum	3
06-808C	8-ft	Feet/Inches/8ths	Aluminum	3
06-808M	2.5m	Metric	Aluminum	3
06-913	13-ft	Feet/10ths/100ths	Fiberglass	4
06-913C	13-ft	Feet/Inches/8ths	Fiberglass	4
06-813	13-ft	Feet/10ths/100ths	Aluminum	4
06-813C	13-ft	Feet/Inches/8ths	Aluminum	4
06-904M	4m	Metric	Fiberglass	4
06-9042MM	4m	Dm/Cm/2mm	Fiberglass	4
06-804M	4m	Metric/mm	Aluminum	4
06-8042MM	4m	Dm/Cm/2mm	Aluminum	4
06-916	16-ft	Feet/10ths/100ths	Fiberglass	5
06-916C	16-ft	Feet/Inches/8ths	Fiberglass	5



Quik-Lok Pole

Bayonet Rod

Cat.#	Length	UOM	Type	Section
06-716	16-ft	Feet/10ths/100ths	Fiberglass	4
06-716C	16-ft	Feet/Inches/8ths	Fiberglass	4
06-816	16-ft	Feet/10ths/100ths	Aluminum	5
06-816C	16-ft	Feet/Inches/8ths	Aluminum	5
06-905M	5m	Metric	Fiberglass	5
06-905MMM	5m	1/2 cm/mm	Fiberglass	5
06-705M	5m	Metric	Fiberglass	4
06-805M	5m	Metric	Aluminum	5
06-805MMM	5m	1/2 cm/mm	Aluminum	5
06-925	25-ft	Feet/10ths/100ths	Fiberglass	6
06-925C	25-ft	Feet/Inches/8ths	Fiberglass	6
06-725	25-ft	Feet/10ths/100ths	Fiberglass	6
06-725C	25-ft	Feet/Inches/8ths	Fiberglass	6
06-907M	7.6m	Metric	Fiberglass	6
06-707M	7.6m	Metric	Fiberglass	6

CST/berger.

Laser Rods and Poles

Bayonet and Quik-Lok

Cat.#	Length	Unit of Measure	Type	Section
09-2082E	8-ft	Feet/Inches/8ths	2	3
09-2082T	8-ft	Feet/Inches/100ths	Bayonet	2
09-2082M	2.5m	Metric	Bayonet	2
09-4154T	15-ft	Feet/Inches/100ths	Quik-Lok	4
09-4154E	15-ft	Feet/Inches/100ths	Quik-Lok	4
06-4154M	4.6m	Metric	Quik-Lok	4

"Cut and Fill" Rod

Cat.#	Length	UOM	Section	Extras
06-TLM	2.4m	Metric	2	
06-TLC	8-ft	Feet/Inches/8ths	2	
06-TLMB	2.4m	Metric	2	Bubble Vial
06-TLCB	8-ft	Feet/Inches/100ths	2	Bubble Vial

"Cut and Fill" Rod

MEASURING WHEELS



Professionals in many fields count on the Rolatape® Professional Series. Featuring all steel construction, a 5-digit ratchet counter, calibrated wide rubber tire.



Cat.#	32-112 112	32-300 300	32-400 400	32-415 415	32-600 600	32-623 623
Wheel Diameter (Circ.)	4 in (1-ft)	11-1/2 in (3-ft)	15-1/4 in (4-ft)	15-1/4 in (4-ft)	23 in (6-ft)	23 in (6-ft)
Counter Reading	^T 10,000 ft/in	^Y 100,000 ft/in	^{M, D, E} 100,000 ft	^{M, D, E} 100,000 ft	100,000 ft	^{M, D} 100,000 ft
Wheels	Dual Plastic	Single Steel	Single Spoked	Single Disk	Single Spoked	Single Spoked
Wheel Stand	-	Available (Add "S")	Yes	Yes	-	Yes
Handle	3-Section	Insert & Lock	Adjustable	Adjustable	Adjustable	Adjustable
Wheel Brake	-	-	Yes	Yes	Yes	Yes

Other Packages Available including ^T Tenth, ^Y Yards, ^M Metric, ^D Dual Counters, as well as ^E Extended Model



Designed to handle the needs of professionals and homeowners alike. While maintaining our focus on quality and accuracy, the Measure Master® Commercial Series features an axle driven counter that adds in forward and subtracts in reverse.

Cat.#	32-12* MM-12	32-TWIN* MM-TWIN	32-30* MM-30	32-50 MM-50	32-66 MM-6.6
Wheel Diameter (Circ.)	4 in (1-ft)	4 in (1-ft)	11-1/2 in (3-ft)	19 in (5-ft)	25 in (6-ft)
Counter Reading	10,000 ft/in	10,000 ft/in	10,000 ft/in	10,000 ft/in	10,000 ft/in
Wheels	Single	Dual	Single	Single	Single
Wheel Stand	-	-	Yes	-	-
Handle	3-Section	3-Section	Insert & Lock	Insert & Lock	Insert & Lock

*Also available in Tenth and Metric. Add "T" for Tenth, and "M" for Metric (i.e. cat.# 32-12T).



Accurate, well balanced, easily portable for many applications. CST wheels feature a gear driven counter made from wear resistant Delrin® enclosed in a weather resistant professional designed housing.

Cat.#	31-40M	31-308	31-20M	31-10M	31-108	31-04P
Wheel Diameter	318mm	10 in	97mm	97mm	4 in	4 in
Wheel Type	Aluminum	Aluminum	ABS Plastic	ABS Plastic	ABS Plastic	ABS Plastic
Counter Reading	1,000 m/dm	10,000 ft/in	1,000 m/cm	10,000 m/cm	10,000 ft/in	No Counter
Wheels	Single	Single	Dual	Single	Single	Single
Wheel Stand	Yes	Yes	-	-	-	-
Handle	Snap-Lock	Snap-Lock	3-Section	3-Section	3-Section	1-Section
Integrated Paint System	-	*Available	-	-	-	Yes

*Add a "-P" when ordering (i.e. 31-308-P)



Stanley® measuring wheels are durable and lightweight easy to read counters

The FatMax® MW50 is design for the professionals in many fields to provide reliable measuring under the toughest conditions.

Cat.#	77-236 MW50	77-195 DMW40	77-194 MW408	1-77-194 MW40	77-193 MW208	1-77-193 MW20	77-247 MW108	77-226 MW10
Wheel Diameter	15.5 in	12 in (318mm)	12 in	318mm	4 in	97mm	4 in	1.6 in
Wheel Type	Spoked	Aluminum	Aluminum	Aluminum	ABS Plastic	ABS Plastic	ABS Plastic	ABS Plastic
Counter Reading	Feet	Digital- ft/Metric	10,000 ft/in	10,000 m/cm	10,000 ft/in	10,000 m/cm	10,000 ft/in	1,000 ft/in
Wheels	Single	Single	Single	Single	Dual	Dual	Single	Single
Wheel Stand	Yes	Yes	Yes	Yes	-	-	-	-
Handle	Metal Lock	Snap-Lock	Snap-Lock	Snap-Lock	3-Section	3-Section	3-Section	3-Section

PROMARKER®

Measure and mark while you walk with ProMarker® marking wand.

Cat.#	32-PMW Marker Wand	32-30PM MM-30 PM	32-400PM 400 PM
Wheel Diameter (Circ.)	4" (1')	11-1/2" (3')	15-1/4" (4')
Counter Reading	10,000 ft/in	^T 100,000 ft/in	^M 100,000 ft
Wheels	n/a	Single	Single Spoked
Wheel Stand	-	Yes	Yes
Handle	Trigger	Adj. w/Trigger	Adj. w/Trigger
Wheel Brake	-	-	Yes

Other Packages Available including ^T Tenth (32-MM-30TPM), ^M Metric (#32-30MPM and #32-400MPM)

MEASURING TAPES

CST/berger.

Pro-Series

Fiberglass Tapes

These Pro-Series Fiberglass Tapes are made with non-woven PVC-coated fiberglass of superior durability.



Cat. #	Length	Sides	UOM	Refill No.
74-Y3001M	300-ft (91m)	2	10th/100ths, M/cm/2mm	73-Y3001M
74-Y3008M	300-ft (91m)	2	Ft/8ths, M/cm/2mm	73-Y3008M
74-Y3001	300-ft	1	Ft/10th/100ths	73-Y3001
74-Y3008	300-ft	1	Ft/Inches/8ths (16" Center)	73-Y3008
74-Y2001	200-ft	1	Ft/10th/100ths	73-Y2001
74-Y2008	200-ft	1	Ft/Inches/8ths (16" Center)	73-Y2008
74-Y1658M	165-ft (50m)	2	Ft/8ths, M/cm/2mm	73-Y1658M
74-Y1651M	165-ft (50m)	2	10th/100ths, M/cm/2mm	not available
74-Y1001M	100-ft (30m)	2	10th/100ths, M/cm/2mm	73-Y1001M
74-Y1008M	100-ft (30m)	2	Ft/8ths, M/cm/2mm	73-Y1008M
74-Y1001	100-ft	1	Ft/10th/100ths	73-Y1001
74-Y1008	100-ft	1	Ft/Inches/8ths (16" Center)	73-Y1008
74-Y501M	50-ft (15m)	2	10th/100ths, M/cm/2mm	not available
74-Y508M	50-ft (15m)	2	Ft/8ths, M/cm/2mm	not available
74-Y501	50-ft	1	Ft/10th/100ths	73-Y501
74-Y20M	20m	2	M/cm/2mm, M/cm	73-Y20M
74-Y30M	30m	2	M/cm/2mm, M/cm	73-Y30M
74-Y50M	50m	2	M/cm/2mm, M/cm	73-Y50M
74-Y100M	100m	2	M/cm/2mm, M/cm	73-Y100M

BRASS PLUMB BOBS

Precision machined for perfect balance and lacquered for a lasting finish. Includes a hardened steel point with ASA thread. Steel ASA screw cap allows storage for an extra point.

Cat. #	Size-Weight	Cat. #	Size-Weight
11-497	6 oz. (170g)	11-553	18 oz. (510g)
11-498	8 oz. (225g)	11-554	24 oz. (680g)
11-499	10 oz. (285g)	11-554A	32 oz. (910g)
11-550	12 oz. (340g)	11-554B	80 oz. (2270g)
11-551	14 oz. (400g)	11-555A	Extra cap only
11-552	16 oz. (455g)	11-555B	Extra point only



GAMMON REELS

An aid to set up and deploy a clean, accurate plumb. Slip the reel into your palm and draw the bob to desired position and stop with finger pressure. Steel clock spring zips the string back into case.

Cat. #	Description
11-728	Gammon Reel®, with hi-vis black and orange target
11-729	12"/3.6m Gammon Reel®
11-730	6 1/2' / 1.9m Gammon Reel®, with 72 lb. test Orange nylon cord
11-731	Bobbin of Orange Nylon Cord, 24 yds./21.9m



CST/berger.

"PRO-SERIES" POCKET TAPES

Power return features a smooth gliding action with a positive thumb lock and release. Weatherproof, impact-resistant plastic cases are enclosed in a rubber housing.

Cat. #	Length	Side
78-R251	25-ft	ft/10ths/100ths
78-R258	25-ft	ft/in/8ths
78-R075M	7.5m	m/cm/mm



78-R258
25' Tape

Tape Graduations


10ths Graduations- Feet



8ths Graduations- Feet



Metric Graduations



Type "A"—Zero begins 10" from end of loop.

Type "B"—Zero begins at end of hook.

CST/berger.

Pro-Series Nylon-Clad Steel Tapes

An indispensable measuring tool designed for the precision-minded user. Open reels feature new rubber reinforced, rounded design, large soft rubber grip handle. 1/2" tape width.



Cat. #	Length	Sides	UOM	End Type
82-30010A	300-ft	1	Ft/10ths/100ths	Type A end
82-30010B	300-ft	1	Ft/10ths/100ths	Type B end
82-30080A	300-ft	1	Ft/Inches/8ths	Type A end
82-30080B	300-ft	1	Ft/Inches/8ths	Type B end
82-30018B	300-ft	2	Ft/10ths, Ft/Inches	Type B end
82-20010A	200-ft	1	Ft/10ths/100ths	Type A end
82-20010B	200-ft	1	Ft/10ths/100ths	Type B end
82-20080A	200-ft	1	Ft/Inches/8ths	Type A end
82-20080B	200-ft	1	Ft/Inches/8ths	Type B end
82-1651MA	165-ft/50m	2	M/10ths, M/Inches	Type A end
82-1658MA	165-ft/50m	2	M/10ths, M/Inches	Type A end
82-10010A	100-ft	1	Ft/10ths/100ths	Type A end
82-10010B	100-ft	1	Ft/10ths/100ths	Type B end
82-10080A	100-ft	1	Ft/Inches/8ths	Type A end
82-10080B	100-ft	1	Ft/Inches/8ths	Type B end
82-10018B	100-ft	2	Ft/10ths, Ft/Inches	Type B end
82-1001MA	100-ft/30m	2	M/10ths, M/Inches	Type A end
82-1008MA	100-ft/30m	2	M/10ths, M/Inches	Type A end
82-30MA	30m	1	Metric	Type A end
82-50MA	50m	1	Metric	Type A end
82-100MA	100m	1	Metric	Type A end

PLUMB BOB TARGETS

Cat. #	Description
11-425	4" x 4" Pressure Sensitive Target, Peel-Off Sheet
11-426	8" x 8" Pressure Sensitive Target, Peel-Off Sheet
11-431	2" x 4" Plastic Rectangular Target, red & white, notched
11-432	2-1/2" x 4" Translucent Yellow Target



REPLACEMENT PLUMB BOB CORD

Braided linen cord comes in 25 yd. spools.

Cat. #	Description
11-732	White- Heavy
11-733	White- Medium
11-735	Orange- Medium



CST/berger

255 W. Fleming Street
Watseka, IL 60970 USA

Phone: 1-815-432-9200

Toll: 800-435-1859

Fax: 815-432-5390

www.cstberger.com

Proven. Innovative. One Solution