


**DAP® WELDWOOD®
Original Contact Cement**


Premium quality, brush grade, neoprene-based contact cement that meets the stringent requirements of the professional user. High strength and initial grab make it ideal for most projects. Fast-drying formula dries in 15-20 minutes. Offers high heat and water resistance when dry. Exceeds industry performance requirements.



Case Code	Size	Color	Product Code	Case Weight (lbs.)	Case Pack	Case Dimensions LxWxH	Case Volume (cu.ft.)	UPC Check Digit	Cases per Pallet
00271	1 PT	TAN	00271	13.75	12	14"x10.5"x4.5"	0.38	5	130
00272	1 QT	TAN	00272	12.75	6	13.5"x9"x5"	0.35	2	144
00273	1 GA	TAN	00273	31.75	4	13.5"x13.5"x8"	0.84	9	45
00274	5 GA	TAN	00274	37.50	1	12"x12.75"x13.75"	1.22	6	36

**DAP® WELDWOOD®
Gel Formula
Contact Cement**


WELDWOOD® Original Contact Cement formula in an easy-to-use gel that won't drip. No mess. Ideal for vertical and overhead surfaces. Easy spread provides excellent coverage. Long assembly/open time.



Case Code	Size	Color	Product Code	Case Weight (lbs.)	Case Pack	Case Dimensions LxWxH	Case Volume (cu.ft.)	UPC Check Digit	Cases per Pallet
25310	1 PT	TAN	25310	13.00	12	14"x10.5"x4.5"	0.38	0	130
25312	1 QT	TAN	25312	13.00	6	13.5"x9"x5"	0.35	4	144
25316	1 GA	TAN	25316	32.25	4	13.5"x13.5"x8"	0.84	2	45

**DAP® WELDWOOD®
Nonflammable
Contact Cement**

High solids polychloroprene, waterborne contact adhesive that meets the stringent requirements of the professional user. Complies with all current VOC requirements. Dries in 30-40 minutes, allowing for extra bonding time. Water resistant when dry. Exceeds industry performance requirements. Low odor. Easy water clean-up.




Case Code	Size	Color	Product Code	Case Weight (lbs.)	Case Pack	Case Dimensions LxWxH	Case Volume (cu.ft.)	UPC Check Digit	Cases per Pallet
25330	1 PT	NATURAL	25330	16.75	12	14"x10.5"x4.5"	0.38	8	130
25332	1 QT	NATURAL	25332	15.75	6	13.5"x9"x5"	0.35	2	144
25336	1 GA	NATURAL	25336	39.25	4	13.5"x13.5"x8"	0.84	0	45



DAP® WELDWOOD®
Contact Cement
Cleaner & Thinner

Fast and easy way to clean dried or fresh adhesive from tools and brushes. Cleans up oil, grease and wax. May be used to delaminate bonded assemblies and thin solvent-based contact cements.



Case Code	Size	Color	Product Code	Case Weight (lbs.)	Case Pack	Case Dimensions LxWxH	Case Volume (cu.ft.)	UPC Check Digit	Cases per Pallet
25350	1 PT	CLEAR	25350	6.50	6	8"x6"x7"	0.19	6	190



Extremely Flammable—Brush Grade

DAP® 0308 Premium Brush Grade High Heat Resistant Contact Adhesive

Superior quality adhesive designed to allow maximum application of

adhesive with minimum strokes of brush or roller. 0308 Premium has developed a broad range of applications in industry. Dries rapidly with high strength and high heat resistance.

Case Code	Size	Color	Drum Type	Case Pack	Case Weight (lbs.)
00094	5 GA	NATURAL		1	36.75
04058	55 GA	NATURAL	O.H.*	1	424.00

DAP® 2056 Professional Brush Grade Contact Adhesive

A medium viscosity formulation which meets the requirements of

many applications. A general purpose contact adhesive, 2056 Professional is often the choice of shops and tradesmen engaged in a variety of projects requiring contact adhesive. Easy to apply. Fast drying.

Case Code	Size	Color	Drum Type	Case Pack	Case Weight (lbs.)
00241	5 GA	NATURAL		1	35.00

Extremely Flammable—Spray Grade

DAP® Landau Top & Trim High Heat Resistant Contact Cement

The ideal contact cement for automotive interior applications.

Its high heat resistance is well suited for adhering headliners, fabric and many other materials during automobile refurbishment. Easy to apply with hot or cold spray equipment.

Case Code	Size	Color	Drum Type	Case Pack	Case Weight (lbs.)
00233	1 GA	NATURAL		4	29.50
00234	5 GA	NATURAL		1	36.00
00235	55 GA	NATURAL		1	404.00
04026	55 GA	NATURAL	T.H.*	1	414.00
04069	55 GA	NATURAL	O.H.*	1	414.00
00237	5 GA	RED		1	36.00

DAP® Landau Top & Trim High Heat Resistant High Solids Contact Adhesive

Offers up to 33% greater coverage than traditional products. Bond strength increases with age. Excellent chemical and water resistance. Ideal for applications

such as automotive, marine or aeronautical interiors, including headliners, vinyl trim, dash coverings, door coverings, floor coverings, panel coverings and upholstery. Ideal for bonding Landau tops constructed of non-penetrable fabric backing.

Case Code	Size	Color	Drum Type	Case Pack	Case Weight (lbs.)
00251	1 GA	NATURAL		4	31.15
00250	5 GA	NATURAL		1	38.00

Extremely Flammable—Spray Grade

DAP® 1145 High Solids High Heat Resistant Spray Grade Contact Adhesive

Offers a number of benefits over standard grade adhesives which is attributable to its high solids, low solvent formula. This allows for a

faster drying time, lower glue line cost, less solvent escapement, lower odor and potential savings, with fewer drums to dispose. 1145 has superior green strength and qualifies for a Class A Flame Spread rating when tested in accordance with ASTM E81 Tunnel Test.

Case Code	Size	Color	Drum Type	Case Pack	Case Weight (lbs.)
04120	5 GA	NATURAL		1	38.00
04121	55 GA	NATURAL	O.H.*	1	419.00
04140	5 GA	RED		1	38.00
04141	55 GA	RED	O.H.*	1	419.00

DAP® 0306/0307 High Heat Resistant Contact Adhesive

This industry standard, used with confidence for years, meets the requirements of a wide range of

applications. Features ease of use and excellent end results. May be applied with standard hot or cold spray equipment.

Case Code	Size	Color	Drum Type	Case Pack	Case Weight (lbs.)
00095	5 GA	NATURAL		1	37.00
00097	5 GA	RED		1	37.00
00098	55 GA	RED	T.H.*	1	404.00
04051	55 GA	NATURAL	O.H.*	1	414.00
04054	55 GA	RED	O.H.*	1	424.00

DAP® RELY-ON® High Heat Resistant Economy Grade Contact Adhesive

A good quality adhesive for many spray applications. May be applied

with standard hot or cold spray equipment. A better adhesive at an economical cost.

Case Code	Size	Color	Drum Type	Case Pack	Case Weight (lbs.)
03505	5 GA	RED		1	38.00
03506	55 GA	RED	O.H.*	1	413.00
03510	5 GA	NATURAL		1	38.00
03511	55 GA	NATURAL	O.H.*	1	413.00

Flammable Solvent

DAP® 0901 Standard Solvent

The ideal solvent for use in conjunction with WELDWOOD® flammable brush and spray grade contact adhesives. Its uses include thinning products back to their

original viscosity, delaminating bonded surfaces, reactivating dried adhesives, cleaning spray gun tips and air caps, and cleaning general overspray and spillages. WELDWOOD® 0901 Standard Solvent is a flammable solvent.

Case Code	Size	Color	Drum Type	Case Pack	Case Weight (lbs.)
00091	5 GA	CLEAR		1	35.25
00092	55 GA	CLEAR	T.H.*	1	377.00

*(T.H.) Tight Head

*(O.H.) Open Head

For more detailed information, request the technical data sheet for any of our products by calling **1 888 327 8477** or visit our website at www.dap.com



Nonflammable—Spray Grade

DAP® 2146 M.C. High Solids Nonflammable Spray Grade Contact Adhesive

This product provides solutions to many problems affecting cabinet shops, laminators, furniture manufacturers and other industries where an alternative to the extremely flammable products must be found for insurance reasons,

state regulations, storage restrictions and OSHA requirements. 2146 M.C. offers excellent green strength and the many benefits of a high solids product. These benefits include faster drying time, lower glue line costs, less solvent escapement, reduced odor and potential savings, with fewer drums to dispose.

Case Code	Size	Color	Drum Type	Case Pack	Case Weight (lbs.)
04652	5 GA	NATURAL		1	54.00
04654	55 GA	NATURAL	O.H.*	1	595.00
04662	5 GA	GREEN		1	54.00
04664	55 GA	GREEN	T.H.*	1	595.00

DAP® 2004/2044 M.C. High Heat Resistant Nonflammable Contact Adhesive

This adhesive is formulated to cure with similar strength as the more hazardous flammable products.

Nonflammable solvents allow the use of the product in areas where flammable products are prohibited. May be applied with standard hot or cold spray equipment. Drying time allows fast processing of substrates.

Case Code	Size	Color	Drum Type	Case Pack	Case Weight (lbs.)
04672	5 GA	NATURAL		1	58.50
04682	5 GA	RED		1	58.50
04684	55 GA	RED	O.H.*	1	636.00

Nonflammable—Solvent

DAP® 0912 M.C. Nonflammable Solvent

The recommended solvent for thinning nonflammable solvent type

contact adhesives. Its uses include thinning products back to their original viscosity and delaminating bonded surfaces.

Case Code	Size	Color	Drum Type	Case Pack	Case Weight (lbs.)
04804	55 GA	CLEAR	T.H.*	1	640.00

*(T.H.) Tight Head *(O.H.) Open Head

Description			Solids (percent)	Viscosity, CPS	Density, lbs./gal.	Color(s)	Sq. Ft. Coverage (2-3 gms. dry)	Shelf Life	VOC Less H ₂ O/ Exempt g/L	Sizes (Gallons)
Brush Grade (Flammable Solvent)										
0308	Premium	HHR*	24	900-1200	6.8	NATURAL	309	1 yr	592/475	5-55
2056	Prof.	HHR*	20	550-800	6.7	NATURAL	253	1 yr	606/490	5-55
Spray Grade (Flammable Solvent)										
1145	High Solids	HHR*	24	350-450	6.8	RED NATURAL	309	6 mos	540/345	5-55
0307	Std.	HHR*	19	130-200	6.6	RED	237	1 yr	621/499	5-55
0306	Std.	HHR*	19	130-200	6.6	NATURAL	237	1 yr	621/499	5-55
RELY-ON	Economy	HHR*	18	130-200	6.6	RED	237	1 yr	621/499	5-55
LANDAU	Std.	HHR*	19	130-200	6.6	NATURAL RED NATURAL	237	1 yr	621/499	1-5-55
Spray Grade (Nonflammable Solvent)										
2146 MC	High solid specialty		25	180-280	10.1	NATURAL GREEN	478	1 yr	14/5	5-55
2044 MC	Fast Dry	HHR*	10	200-350	10.9	RED	206	1 yr	54/6	5-55
2004 MC	Fast Dry	HHR*	10	200-350	10.9	NATURAL	206	1 yr	54/6	5-55

*(HHR) High Heat Resistance

**DAP® WELDWOOD®**
Carpenter's Glue

Professional quality aliphatic resin wood and multi-purpose glue providing a high strength bond. Sets fast, grips tight and sands easily when dry. Heat, water and solvent resistant. Non-toxic. Low VOC.



Case Code	Size	Color	Product Code	Case Weight (lbs.)	Case Pack	Case Dimensions LxWxH	Case Volume (cu.ft.)	UPC Check Digit	Cases per Pallet
00489	4 OZ	YELLOW	00489	17.00	48	15"x10.5"x6.5"	0.59	4	60
00490	8 OZ	YELLOW	00490	17.50	24	13"x10"x7.5"	0.56	0	56
00491	1 PT	YELLOW	00491	16.00	12	12.5"x8.5"x9"	0.55	7	72
00492	1 QT	YELLOW	00492	32.00	12	17.5"x9.5"x10"	0.96	4	40
00493	1 GA	YELLOW	00493	37.50	4	13"x12.5"x11.5"	1.08	1	27
00494	5 GA	YELLOW	00494	46.00	1	12.25"x12.25"x14.75"	1.28	8	36
00495	55 GA	YELLOW	00495	541.50	1	23.5"x23.5"x34.25"	10.95	5	4

DAP® WELDWOOD®
Hobby 'N Craft Glue

High quality polyvinyl acetate general purpose white glue for home, shop and school use. Forms a strong durable bond. Sets fast and dries clear. Non-toxic. Low VOC.



Case Code	Size	Color	Product Code	Case Weight (lbs.)	Case Pack	Case Dimensions LxWxH	Case Volume (cu.ft.)	UPC Check Digit	Cases per Pallet
00278	4 OZ	WHITE	00278	17.50	48	15"x10.5"x6.5"	0.59	4	60
00280	8 OZ	WHITE	00280	17.50	24	13"x10"x7.5"	0.56	7	56
00281	1 PT	WHITE	00281	16.00	12	12.5"x8.5"x9"	0.55	4	72
00282	1 QT	WHITE	00282	33.25	12	17.5"x9.5"x10"	0.96	1	40
00283	1 GA	WHITE	00283	37.50	4	12.5"x12.5"x11"	0.99	8	27
00284	5 GA	WHITE	00284	47.50	1	13.5"x12"x12"	1.13	5	36
00286	55 GA	WHITE	00286	541.50	1	23.5"x23.5"x34.25"	10.95	9	4



DAP® WELDWOOD® Multipurpose Spray Adhesive

DAP® Weldwood® Multipurpose Spray Adhesive is a mist formula that can be used for the temporary or permanent bonding of lightweight materials including foils, carpeting, papers, foams and felt. Fast tack. VOC compliant with all current regulations.



Case Code	Size	Color	Product Code	Case Weight (lbs.)	Case Pack	Case Dimensions LxWxH	Case Volume (cu.ft.)	UPC Check Digit	Cases per Pallet
00118	16.0 OZ	CLEAR	00118	17.00	12	12"x9.5"x9.75"	0.57	3	80

DAP® WELDWOOD® High Strength Spray Adhesive

DAP® WELDWOOD® High Strength Spray Adhesive web formula is a high-strength, high-temperature resistant formulation that bonds wood, metal and plastic. Long open time. VOC compliant with all current regulations.



Case Code	Size	Color	Product Code	Case Weight (lbs.)	Case Pack	Case Dimensions LxWxH	Case Volume (cu.ft.)	UPC Check Digit	Cases per Pallet
00121	16.0 OZ	CLEAR	00121	17.00	12	12"x9.5"x9.75"	0.57	3	80

**DAP® WELDWOOD®
Plastic Resin Glue**

Powdered, ureaformaldehyde wood glue activated by mixing with water. Forms a bond stronger than the wood itself. Meets Federal Specification A-A-3052. Low VOC.



Case Code	Size	Color	Product Code	Case Weight (lbs.)	Case Pack	Case Dimensions LxWxH	Case Volume (cu.ft.)	UPC Check Digit	Cases per Pallet
00203	1 LB	TAN	00203	8.00	6	15"x10"x5"	0.43	6	54
00204	4.5 LB	TAN	00204	21.50	4	16"x16"x8"	1.19	3	30
00208	300 LB	TAN	00208	317.00	1	23.5"x23.5"x34.25"	10.95	1	4

**DAP® WELDWOOD®
Waterproof
Resorcinol Glue**

Two-component glue ideal for exterior structural applications. 100% waterproof and weatherproof. Meets MIL-A-46051 (Type I, Grade A) (Type II, Grade C) and MIL-A22397 (Grade A).



Case Code	Size	Color	Product Code	Case Weight (lbs.)	Case Pack	Case Dimensions LxWxH	Case Volume (cu.ft.)	UPC Check Digit	Cases per Pallet
00227	1 PT	PURPLE	00227	12.00	6	10.5"x7"x8"	0.34	2	100

**DAP® WELDWOOD®
Contact Cement**

Instantly bonds on contact. Can be used on a variety of materials. Provides a durable, water resistant bond. Handy applicator included in 1 oz. bottle.



Case Code	Size	Color	Product Code	Case Weight (lbs.)	Case Pack	Case Dimensions LxWxH	Case Volume (cu.ft.)	UPC Check Digit	Cases per Pallet
00102	1 OZ	TAN	00102	2.50	12	7"x7"x4.5"	0.13	2	240
00107	3 OZ	TAN	00105	5.00	12	6"x6"x5"	0.10	3	336

**DAP® FUN-TAK®
Reusable Adhesive**

Reusable, removable blue adhesive that replaces tape, tack and nails. No more holes in walls and no more tears from tape or tacks. Non-toxic.



Case Code	Size	Color	Product Code	Case Weight (lbs.)	Case Pack	Case Dimensions LxWxH	Case Volume (cu.ft.)	UPC Check Digit	Cases per Pallet
01201	1 EA	BLUE	01201	1.25	12	6.5"x4"x4.5"	0.07	1	528
01205*	28 GR	BLUE	01201	3.50	36	12"x4.5"x6.5"	0.20	1	150

* includes counter display



DAP® BEATS THE NAIL®
All-Purpose
Construction Adhesive

The best all-purpose construction adhesive. For general construction, remodeling, maintenance and repair projects. Quick-grab formula provides a high-strength, heat and water resistant bond to a variety of substrates. Meets ASTM Specification C 557. Interior/exterior use.



Case Code	Size	Color	Product Code	Case Weight (lbs.)	Case Pack	Case Dimensions LxWxH	Case Volume (cu.ft.)	UPC Check Digit	Cases per Pallet
25098	10.3 OZ	GRAY	25082	13.50	12	8"x6"x12"	0.33	6	108
25082	10.3 OZ	GRAY	25082	27.00	24	12"x8"x12"	0.66	6	54
25084	29 OZ	GRAY	25084	35.50	12	10.5"x8"x17"	0.82	0	40

DAP® BEATS THE NAIL®
All-Purpose Trowelable
Construction Adhesive

All-purpose, trowel grade, solvent-based construction adhesive for general construction, remodeling, maintenance and repair projects. Reduces nailing, squeaks and nail pops. Quick-grab formula provides a high strength, heat and water resistant bond to a variety of substrates.



Case Code	Size	Color	Product Code	Case Weight (lbs.)	Case Pack	Case Dimensions LxWxH	Case Volume (cu.ft.)	UPC Check Digit	Cases per Pallet
25088	1 GA	TAN	25088	44.25	4	13.5"x13.5"x8"	0.84	8	45
00034	5 GA	TAN	00034	54.00	1	12"x12.75"x10.25"	0.91	6	36

DAP® 2000®
Heavy-Duty Projects
Construction Adhesive

A high strength, weatherproof adhesive specifically formulated for projects requiring superior holding power. Quick-grab formula bonds to a wide variety of substrates. Meets ASTM Specification C 557. Interior/exterior use.



Case Code	Size	Color	Product Code	Case Weight (lbs.)	Case Pack	Case Dimensions LxWxH	Case Volume (cu.ft.)	UPC Check Digit	Cases per Pallet
25016	10.3 OZ	GRAY	25010	13.75	12	8"x6"x12"	0.33	9	108
25107	29 OZ	GRAY	25107	35.25	12	10.5"x8"x17"	0.82	6	40



DAP® 4000®
Subfloor & Deck
Construction Adhesive

A premium grade, weatherproof formulation that meets APA AFG-01, ASTM Specification D 3498 and conforms to HUD UM-60a. It reduces nailing requirements, floor squeaks and nail pops. Forms a permanent bond on wet, frozen and treated lumber. Easy gunning. Interior/exterior use.



Case Code	Size	Color	Product Code	Case Weight (lbs.)	Case Pack	Case Dimensions LxWxH	Case Volume (cu.ft.)	UPC Check Digit	Cases per Pallet
25028	10.3 OZ	TAN	25020	11.50	12	8"x6"x12"	0.33	8	108
25117	29 OZ	TAN	25117	29.25	12	10.5"x8"x17"	0.82	5	40

DAP® Drywall
Construction Adhesive

Specially formulated for bonding drywall, paneling and plywood to wood or steel framing. It reduces fastener use up to 50%. Quick-grab formula requires less bracing. Meets ASTM Specification C 557. Interior use.



Case Code	Size	Color	Product Code	Case Weight (lbs.)	Case Pack	Case Dimensions LxWxH	Case Volume (cu.ft.)	UPC Check Digit	Cases per Pallet
25037	29 OZ	TAN	25037	29.00	12	10.5"x8"x17"	0.82	6	40

DAP® Panel & Foam
Construction Adhesive

A high quality, dual-purpose adhesive designed to bond paneling or foamboard insulation to a variety of substrates. Quick-grab formula reduces nailing requirements. Won't etch or burn through. Meets ASTM Specification C 557. Interior/exterior use.



Case Code	Size	Color	Product Code	Case Weight (lbs.)	Case Pack	Case Dimensions LxWxH	Case Volume (cu.ft.)	UPC Check Digit	Cases per Pallet
25003	10.3 OZ	LIGHT GRAY	25005	13.75	12	8"x6"x12"	0.33	5	108



DAP® Tub Surround & Shower Wall Construction Adhesive

Specifically formulated for the installation of tub surrounds and shower wall enclosures to a variety of substrates. Quick-grab formula requires no bracing and provides a strong steam, heat and water resistant bond. Won't harm most plastic tub surrounds and shower walls. Interior use.



Case Code	Size	Color	Product Code	Case Weight (lbs.)	Case Pack	Case Dimensions LxWxH	Case Volume (cu.ft.)	UPC Check Digit	Cases per Pallet
25284	10.3 OZ	LIGHT GRAY	25280	14.00	12	8"x6"x12"	0.33	6	108

DAP® FRP Adhesive

Trowel grade, latex-based formula for bonding FRP panels to concrete, plaster, plywood and gypsum wallboard. For interior use. Nonflammable, fast-setting and water resistant.



Case Code	Size	Color	Product Code	Case Weight (lbs.)	Case Pack	Case Dimensions LxWxH	Case Volume (cu.ft.)	UPC Check Digit	Cases per Pallet
60480	1 GA	WHITE	60480	47	4	15.5"x15.5"x7.75"	1.10	3	30
60481	4 GA	WHITE	60481	47	1	12"x12"x14"	1.20	0	36



DAP® Butyl-Flex®
Gutter & Flashing
VOC-Compliant
Adhesive

Butyl rubber-based, lower solvent formula provides a durable, flexible and watertight bond for gutters, drainspouts, lap joints, flashing, roof vents, aluminum siding and other metal joints. Stands up to weather and temperature extremes.



Case Code	Size	Color	Product Code	Case Weight (lbs.)	Case Pack	Case Dimensions LxWxH	Case Volume (cu.ft.)	UPC Check Digit	Cases per Pallet
27062	10.1 OZ	WHITE	27062	13.75	12	8"x6"x12"	0.33	6	108

DAP® BEATS THE NAIL®
VOC-Compliant
All-Purpose
Construction Adhesive

This latex-based formula provides the same superior performance as the solvent-based BEATS THE NAIL® adhesive. It is VOC-compliant and meets ASTM Specification C 557. Low odor and easy water clean-up. Interior/exterior use.



Case Code	Size	Color	Product Code	Case Weight (lbs.)	Case Pack	Case Dimensions LxWxH	Case Volume (cu.ft.)	UPC Check Digit	Cases per Pallet
25080	3.5 OZ	WHITE	25080	4.50	12	9.5"x7.25"x4.25"	0.17	2	240
27050	10.3 OZ	WHITE	27050	14.00	12	8"x6"x12"	0.33	3	108
27058	29 OZ	WHITE	27058	35.00	12	10.5"x8"x17"	0.82	9	40

DAP® 2000®
Heavy-Duty Projects
VOC-Compliant
Construction Adhesive

This solvent-based, low VOC formula provides a permanent, high-strength, weatherproof bond similar to the standard solvent-based HEAVY-DUTY PROJECTS CONSTRUCTION adhesive. Quick-grab formula bonds to a wide variety of substrates. Interior/exterior use.



Case Code	Size	Color	Product Code	Case Weight (lbs.)	Case Pack	Case Dimensions LxWxH	Case Volume (cu.ft.)	UPC Check Digit	Cases per Pallet
27015	10.3 OZ	GRAY	27015	12.00	12	8"x6"x12"	0.33	2	108



DAP® 4000®
VOC-Compliant
Subfloor & Deck
Construction Adhesive

This latex-based formula provides the same superior performance as the solvent-based 4000® SUBFLOOR adhesive. It is VOC-compliant and meets APA AFG-01, ASTM Specification D 3498 and conforms to HUD UM-60a. Low odor and easy water clean-up. Interior/exterior use.



Case Code	Size	Color	Product Code	Case Weight (lbs.)	Case Pack	Case Dimensions LxWxH	Case Volume (cu.ft.)	UPC Check Digit	Cases per Pallet
27038	29 OZ	TAN	27038	33.00	12	10.5"x8"x17"	0.82	1	40
27030	10.3 OZ	TAN	27030	12.00	12	8"x6"x12"	0.33	5	108

DAP® 7000®
VOC-Compliant
Subfloor & Deck
Construction Adhesive

A solvent-based, VOC-compliant formula that meets APA AFG-01, ASTM Specification D 3498 and conforms to HUD UM-60a. Premium grade, weatherproof formulation reduces nailing requirements, floor squeaks and nail pops. Forms a permanent bond on wet, frozen and treated lumber. Easy gunning. Interior/exterior use.



Case Code	Size	Color	Product Code	Case Weight (lbs.)	Case Pack	Case Dimensions LxWxH	Case Volume (cu.ft.)	UPC Check Digit	Cases per Pallet
27042	29 OZ	TAN	27042	28.50	12	10.5"x8"x17"	0.82	8	40
27044	10.3 OZ	TAN	27044	12.00	12	8"x6"x12"	0.33	2	108

DAP® Panel & Foam
VOC-Compliant
Construction Adhesive

This latex-based formula provides the same superior performance as the solvent-based PANEL & FOAM CONSTRUCTION adhesive. VOC compliant. Won't damage polystyrene foam. Low odor and easy water clean-up. Interior/exterior use.



Case Code	Size	Color	Product Code	Case Weight (lbs.)	Case Pack	Case Dimensions LxWxH	Case Volume (cu.ft.)	UPC Check Digit	Cases per Pallet
27025	10.3 OZ	LIGHT GRAY	27025	12.00	12	8"x6"x12"	0.33	1	108



DAP® Cove Base
VOC-Compliant
Construction Adhesive

Latex-based, VOC-compliant formula bonds vinyl or rubber cove base to most interior wall surfaces. Quick-grab formula requires no bracing. Non-staining and water resistant when dry. Easy water clean-up. Interior use.



Case Code	Size	Color	Product Code	Case Weight (lbs.)	Case Pack	Case Dimensions LxWxH	Case Volume (cu.ft.)	UPC Check Digit	Cases per Pallet
25032	10.3 OZ	LIGHT GRAY	10934	14.00	12	8"x6"x12"	0.33	6	108

DAP® Tub Surround & Shower Wall
VOC-Compliant
Construction Adhesive

This latex-based formula provides the same superior performance as the solvent-based TUB SURROUND & SHOWER WALL adhesive. VOC compliant. Won't harm plastic tub surrounds and shower walls. Low odor and easy water clean-up. Interior use.



Case Code	Size	Color	Product Code	Case Weight (lbs.)	Case Pack	Case Dimensions LxWxH	Case Volume (cu.ft.)	UPC Check Digit	Cases per Pallet
27020	10.3 OZ	CLEAR	27020	9.75	12	8"x6"x12"	0.33	6	108

**DAP® WELDWOOD®
Multi-Purpose
Floor Adhesive**

High strength, trowel grade, latex-based adhesive for bonding many types of floor coverings over a variety of surfaces. Formula provides greater shrink resistance and allows for easy repositioning during installation. Water resistant. Low odor, low VOC, nonflammable and easy water clean-up. Interior use.



Case Code	Size	Color	Product Code	Case Weight (lbs.)	Case Pack	Case Dimensions LxWxH	Case Volume (cu.ft.)	UPC Check Digit	Cases per Pallet
00141	1 QT	OFF WHITE	00141	16.75	6	15.25"x10.25"x5"	0.45	1	84
00142	1 GA	OFF WHITE	00142	43.25	4	15.5"x15.5"x7.75"	1.10	8	30
00144	4 GA	OFF WHITE	00144	43.00	1	12"x12"x14"	1.20	2	36

**DAP® WELDWOOD®
General Purpose
Floor Adhesive**

Versatile, trowel grade, latex-based adhesive for the installation of carpet, sheet flooring and tile. Longer working time allows for easy repositioning during installation. Easy to spread. Low VOC, nonflammable and easy water clean-up. Interior use.



Case Code	Size	Color	Product Code	Case Weight (lbs.)	Case Pack	Case Dimensions LxWxH	Case Volume (cu.ft.)	UPC Check Digit	Cases per Pallet
25226	1 QT	OFF WHITE	25226	15.75	6	15.25"x10.25"x5"	0.45	4	84
25228	1 GA	OFF WHITE	25228	40.75	4	15.5"x15.5"x7.75"	1.10	8	30
25231	4 GA	OFF WHITE	25231	40.50	1	12"x12"x14"	1.20	8	36

**DAP® WELDWOOD®
Sheet Flooring Adhesive**

Trowel grade, latex-based, water resistant adhesive designed for the installation of synthetic felt-backed resilient sheet goods. Allows for easy repositioning during installation. Low odor, low VOC, nonflammable and easy water clean-up. Interior use.



Case Code	Size	Color	Product Code	Case Weight (lbs.)	Case Pack	Case Dimensions LxWxH	Case Volume (cu.ft.)	UPC Check Digit	Cases per Pallet
25176	1 QT	OFF WHITE	25176	16.75	6	15.25"x10.25"x5"	0.45	2	84
25178	1 GA	OFF WHITE	25178	43.25	4	15.5"x15.5"x7.75"	1.10	6	30

**DAP® WELDWOOD®
Wood Floor Adhesive**

High solids, trowel grade, water-based synthetic adhesive developed specifically for installation of prefinished wood flooring. For use on, above or below grade. Allows for normal expansion and contraction of wood floor. Good initial grab and firm-setting. Excellent water resistance. Low VOC, nonflammable and easy water clean-up. Interior use.



Case Code	Size	Color	Product Code	Case Weight (lbs.)	Case Pack	Case Dimensions LxWxH	Case Volume (cu.ft.)	UPC Check Digit	Cases per Pallet
25130	1 QT	OFF WHITE	25130	18.50	6	15.25"x10.25"x5"	0.45	4	84
25133	1 GA	OFF WHITE	25133	48.00	4	15.5"x15.5x7.75"	1.10	5	30
25136	4 GA	OFF WHITE	25136	47.75	1	12"x12"x14"	1.20	6	36

**DAP® WELDWOOD®
Multi-Purpose Ceramic
Tile Adhesive**

High strength, trowel grade, latex-based adhesive for installing ceramic and mosaic tile to floors, walls and countertops. Easy to spread, quick-grab formula requires no bracing. Provides excellent water resistance. Low VOC, nonflammable and easy water clean-up. Interior use.



Case Code	Size	Color	Product Code	Case Weight (lbs.)	Case Pack	Case Dimensions LxWxH	Case Volume (cu.ft.)	UPC Check Digit	Cases per Pallet
25190	1 QT	OFF WHITE	25190	21.50	6	15.25"x10.25"x5"	0.45	8	84
25192	1 GA	OFF WHITE	25192	56.25	4	15.5"x15.5x7.75"	1.10	2	30

**DAP® WELDWOOD®
Cove Base Adhesive**

Trowel grade, latex-based adhesive for installing vinyl rubber cove base. Provides good initial tack and easy spreading for rapid installation. No bracing required. Non-staining and excellent water resistance. Low odor, low VOC, nonflammable and easy water clean-up. Interior use.



Case Code	Size	Color	Product Code	Case Weight (lbs.)	Case Pack	Case Dimensions LxWxH	Case Volume (cu.ft.)	UPC Check Digit	Cases per Pallet
25032	10.3 OZ	OFF WHITE	10934	13.25	12	8"x6"x12"	0.33	6	108
25053	1 QT	OFF WHITE	25053	19.50	6	15.25"x10.25"x5"	0.45	6	84
25054	1 GA	OFF WHITE	25054	51.25	4	15.5"x15.5x7.75"	1.10	3	30
25056	4 GA	OFF WHITE	25056	51.00	1	12"x12"x14"	1.20	7	36

**DAP® WELDWOOD®
Carpet Adhesive**

High strength, trowel grade, latex-based adhesive designed for the installation of most interior carpets. Water resistant when dry. Low odor, low VOC, nonflammable and easy water clean-up. Interior use.



Case Code	Size	Color	Product Code	Case Weight (lbs.)	Case Pack	Case Dimensions LxWxH	Case Volume (cu.ft.)	UPC Check Digit	Cases per Pallet
00185	1 QT	TAN	00185	16.75	6	15.25"x10.25"x5"	0.45	5	84
00186	1 GA	TAN	00186	43.25	4	15.5"x15.5"x7.75"	1.10	2	30

**DAP® WELDWOOD®
All Weather Outdoor
Carpet Adhesive**

High strength, trowel grade, solvent-based adhesive for the installation of most outdoor carpets and artificial turfs. Weatherproof formula withstands rain, snow, ice and freezing. Use in cool or hot weather. Fast-grab. Resists curling. Exterior use.



Case Code	Size	Color	Product Code	Case Weight (lbs.)	Case Pack	Case Dimensions LxWxH	Case Volume (cu.ft.)	UPC Check Digit	Cases per Pallet
00442	1 QT	TAN	00442	18.00	6	13.5"x9"x5"	0.35	9	144
00443	1 GA	TAN	00443	44.00	4	13.5"x13.5"x8"	0.84	6	45
00444	3.5GA	TAN	00444	38.00	1	12"x12.75"x10.25"	0.91	3	48

**DAP® WELDWOOD®
Floor Tile Adhesive**

Trowel grade, latex-based, pressure-sensitive adhesive for the installation of interior floor tile. Offers longer working time for easy repositioning. Dries transparent, eliminating dark lines between tiles. Water resistant. Low odor, low VOC, nonflammable and easy water clean-up. Interior use.



Case Code	Size	Color	Product Code	Case Weight (lbs.)	Case Pack	Case Dimensions LxWxH	Case Volume (cu.ft.)	UPC Check Digit	Cases per Pallet
00136	1 QT	CLEAR	00136	14.50	6	15.25"x10.25"x5"	0.45	7	84
00137	1 GA	CLEAR	00137	37.75	4	15.5"x15.5"x7.75"	1.10	4	30
00139	4 GA	CLEAR	00139	37.50	1	12"x12"x14"	1.20	8	36