HIGH QUALITY **AIRTOOLS AND ACCESSORIES**

SPRAY GUNS KITS SANDING TOOLS BLOCKING TOOLS SANDERS SCRAPERS POLISHERS SCALERS GRINDERS

IMPACT WRENCHES

AIR HAMMERS

AIR NIBBLERS

CUTTING TOOLS

PUNCH TOOLS

SAND BLASTER

DRILLS

SCREW DRIVERS

GREASEGUN=

TOOL KITS

HAND TOOLS

OEM PARTS &

PRODUCTS

AUTO REFINISHING PRODUCTS

SPRAY GUN AIRTOOL SANDING BLOCK CATALOG

TRADE ASSOCIATES, INC.

www.dura-block.com phone: 253-854-0090 fax: 253-852-6452 email: orderdesk@dura-block.com



Since 1981 Trade Associates has supplied top quality industrial tools under the Air Force, Mark 1, Dura-Block and other private brand names. Aggressive quality control and strong customer support back up every product we deliver. A worldwide network of suppliers and inspectors delivers the best products available. We feature premium tools! From our Made in USA products to our professional line of Sprayguns, every



Trade Associates product is inspected, tested and supported by a worldwide team of experts.

Prompt customer support for our products is accomplished through our toll-free Customer Hot Line (1-800-537-5455) and our complete inventory of parts for everything we sell. Calling our Hot Line puts you directly in touch with experts who can answer questions,

trouble shoot your tool or quickly send you the parts you need. You speak to real people and get real results.

We provide versatile, customer friendly merchandising displays, award winning packaging and a full mix of products. Because of this, we are able to tailor a personalized response to fit each customer's specific needs.

Whether it's a farm store or a big box retailer, our flexibility helps ensure success for each customer. Our pricing programs are also tailored to the needs of each customer. We offer FOB country of origin, FOB destination, warehouse distribution or product drop shipped directly to store locations.

In addition to our finished products division, we offer international sourcing and delivery of OEM parts for assembly and finished products in private label packaging. Parts of aluminum forging, extruding, die casting and machining as well as a wide variety of steel, plastic and other materials are supplied to manufacturers worldwide. For more information, item pricing or to place an order, contact us today.



Trade Associates, Inc. 6324 S. 199th Place, Suite 101 Kent, WA 98032

Phone: 253-854-0090 Fax: 253-852-6452

Email: orderdesk@dura-block.com

www.dura-block.com

Table of Contents

Spray Guns 4
Cup Eliminator7
007 Spray Gun System8
Dura-Block10
Made in USA12
Dura-Scrub13
Sanders & Buffers14
Cutting & Punching15
Grinders16
Impact Wrenches18
Ratchets19
Cutting & Punch Tools20
Drills & Screwdrivers21
Accessories22
RC Helicoptersback pg

OEM Parts and Products

Trade Associates sources and delivers parts and finished products around the world under private brand names which are household words. If you need a part made to your specifications or have a product you want produced, packaged and delivered to your warehouse.

Call us! 253-854-0090 Spray Guns

AF7001GMS Professional High **Pressure** Spray Gun

Designed for full flow painting applications with a broad viscosity range. Uses include fine finishes, metallics and other general painting and refinishing. Well balanced to reduce operator fatigue. Fluid tip and needle are stainless steel Solvent resistant seals. Spray pattern can be easily adjusted from an oval spray pattern to a broad fan spray. Gravity Feed.

Specifications:

Cup	0.60 liter
Pressure	45-55 PSI
Air Inlet	1/4" NPS
Fluid Orifice	1.40 mm
Air Consumption	10 CFM @ 50 PSI
Color	Red

Nozzle & Needle Sets: 7001GMS -130...1.30mm 7001GMS -150...1.50mm 7001GMS -170...1.70mm 7001GMS -190...1.90mm

7001GMS -220...2.20mm

AE7001GMS Patents Country Canada Patent No 94910 94910 40104273.1 D448451 94911 D448830 6863227 105058 Germany 3471326D addition patents pending

AF7002GMS Micro Touch-up Spray Gun

Designed for full flow painting applications with a broad viscosity range. Uses include fine finishes, metallics and other general painting and refinishing. Well balanced to reduce operator fatigue. Fluid tip and needle are stainless steel. Solvent resistant seals. Spray pattern can be easily adjusted from an oval spray pattern to a broad fan spray. Gravity Feed.

Specifications:

Cup	250 cc
	35 PSI
Air Inlet	1/4" NPS
Fluid Orifice	1.0 mm
Air Consumption	2-3 CFM @ 35 PSI

AF7002R: Rebuild Kit. Nozzle & Needle Sets:

7002GMS - 050...0.50mm 7002GMS - 080...0.80mm 7002GMS -100...1.00mm 7002GMS -120...1.20mm

AF7002GMS Patents: Country Pate Canada 949 Germany 4010 40104273.1 D448451 USA Canada 94911 USA USA USA Chin3 D448830 6863227 105058 3471326D D103109 D505072 addition patents pendi

AF7003GMS Professional HVLP Spray Gun

The Professional Gravity Feed HVLP Spray Gun includes an anti-drip nozzle, material sieve, stainless nozzle and needles. Self adjusting needle packing and independent air control. Independent pressure control, and fluid adjustment. Meets or exceeds environmental protection laws. AF1024 Air Regulator included. (Also available in kit form below.)

Specifications:

Cup	0.60 liter
Pressure	43 PSI
Air Inlet	1/4" NPS
Fluid Orifice	1.5 mm
Air Consumption	8.5 CFM @ 43 PSI
Color	Red

AF7003R: Rebuild Kit. Nozzle & Needle Sets:

7003GMS -1301.30mm
7003GMS -1501.50mm
7003GMS -1701.70mm
7003GMS -1901.90mm
7003GMS -2202.20mm

AF7003GMS Patents:
Country Patent No.
Canada 94910
Germany 40104273.1
USA D448451
94911
2048830 D448830 6863227 105058 3471326D D103109 D505072 China

AF7004GMS Micro HVLP Touch-up Spray Gun

The Professional Gravity Feed Micro HVLP Touch-up Spray Gun includes an anti-drip nozzle, material sieve, stainless nozzle and needles. Self adjusting needle packing and independent air control. Independent pressure control, and fluid adjustment. Meets or exceeds environmental protection laws. AF1024 Air Regultor included. (Also available in kit form below.)

Specifications:

Cup	250cc
Pressure	29 PSI
Air Inlet	1/4" NPS
Fluid Orifice	1.0 mm
Air Consumption	2.5 CFM @ 29 PSI

AF7003R: Rebuild Kit. **Nozzle & Needle Sets:**

7004GMS - 0500.50mm
7004GMS - 0800.80mm
7004GMS - 1001.00mm
7004GMS - 1201.20mm

AF7004GMS Patents: ents: Patent No. 94910 40104273.1 D448451 94911 D448830 6863227 105058 3471326D Country Canada China addition patents pending

AF7001GMK Professional High Pressure Spray Gun Kit

Contains both HVLP Gravity Feed AF7001 with 600cc paint cup for general finish work and high pressure Micro touch Up AF7002 with 125cc paint cup for small area touch up applictions. Both units have stainless steel

fluid nozzle and needle, blow molded carrying case and cleaning tools included.

AF7001GMK Patents Country Patent Canada 94910 40104273.1 Germany USA D448451 Canada USA USA USA 94911 D448830 6863227 105058



3471326D

AF0009 **Basic Spray Gun**

Our Basic Spray Gun is a multifunction general purpose unit for home, farm and workshop use. Includes internal and external mix fan nozzles, and 1 quart cup.

Specifications: One Full Size Spray Gun

Cup1 at. Fluid Nozzle....

AF7003GMK **Pro HVLP** Spray Gun Kit

Contains both HVLP Gravity Feed AF7003GM

with 600cc paint cup for general finish work and high pressure Micro Touch Up AF7002GM with 125cc paint cup for small area touch up applictions. Both units have stainless steel fluid nozzle and needle, blow molded carrying case and cleaning tools included.

Full Range HVLP Series

Affordable spray guns which provide quality finishing at the lowest possible cost. Excellent atomization, full control and a broad range of nozzle sizes.

AF1110 Touch Up 1.10mm HVLP Spray Gun AF1130 Full Size 1.3mm HVLP Spray Gun AF1140 Full Size 1.4mm HVLP Spray Gun

AF1150 Full Size 1.5mm HVLP Spray Gun

Spray Guns

007K - Large Kit Professional Spray Gun System

Contains 007 Handle, 007 1.3mm head, 1.4mm head & 1.7mm head, 1000cc aluminum cup, 600cc plastic cup, 400cc aluminum cup, mini diaphram regulator with gauge, patented cup swivel, rebuild kit, cleaning kit with tools and a locking carrying case with keys.

007SK - Small Kit Professional Spray Gun System

Contains 007 Handle, 007 1.2mm head, & 1.4mm head, mini diaphram regulator with gauge, patented cup swivel, rebuild kit, cleaning kit with tools and a locking carrying case with keys.

See pages 8 & 9 for detailed 007 overview.

AF800K Professional HVLP Spray Gun Kit



This kit includes one full size and one micro size HVLP Gravity Feed Spray Guns, regulator and carrying case. All spray guns have antidrip nozzles, material sieves, stainless steel nozzles and needles, self adjusting needle packing, independent air control and fluid adjustments. Cleaning Kit included.

Specifications:

One Full Size Spray Gun

Cup	600cc
Fluid Nozzle	1.4mm
Working Pressure	43 PSI
Air Consumption	12.5 CFM @43 PSI
	1/4" NPS

One Micro Size Spray Gun

Cup	125 cc
Fluid Nozzle	1.0 mm
Working Pressure	35 PSI
Air Consumption	3.0 CFM @35 PSI
Air Inlet	1/4" NPS

AFB7S Silver Touch Spray Gun Kit

The Silver Touch Spray Gun is manufactured to the highest factory tolerances for years of quality service.
The Silver Touch is a professional spray gun that can be used at work, around the house and on the farm and for any spray job, big or small. 4 CFM to 7 CFM air compressor range and 50-60 PSI range. Net weight 2.6 lb. with Canister.

Specifications:

Weight	2.6 lbs.
Air Consumption	
Operating Pressure	50-60 PSI
Canister	1 Quart
Fluid Orifice	1.8 mm
Color	Black

AFB7SR: Rebuild Kit.

AK900 Professional HVLP Spray Gun kit



This kit includes two full size and one micro size HVLP Gravity Feed Spray Guns, one regulator, 2 1000cc cups and a carrying case. All spray guns have anti-drip nozzles, material sieves, stainless steel nozzles and needles, self adjusting needle packing, independent air control and fluid adjustments. Cleaning Kit included.

Specifications:

Two Full Size Spray Guns

Aluminum cup	1000cc
Fluid Nozzle	1.4 & 1.7mm
Working Pressure	43 PSI
Air Consumption	12.5 CFM @43 PSI
Air Inlet	

One Micro Size Spray Gun

One Micro Size Spray dun
Aluminum Cup250cc
Fluid Nozzle1.0 mm
Working Pressure35 PSI
Air Consumption3.0 CFM @35 PSI
Air Inlet1/4" NPS
Included in the kit: Two regulators, 3 alu-
minum cannisters, cleaning kit and plastic
carrying case.
Meets or excedes environmental laws

AF1011 Professional Airbrush Kit

Complete kit contains a precision double action airbrush with 7cc color cup, air supply hose, adapter, universal hose coupler, nozzle wrench and instuction manual. The AF1011 is a general purpose airbrush suitable for fabric art, posters, custom painting, and general spraying needs. Works well with acrylic paint, oil paints, dyes, fabric paints, lacquers and enamels.

AK1000 Spray Gun kit



The professional Gravity Feed HVLP Spray Gun Kit includes three full size HVLP Gravity Feed Spray Guns, one Micro HVLP Gravity Feed Spray gun and one regulator. All spray guns have anti-drip nozzles, material sieves, stainless steel nozzles and needles, self adjusting needle packing, independent air control and fluid adjustments. Cleaning Kit included.

Specifications:

Three Full Size Spray Guns

Cups	500cc & 1000cc
Fluid Nozzle	1.3, 1.5 and 1.7mm
Working Pressure	43 PSI
Air Consumption	12.5 CFM @43 PSI
Air Inlet	1/4" NPS

One Micro Size Spray Gun

Aluminum cup	250 cc
Fluid Nozzle	1.0 mm
Working Pressure	35 PS
Air Consumption	3.0 CFM @35 PS
Air Inlet	

Kit includes (1) 1000cc aluminium cup, (1) 250cc aluminium cup, (5) Dura-Block 500cc Cup Eliminators and one regulator. Meets or excedes enviromental laws

Spray Gun Accessories



Spray Gun Cups and Covers

AF7001GMS, AF7003GMS, 007

PC600-600CC Plastic Cup and Cover AC400-400CC Aluminum Cup and Cover AC600-600CC Aluminum Cup and Cover AC1000-1000CC Aluminum Cup and Cover AF7002GMS, AF7004GMS

7002GMS and AF7007 Micro Touch-Up Spray Gun

PC125-125cc Plastic Cup and Cover. AC200-200cc Aluminum Cup and Cover. AC250-250cc Aluminum Cup and Cover.





Air Cap/Fluid Nozzle/ Needle Combinations

Allows changes to accommodate various paint viscosities.

Allows changes to accommodate various paint viscosities.		
7001GMS Professional Spray Gun GMS		
7001GMS-140	1.40mm Combination (Standard)	
7001GMS-170	1.70mm Combination	
7001GMS-200	2.00mm Combination	
7002GMS Micro Touch-Up Spray	Gun GMS	
7002GMS-050		
7002GMS-080	0.80mm Combination (Standard)	
7002GMS-100	1.00mm Combination	
7003GMS HVLP Spray Gun GMS		
7003GMS-130	1.30mm Combination	
7003GMS-150	1.50mm Combination (Standard)	
7003GMS-170	1.70mm Combination	
7003GMS-190		
7003GMS-220	2.20mm Combination	
7004GMS HVLP Micro Touch-Up Spray Gun GMS		
7004GMS-050		
7004GMS-080	0.80mm Combination (Standard)	
700 (ONIC 100	1 00mm Combination	

Canister Swivel Attachment

Compatable both ways. Works on male and female treaded guns. Fits all spray guns with the following thread sizes:

GMS-L M16x1.5mm/pitch (full size gravity gun) **GMS-S** M14x1.0mm/pitch (touch-up gravity feed gun)

GMS-L/GMS-S Patents: Country Patent





Umnuh THE PERFECT DISPOSABLE PAINT CUP! A FAVORITE AMONG THE PROFESSIONALS. > NO CONTAMINATION > DURABLE, POLYETHELENE > WORKS OR ADAPTS WITH **SAVES VIRTUALLY ALL GRAVITY FEED SPRAYGUNS** > Time > NO CLEAN UP, FULLY DISPOSABLE & > Solvents RECYCLABLE > Money > EXTREMELY AFFORDABLE > Environment



U.S. and foreign patents pending Vehicle Courtesy of: Steve's Auto Restorations, Inc.



Dura-Block Cup Eliminators Model CE 500 are engineered to fit all full size gravity feed spray guns with 16mm female, 1.5mm thread. This includes older model SATA, current models: Iwata, Mark I, Air Force, Dura-Block, AIDR, Advantage, AirVerter, AES, AmPro, Astro-M-Star, ATD, CA Technologies, Campbell, Cent-Neu, Goni, Husky, Ingersol Rand, M-Star, Mac-Econocoat, Matco, MSB, Nesco, Porter Cable, Nikota, Sharpe, Sunex, Trem Pro, Vaper, Warwick, Spray-It and Star-III Guns and many others with 16mm female, 1.5mm thread. For other spray guns, there are two adapters included in each carton which allow the Cup Eliminators to be used with other guns.

#1 Red Adapter can be used with spray guns having cup connection threads 3/8 Male, 18 Thread, including Sharpe Cobalt HVLP (USA), Platinum HVLP, Titanium T-1 HVLP, SGF-98 and Snap-On BF900EXC6 and others 3/8 Male, 18 Thread.

#2 Blue Adapter can be used with spray guns having internal cup connection threads 3/8 inch Male, 19 Thread, including most Binks, DeVilbiss, Ecco, Sharpe and Graco guns and others with 3/8 inch Male. 19 Thread (British Std. Pipe).

#3 Black Adapter can be used with Sata 2000 series. The 3000 series can be used in conjunction with Sata QCC Adapter model #96719.

#4 Gray Adapter can be used with spray guns having cup connection threads 16mm male, 1.5mm thread, including DeVilbiss Finishline FLG-1 and others. 3/8" Male, 18 Thread.

> 50 per case (each inner contains #1, 2, 3 & 4 adapters)

CE₄

CE₃

到月海一岁0月8

007 Professional Spray Gun System















Detachable Head



Patented design allows users to detach the head in seconds, and leave material in the cup! Switch colors, or nozzles in no time.

Anodized Color Kits:



Each color acent kit includes 1 Trigger, 1 air cap and 3 knobs.

Available colors:

Tiranasio con	Tituliable colorer		
007T-Black	Accent Kit		
007T-Red	Accent Kit		
007T-Blue	Accent Kit		
007T-Purple	Accent Kit		
007T-Silver	Accent Kit		
007T-Gold	Accent Kit		
007T-Green	Accent Kit		



specifications:

	10.5 CFM @ 29 PSI Ire29 PSI
Gun Weight	18.5 oz.
Body Material Cup Sizes Available	Forged 7075 Aircraft Grade Aluminum 400cc, 600cc, 1000cc 500cc

ADDITIONAL NOZZLE/ NEEDLE HEADS AVAILABLE:


1.2mm | 1.3mm 1.4mm | 1.5mm 1.7mm | 1.9mm 2.2mm | 3.0mm

And we're working on more!

Parts are readily available for all Dura-Block products.

Additional sizes coming soon.

1.800.537.5455 www.dura-block.com



THE PERFECT SANDING TOOL!

A FAVORITE AMONG PROFESSIONALS WHEN BLOCKING ALL SURFACES.

Dura-Block Kits Available

NEW 5 Piece AF44XDVD Kit contents:

1 **AF4401** 1/3 Block 1 **AF4402** 2/3 Block **Full Size Block** 1 **AF4403** 1 **AF4409** Long Block 1 **AF4410 Marine Block**

Includes FREE Airbrush Action DVD: A comprehensive guide to surface preparation and block sanding from the staff of Steve's Auto Restoration, one of the world's

Dura-Scrub Soap

leading hot rod builders.

7 Piece AF44L Kit contents

Standard Block 1 AF4400 1 **AF4401** 1/3 Block 1 **AF4402** 2/3 Block **Full Size Block** 1 **AF4403 Round Block** 1 **AF4404** 1 AF4405 Scruff Block

6 Piece AF44A Kit contents:

1 AF4400 Standard Block 1/3 Block 1 **AF4401** 2/3 Block 1 **AF4402** 1 **AF4404 Round Block** 2 **AF4405 Scruff Block**

AF44XDVD Kit



AF44A Kit

1 AF4408-S

TRADE ASSOCIATES, INC. PHONE: 253-854-0090 FAX: 253-852-6452 EMAIL: orderdesk@dura-block.com

FOR THE PERFECT FINISH






AF4400 Standard Block

This block is designed to follow contours or flats. No dents, no ripples.

Size: 3/4"H x 1-3/8"W x 11"L





UPC # 0-35656-15146-2

Ships 96 per master / 24 per inner.



AF4402 2/3 Block

This block is designed to allow the user to accurately block flat panels and panels with slight curves.

Size: 1-1/2"H x 2-5/8"W x 11"L

UPC # 0-35656-15147-9

Ships 48 per master / 12 per inner.



AF4403 Full Size Block

A favorite among the professionals when blocking large surfaces. Size: 1-1/2"H x 2-5/8"W x 16"L

UPC # 0-35656-15148-6

Ships 48 per master / 8 per inner.



AF4404 Round Block

This is the "Round" style block. Use to sand and block highly curved surfaces.

Size: 11"L. Thickness: 1-1/4"

UPC # 0-35656-15149-3

Ships 96 per master / 24 per inner.



AF4405 Scruff Block

This block is designed for sanding and prep work. It allows for easy use and much improved durability and firmness.

Size: 5/8"H x 2-1/2"W x 5-3/8"L

UPC # 0-35656-15150-9

Ships 240 per master / 24 per inner.



AF4406 Tear Drop Block

This "tear drop" adds a rounded curve with a flat surface for hard to sand areas.

Size: 10-7/8"L, Thickness: 2-1/8" at max.

UPC # 0-35656-15144-8

Ships 48 per master / 12 per inner.



AF4409 Long Block

This block is designed to allow the user to accurately block flat panels and panels with slight curves.

Size: 1-1/2"H x 2-5/8"W x 24"L

UPC # 0-35656-15151-6

Ships 48 per master / 12 per inner.



AF4410 Marine Block

A favorite among the professionals when blocking large surfaces.

Size: 1-1/2"H x 2-5/8"W x 30"L

UPC # 0-35656-15152-3

Ships 48 per master / 8 per inner.



AF4411 Dura-Disc

Designed to accurately block curved or flat surfaces. To be used with 6" round paper.

Size: 5/8"H x 2-1/2"W x 6"L

UPC # 0-35656-15159-2

Ships 240 per master / 24 per inner.



AF4412 1/3 Radius Block

This curved face block is designed to follow slightly curved or flat panels without digging fill material. Accepts 2-3/4" PSA sticky paper.

Size: 1-3/4"H x 2-5/8"W x 5-1/2"L

UPC # 0-35656-15153-0

Ships 96 per master / 24 per inner.



AF4413 2/3 Radius Block

This curved face block is designed for blocking of flat panels and panels with slight curves. Accepts 2-3/4" PSA sticky paper.

Size:1-3/4"H x 2-5/8"W x 11"L

UPC # 0-35656-15154-7

Ships 48 per master / 12 per inner.



AF4414 Full Size Radius Block

A favorite among the professionals when blocking complex large surfaces. Accepts

2-3/4" PSA sticky paper.

Size: 1-3/4"H x 2-5/8"W x 16"L UPC # 0-35656-15155-4

Ships 48 per master / 8 per inner.



AF4415 Composite Block

Rigid injection molded composites makes this perfectly milled block our most accurate

for flat surfaces.

Size: 1-1/2"H x 2-5/8"W x 11"L

UPC # 0-35656-15156-1

Ships 48 per master / 12 per inner.



AF4417 1/3 Hook & Loop Block

This innovative Velcro Series block has been designed to flex with the contour of any car. Size: 1-1/2"H x 2-5/8"W x 5-1/2"L

UPC # 0-35656-15157-8

Ships 96 per master / 24 per inner



AF4418 2/3 Hook & Loop Block

This innovative Velcro Series block has been designed to flex with the contour of any car. It features a unique pad placement allowing for optimal accuracy.

Size: 1-1/2"H x 2-5/8"W x 11"L

UPC # 0-35656-15158-5

Ships 48 per master / 12 per inner.



AF4419 Full Size Hook & Loop


This innovative Velcro Series block has been designed to flex with the contour of any car.

Size: 1-1/2"H x 2-5/8"W x 16"L

UPC # 0-35656-15159-2

Ships 48 per master / 8 per inner





Made in the USA

USA-1070 High-Speed Disc Sander

This journeyman quality high-speed disc sander is an excellent choice for a variety of sanding applications. The built in air-speed regulator, light weight design and vibration free performance makes it ideal for touch-up and feather edge sanding where perfection counts. Includes two backing pads and hub wrench. **Made in the USA**.

Specifications:

Weight	2-1/2 lbs.
Length	5-1/4"
Pad Sizes	3" and 4-1/2"
Free Speed	18,000 RPM
Operating Pressure	90 PSI
Air Consumption	6 CFM

USA-3125 High-Speed Mini Die Grinder

This mini version of the USA-3025 is designed for general purpose use such as grinding, polishing and deburring. Small size allows for use in confined areas. Features 1/4" collet, rear exhaust and safety throttle lever. Made in the USA.

Specifications:

Free Speed	30,000 RPM
Operating Pressure	90 PSI
Air Consumption	3.0 CFM
Air Inlet	1/4" NPT
Weight	2-1/2 lbs.
Length	5.80"

USA-4050 Low Speed In-Line Air Drill

The low speed and high torque of this superior quality in-line air drill makes it perfect for use on heat sensitive materials, for material removal, and tire buffing. Equipped with safety throttle lever. **Made in the USA.**

Specifications:

opeoou.oo.	
Weight	2-1/4 lbs.
Length	8-1/2"
Chuck Capacity	3/8"
Free Speed	3,500 RPM
Air Consumption	4 CFM
Operating Pressure	90 PSI

USA-6510 Low Speed « Air Buffer & Quick Change Chuck

This low speed tire repair tool is excellent for a variety of repair tasks requiring high torque and low speed. Great for tube and tire surface preperation prior to patching. Features rear exhaust performance and safety throttle lever. Includes one quick change adapter.

Made in the USA. Specifications:

Weight	2-1/4 lbs.
Length	8.25"
Air Inlet	1/4" NPT
Free Speed	3,500 RPM
Operating Pressure	90 PSI
Air Consumption	4 CFM

USA-4138 High Speed Air Drill

The compact design and vibrationless per mance of this superior quality high Speed Air Drill makes it perfect for drilling in sheet metal, plastic and wood. Useful in many brushing and deburring operations. Features through-handle exhaust.

Made in the USA. Specifications:

Weight	2-1/4 lbs.
Length	5-1/4"
Chuck Capacity	
Free Speed	
Operating Pressure	
Air Consumption	

USA-3150 High-Speed Mini Angle Head Die Grinder

Compact design works great in confined areas where a straight tool cannot be used. Rear exhaust, 25,000 RPM performance is ideal for general purpose applications. Features 1/4" collet and safety throttle lever.

Made in the USA with US and foreign parts.

Specifications:

Free Speed	25,000 RPM
Air Pressure	90 PSI
Air Consumption	3.0 CFM
Weight	85 lbs.
Length	5.80 "

Dura-Scruh









- Scrubbing and sudsing are now done in one easy process.
- A special industrial scrubbing pad is combined into each bar of soap.
- Cleans 10 times more effectively than standard bars of soap.
- ➤ Large 4 ounce bars, 4 per display box.

SURFACE SAND, PREP AND PAINT PERFORMANCE PRODUCTS

Sanders & Buffers

AF1005B 6 inch Industrial grade Dual **Action Sander**



The Dual Action Sander is a professional sander for all sanding applications. The guiet random sanding action assures a smooth pattern-free finish. Expertly engineered and constructed, the pad and the head move in diffent directions for maximum smooth surface contact. Built in regulator allows power and speed control at the tool.

AF1005-P: 6" Replacement Pad **Specifications:**

Air Pressure	90 PSI
Length	10"
Weight	4.2 lbs.
Air Inlet	1/4" NPT
Pad Diameter	6"
Free Speed	10,000 RPM
Air Consumption	4 CFM
Hose Size	3/8" I.D.

AF1005-2A 6 inch Heavy Duty Dual Action Sander

Professional quality dual action sander. Quiet random sanding action assures a smooth patternfree finish. Expertly engineered and constructed, the pad and head move in different directions for maximum uniform surface contact. Dual action produces minimal heat build up and abrasive loading. Built in regulator allows power and speed control at the tool.

AF1005-P: 6" Replacement Pad **Specifications:**

Orbital Stroke	3/16"
Operating Pressure	90 PSI
Hose Size Minimum	3/8" I.D.
Pad Sizes	5" or 6"
Speed	10,000 RPM
Air Consumption	6 CFM
Air Inlet	1/4" NPT
Weight	4.2 lbs.

"Jitterbug" Orbital Sander

The "Jitterbug" Orbital Sander is designed for one hand sanding. Recommended for dry or wet sanding on paint, plaster and fiberglass, on cars,



Specifications:

Paper Size	3 1/2" x 6 1/2"
Speed	8000 RPM
Orbital Stroke	3/16"
Air Consumption	5 CFM
Air Inlet	1/4" NPT
Air Hose Size	3/8" I.D.
Recommended Air Pressure	90 PSI



The Palm Sander is designed for one handed sanding. Recommended for dry or wet sanding. Extremely efficient and lightweigt.

Specifications:

Paper Size	6 PSA paper
Speed	10,000 RPM
Orbital Stroke	3/16"
Air Consumption	5.5 CFM
Air Inlet	1/4" NPT
Air Hose Size	3/8" I.D.
Recommended Air Pressure	90 PSI

AF197T Straight Line Sander

Dual piston action for dependable power. Contoured handle minimizes operator fatigue. Suitable for work in large areas requiring extra flat finish

Specifications:

Free Speed	2100 SPM
Air Inlet	1/4" NPT
Air Pressure	90 PSI
Air Consumption	5.5 CFM
Hose Size	3/8" I.D.
Weight	5.5 lb.
Length	14"
Pad Size	2-3/4" x 15-3/4"

5 inch High Speed Air Sander



Easy to handle pistol grip design. Trigger throttle for positive speed control. Built-in air regulator for precise speed control. Excellent motor balance produces extremely low vibration, making this an effortless tool to use. Comes complete with 3", 4-1/2" and 5-1/2" sanding pads.

Specifications:

Free Speed	18,000 RPM
Air Consumption	4 CFM
Hose Size	3/8" I.D.
Working Pressure	90 PSI
Air Inlet	

AF6008 7 inch Angle Sander



Lightweight and powerful. Used for removing rust, smoothing body filler and general sanding. Two spanners included.

Specifications:

4500 RPM
7"
12 CFM @ 90 PS
3/8" I.D. Minimum
1/4" NPT
5/8" - 11" UNC

Cutting & Punching

AF1001 150mm Air Hammer with 4 Chisels



Contoured one piece polished aluminum housing for comfortable grip. Positive action trigger and built in regulator for easy speed and power control. Quick change spring for easy chisel changes. This unit is ideal for muffler and tail pipe removal, spot weld busting, panel cutting and a host of other jobs. Includes punch, ripping chisel, cold chisel and panel cutter.

Specifications:

Blows per Minutve	4500
Bore	3/4"
Stroke	1-5/8
Air Inlet Size	1/4" NPT
Hose Size	3/8" I.D.
Working Pressure	90 PSI
Air Consumption	4 CFM
Length	5-1/4v

AF2065 4 piece Air Chisel Set



Four piece air chisel set includes flat chisel, tapered punch, panel cutter and weld buster with 0.401" round shank size. For use with Mark 1 AF1001, AF1001-2, and most other 0.401" round nozzle air hammers.

AF1001-ACC Spring Retainer

For use with AF1001, AF1001-2 and most other air hammers.



AF1008 **16 gauge Air Nibbler**



This ultra-light tool weighs just over 2 lbs. and cuts through 16 gauge mild steel without deforming the sheet or leaving a burr. Die adjusts for cutting forward, backward, right or left. Ideal tool for metal fabrication.

Specifications:

Cutting Capacity (Thickness)	
Steel	1/16"
Aluminum	5/64"
Free Speed	3,500 SPM
Air Consumption	4 CFM
Air Pressure	90 PSI
Air Inlet Size	1/4" NPT
Hose Size	3/8" I.D.

AF1008P Air Nibbler Punch – Hardened alloy steel punch for clean cuts and long life.

AF1008D Air Nibbler Die – Hardened alloy steel die for clean, smooth cutting and long life.

OEM Parts and Products

Trade Associates
sources and delivers
parts and finished
products around the
world under private
brand names which are
widely known. If you
need a part made to your
specifications or have a
product you want
produced, packaged and
delivered to your
warehouse.

Call us! 253-854-0090

Our Worldwide Network of suppliers and inspectors deliver the best products available.

Grinders

High Speed Mini Grinder



This extremely versatile tool is complete with 1/8" and 1/4" Collets. Accepts a wide variety of bits including Black & Decker, Dremel and others readily available. Lever throttle for positive speed control. All ball bearing for smooth operation and long life. Suitable for a wide variety of grinding operations.

Specifications:

Collet	1/4" & 1/8"
Free Speed	18,000 RPM
Recommended Air Pressure	90 PSI
Avg. Air Consumption	8 CFM
Air Inlet	1/4" NPT
Hose Size	3/8" I.D.
Length	5-1/2"
Weight	0.9 lbs

AF6007 4 inch Angle Grinder

Lightweight and powerful. Use for removing rust, smoothing welds and general deburring. Two



spanners included. Grinding wheel included.

Specifications:

Free Speed	11,000 RPM
Wheel Size	4"
Air Requirement	6 CFM @ 90 PSI
Hose Size	3/8" I.D. Minimum
Air Inlet	1/4" NPT
Spindle Size	3/8" - 24 UNF

AF1045 10 Piece Mounted Stone Set



For use with Mark 1 AF1004 Mini Die Grinder. For grinding, polishing, carving and burning. Made of aluminum oxide. Completed with 5 piece 1/4" mounted stone and 5 piece 1/8" shank mounted stone.

AF2000 Air Mini Die Grinder



Designed for general purpose use, such as grinding, polishing, and deburring This lightweight and compact air die grinder is versatile and economical. Includes safety trigger.

Specifications:

Free Speed	27,000 RPM
Average Air Consumption	3.0 CFM
Air Inlet	1/4" NPT
Collet Size	1/4"
Minimum Hose Size	3/8" I.D.
Length	4-3/4"

AF2001K Mini Angle Die Grinder Kit



Contains:

- 1 AF2001 1/4" Mini Angle Die Grinder
- 1 1/8" Collet
- 5 1/4" Shank Mounted Stones
- 5 1/8" Shank Mounted Stones
- 2 Spanners
- 1 Blow Molded Storage Case See specifications for AF2001 above.

AF2001 Mini Die Grinder




Angle head design allows access to hard to reach areas. Designed for general purpose use such as grinding, polishing, and deburring. Includes safety trigger.

Specifications:

Free Speed	20,000 RPM
Average Air Conumption	3.0 CFM
Air Inlet	1/4" NPT
Collet Size	1/4"
Minimum Hose Size	3/8" I.D.
Length	5"

AF2013BK Air Angle Die grinder Kit



Contains:


- 1 AF2013B 1/4" Air Angle Die Grinder
- 1 1/8" Collet
- 5 1/4" Shank Mounted Stones
- 5 1/8" Shank Mounted Stones
- 2 Spanners
- 1 Blow Molded Storage Case

In-Stock Now

This kit includes one full-size and one micro-size HVLP Gravity Feed Spray Gun, a regulator, one 600cc aluminum cup, one 250cc aluminum cup, and a durable blow molded carrying case. All spray guns have anti-drip nozzles, material sieves, stainless steel needles and nozzles, self-adjusting needle packing, independant air control and fluid adjustments. Also includes cleaning kit.

Features:

Full-Size Spray Gun with 1.4mm nozzle Micro-Size Spray Gun with 1.0mm nozzle Blow Molded Carrying Case 600cc Aluminum Paint Cup 250cc Aluminum Paint Cup Air Regulator Cleaning Kit



AK1000 - HVLP SPRAY GUN KIT

This professional spray gun kit includes three full-size HVLP Gravity Feed Spray Guns, one micro HVLP Gravity Feed Spray Gun, and one regulator. All guns feature anti-drip nozzles, material sieves, stainless steel needles and nozzles, self-adjusting needle packing, independant air control and fluid adjustment.

Also includes cleaning kit, 1000cc & 250cc aluminum cups, plus five

"Cup Eliminator" 500cc disposable plastic paint cups.





Impact Wrenches &

AF1003 1/2 inch Air Impact Wrench



This high quality unit is built for years of dependable service. Built in regulator allows for torque settings: 230, 215, 195 and 150 ft. lbs. of torque. Push-pull reversing lever for easy operation.

Specifications:

Bolt Capacity	5/8"
Drive	1/2"
Maximum torque	230 ft. lbs.
Air Inlet	1/4" NPT
Overall Length	7"
Air Consumtion	4 CFM
Air Pressure	90 PSI
Free Speed	7000 RPM

AF3002 Heavy Duty 1/2 Inch Air Impact Wrench



Dynamic pin clutch design develops up to 380 ft. lbs. of torque. Alloy steel anvil and steel clutch housing. Dependable built in power regulator. Contoured grip with ballanced weight distribution reduces operator fatigue.

Specifications:

Bolt Capacity	3/4"
Drive	1/2"
Torque	350 ft. lbs.
Maximum Torque	380 ft. lbs.
Overall Length	7"
Air Consumption	5.5 CFM
Air Pressure	90 PSI
Free Speed	7000 RPM
Air Inlet Thread Size	1/4" NPT
Hose Size	3/8" I.D.

AF3001 Heavy Duty 3/4 inch Air Impact Wrench



Specifications:

opoomounomon	
Drive	3/4"
Bolt Capacity	1"
Free Speed	4200 RPM
Blows per Minute	1000
Working Torque	700 ft. lbs.
Ultimate Torque	800 ft. lbs.
Air Consumption	7.5 CFM
Air Pressure	90 PSI
Air Inlet	1/4" NPT
Hose Size	3/8" I.D.

AF6002 3/8 inch Pistol Grip Imact Wrench

Rocking dog clutch delivers dependable power and durability. Convenient forward and reverse lever for single-handed operation. Built-in regulator, ring socket retainer and comfortable contoured aluminum handle.

Specifications:

Free Speed	9000 RPM
Maximum Torque	100 ft. lbs.
Air Inlet	1/4" NPT
Air Consumption	3 CFM @ 90 PSI
Hose Diameter	3/8: minimum

AF2064 Flip Socket with Extension Bar

Air impact Flip socket with Extension allows quick changes between 3/4" and 13/16" nut size. For use with Mark 1 AF1003, AF3002 and most other 1/2" impact





wrenches. Chrome vanadium steel and heat treated. Professional Quality.

11 piece Impact Sockets

AF2503 - Metric sizes: 11mm, 12mm, 13mm, 14mm, 16mm, 17mm, 19mm, 21mm, 22mm, and 24mm



AF2502 - S.A.E. sizes: 7/16", 1/2", 9/16", 5/8", 11/16", 3/4", 13/16", 7/8", 15/16", 1"

9 piece Impact Sockets

AF2513 - SAE Sizes: 3/8", 7/16", 1/2", 9/16", 5/8", 11/16", 3/4", 13/16", 1"



AF2514 - Metric sizes: 10mm, 11mm, 12mm, 13mm, 14mm, 16mm, 17mm, 19mm.



12 piece Impact Socket Sets

AF2515 - SAE size: 3/8", 7/16", 1/2", 9/16", 5/8", 11/16", 3/4", 13/16",7/8", 15/16", 1"

AF2516 – Metric sizes: 10mm, 11mm, 12mm, 13mm, 14mm, 16mm, 17mm, 19mm, 21mm, 22mm, 24mm.

AF7808 17 Piece Air Tool Kit -Air Impact Wrench & Sockets



Includes: 1/2" air impact wrench, 10 impact sockets, blow molded carrying case, 5" extension bar, oil pot, hex wrench, mini-oiler, and nipple.

Socket Sizes: 7/16", 1/2", 9/16", 5/8", 11/16", 3/4", 13/16", 7/8", 15/16", 1"

Ratchet Wrenches

AF1007A 1/4 inch Air Speed Ratchet Wrench

Ideal for trim, motorcycles and other smaller jobs. This unit features button throttle, rear exhaust, ball bearing construction and is fully reversible.



Specifications:

5/16"
1/4"
3 CFM
90 PSI
1/4" NPT
240 RPM
15 ft. lbs.
5/16" ID
8"

AF1006B 3/8 inch Air Ratchet Wrench

Only 6-1/2" overall length makes this tool a must for use in tight spots. Reversible. Positive socket retention. Fast 250 RPM with 20 ft. lbs. torque. The perfect tool for light assembly, bicycle and other repairs.



Specifications:

Bolt Capacity	5/16"
Drive	
Air Consumption	3 CFM
Air Pressure	
Air Inlet	1/4" NPT
Free Speed	250 RPM
Maximum Torque	
Length	
- 0-	

AF1009-6 3/8 inch Butterfly Air Impact Wrench



This versatile tool allows immediate forward and reverse, as well as speed control without taking your hands off the work. Eight torque settings. Swivel air inlet and compact size allow easy access to tight spots.

Socket Sets sold separately.

Specifications:

opoomouno	
Drive	3/8"
Free Speed	10,000 RPM
Maximum Torque	75 ft. lbs.
Air Inlet	1/4" NPT
Overall Length	5-1/2"
Air Consumption	3.0
Air Pressure	90 PSI
Net Weight	1-3/4 lbs.

AF5001A 3/8 inch Stubby Air Ratchet

Only 6-1/2" overall length makes this tool a must for use in tight spots. Reversible. Positive socket retention. Fast 250 RPM with 20 ft. lbs. torque. The perfect tool for light assembly, bicycle and other repairs.



Specifications:

opoomounono	
Bolt Capacity	5/16"
Drive	
Air Consumption	3 CFM
Air Pressure	90 PSI
Air Inlet	1/4" NPT
Free Speed	250 RPM
Maximum Torque	20 ft. lbs.
Length	6-1/2"

AF1062 - 62 Piece Air Tool Kit



3/8" Ratchet Wrench
1/2" Impact Wrench
150mm Air Hammer
10 1/2" Drive Sockets: 12mm, 13mm, 15mm,
16mm, 17mm, 1/2", 9/16", 5/8", 3/4", 13/16"
3" Extension, 1/2" Drive
3/8" - 1/2" Socket Adapter
3/8" Drive Bit Adapter
Blow Gun
Safety Nozzle
Inflator Nozzle

Inflator Nozzle
Inflation Needle
Blow Gun Adapter
Rubber Blow Gun Tip
Blow Gun Nozzle
Thread Seal Tape
Mini Oiler

3x Phillips (#1, #2, #3) 5x Torx (T15, T20, T25, T27, T30) 3x Flat (3/16, 1/4, 1/8) 6x Hex (4mm, 5mm, 1/8", 5/32", 3/16", 1/4") 3x Square (S1, S2, S3) 5x 1/4" Industrial Plug--1/4" Male NPT Air Chuck - 1/4" Female NPT 3 Chisels - Punch, Flat, Weld Hex Nipple -1/4" Male PT Hex Connector -1/4" Female NPT Tire Gauge - 10-50 PSI 1/4" Industrial Coupler -1/4" Female NPT 1/4" Swivel Connector 4mm Hex Wrench Spring Retainer Blow Molded Carrying Case

Cutting & Punch Tools

AF1022 Air Utility Cut-Off Tool



hangers, sheet metal, radiator hose clamps, rusted bumper bolts, and steel rods up to 3/4" thick. Standard equipment includes an abrasive 3" disc, independent power regulator, and features a hand guard trigger.

Specifications:

Wheel Diameter	3"
Free Speed	18,000 RPM
Air Consumption	4 CFM
Operating Pressure	90 PSI
Net Weight	1-5/8 lbs.
Overall Length	6"
Air Inlet Size	1/4" NPT
Minimum Hose Size	3/8" I.D.

AF1022A & AF1022E Aluminium Oxide Disk Assortment



AF1022A – 2 Piece Aluminum Oxide Disk: For use with AF1022 Utility Cut-Off Tool. Constructed of 2 fiberglass layers specially coated for added strength. Maximum safe speed 20,000 RPM. Size: 3" dia by 1/16" with 3/8" hole. *Imported*

AF1022E – 4 Piece Assorted Disks: For use with AF1022 Utility Cut-Off Tool. Constructed of 2 fiberglass layers, specially coated for added strength,. Maximum safe speed 20,000 RPM. Size 3" diameter by 1/16" with 3/8" hole.

Contains:

- 1 Aluminum Oxide Disk: For cutting sheet metal, bolts, sanding, leveling and trimming corners.
- 1 Silicone Carbide Disk: For fine cutting of natural and artificial stone.
- 1 White Aluminum Oxide Disk: For cutting steel and stainless steel.
- 1 Green Silicon Carbide Disk: For cutting natural and artificial stone.

A5004 **Air Body Saw**

Makes one handed cuts in tight places easy. Built in regulator allows positive speed control. Adjustable blade guard controls depth of cut. Cuts flat or curved surfaces, up to 1.6 mm mild steel or aluminum, plastic, fiberglass and other materials. Includes blade wrench and 4 blades.



Specifications:

Free Speed	10,000 SPM
Average CFM	8 CFM
Air Inlet	1/4" NPT
Stroke	3/8"
Air Pressure	90 PSI
Hose Size	3/8" I.D.

AF5003 Air Punch & Flange Tool

Ideal tool for auto-body and metal working. Allows creation of flanged edge for smooth joints. Reduces use of body putty and creates a truly professional finish. Punch makes bolt holes easy. 14 gauge capacity.



Specifications:

Capacity-flange	14 gauge
Capacity-punch	14 gauge
Air Consumption	4.0 CFM
Air Inlet	1/4" NPT
Hose Size	3/8" I.D.
Air Pressure	90 PSI
Punch Hole Size	3/16 ID

AF6006 Metal Shear, Pistol Type

Cut sheet metal cleanly and without distorted edges.



Specifications:

2200 SPM
3/64" (1.2mm)
1/16" (1.6mm)
360 degrees
4 CFM @ 90 PSI
3/8" I.D. Minimum
1/4" NPT
7/32" (5.5mm)

AF6009 Straight type Air Needle Scaler

Chip concrete and brick easily. Clean castings, scale and paint and rust.



Specifications:

4500BPM
3mm x 180mm (1)x19 pcs
10 CFM@ 90 PSI
3/8" I.D.
1/4: NPT

AF6010 Weld Flux Scaler

Ideal for fabrication shops, removing weld flux, scale and other cleaning operations. Chisels not included.



Specifications:

Blows pre Minute	4500 BPM
Working Pressure	90 PSI
Air Consumption	8 CFM
Hose Size	3/8" I.D.
Air Inlet	1/4" NPT
Chisel Size	1/2" square

Drills & Screwdrivers

AF1002B 3/8 inch Planetary Gear Air

Comfort contoured handle eliminates operator fatigue. Handle exhaust directs air away from work.



to 2.200 RPM chuck speed through specially designed planetary idler gears producing even application of torque. Ball bearing construction. Ideal for all general purpose drilling. Includes 3/8" U.S. Jacobs chuck for accuracy.

Specifications:

Chuck Size	3/8"
Spindle Thread	3/8"-24 UNF
Free Speed	2200 RPM
Air Inlet	1/4" NPT
Air Consumption	4 CFM
Working Pressure	90 PSI

AF6001 3/8 inch Reversable Drill

Ideal for tough jobs. A great tool for drilling, honing, wire brushing and reaming. Convenient side switch allows single-handed changes in direction. Three geared drive system for added power.



Specifications:

Free Speed	1800 RPIV
Chuck Size	
Air Inlet	1/4" NPT
Spindle Thread	3/8"-24 UNF
Hose Diameter	3/8" I.D. minimum
Air Consumption	4 CFN

AF5009 1/2 inch Reversible Air Drill

Pistol grip reversible drill with side handle (not shown). This is truly a professional unit. Complete with precision U.S. Jacobs chuck. Low speed, high torque delivers the power for hard drilling.



Specifications:

Free Speed	500 RPM
Spindle Thread	3/8" -24 UNF
Air Consumption	4 CFM
Air Inlet	1/4" NPT
Air Pressure	90 PSI
Chuck Size	1/2"

AF5005 Twin Hammer Air Impact Screwdriver



sheet metal, wood and other materials. Combines a fast 700 RPM with 110 in. lbs. of torque for a fast, powerful tool. Impact mechanism drives screws where ordinary drivers can't.

Specifications:

•	
Free Speed	500RPM
Shank	1/4"
Screw Capacity	5-6mm
Torque	110in. lbs.
Air Consumption	4 CFM
Air Pressure	90 PSI
Air Inlet	1/4" NPT

AF5008 Air Screw Driver Straight-Reversible

The most convenient assembly tool you can buy. Push-on, auto-off operation. Fast and efficient. Used in factories, assembly plants and other continuous use applications. Adjustable clutch gives you the exact torque you want each and every time.



Specifications:

Free Speed	1100 RPM
Shank	1/4"
Screw Capacity	2-3mm
Minimum Torque	10-18 in. lbs.
Air Consumption	2.5 CFM
Air Pressure	90 CFI
Air Inlet	1/4" NPT

AF6005 1/4 inch Screwdriver

Pistol type tool drives screws and tightens nuts to the desired torque. Torque adjustment from 45 to 115 inch pounds. Reversible.



Specifications:

Free Speed	1800 RPM
Bit Size	1/4" shank
Torque	45 to 115 in. lbs.
Air Consumption	4CFM @ 90 PSI
Hose Size	3/8" I.D. minimum
Air Inlet	1/4" NPT

OEM Parts and Products

Trade Associates sources and delivers parts and finished products around the world under private brand names which are household words. If you need a part made to your specifications or have a product you want produced, packaged and delivered to your warehouse.

Call us! 253-854-0090

Accessories

AF1016 Air Filters

This filter removes unwanted dust, water and other impurities in compressed air. One of the major contributers to air tool breakdowns is dirt. This is vital to safeguarding your investment in tools. Proper filtering of your air supply improves tool performance and extends the life of the tool.



Specifications:

Pipe Diameter	3/8" NPT
Maximum Pressure	150 PSI
Temperature	20° F to 125° F

AF1030 Water and Oil Seperaror

Removes unwanted dust, water and oil from air lines with very little pressure reduction. Useful in spraying and painting applications. For use with Mark 1 Air Spray Gun and other high pressure spray guns and air tools. This simple device is easily attached between your spray gun or air tool and the air line.



Specifications:

Air Inlet/Outlet1	/4"	NPT
-------------------	-----	-----

AF1021 Air Regulator & Gauge

1/4" (M) x 1/4" (M) Adapter included.



1 //" NIDO (NA) :--

Specifications:

Inread size	1/4" NPS (IVI) IN
	1/4" NPS (F) out
Air Inlet	1/4" NPT
Max. Working Pressure	135 PSI

AF1012 Mini In-Line Oiler

This 1/4 inch NPT Mini In-line oiler is portable and convenient. Feeds lubrication directly into your air line for longer tool life and improved efficiency. Protect your tools against rust and failure.



Thread	Size	1/4"	NPT

RAH25 1/4 inch by 25 foot Recoil Hose

Extends to 25 feet vet recoils compactly to store out of the way. Ideal for over head applications and in assembly work. This quality hose handles up to 200 PSI. 1/4" NPT Brass fittings.

Specifications:

Air Inlet	1/4" NPT
Max. Working Pressure	135 PSI

AF1041 2-1/2 foot Whip Hose with **Swivel**

Allows free movement of tool without strain on coupler, tool or hose.

Reccomended for all air tools. Relieves strain on the inlet bushing for longer life. Makes tools easy to use for less operator fatigue. Handles up to 200 PSI working pressure, with 1/4" NPT air inlet. Extends tool and hose life. 1 piece per card.

Specifications:

Air Inlet	1/4: [NPT
Max. Working Pressure	200	PSI

AF1049 **Brass Air Regulator**

Useful accessory for control of air flow to tools and accessories. Solid brass construction. 1/4" NPT Threads.



Specifications:

Thread Size 1/4" NPT

AF2061 Pressure Gauge



Specifications:


Range1	60 PSI
Male, back mount1	

AF2068 3/8 Inch Male Hose **Connector**

3/8" NPT (M) x 3/8" NPT (M) male hose connector. Commonly used to connect hoses with 3/8" NPT (F) fittings. Two pieces per card. Solid brass.



AF2066 1/4 inch Hose **Connectors**



AH2067 1/4 inch Hose **Connectors**



1/4" NPT (M) x 1/4" NPT (M) male hose connector. Commonly used to connect hoses with 1/4" NPT (F) fittings. Two pieces per card. Solid brass.

AF2063 **Brass Adapter**



3/8" NPT (F) x 1/4" NPT (M). Reduces 3/8" NPT (M) thread to 1/4' NPT (M) thread. Ideal for connecting 3/8" NPT (M) air hose fitting to tools with 1/4" NPT (F) inlet. Solid brass.

Solid Polished Brass Couplers



AF22B - 5 Piece Brass Coupler Set. Male Quick Connect, 1/4" NPT Outside thread. Male Quick Connect, 1/4" NPT, Inside thread. Female Quick Connect, 1/4" NPT.

AF1031 Heavy Duty Tire Inflator with Gauge

In-line gauge measures from 10 to 120 lbs. in 2 lb. increments. Weather-proof aluminum body with corrosion-resistant brass valve. Two steel washers for air-tight seal. 6" chromeplated steel dual chuck. Extension cap that fits most rim cover holes, 1/4" female NPT.

Accessories

AF0055 17 Piece Pneumatic Accessory Set



This accessory assortment contains items needed daily. These are the items you always need, but can never find. Everything from A to Z in accessories.

Contains:

- 1 Blow Gun 1/4" NPT
- 1 Tapered Rubber Inflator
- 1 High Pressure Nozzle
- 1 Tapered Brass Hose Nozzle
- 1 Safety Nozzle/Adapter
- 1 Bronze Inflator Needle
- 2 Universal Adapters 1/4" NPT
- 1 Dual Tire Chuck
- 1 Air Gauge 120 PSI
- 2 Female Connectors 1/4" NPT
- 2 Male Connectors 1/4" NPT
- 2 Female Quick Coupler 1/4" NPT
- 1 Power Wire Brush 4-1/2"



This handy accessory comes with both a high velocity vnozzle and a threaded standard nozzle. 1/4" NPT female threads.

AF1036 Female Air Chuck

Used for filling auto, truck and bicycle tires.

1 Piece per card. 1/4" NPT.



AF2060 **Dual Foot Air Chuck**



AF1017 Engine Cleaning Gun

This Engine
Cleaning gun
is ideal for
general cleaning.
A wide variety of



solvents and degreasers may be used for a multude of jobs. 4' suction tube included.

Specifications:

Air Inlet......1/4" NPT

AF2064 Flip Socket with Extension Bar

Air impact Flip socket with extention bar allows quick changes between 3/4" and 3/16" nut size. For use with Mark1



AF1003, AF3002 and most other 1/2" impact wrenches. Chrom vandium steel and heat treated. Professional quality.

AF3003 Flip Socket

1/2" Drive Flip Impact Socket For Lug Nuts



9 piece 3/4 Inch Drive Impact Socket Sets



AF834-(SAE sizes)

Contains 3/4", 13/16", 7/8", 5/16", 1", 1-1/16", 1-1/8", 1-1/4" in a sturdy metal case.

AF835-(Metric sizes)

(Metric sizes) Contains 19mm, 21mm, 24mm, 26mm, 27mm, 29mm, 30mm, 32mm in a sturdy

AF1001-ACC Spring Retainer

For use with AF1001, AF1001-2 and most other air hammers.



AF1018/AF1018N Heavy Duty Sand Blaster Kit

AF1018- This tough precision crafted tool is perfect for removing rust, spray cleaning parts, etching glass and many other applications. Its special design allows for quick and efficient sand blasting as well as liquid or air cleaning.



Contains:

- 1 Gun
- 1 10' Rubber Hose
- 1 Long Wearing Ceramic Nozzle
- 1 Aspirator Tube
- 3 Orifices: 1/8", 3/32", 5/64"
- · Hex Wrench and Packing

AF1018N- Ceramic Tips for AF1018 Long wearing replacement nozzles for AF1018 Air Sand Blaster Kit. Two pieces.



AF1022A & AF1022E Aluminium Oxide Disk Assortment



AF1022A – 2 Piece Aluminum Oxide Disk: For use with AF1022 Utility Cut-Off Tool. Constructed of 2 fiberglass layers specially coated for added strength. Maximum safe speed 20,000 RPM. Size: 3" dia by 1/16" with 3/8" hole. *Imported*

AF1022E – 4 Piece Assorted Disks: For use with AF1022 Utility Cut-Off Tool. Constructed of 2 fiberglass layers, specially coated for added strength, Maximum safe speed 20,000 RPM. Size 3" diameter by 1/16" with 3/8" hole.

Contains:

- 1 Aluminum Oxide Disk: For cutting sheet metal, bolts, sanding, leveling and trimming corners.
- 1 Silicone Carbide Disk: For fine cutting of natural and artificial stone.
- 1 White Aluminum Oxide Disk: For cutting steel and stainless steel.
- 1 Green Silicon Carbide Disk: For cutting natural and artificial stone.

RC AERODYNE

PRECISION ENGINEERED MICRO-AVIATION PRODUCTS



SCALE HELICOPTER FUSELAGES

ARF SCALE AIRPLANES

HIGH QUALITY MECHANICS

ROTOR HEADS

LED LIGHTING SYSTEMS

Gyroscopes & Batteries

Assembly Tools

WWW.SCALEFLYING.COM

600 SIZE FUSELAGES - INCLUDES SCALE COCKPIT & LED LIGHTING SYSTEM



EUROCOPTER FENNEC AS350 CIVILIAN FUSELAGE

LENGTH: 54.5" WIDTH: 9" HEIGHT: 9.75" MAIN SHAFT TO TAIL ROTOR HOUSING: 32" MAIN SHAFT TO BACK SEAT: 7.5"

\$349.00



EUROCOPTER FENNEC AS550 MILITARY FUSELAGE

LENGTH: 54.5" WIDTH: 9" HEIGHT: 9.75" MAIN SHAFT TO TAIL ROTOR HOUSING: 32" MAIN SHAFT TO BACK SEAT: 7.5"

\$389.00



AGUSTAWESTLUND AW-109 Civilian Fuselage

LENGTH: 57.5" WIDTH: 8.5" HEIGHT: 10.75"
MAIN SHAFT TO TAIL ROTOR HOUSING: 31.5"
MAIN SHAFT TO BACK SEAT: 7.5"

\$369.00



AGUSTAWESTLUND AW-109 MILITARY FUSELAGE

LENGTH: 57.5" WIDTH: 8.5" HEIGHT: 10.75"
MAIN SHAFT TO TAIL ROTOR HOUSING: 31.5"
MAIN SHAFT TO BACK SEAT: 7.5"

\$389.00

AGUSTAWESTLUND AW-109 COAST GUARD FUSELAGE

LENGTH: 57.5" WIDTH: 8.5" HEIGHT: 10.75"
MAIN SHAFT TO TAIL ROTOR HOUSING: 31.5"
MAIN SHAFT TO BACK SEAT: 7.5"

\$389.00



EUROCOPTER FENNEC AS350 BLACK OPS FUSELAGE

LENGTH: 54.5" WIDTH: 9" HEIGHT: 9.75" Main Shaft to Tail Rotor Housino: 32" Main Shaft to Back Seat: 7.5"

\$349.00

500 SIZE FUSELAGES



MD HELICOPTERS MD 530

MILITARY FUSELAGE

LENGTH: 34.5" WIDTH: 6.25" HEIGHT: 9.5"
MAIN SHAFT TO TAIL ROTOR SHROUD: 22+"

\$189.00



EUROCOPTER EC 135

MEDIC FUSELAGE

LENGTH: 38.5" WIDTH: 5.75" HEIGHT: 9"
MAIN SHAFT TO TAIL ROTOR SHROUD: 23"

\$199.00



EUROCOPTER EC 135

CIVILIAN FUSELAGE

LENGTH: 38.5" WIDTH: 5.75" HEIGHT: 9"
MAIN SHAFT TO TAIL ROTOR SHROUD: 23"

\$199.00

TRADE ASSOCIATES, INC. 6324 S. 199th Place, Suite 101 Kent, WA 98032 USA

www.dura-block.com www.scaleflying.com phone: 253-854-0090 email: orderdesk@dura-block.com