



PRODUCTS

Effective September 2010

CUSTOMERS FIRST. ALWAYS.

PARTNERING FOR SUCCESS

Our dedication to lifting you higher extends well beyond the physical reach of our products. We thrive on building satisfying customer relationships founded on the idea of partnership. Because you, our customer, are at the center of everything we do.

Since 1966, we've been developing products to solve your worksite challenges — and that process never ends. Our team of product managers and engineers uses your input to design new products, featuring the latest technology to meet your changing needs. Then we manufacture those products to stringent standards that help increase quality, lower costs and give you exceptional value for years to come.

PROVIDING SUPERIOR VALUE

Our commitment doesn't end with the sale. Our dedicated service teams are available 24 hours a day, 365 days a year to provide support when you need it most. Our extensive parts network ships most parts within 24 hours, too. Simply put, we're always working to help maximize your "up time" so you can be more successful.

Genie is driven by one goal: doing the right thing, at the right time for our customers. That's not just what we do; it's who we are. So tell us what you need. We're listening.

MATERIAL LIFTS

Material Lifts

Lift, lower or move heavy loads in a variety of applications.

- Sturdy construction, reliable performance and ease of use make these lifts favorites on a wide variety of job sites.
- These versatile lifts offer a large selection of models and options providing the opportunity to create just the lift you need.



Super Hoist™ | 3.8, 5.6

LIFT HEIGHT	12 ft 5.6 in – 18 ft 4.5 in	3.80 m – 5.60 m
LIFT CAPACITY	250 – 300 lbs	113 – 136 kg
WEIGHT*	75 – 82 lbs	34 – 37 kg

Genie® Super Hoist™ (GH™) portable telescoping pneumatic hoist uses compressed air to lift up to 300 lbs (136 kg) to heights of 12 ft 5.6 in (3.8 m) or up to 250 lbs (113 kg) up to 18 ft 4.5 in (5.60 m).



Load Lifter™

LIFT HEIGHT	5 ft 7 in	1.70 m
LIFT CAPACITY	200 lbs	91 kg
WEIGHT*	65 lbs	29 kg

The Genie® Load Lifter™ (LL™) lifts up to 200 lbs (91 kg) to a height of 5 ft 7 in (1.70 m). Stores easily with compact dimensions of 45 x 15 x 20.5 in (1.10 m x 38 cm x 52 cm).



Genie® Lift™ | 4, 8, 10, 12

LIFT HEIGHT	5 ft 11 in – 13 ft 9.5 in	1.80 m – 4.20 m
LIFT CAPACITY**	350 – 500 lbs	159 – 227 kg
WEIGHT*	113 – 433 lbs	51 – 196 kg

** With 12 in (30 cm) load center.

The Genie® Lift™ (GL™) lifts up to 500 lbs (227 kg) to heights of up to 13 ft 9.5 in (4.20 m). Customize the GL™ for your job with three bases, various load handling attachments and optional tires and ladders.

* Weight may vary depending on options and/or country standards.



Compact Options for Every Load

For handling all your lifting needs faster and easier, these heavy-duty material lifts can be operated by one person who can easily lift, lower and move loads.

MATERIAL LIFTS



Superlift Contractor® | 12, 18, 24

LIFT HEIGHT	11 ft 2 in – 24 ft	3.40 m – 7.32 m
LIFT CAPACITY**	650 lbs	296 kg
WEIGHT*	225 – 347 lbs	102 – 157 kg

** With 14 in (36 cm) load center.

The Genie® Superlift Contractor® (SLC™) lifts 650 lbs (295 kg) to heights of up to 24 ft (7.32 m). Designed for the construction industry, the SLC™ offers extreme durability and easy transport.



Superlift Advantage® | 5, 10, 15, 20, 25

LIFT HEIGHT	4 ft 10.5 in – 26 ft .5 in	1.49 m – 7.94 m
LIFT CAPACITY**	650 – 1000 lbs	296 – 454 kg
WEIGHT*	215 – 450 lbs	98 – 204 kg

** With 18 in (46 cm) load center.

The Genie® Superlift Advantage® (SLA™) is a manually operated material lift with multiple bases and load handling options. It lifts up to 1,000 lbs (454 kg) of material to heights of up to 11 ft 5.5 in (3.49 m) and up to 650 lbs (295 kg) to heights of 26 ft .5 in (7.94 m).



Super Tower™ | 20, 25

LIFT HEIGHT	19 ft 6 in – 26 ft .5 in	5.94 m – 7.94 m
LIFT CAPACITY**	650 – 800 lbs	295 – 363 kg
WEIGHT*	507 – 555 lbs	230 – 252 kg

** With 18 in (46 cm) load center.

The Genie® Super Tower™ (ST™) telescopes theatrical lighting and scenery weighing up to 800 lbs (363 kg) and can lift to heights of up to 26 ft .5 in (7.94 m). Standard flat black anodized finish lets the ST™ blend in backstage.



Ready to Work

Heavy-duty design, yet light-weight and portable. Genie® material lifts are quick to set up, require no tools and are ready to work in seconds.



The Ultimate Stage Hand

Lifts and supports lighting systems, sound systems and stage scenery.

AERIAL WORK PLATFORMS

Aerial Work Platforms

Economical solution for all of your access needs.

- Choose from compact, rough terrain, standard or wide base models that lift one or two people.
- All models offer quick setup and excellent maneuverability.
- Perfect for schools, churches, warehouses and more.

AWP™-20S

WORKING HEIGHT	26 ft 1 in	8.12 m
PLATFORM HEIGHT	20 ft 1 in	6.12 m
LIFT CAPACITY	350 lbs	159 kg
POWER	AC or DC	
WEIGHT*	660 – 766 lbs	299 – 347 kg

AWP™-25S

WORKING HEIGHT	30 ft 10 in	9.57 m
PLATFORM HEIGHT	24 ft 10 in	7.57 m
LIFT CAPACITY	350 lbs	159 kg
POWER	AC or DC	
WEIGHT*	694 – 817 lbs	315 – 371 kg

AWP™-30S

WORKING HEIGHT	35 ft 6 in	11.00 m
PLATFORM HEIGHT	29 ft 6 in	9.00 m
LIFT CAPACITY	350 lbs	159 kg
POWER	AC or DC or air motor power	
WEIGHT*	729 – 867 lbs	331 – 393 kg

AWP™-36S

WORKING HEIGHT	42 ft 5 in	13.10 m
PLATFORM HEIGHT	36 ft 5 in	11.10 m
LIFT CAPACITY	350 lbs	159 kg
POWER	AC or DC	
WEIGHT*	1,017 – 1,107 lbs	461 – 502 kg

AWP™-40S

WORKING HEIGHT	46 ft 4 in	14.29 m
PLATFORM HEIGHT	40 ft 4 in	12.29 m
LIFT CAPACITY	300 lbs	136 kg
POWER	AC or DC	
WEIGHT*	1,040 – 1,130 lbs	472 – 513 kg

IWP™-20S

WORKING HEIGHT	26 ft 6 in	8.24 m
PLATFORM HEIGHT	20 ft 6 in	6.24 m
LIFT CAPACITY	350 lbs	159 kg
POWER	AC or DC	
WEIGHT*	1,245 – 1,345 lbs	565 – 610 kg

IWP™-25S

WORKING HEIGHT	30 ft 5 in	9.44 m
PLATFORM HEIGHT	24 ft 5 in	7.44 m
LIFT CAPACITY	350 lbs	159 kg
POWER	AC or DC	
WEIGHT*	1,290 – 1,390 lbs	585 – 630 kg

IWP™-30S

WORKING HEIGHT	35 ft 6 in	11.00 m
PLATFORM HEIGHT	29 ft 6 in	9.00 m
LIFT CAPACITY	350 lbs	159 kg
POWER	AC or DC	
WEIGHT*	1,430 – 1,530 lbs	649 – 694 kg

DPL™-25S

WORKING HEIGHT	31 ft 4 in	9.70 m
PLATFORM HEIGHT	25 ft 4 in	7.70 m
LIFT CAPACITY	750 lbs	340 kg
POWER	AC or DC	
WEIGHT*	1,371 – 1,493 lbs	622 – 677 kg

DPL™-30S

WORKING HEIGHT	36 ft	11.14 m
PLATFORM HEIGHT	30 ft	9.14 m
LIFT CAPACITY	750 lbs	340 kg
POWER	AC or DC	
WEIGHT*	1,474 – 1,589 lbs	669 – 721 kg

DPL™-35S

WORKING HEIGHT	40 ft 10 in	12.62 m
PLATFORM HEIGHT	34 ft 10 in	10.62 m
LIFT CAPACITY	600 lbs	272 kg
POWER	AC or DC	
WEIGHT*	1,574 – 1,789 lbs	714 – 811 kg

* Weight will vary depending on options and/or country standards.

Doorway Access

Most aerial work platforms easily roll through standard doorways. The larger AWP™ models have a tilt-back system that allows easy access through doors.

RUNABOUTS & QUICKSTOCKS



Streamlining Inventory Management

The Genie® QuickStock™ (QS) lift is designed to make your inventory picking faster, easier and safer than rolling stairs or manually propelled lifts.

QS™-12



WORKING HEIGHT	17 ft 5 in	5.48 m
PLATFORM HEIGHT	11 ft 5 in	3.48 m
LIFT CAPACITY	500 lbs	227 kg
POWER	24 V (four 6 V 200 Ah batteries)	
WEIGHT*	1,581-1,609 lbs	717-730 kg

QS™-15



WORKING HEIGHT	20 ft 8 in	6.47 m
PLATFORM HEIGHT	14 ft 8 in	4.47 m
LIFT CAPACITY	500 lbs	227 kg
POWER	24 V (four 6 V 200 Ah batteries)	
WEIGHT*	2,192-2,220 lbs	994-1007 kg

QS™-20



WORKING HEIGHT	25 ft 11 in	8.07 m
PLATFORM HEIGHT	19 ft 11 in	6.07 m
LIFT CAPACITY	350 lbs	159 kg
POWER	24 V (four 6 V 200 Ah batteries)	
WEIGHT*	2,451-2,479 lbs	1112-1124 kg

GRC™-12



WORKING HEIGHT	18 ft	5.66 m
PLATFORM HEIGHT	12 ft	3.66 m
LIFT CAPACITY	500 lbs	227 kg
POWER	24 V (four 6 V 225 Ah batteries)	
WEIGHT*	1,916 lbs	869 kg

Runabouts

Compact, lightweight solution for increasing productivity.

- Ideal choice when access is tight. These units fit through doors, down narrow aisles and on elevators, getting you to hard-to-reach worksites.
- Ideal tool for warehousing, stock-picking, transporting, inventory management, general maintenance and construction.



Compact Solution

The compact, lightweight Runabout™ can go almost anywhere, increasing job site productivity.

GR™-12



WORKING HEIGHT	17 ft 5 in	5.48 m
PLATFORM HEIGHT	11 ft 5 in	3.48 m
LIFT CAPACITY	500 lbs	227 kg
POWER	24 V (four 6 V 225 Ah batteries)	
WEIGHT*	1,581 lbs	717 kg

GR™-15



WORKING HEIGHT	20 ft 8 in	6.47 m
PLATFORM HEIGHT	14 ft 8 in	4.47 m
LIFT CAPACITY	500 lbs	227 kg
POWER	24 V (four 6 V 225 Ah batteries)	
WEIGHT*	2,192 lbs	994 kg

GR™-20



WORKING HEIGHT	25 ft 11 in	8.07 m
PLATFORM HEIGHT	19 ft 11 in	6.07 m
LIFT CAPACITY	350 lbs	159 kg
POWER	24 V (four 6 V 225 Ah batteries)	
WEIGHT*	2,451 lbs	1,112 kg



SELF-PROPELLED SCISSOR LIFTS



Self-Propelled Scissor Lifts

Perfect solution for increasing worksite productivity.

- Electric models are great for indoor and outdoor applications with firm, level surfaces.
- Perfect for jobs that require greater lift capacity and maximum platform workspace.
- Rough Terrain models provide maximum productivity in more demanding outdoor worksites.



GS™-1530

WORKING HEIGHT	21 ft	6.57 m
PLATFORM HEIGHT	15 ft	4.57 m
LIFT CAPACITY	600 lbs	272 kg
POWER	DC	
WEIGHT (ANSI/CSA)*	2,575 lbs	1,168 kg



GS™-2646

WORKING HEIGHT	32 ft	9.92 m
PLATFORM HEIGHT	26 ft	7.92 m
LIFT CAPACITY	1,000 lbs	454 kg
POWER	DC	
WEIGHT (ANSI/CSA)*	4,312 lbs	1,956 kg



GS™-1930

WORKING HEIGHT	25 ft	7.79 m
PLATFORM HEIGHT	19 ft	5.79 m
LIFT CAPACITY	500 lbs	227 kg
POWER	DC	
WEIGHT (ANSI/CSA)*	2,702 lbs	1,226 kg



GS™-3246

WORKING HEIGHT	38 ft	11.75 m
PLATFORM HEIGHT	32 ft	9.75 m
LIFT CAPACITY	700 lbs	318 kg
POWER	DC	
WEIGHT (ANSI/CSA)*	5,211 lbs	2,364 kg



GS™-2032

WORKING HEIGHT	26 ft	8.10 m
PLATFORM HEIGHT	20 ft	6.10 m
LIFT CAPACITY	800 lbs	363 kg
POWER	DC	
WEIGHT (ANSI/CSA)*	3,574 lbs	1,621 kg



GS™-2668 DC

WORKING HEIGHT	32 ft	9.92 m
PLATFORM HEIGHT	26 ft	7.92 m
LIFT CAPACITY	1,250 lbs	567 kg
POWER	DC	
WEIGHT	6,657 lbs	3,020 kg



GS™-2632

WORKING HEIGHT	32 ft	9.92 m
PLATFORM HEIGHT	26 ft	7.92 m
LIFT CAPACITY	500 lbs	227 kg
POWER	DC	
WEIGHT (ANSI/CSA)*	4,413 lbs	2,002 kg



GS™-3268 DC

WORKING HEIGHT	38 ft	11.75 m
PLATFORM HEIGHT	32 ft	9.75 m
LIFT CAPACITY	1,000 lbs	454 kg
POWER	DC	
WEIGHT*	7,908 lbs	3,587 kg



GS™-3232

WORKING HEIGHT	38 ft	11.75 m
PLATFORM HEIGHT	32 ft	9.75 m
LIFT CAPACITY	500 lbs	227 kg
POWER	DC	
WEIGHT (ANSI/CSA)*	5,185 lbs	2,352 kg



GS™-2668 RT

WORKING HEIGHT	32 ft	9.92 m
PLATFORM HEIGHT	26 ft	7.92 m
LIFT CAPACITY	1,250 lbs	567 kg
POWER	Gas/LPG or Diesel	
WEIGHT*	6,737 lbs	3,056 kg



GS™-2046

WORKING HEIGHT	26 ft	8.10 m
PLATFORM HEIGHT	20 ft	6.10 m
LIFT CAPACITY	1,200 lbs	544 kg
POWER	DC	
WEIGHT (ANSI/CSA)*	3,977 lbs	1,804 kg



GS™-3268 RT

WORKING HEIGHT	38 ft	11.75 m
PLATFORM HEIGHT	32 ft	9.75 m
LIFT CAPACITY	1,000 lbs	454 kg
POWER	Gas/LPG or Diesel	
WEIGHT*	8,084 lbs	3,667 kg

* Weight may vary depending on options and/or country standards.

SELF-PROPELLED SCISSOR LIFTS



Quiet Convenience

Genie® electric scissors generate low noise levels, allowing operation in sound sensitive environments.



GS™-3384 RT

WORKING HEIGHT	39 ft	12.06 m
PLATFORM HEIGHT	33 ft	10.06 m
LIFT CAPACITY	2,500 lbs	1,134 kg
POWER	Gas/LPG or Diesel	
WEIGHT*	12,005 lbs	5,445 kg



GS™-3390 RT

WORKING HEIGHT	39 ft	12.06 m
PLATFORM HEIGHT	33 ft	10.06 m
LIFT CAPACITY	2,500 lbs	1,134 kg
POWER	Gas/LPG or Diesel	
WEIGHT*	12,085 lbs	5,482 kg



GS™-4390 RT

WORKING HEIGHT	49 ft	15.11 m
PLATFORM HEIGHT	43 ft	13.11 m
LIFT CAPACITY	1,500 lbs	680 kg
POWER	Gas/LPG or Diesel	
WEIGHT*	12,925 lbs	5,862 kg



GS™-5390 RT

WORKING HEIGHT	59 ft	18.15 m
PLATFORM HEIGHT	53 ft	16.15 m
LIFT CAPACITY	1,500 lbs	680 kg
POWER	Gas/LPG or Diesel	
WEIGHT*	16,698 lbs	7,574 kg



Expansive Platform

A large work deck with front extension and optional rear deck extension provides ample area for jobs requiring a large amount of platform space.

Power and Performance

Powerful four-wheel drive RT scissor lifts have positive traction control that is ideal for increasing productivity in demanding outdoor worksites.



SELF-PROPELLED ARTICULATING Z™-BOOMS



Self-Propelled Articulating Z™-Booms Electric Powered

Your choice for reaching indoor working heights
of 35 ft 2 in (10.89 m) to 51 ft 8 in (15.92 m).

- Ideal for “up and over” reach requirements in very confined areas and narrow passageways.
- Suitable for indoor and outdoor smooth surface use.
- Capable of passing through standard double doorways.
- Perfect for applications where quiet, emission free operation is required.



Z™-30/20N

WORKING HEIGHT	36 ft	11.14 m
HORIZONTAL REACH	21 ft 5 in	6.53 m
UP & OVER CLEARANCE	12 ft 8 in	3.86 m
LIFT CAPACITY	500 lbs	227 kg
POWER	DC	
WEIGHT*	14,170 lbs	6,427 kg



Z™-40/23N

WORKING HEIGHT	46 ft 5 in	14.32 m
HORIZONTAL REACH	22 ft 8 in	6.91 m
UP & OVER CLEARANCE	21 ft 3 in	6.48 m
LIFT CAPACITY	500 lbs	227 kg
POWER	DC	
WEIGHT*	15,230 lbs	6,908 kg



Z™-30/20N RJ

WORKING HEIGHT	35 ft 2 in	10.89 m
HORIZONTAL REACH	20 ft 6 in	6.25 m
UP & OVER CLEARANCE	12 ft 8 in	3.86 m
LIFT CAPACITY	500 lbs	227 kg
POWER	DC	
WEIGHT*	14,220 lbs	6,450 kg



Z™-40/23N RJ

WORKING HEIGHT	46 ft 5 in	14.32 m
HORIZONTAL REACH	22 ft 8 in	6.91 m
UP & OVER CLEARANCE	21 ft 3 in	6.48 m
LIFT CAPACITY	500 lbs	227 kg
POWER	DC	
WEIGHT*	15,300 lbs	6,940 kg



Z™-34/22N

WORKING HEIGHT	40 ft 6 in	12.52 m
HORIZONTAL REACH	22 ft 3 in	6.78 m
UP & OVER CLEARANCE	15 ft 2 in	4.62 m
LIFT CAPACITY	500 lbs	227 kg
POWER	DC	
WEIGHT*	11,400 lbs	5,171 kg



Bi-Energy and Z™-45/25 DC

WORKING HEIGHT	51 ft 6 in	15.87 m
HORIZONTAL REACH	25 ft	7.62 m
UP & OVER CLEARANCE	23 ft 1 in	7.04 m
LIFT CAPACITY	500 lbs	227 kg
POWER	DC or Bi-Energy	
WEIGHT*	(DC) 15,350 lbs	6,963 kg
	(Bi) 15,850 lbs	7,190 kg




Bi-Energy and Z™-34/22 DC

WORKING HEIGHT	40 ft 6 in	12.52 m
HORIZONTAL REACH	22 ft 3 in	6.78 m
UP & OVER CLEARANCE	14 ft 11 in	4.55 m
LIFT CAPACITY	500 lbs	227 kg
POWER	DC or Bi-Energy	
WEIGHT*	(DC) 11,000 lbs	4,990 kg
	(Bi) 12,000 lbs	5,443 kg



Bi-Energy and Z™-45/25 J

WORKING HEIGHT	51 ft 9 in	15.94 m
HORIZONTAL REACH	25 ft 1 in	7.65 m
UP & OVER CLEARANCE	23 ft 1 in	7.04 m
LIFT CAPACITY	500 lbs	227 kg
POWER	DC or Bi-Energy	
WEIGHT*	(DC) 16,300 lbs	7,394 kg
	(Bi) 16,800 lbs	7,620 kg



Z™-34/22 IC

	2WD		4WD	
WORKING HEIGHT	40 ft 6 in	12.52 m	40 ft 10 in	12.62 m
HORIZONTAL REACH	22 ft 3 in	6.78 m	22 ft 3 in	6.78 m
UP & OVER CLEARANCE	14 ft 11 in	4.55 m	15 ft	4.57 m
LIFT CAPACITY	500 lbs	227 kg	500 lbs	227 kg
POWER	Gas/LPG or Diesel		Gas/LPG or Diesel	
WEIGHT*	10,150 lbs	4,604 kg	10,450 lbs	4,740 kg



Z™-45/25 RT

WORKING HEIGHT	51 ft 11 in	16.00 m
HORIZONTAL REACH	25 ft	7.62 m
UP & OVER CLEARANCE	23 ft 6 in	7.16 m
LIFT CAPACITY	500 lbs	227 kg
POWER	Gas/LPG or Diesel	
WEIGHT*	(2WD) 13,675 lbs	6,203 kg
	(4WD) 13,875 lbs	6,294 kg

* Weight may vary depending on options and/or country standards.


SELF-PROPELLED ARTICULATING Z™-BOOMS



Self-Propelled Articulating Z™-Booms
Engine Powered


The perfect tool for reaching heights between 40 ft 6 in (12.52 m) and 141 ft (43.15 m) or reaching out a maximum of 69 ft 9 in (21.26 m).

- Z™-boom design provides lifting versatility with “up and over” positioning and excellent outreach.
- Ideal for outdoor construction and industrial applications.
- Rough Terrain (RT) models are excellent for traveling over irregular or bumpy ground to a worksite.
- Models with oscillating axles provide a smoother ride over rough surface conditions.




Z™-45/25J RT

WORKING HEIGHT	52 ft 2 in	16.07 m
HORIZONTAL REACH	25 ft 1 in	7.65 m
UP & OVER CLEARANCE	23 ft 6 in	7.16 m
LIFT CAPACITY	500 lbs	227 kg
POWER	Gas/LPG or Diesel	
WEIGHT*	(2WD) 14,300 lbs	6,486 kg
	(4WD) 14,500 lbs	6,577 kg




Z™-80/60

WORKING HEIGHT	84 ft	25.77 m
HORIZONTAL REACH	60 ft	18.29 m
UP & OVER CLEARANCE	29 ft	8.83 m
LIFT CAPACITY	500 lbs	227 kg
POWER	Gas/LPG or Diesel	
WEIGHT*	(2WD) 35,900 lbs	16,284 kg
	(4WD) 37,500 lbs	17,010 kg



Z™-60/34

WORKING HEIGHT	66 ft 4 in	20.39 m
HORIZONTAL REACH	36 ft 3 in	11.05 m
UP & OVER CLEARANCE	27 ft	8.23 m
LIFT CAPACITY	500 lbs	227 kg
POWER	Gas/LPG or Diesel	
WEIGHT*	22,520 lbs	10,215 kg



Z™-135/70

WORKING HEIGHT	141 ft	43.15 m
HORIZONTAL REACH	69 ft 9 in	21.26 m
UP & OVER CLEARANCE	32 ft 6 in	9.91 m (RISER RETRACTED)
	75 ft 6 in	23.01 m (RISER EXTENDED)
LIFT CAPACITY	600 lbs	272 kg
POWER	Diesel	
WEIGHT*	44,900 lbs	20,366 kg



Tight Maneuverability

The electric boom line includes many narrow models for accessing confined work areas and driving through standard doorways.

Up, Out and Over

Articulating Z™-booms provide the ultimate in lifting and working versatility with up, out and over positioning. You can get into spots that were never possible before with a Z™-boom.

SELF-PROPELLED TELESCOPIC Z™-BOOMS

Self-Propelled Telescopic Z™-Booms

The lift you want when you need to reach out horizontally between 31 ft 8 in (9.65 m) and 80 ft (24.38 m) and reach heights of 46 ft (14.20 m) to 131 ft 2 in (40.15 m).

- Excellent choice when an operator needs to reach work at a distance where terrain and obstacles prevent close access.
- Models with jibs can access hard to reach locations above and below the obtained reach and maneuver platforms directly into place.
- Great for high performance applications where drive speed, lift speed and rough terrain capability are important.



S™-40

WORKING HEIGHT	46 ft	14.20 m
PLATFORM HEIGHT	40 ft	12.20 m
HORIZONTAL REACH	31 ft 8 in	9.65 m
LIFT CAPACITY	500 lbs	227 kg
POWER	Gas/LPG or Diesel	
WEIGHT*	12,300 lbs	5,578 kg



S™-45

WORKING HEIGHT	51 ft	15.72 m
PLATFORM HEIGHT	45 ft	13.72 m
HORIZONTAL REACH	36 ft 8 in	11.18 m
LIFT CAPACITY	500 lbs	227 kg
POWER	Gas/LPG or Diesel	
WEIGHT*	15,200 lbs	6,893 kg



S™-60X

WORKING HEIGHT	66 ft	20.30 m
PLATFORM HEIGHT	60 ft	18.30 m
HORIZONTAL REACH	50 ft 10 in	15.48 m
LIFT CAPACITY	500-1000 lbs	227-454 kg
POWER	Gas/LPG or Diesel	
WEIGHT*	(2WD)	20,570 lbs
	(4WD)	20,740 lbs
		9,330 kg
		9,408 kg



S™-65

WORKING HEIGHT	71 ft	21.80 m
PLATFORM HEIGHT	65 ft	19.80 m
HORIZONTAL REACH	56 ft 2 in	17.10 m
LIFT CAPACITY	500 lbs	227 kg
POWER	Gas/LPG or Diesel	
WEIGHT*	(2WD)	22,100 lbs
	(4WD)	22,270 lbs
		10,024 kg
		10,102 kg



S™-80X

WORKING HEIGHT	86 ft	26.2 m
PLATFORM HEIGHT	80 ft	24.40 m
HORIZONTAL REACH	71 ft 6 in	21.80 m
LIFT CAPACITY	500-1000 lbs	227-454 kg
POWER	Gas/LPG or Diesel	
WEIGHT*	(2WD)	35,460 lbs
	(4WD)	35,560 lbs
		16,084 kg
		16,130 kg



S™-85

WORKING HEIGHT	91 ft	27.7 m
PLATFORM HEIGHT	85 ft	25.90 m
HORIZONTAL REACH	76 ft 6 in	23.3 m
LIFT CAPACITY	500 lbs	227 kg
POWER	Gas/LPG or Diesel	
WEIGHT*	(2WD)	37,900 lbs
	(4WD)	38,000 lbs
		17,191 kg
		17,236 kg



S™-100

WORKING HEIGHT	106 ft	32.48 m
PLATFORM HEIGHT	100 ft	30.48 m
HORIZONTAL REACH	75 ft	22.86 m
LIFT CAPACITY	750 lbs	340 kg
POWER	Diesel	
WEIGHT*	39,700 lbs	18,008 kg



S™-105

WORKING HEIGHT	111 ft	34.00 m
PLATFORM HEIGHT	105 ft	32.00 m
HORIZONTAL REACH	80 ft	24.38 m
LIFT CAPACITY	500 lbs	227 kg
POWER	Diesel	
WEIGHT*	40,000 lbs	18,144 kg



S™-120

WORKING HEIGHT	126 ft	38.58 m
PLATFORM HEIGHT	120 ft	36.58 m
HORIZONTAL REACH	75 ft	22.86 m
LIFT CAPACITY	750 lbs	340 kg
POWER	Diesel	
WEIGHT*	44,340 lbs	20,112 kg



S™-125

WORKING HEIGHT	131 ft 2 in	40.15 m
PLATFORM HEIGHT	125 ft 2 in	38.15 m
HORIZONTAL REACH	80 ft	24.38 m
LIFT CAPACITY	500 lbs	227 kg
POWER	Diesel	
WEIGHT*	44,640 lbs	20,248 kg

* Weight may vary depending on options and/or country standards.

SELF-PROPELLED TELESCOPIC S™-BOOMS

Terrain Tracking Axle Option

Oscillating axle senses the terrain and adjusts the axle to maintain four point contact while driving on uneven ground for a smoother ride and reduced platform movement.



S™-60X and S™-65 TraX

A four-point rubber track system offers increased flotation and traction for traveling in a diverse range of weather and ground conditions, yet steers like a wheeled boom for maneuvering close to walls and foundations. Plus, the S™-60X & S™-65 TraX are transportable without over-width permits.



S™-60X TraX

WORKING HEIGHT	66 ft 2 in	20.34 m
PLATFORM HEIGHT	60 ft 2 in	18.34 m
HORIZONTAL REACH	50 ft 10 in	15.48 m
LIFT CAPACITY	660-1,100 lbs	299-499 kg
POWER	Gas/LPG or Diesel	
WEIGHT*	25,430 lbs	11,535 kg



S™-65 TraX

WORKING HEIGHT	71 ft 2 in	21.86 m
PLATFORM HEIGHT	65 ft 2 in	19.86 m
HORIZONTAL REACH	56 ft 2 in	17.10 m
LIFT CAPACITY	500 lbs	227 kg
POWER	Gas/LPG or Diesel	
WEIGHT*	26,960 lbs	12,229 kg



S™-60 XC

WORKING HEIGHT	64 ft 4 in	19.78 m
PLATFORM HEIGHT	58 ft 4 in	17.78 m
HORIZONTAL REACH		
Maximum outreach zone	50 ft 10 in	15.48 m
Maximum capacity zone	38 ft 11 in	11.86 m
LIFT CAPACITY		
Maximum outreach zone	750 lbs	340 kg
Maximum capacity zone	1,250 lbs	567 kg
POWER	Gas/LPG or Diesel	
WEIGHT*	(2WD)	22,038 lbs 9,996 kg
	(4WD)	22,208 lbs 10,073 kg



S™-60 XC Extra Capacity Boom

- An 8 ft (2.44 m) platform increases your flexibility with three-person capacity and platform load and position monitoring.
- With a platform load capacity of 750 lbs (340 kg) throughout the entire range of motion up to 50 ft 10 in (15.48 m) horizontal outreach, the S™-60 XC allows you to realize greater returns on your investment.
- An industry leader in load capacity, the S™-60 XC handles loads up to 1,250 lbs (567 kg) within 75% of full range-of-motion up to 40 ft 8 in (12.38 m) horizontal outreach, maximizing your productivity.

TRAILER-MOUNTED Z™-BOOMS



Trailer-Mounted Z™-Booms

Extremely versatile and easy to use.

- An excellent value in high reach equipment. The hydraulic outriggers and automatic machine leveling provide quick, efficient setup.
- A favorite with contractors and rental yards. The TZ™-50 has an industry-leading working range and an optional hybrid DC/gas charging system.



TZ™-34/20

WORKING HEIGHT	40 ft	12.36 m
PLATFORM HEIGHT	34 ft	10.36 m
HORIZONTAL REACH	18 ft 4 in	5.59 m
LIFT CAPACITY	460 – 500 lbs	209 – 227 kg
POWER	DC	
WEIGHT*	3,155 lbs	1,431 kg



TZ™-50

WORKING HEIGHT	55 ft 6 in	17.09 m
PLATFORM HEIGHT	49 ft 6 in	15.09 m
HORIZONTAL REACH	29 ft 2 in	8.89 m
LIFT CAPACITY	500 lbs	227 kg
POWER	DC, Hybrid DC/Gas (gas for charging only)	
WEIGHT*	4,400 lbs	1,996 kg



Easy to Maneuver and Position

The TZ™-34/20 is lightweight and easy to maneuver, position and store. It meets the challenges of the working environment.



Increase Your Productivity

The exclusive self-leveling system on the TZ™-50 allows the operator to set up the machine in less than 60 seconds when the operator deploys all four outriggers simultaneously.

TELEHANDLERS

Telehandlers

Your choice for worksite versatility and productivity.

- Extreme versatility makes Genie® telehandlers a valuable and cost-effective investment for any worksite.
- These are the perfect machines for any task that requires lifting, moving, digging or placing objects exactly where you need them.
- Select from a wide variety of attachments that will expand work capabilities to match the exact job you need to tackle.
- Ideal for masonry, construction, farming or landscape applications.



Compact Performance

Achieve maximum maneuverability in tight access areas with the compact rough terrain models.



Twin Axle Mounted Stabilizers

Allow quick and easy leveling. Available on the GTH™-1056.



Cab With a View

Operators have the advantage of excellent visibility.



Powerful Flexibility

Powerful diesel engine and 4WD coupled with 4WS and three different steering modes allow these machines to operate on almost any worksite.

GTH™-5519

MAXIMUM LIFT CAPACITY	5,500 lbs	2,500 kg
MAXIMUM LIFTING HEIGHT	19 ft	5.79 m
MAXIMUM HORIZONTAL	11 ft	3.35 m
OPERATING WEIGHT	9,800 lbs	4,450 kg

GTH™-644

MAXIMUM LIFT CAPACITY	6,000 lbs	2,722 kg
MAXIMUM LIFTING HEIGHT	44 ft	13.41 m
MAXIMUM HORIZONTAL	27 ft	8.23 m
OPERATING WEIGHT	21,500 lbs	9,752 kg

GTH™-844

MAXIMUM LIFT CAPACITY	8,000 lbs	3,629 kg
MAXIMUM LIFTING HEIGHT	44 ft	13.41 m
MAXIMUM HORIZONTAL	27 ft	8.23 m
OPERATING WEIGHT	22,500 lbs	10,206 kg

GTH™-1056

MAXIMUM LIFT CAPACITY	10,000 lbs	4,536 kg
MAXIMUM LIFTING HEIGHT	56 ft 10 in	17.32 m
MAXIMUM HORIZONTAL	42 ft	12.80 m
OPERATING WEIGHT	30,000 lbs	13,608 kg

TRAILER-MOUNTED LIGHT TOWERS



Light Towers

28-30 ft (8.53-9.14 m) floodlight towers provide 4,000 watts of light-illuminating up to 7.5 acres.

A durable design with industry-proven components provides a reliable lighting solution for your job site.



RL4000

TOWER HEIGHT	30 ft	9.14 m
WIDTH STOWED	4 ft 6 in	1.37 m
LENGTH STOWED	14 ft 2 in	4.33 m
DRY WEIGHT	1,725 lbs	783 kg



AL4000

TOWER HEIGHT	30 ft	9.14 m
WIDTH STOWED	5 ft 2 in	1.56 m
LENGTH STOWED	14 ft 11 in	4.55 m
DRY WEIGHT	1,950 lbs	885 kg



AL5000

TOWER HEIGHT	30 ft	9.14 m
WIDTH STOWED	6 ft 9 in	2.04 m
LENGTH STOWED	15 ft 3 in	4.65 m
DRY WEIGHT	2,239 lbs	1,016 kg



AL8000 HT

TOWER HEIGHT	28 ft 9 in	8.76 m
WIDTH STOWED	6 ft 9 in	2.07 m
LENGTH STOWED	8 ft 2 in	2.49 m
DRY WEIGHT	2,605 lbs	1,185 kg



TML™-4000

TOWER HEIGHT	30 ft	9.14 m
WIDTH STOWED	4 ft 6 in	1.37 m
LENGTH STOWED	14 ft 2 in	4.33 m
DRY WEIGHT	1,810 lbs	821 kg



MODELS

Portable Material Lifts

Super Hoist™
Load Lifter™
Genie® Lift™
Superlift Contractor®
Superlift Advantage®
Super Tower™

Aerial Work Platforms

AWP™ Super Series

AWP™-20S
AWP™-25S
AWP™-30S
AWP™-36S
AWP™-40S

IWP™ Super Series

IWP™-20S
IWP™-25S
IWP™-30S

DPL™ Super Series

DPL™-25S
DPL™-30S
DPL™-35S

Runabouts

GR™-12
GR™-15
GR™-20
GRC™-12

QuickStock

QS™-12
QS™-15
QS™-20

Self-Propelled Scissor Lifts

GS™-1530
GS™-1930
GS™-2032
GS™-2632
GS™-3232
GS™-2046
GS™-2646
GS™-3246
GS™-2668 DC
GS™-3268 DC
GS™-2668 RT
GS™-3268 RT
GS™-3384 RT
GS™-3390 RT
GS™-4390 RT
GS™-5390 RT

Self-Propelled Articulating Z™-Booms

Z™-30/20N
Z™-30/20N RJ
Z™-34/22 DC
Z™-34/22 Bi-Energy
Z™-34/22N
Z™-34/22 IC
Z™-40/23N
Z™-40/23N RJ
Z™-45/25 DC
Z™-45/25J DC
Z™-45/25 Bi-Energy
Z™-45/25J Bi-Energy
Z™-45/25 RT
Z™-45/25J RT
Z™-60/34
Z™-80/60
Z™-135/70

Self-Propelled Telescopic S™-Booms

S™-40	S™-45
S™-60X	S™-65
S™-60 TraX	S™-65 Trax
S™-60 XC	S™-80X
S™-85	S™-100
S™-105	S™-120
S™-125	

Trailer-Mounted Z™-Booms

TZ™-34/20
TZ™-50

Telehandlers

GTH™-5519
GTH™-636
GTH™-644
GTH™-844
GTH™-1056

Trailer-Mounted Light Towers

TML™-4000	AL4000
RL4000	AL8000 HT
AL5000	



www.genieindustries.com

GENIE UNITED STATES

18340 NE 76th Street
P.O. Box 97030
Redmond, Washington 98073-9730

Telephone **+1 (425) 881-1800**
Toll Free in USA/Canada **+1 (800) 536-1800**
Fax +1 (425) 883-3475

GENIE EUROPE

The Maltings
Wharf Road
Grantham NG31 6BH
UK

Telephone **+44 (0) 1476 584333**
Fax +44 (0) 1476 584334
Email AWP-InfoEurope@terex.com

Distributed By:

Effective Date: September, 2010. Product specifications and prices are subject to change without notice or obligation. The photographs and/or drawings in this document are for illustrative purposes only. Refer to the appropriate Operator's Manual for instructions on the proper use of this equipment. Failure to follow the appropriate Operator's Manual when using our equipment or to otherwise act irresponsibly may result in serious injury or death. The only warranty applicable to our equipment is the standard written warranty applicable to the particular product and sale and we make no other warranty, express or implied. Products and services listed may be trademarks, service marks or trade-names of Terex Corporation, Genie Industries, Inc. and/or their subsidiaries in the U.S.A. and many other countries. All rights are reserved. Terex is a Registered Trademark of Terex Corporation in the U.S.A. and many other countries. Genie, Superlift Contractor, and Superlift Advantage are Registered Trademarks of Genie Industries, Inc. in the U.S.A. and many other countries. Genie is a Terex Brand. © 2010 Terex Corporation. Small Family 138K 0309L. Part No. 109385.