

Sensors for liquid level, flow and position.

Magnetic reed switches.



Sensors for liquid level, flow and position. Magnetic reed switches.

Gentech is a manufacturer and supplier of switching, sensing and control solutions, including Liquid Level Sensors, Flow Switches, Position Sensors and Magnetic Reedswitches. As well as the standard range of products, Gentech specialise in custom solutions to meet a wide range of applications.





LS Series

This series in a wide range of materials, switching and fitting options. With UL & WRAS Models.

Top or bottom - Float switches



VS Series

With wide range of materials and switching options, also can be internally or externally fitted.



ESS Series

The analogue sensor for contents measurement in standard lengths to 1 metre long with various tank fitting options.



LCS Series

Push fit external mounted sensor, with cable or with integral connector.



VSS Series

In stainless steel this product is used for food and harsh chemical applications.



VCS Series

VCS series expanded to metal models in brass and stainless steel.



LDS Series

This series has close differential between operate and release, for sensing small change in the liquid level.



VCS Series

This series of compact sensors in a range of plastics suitable for



boiling water and fuels.



ISO/TS 16949:2002.



UL/CSA



POTABLE WATER





ATEX







RS Series

Available with internal and external fit - ideal for the tight corner of the tank.



brass and stainless steel

EVS Series

The extended range

of sensors in plastics,

can have up to 3 floats and up to 1 metre long.

Liquid level sensors - Solid state



OS Series Optical liquid level sensing, with NPN or PNP outputs to switch

for logic circuitry.



Flow Switches

FS Series
In 3/4" BSP+NPSC
fittings, this Noryl +
brass material with low
volts and ac control
circuitry, switching at
less than 1L/min.



Position Sensors



PS1 & PS2



PS6 Series Protected reedswitches and for through hole fitting these position sensors are in small sizes.



TS Series
The PTC characteristics make this sensor sensitive to change in the medium.



FS Series
In brass and 22mm
pipe size. with
compression fittings,
low
volts dc and ac circuitry
- switching 1L/min.



PS3 Series
This package designed specifically for business machines is small in size and with matching magnet and ribbon cable.



PS7 Series
Sub miniature in
concept, with low
profile the single screw
mounting, the sensor
is ideal for robot arm
actuators.





FS Series
This 15mm low volts
switch with vertical and
horizontal fit models
in copper tube.



PS4 Series
Packaged reedswitches for safe and
alarm circuits. With a
powerful magnet it will
operate at greater than
20mm.



PS8 Series
Threaded proximity
switches end operated
to the target with
thread adjustment and
fitting. With matching
magnets.



FCS Series
In PPS and Noryl
with 3/8" BSP & NPT
fittings, the switch
point 0.5 to 0.6L/min in
horizontal plane. Can
also be vertically
mounted.



PS5 Series
The cylindrical sensor ideal for end operation and proximity application can be clipped into place.



PSS Series
The sensor with vane operation, to break the magnetic field with lead or fast on terminals.



Custom Solutions

ULS Series





VCS Series

BVS Series

Gentech International Ltd Grangestone Industrial Estate Girvan Ayrshire KA26 9PS United Kingdom

Tel: +44 1465 713581 Fax: +44 1465 714974 Email: info@gentechsensors.com www.gentechsensors.com

Designing sensing solutions today, for tomorrow's application demands...

PS Series