



RING TERMINALS



R SERIES

NON-INSULATED

NAED NUMBER	CATALOG NUMBER	WIRE SIZE	STUD SIZE	COLOR	DIMENSIONS		QTY/ BOX	EST. SHIPPING	
					L	W		WEIGHT (lbs)	UNIT
16006	R 18-6	#18-22	6	-	.614	.315	100	0.17	BOX
16008	R 18-8		8					0.17	BOX
16010	R 18-10		10					0.14	BOX
16014	R 18-14	1/4			.795	.472		0.15	BOX
16026	R 14-6	#14-16	6	-	.630	.315	50	0.18	BOX
16028	R 14-8		8					0.18	BOX
16030	R 14-10		10					0.18	BOX
16034	R 14-14		1/4					0.26	BOX
16036	R 14-56	5/16	.846	.472				0.26	BOX
16046	R 10-6	#10-12	6	-	.906	.472	25	0.18	BOX
16048	R 10-8		8					0.18	BOX
16050	R 10-10		10					0.18	BOX
16054	R 10-14		1/4					0.25	BOX
16056	R 10-56		5/16					0.29	BOX
16058	R 10-38		3/8					0.28	BOX
16060	R 10-48	1/2	1.4	.81				0.14	BOX
16064	R 8-14	#8	1/4	-	1.07	.60	25	0.22	BOX
16068	R 8-38		3/8					0.20	BOX
16084	R 6-14	#6	1/4	-	1.2	.63	25	0.31	BOX
16088	R 6-38		3/8					0.26	BOX
16089	R 6-48		1/2					0.47	BOX



Butted Seam



Non-Insulated

Brazed Seam

NYLON INSULATED

16206	R 18-6N	#18-22	6	RED	.831	.315	100	0.20	BOX		
16208	R 18-8N		8					0.20	BOX		
16210	R 18-10N		10					0.25	BOX		
16214	R 18-14N		1/4					1.008	.472	0.30	BOX
16226	R 14-6N	#14-16	6	BLUE	.846	.315	50	0.23	BOX		
16228	R 14-8N		8					0.24	BOX		
16230	R 14-10N		10					0.29	BOX		
16234	R 14-14N		1/4					1.059	.472	0.36	BOX
16236	R 14-56N	5/16	1.059	.472				0.40	BOX		
16246	R 10-6N	#10-12	6	YELLOW	1.063	.374	50	0.28	BOX		
16248	R 10-8N		8					0.28	BOX		
16250	R 10-10N		10					0.28	BOX		
16254	R 10-14N		1/4					1.201	.472	0.34	BOX
16256	R 10-56N		5/16					1.398	.591	0.34	BOX
16258	R 10-38N		3/8					1.398	.591	0.34	BOX



Nylon-Insulated Sleeved Barrel

For other sizes and types, consult factory.



RING TERMINALS

R SERIES

VINYL INSULATED

NAED NUMBER	CATALOG NUMBER	WIRE SIZE	STUD SIZE	COLOR	DIMENSIONS		QTY/ BOX	EST. SHIPPING	
					L	W		WEIGHT (lbs)	UNIT
16104	R 18-4V	#18-22	4	RED	.90	.25	100	0.20	BOX
16106	R 18-6V		6		.831	.315		0.20	BOX
16108	R 18-8V		8		.827	.315		0.20	BOX
16110	R 18-10V		10		.827	.315		0.20	BOX
16114	R 18-14V		1/4		1.008	.472		0.28	BOX
16126	R 14-6V	#14-16	6	BLUE	.717	.256	50	0.22	BOX
16128	R 14-8V		8		.846	.315		0.25	BOX
16130	R 14-10V		10		.846	.315		0.30	BOX
16124	R 14-14V		1/4		1.059	.472		0.31	BOX
16136	R 14-56V		5/16		1.059	.472		0.32	BOX
16138	R 14-38V	3/8	1.19	.56	0.16	BOX			
16146	R 10-6V	#10-12	6	YELLOW	1.063	.374	50	0.22	BOX
16148	R 10-8V		8		1.063	.374		0.21	BOX
16150	R 10-10V		10		1.063	.374		0.22	BOX
16154	R 10-14V		1/4		1.201	.472		0.29	BOX
16156	R 10-56V		5/16		1.398	.591		0.28	BOX
16158	R 10-38V	3/8	1.398	.591	0.27	BOX			
16160	R 8-10V	#8	#10	RED	1.4	.60	25	0.27	BOX
16164	R 8-14V		1/4					0.25	BOX
16168	R 8-38V		3/8					0.22	BOX
16180	R 6-10V	#6	#10	BLUE	1.5	.62	25	0.36	BOX
16184	R 6-14V		1/4		1.6			0.32	BOX
16186	R 6-56V		5/16		1.6			0.34	BOX
16188	R 6-38V		3/8		1.6			0.35	BOX
16189	R 6-48V		1/2		2.0			.87	0.51
16194	R 4-14V	#4	1/4	YELLOW	1.8	.68	10	0.30	BOX
16196	R 4-56V		5/16					0.30	BOX
16198	R 4-38V		3/8					0.30	BOX
16199	R 4-48V		1/2					0.31	BOX



Butted Seam




Vinyl Insulated

Brazed Seam



FORK TERMINALS



S SERIES

NON-INSULATED

NAED NUMBER	CATALOG NUMBER	WIRE SIZE	STUD SIZE	COLOR	DIMENSIONS		QTY/ BOX	EST. SHIPPING	
					L	W		WEIGHT (lbs)	UNIT
16301	S 18-4	#18-22	4	—	.630	.228	100	0.15	BOX
16305	S 18-6		6		.630	.224		0.16	BOX
16311	S 18-8		8		.646	.276		0.17	BOX
16315	S 18-10		10		.689	.378		0.15	BOX
16321	S 18-14	1/4			.787	.433		0.15	BOX
16335	S 14-6	#14-16	6	—	.622	.252	50	0.17	BOX
16341	S 14-8		8		.630	.315		0.18	BOX
16345	S 14-10		10		.630	.315		0.17	BOX
16351	S 14-14		1/4		.787	.472		0.17	BOX
16365	S 10-6	#10-12	6	—	.717	.354	50	0.18	BOX
16371	S 10-8		8					0.14	BOX
16375	S 10-10		10					0.14	BOX
16381	S 10-14		1/4					.992	.354



Non-Insulated Butted Seam

VINYL INSULATED

16401	S 18-4V	#18-22	4	RED	.846	.228	100	0.21	BOX
16405	S 18-6V		6		.896	.228		0.20	BOX
16411	S 18-8V		8		.862	.250		0.20	BOX
16415	S 18-10V		10		.906	.376		0.20	BOX
16421	S 18-14V	1/4			1.004	.433		0.17	BOX
16431	S 14-4V	#14-16	4	BLUE	.839	.252	50	0.21	BOX
16435	S 14-6V		6		.839	.252		0.23	BOX
16441	S 14-8V		8		.846	.315		0.27	BOX
16445	S 14-10V		10		.846	.315		0.23	BOX
16451	S 14-14V	1/4			1.004	.472		0.21	BOX
16465	S 10-6V	#10-12	6	YELLOW	1.012	.354	50	0.21	BOX
16471	S 10-8V		8					0.21	BOX
16475	S 10-10V		10					0.21	BOX
16481	S 10-14V		1/4					1.287	.354



Vinyl Insulated Butted Seam

NYLON INSULATED

16501	S 18-4N	#18-22	4	RED	.846	.228	100	0.25	BOX
16505	S 18-6N		6		.896	.224		0.26	BOX
16511	S 18-8N		8		.862	.276		0.27	BOX
16515	S 18-10N		10		.906	.378		0.28	BOX
16521	S 18-14N	1/4			1.004	.433		0.28	BOX
16535	S 14-6N	#14-16	6	BLUE	.839	.252	50	0.29	BOX
16541	S 14-8N		8		.846	.315		0.28	BOX
16562	S 14-10N		10		.846	.315		0.27	BOX
16563	S 14-14N		1/4		1.004	.472		0.35	BOX
16565	S 10-6N	#10-12	6	YELLOW	1.012	.354	50	0.25	BOX
16571	S 10-8N		8					0.25	BOX
16575	S 10-10N		10					0.25	BOX
16581	S 10-14N		1/4					1.287	.354



Nylon Insulated Sleeved Barrel



Flange Spade
Suffix "F"



Locking Spade
Suffix "L"



Block Spade
Suffix "B"



SPLICES




BUTT SPLICES


NAED NUMBER	CATALOG NUMBER	WIRE RANGE	COLOR	L	QTY/BOX	EST. SHIPPING	
						WEIGHT (lbs)	UNIT
70000	B 18	#18-22	-	.57	100	0.19	BOX
70001	B 14	#14-16	-	.57	100	0.23	BOX
70002	B 10	#10-12	-	.57	50	0.21	BOX
70004	* B 10S	#10-12	-	.82	50	0.27	BOX
70003	* B 8	#8	-	.82	25	0.24	BOX
70010	B 18V	#18-22	RED	.95	100	0.25	BOX
70011	B 14V	#14-16	BLUE	1.02	100	0.31	BOX
70012	B 10V	#10-12	YELLOW	1.01	50	0.27	BOX
70013	* B 8V	#8	RED	1.46	25	0.27	BOX
70020	B 18N	#18-22	RED	1.01	100	0.32	BOX
70021	B 14N	#14-16	BLUE	1.02	100	0.33	BOX
70022	B 10N	#10-12	YELLOW	1.01	50	0.32	BOX

* Seamless

Non-Insulated
Butted Seam



Vinyl Insulated
Butted Seam



Nylon Insulated
Seamless

NYLON PIGTAILS

70031	C 14N	#14-22	Clear	.69	100	0.14	BOX
70032	C 10N	#10-18	Clear	.73	50	0.15	BOX

Closed
End Connectors



SNAP PLUGS

Male

70050	SP 14	#14-16	-	.58	50	0.12	BOX
70051	SP 14V		BLUE	.84	50	0.15	BOX

Vinyl Insulated
Butted Seam



Female

70061	FSP 156N	#14-16	BLUE	1.025	50	0.15	BOX
-------	-----------------	--------	------	-------	----	------	-----

Nylon Insulated
Seamless






SPADE DISCONNECTS




F/M SERIES

NAED NUMBER	CATALOG NUMBER	WIRE RANGE	STOCK & SPADE SIZE	COLOR	DIMENSIONS		QTY/ BOX	EST. SHIPPING WEIGHT (lbs) UNIT	
					L	W			
FEMALE DISCONNECTS									
16600	F 18-110		.020 x .110		.54	.16	100	0.08	BOX
16602	F 18-187	#18-22	.020 x .187	—	.63	.23		0.13	BOX
16604	F 18-250		.032 x .250		.63	.31		0.19	BOX
16606	F 14-110		.020 x .110		.54	.16		0.10	BOX
16608	F 14-187	#14-16	.020 x .187	—	.63	.23		0.13	BOX
16610	F 14-250		.032 x .250		.63	.31	0.22	BOX	
16612	F 10-250	#10-12	.032 x .250	—	.63	.31	50	0.13	BOX
16620	F 18-110V		.020 X.110		.77	.16	100	0.13	BOX
16622	F 18-187V	#18-22	.020 X.187	RED	.86	.23		0.14	BOX
16624	F 18-250V		.032 X.250		.93	.31		0.15	BOX
16626	F 14-110V		.020 X.110		.77	.16		0.15	BOX
16628	F 14-187V	#14-16	.020 X.187	BLUE	.87	.23		0.18	BOX
16630	F 14-250V		.032 X.250		.87	.31	0.16	BOX	
16632	F 10-250V	#10-12	.032 X.250	YELLOW	.93	.31	50	0.16	BOX
16640	F 18-110N		.020 X.110		.77	.16	100	0.16	BOX
16642	F 18-187N	#18-22	.020 X.187	RED	.87	.23		0.19	BOX
16644	F 18-250N		.032 X.250		.87	.32		0.23	BOX
16646	F 14-110N		.020 X.110		.77	.16		0.18	BOX
16648	F 14-187N	#14-16	.020 X.187	BLUE	.87	.23		0.23	BOX
16650	F 14-250N		.032 X.250		.87	.32	0.29	BOX	
16652	F 10-250N	#10-12	.032 X.250	YELLOW	.97	.31	50	0.21	BOX
MALE DISCONNECTS									
16660	M 18-250	#18-22	.032 X .250	—	.72	.25	100	0.12	BOX
16662	M 14-187	#14-16	.020 X .187	—	.51	.19		0.18	BOX
16664	M 14-250		.032 X .250	—	.72	.25		0.21	BOX
16666	M 10-250	#10-12	.032 X.250	—	.77	.25	50	0.15	BOX
16680	M 18-250V	#18-22	.032 X.250	RED	.97	.25	100	0.23	BOX
16682	M 14-187V	#14-16	.020 X.187	BLUE	.80	.19		0.13	BOX
16684	M 14-250V		.032 X.250		.94	.25		0.17	BOX
16686	M 10-250V	#10-12	.032 X.250	YELLOW	1.05	.25	50	0.12	BOX
16690	M 18-250N	#18-22	.032 X.250	RED	.97	.25	100	0.26	BOX
16692	M 14-187N	#14-16	.020 X.187	BLUE	.82	.19		0.17	BOX
16694	M 14-250N		.032 X.250		.97	.25		0.33	BOX
16696	M 10-250N	#10-12	.032 X.250	YELLO	1.05	.25		50	0.24

Non-Insulated Butted Seam




Vinyl Insulated Butted Seam




Nylon Insulated Sleeved Barrel

Non-Insulated Butted Seam



Vinyl Insulated Butted Seam



Nylon Insulated Sleeved Barrel



SPADE DISCONNECTS

FULLY NYLON INSULATED

For use where a touch-safe connection is important
Copper, tin-plated
Fully nylon insulated

F/M-FN SERIES

Straight Configuration

NAED NUMBER	CATALOG NUMBER	WIRE RANGE	COLOR	SPADE SIZE	DIMENSIONS		QTY/ BOX	EST. SHIPPING	
					LENGTH	WIDTH		WEIGHT (lbs)	UNIT

FEMALE DISCONNECTS

16705	F 18-250FN	#18-22	RED		.84			0.13	BOX
16715	F 14-250FN	#14-16	BLUE	.032 X .250	.84	.38	50	0.13	BOX
16725	F 10-250FN	#10-12	YELLOW		.94			0.18	BOX

MALE DISCONNECTS

16706	M 18-250FN	#18-22	RED		1.0			0.15	BOX
16716	M 14-250FN	#14-16	BLUE	.032 X .250	1.0	.47	50	0.13	BOX
16726	M 10-250FN	#10-12	YELLOW		1.1			0.22	BOX

FL-FN SERIES

Flag Configuration

FEMALE DISCONNECTS

NAED NUMBER	CATALOG NUMBER	WIRE RANGE	COLOR	SPADE SIZE	DIMENSIONS		QTY/ BOX	EST. SHIPPING	
					LENGTH	WIDTH		WEIGHT (lbs)	UNIT
16708	FL 18-250FN	#18-22	RED		.38	.56	50	0.16	BOX
16718	FL 14-250FN	#14-16	BLUE	.032 X .250	.38	.63	50	0.16	BOX

NON-INSULATED

FL SERIES

Flag Configuration

NAED NUMBER	CATALOG NUMBER	WIRE RANGE	SPADE SIZE	DIMENSIONS		QTY/ BOX	EST. SHIPPING	
				LENGTH	WIDTH		WEIGHT (lbs)	UNIT
16722	FL 14-250	#14-18		.52	.38	50	0.11	BOX
16720	FL 10-250	#10-12	.032 X .250	.63	.38	50	0.12	BOX



MMF SERIES

Split Configuration

NAED NUMBER	CATALOG NUMBER	WIRE RANGE	SPADE SIZE	DIMENSIONS		QTY/ BOX	EST. SHIPPING	
				LENGTH	WIDTH		WEIGHT (lbs)	UNIT
16724	MMF-250	-	.032 X .250	.75	.56	50	0.18	BOX



Male and female FN
Straight Configuration
Spade Disconnects
form fully insulated sets.





CRIMP TERMINALS


HIGH TEMPERATURE

For high temperature applications such as in heating systems, glass furnaces, processing ovens, HVAC systems

Rated for temperature up to 700°F

Mild steel with bright nickel plating, non-insulated, butted seam

Use on high-temperature wire suitable for the environment



R-HT SERIES

Ring Terminals

NAED NUMBER	CATALOG NUMBER	WIRE RANGE	STUD SIZE	DIMENSIONS		QTY/ BOX	EST. SHIPPING	
				LENGTH	WIDTH		WEIGHT (lbs)	UNIT
16803	R 18-10HT	#18-22	#10	.69	.31	50	0.07	BOX
16811	R 14-6HT		#6	.65	.25		0.08	BOX
16813	R 14-10HT	#14-16	#10	.69	.31	50	0.09	BOX
16814	R 14-14HT		1/4	.90	.46		0.11	BOX
16821	R 10-6HT		#6	.67	.28		0.15	BOX
16822	R 10-8HT		#8	.72	.37		0.16	BOX
16823	R 10-10HT	#10-12	#10	.72	.37	50	0.14	BOX
16824	R 10-14HT		1/4	.91	.53		0.22	BOX
16825	R 10-38HT		3/8	.97	.60		0.20	BOX
16833	R 8-10HT	#8	#10	.97	.47	25	0.16	BOX
16834	R 8-14HT		1/4				0.16	BOX



S-HT SERIES

Fork Terminals

NAED NUMBER	CATALOG NUMBER	WIRE RANGE	STUD SIZE	DIMENSIONS		QTY/ BOX	EST. SHIPPING	
				LENGTH	WIDTH		WEIGHT (lbs)	UNIT
16841	S 14-6HT	#14-16	#6	.68	.34	100	0.16	BOX
16842	S 14-8HT	#14-16	#8	.68	.34	100	0.16	BOX
16854	S 10-10HT	#10-12	#10	.75	.38	50	0.13	BOX



F/M-HT SERIES

Spade Disconnects


NAED NUMBER	CATALOG NUMBER	WIRE RANGE	SPADE SIZE	DIMENSIONS		QTY/ BOX	EST. SHIPPING	
				LENGTH	WIDTH		WEIGHT (lbs)	UNIT

FEMALE DISCONNECTS

16865	F 14-250HT	#14-16	.032 x .250	.63	.31	50	0.10	BOX
16875	F 10-250HT	#10-12	.032 x .250	.63	.31	50	0.11	BOX

MALE DISCONNECTS


16885	M 14-250HT	#14-16	.032 x .250	.70	.25	50	0.18	BOX
-------	------------	--------	-------------	-----	-----	----	------	-----



B-HT SERIES

Butt Splices

NAED NUMBER	CATALOG NUMBER	WIRE RANGE	DIMENSIONS		QTY/ BOX	EST. SHIPPING	
			LENGTH	I.D.		WEIGHT (lbs)	UNIT
16893	B 14HT	#14-16	.57	.090	50	0.11	BOX
16894	B 10HT	#10-12	.57	.138	50	0.19	BOX





SOLDERING LUGS – COPPER

Middle weight lugs for soldering applications
Can be installed as compression lugs

D1 SERIES

NAED NUMBER	CATALOG NUMBER	WIRE SIZE	STUD SIZE	AMP RATING	CTN QTY	EST. SHIPPING	
						WEIGHT (lbs)	UNIT
70900	D 1	#10 STR	8	25	250	0.84	CTN
70905	D 2	#8 STR	10	35	200	1.60	CTN
70915	D 3	#6 STR	10	50	200	2.35	CTN
70920	D 4	#4 STR	1/4	70	125	1.74	CTN
70925	D 5	#2 STR	1/4	90	100	3.70	CTN
70930	D 6	1/0 STR	1/4	125	100	3.80	CTN
70935	D 7	2/0 STR	3/8	150	100	5.07	CTN
70940	D 8	3/0 STR	3/8	175	50	3.10	CTN
70945	D 9	4/0 STR	3/8	225	50	3.78	CTN
70950	D 10	250 MCM	3/8	250	25	2.92	CTN
LARGER STUD							
70926	D 15	#2 STR	5/16	90	100	2.29	CTN
70931	D 16	1/0 STR	1/2	125	100	3.60	CTN
70936	D 17	2/0 STR	1/2	150	100	4.54	CTN
70941	D 18	3/0 STR	1/2	175	50	3.16	CTN
70946	D 19	4/0 STR	1/2	225	50	3.82	CTN
70951	D 20	250 MCM	1/2	250	25	3.68	CTN
70955	D 21	400 MCM	1/2	325	25	5.56	CTN

For tin plating add suffix "P" to CATALOG NUMBER.

