AMMONIA EMERGENCY KIT

FOR AMMONIA CYLINDERS DOT 3A480 & 4AA480



The Anhydrous Ammonia Cylinder Emergency Kit is designed to contain leaks at the valve and side wall of ammonia cylinders conforming to DOT specification 3A480 & 4AA480. The Kit includes EPDM molded gaskets, valve containment device, side wall patching device and an ammonia valve yoke with adapter. All kit parts are labeled and color coded blue for ammonia use. Two instruction booklets explaining the application of each device are included.

Emergency Kit Devices Include:

Device #1: designed to contain leaks in and around the cylinder valve. Device #1 will accommodate cylinders up to 15" in diameter with either bumped or foot-ring cylinder bottoms.


Device #8: a patching device designed for sealing leaks in the cylinder side wall.

Features Exclusive to the Ammonia Kit:

- Hood 1ANH -Ammonia steel outlet valve
- 1EPR Gasket -Molded EPDM Hood Gasket
- 8DNH Patch Formed with a larger sealing radius to match ammonia cylinders
- 8-9EP Gasket Molded EPDM Patch Gasket
- 102NH Wrench Open-end wrench to fit ammonia cylinders
- A-9NH Valve Yoke Standard valve yoke for ammonia cylinder use
- A-10NH Valve Adapter Standard valve adapter for ammonia cylinder use
- All parts are labeled with ammonia part numbers and color coded blue



CHLORINE INSTITUTE EMERGENCY KIT "A" Applications And Parts List




Part Number	Name	Quantity Per Kit
1A2 1BRV 1C1 1D1 1K1 1EFP 1R	Hood Assembly, with (1V) Vent Valve Gasket, Molded Viton**, 5-7/8 OD x 4-5/8 ID x 3/16 wall Yoke Cap Screw Cap Screws Base Assembly with Chains Ramp	1 2 1 1 3 1
2 2B 8A 8B 8C 8D 8EV	Clamp Assembly (2A,2C,2D) Gasket, Garlock 3000, 15/16 dia. x 1/16 Chain Yoke Cap Screw Steel Patch Gasket, Viton**, 3" sq. x 1/8	1 10 1 1 1 1 2
200 201 203	Wrench, 3/8 sq. box, 1-1/4 open end 7-1/4" Wrench, straight open end, 1-1/4 x 1-1/8 x 12-1/8 Wrench, combination, 7/16 x 7-1/4"	1 1 1
A-1 A-2 A-3 A-4 A-5 A-6 A-7 A-8 A-9 A-10 A-12 A-13 A-14	Hammer, Machinist 3 lb. Hacksaw, 10", and 3 blades Drift Pin, 5/32 x 1/2 x 6 Drift Pin, 7/8 x 1-1/4 x 8 Ring, vent valve packing, 7/8 OD x 15/32 ID x 1/4 sq. Railroad Car Seal Gasket Sack Paint Scraper, 1-1/4 blade Valve Yoke Valve Adapter (820-hose) Washer, valve outlet, 15/16 OD x 9/16 ID 1/16 Plastic Box file, 8"	1 1 2 2 5 1 1 1 1 1 1 1 1 1
144 151A	Toll Roll Kit Box, 35 x 13-3/4 x 14-1/4	1
- - -	Instruction Booklet Chlorine Manual Parts List	2 1 1
*Note: **Note:	Emergency Kit A weighs 109 lbs. Viton @ fluoroelastomer is a registered trademark of E. I. du Pont de Nemours, Inc.	


Authorized, trained personnel equipped with suitable respiratory equipment should investigate chlorine leaks promptly. All other persons should be restricted from the affected area.


Ammonia Emergency Kit Parts List


PART#	DESCRIPTION	QTY./KIT
1ANH 1CNH 1DNH 1ENH 1EPR 1KNH 1RNH 8ANH 8BNH 8CNH 8DNH 8-9EP 200NH 101NH 102NH A-1NH A-3NH A-4NH A-7NH A-8NH A-9NH A-10NH 144NH 151NH	Hood Assembly (with vent valve 1VNH) Yoke Cap Screw Base Assembly (with Chains 1FNH) Gasket, Molded EPDM Cap Screw Ramp Chain Yoke Cap Screw Patch Gasket, EPDM, 3" square x 1/8 thick Wrench, 3/8 sq. box, 1-1/4 open end x 7-1/4 Wrench, straight open end, 1-1/4 x 12 lg Wrench, straight open end, 1-3/8 x 12 lg Hammer, machinist, 48 oz Drift Pin, 9/32 x 1/2 x 6 lg Drift Pin, 7/8 x 1-1/4 x 8 lg Gasket Sack Paint Scraper, 1-1/4 blade Ammonia Valve Yoke Ammonia Valve Yoke Adapter Tool Roll Kit Box, 34"L x 16-1/2"H x 16"W Instruction Booklet	1 1 1 2 3 1 1 1 1 1 2 1 1 1 1 1 1 1 1 1



MAXIMUM AMMONIA CYLINDER DIMENSIONS







MAXIMUM CYLINDER PRESSURE: 100 PSI.

ACTUAL CYLINDER DIMENSIONS MUST BE LESS THAN MAXIMUM DIMENSIONS SHOWN TO ENSURE PROPER FIT.