



Roller Doors

Provide safety from weld flash!
Safe entry into hazardous areas!
Reduces maintenance costs!

Safe-T-Barrier Roller Doors.....	13:2
Safe-T-Barrier Technical Data.....	13:3



Safe-T-Barrier Roller Doors Heavy Duty, Motor Driven Safety Barrier Curtains

Our Safe-T-Barrier high-speed roller door provides safety from weld flash, flying debris and entry into hazardous work areas. This roller door is ideal for applications where safety light curtains do not offer a sufficient level of safety.

The door features durable black Armorpleat™ fabric with steel barrier bars sewn into the curtain. A soft cotton edge protects personnel and property from impact damage. Vertical uprights are included as well.

The door is available in 208/230V, 460/480V or 575V 3-phase electric, and can be ordered with control reliable level 4 safety interrupt control switches.



Applications

Reduces downtime and maintenance costs and provides safety from weld flash, flying debris and entry into work area.

Features

- Soft bottom edge protects personnel and property from impact damage
- High speed of 24" per second operation helps improve productivity
- Safety interrupt switches provide safety and automate process

Safe-T-Barrier Technical Data

Manufacturer.....JOKAB SAFETY
Ordering Data..... call Jokab Safety
Size
 Minimum.....2'2"w x 8'0"h
 Maximum.....12'6"w x 12'0"h
Speed..... 24" per second operation
Curtain Material.....Standard 50 oz. black Armorpleat™ with
 optional 21" high, full-width vision panel
Roller Tube..... 4" diameter steel tube

Curtain Guides..... 14 gauge steel
Header Material..... 8" x 2" x 11-1/2 lbs. c-channel
Motor..... 3 phase, 1/2 H.P. motor with brake
Gear Box..... worm gear reducer, 15:1 ratio
Control Box
 Optional PLC style.....16" x 14" x 8"
 Optional standard non PLC style.....size 12" x 10" x 6"
Warranty.....limited 1-year parts

Safe-T-Barrier Dimensions



