

# Kelly® Commercial Truck Tires



**KELLY**  **TIRES™**

A Good Deal  
On A Great Tire™

A Good Deal On A Great Tire™ is an accurate description of Kelly commercial tires. The value of the Kelly brand is evident in the miles of original tread life and tough casings that can usually be retreaded multiple times for additional miles of service. Kelly commercial tires are also backed by a nationwide limited warranty,\* and are available for all types of commercial applications. You can find these popular commercial tires at Kelly Dealers and many truck stops across the country.

Size/Type Chart

	Long Haul			Regional					Mixed Service		
Kelly Product Line	KLHA® Page 3	KDA® Page 3	KTSA® Page 4	KDM® I Page 4	Kelly KRH™ Page 5	KSE™ Page 5	KSR™ I Page 6	Kelly KRP® Page 6	KRM™ Page 7	KRM™ I Page 7	KRM™ I SS Page 8
11R22.5	G	G	G	G,H	H	G					
12R22.5									H		
11R24.5	G	G	G	G,H	H	G					
215/75R17.5							H				
225/70R19.5								G			
245/70R19.5							G				
255/70R22.5			H				H				
295/75R22.5	G	G	G	G	G	G					
315/80R22.5										L	
385/65R22.5											J
425/65R22.5											L
285/75R24.5	G	G	G	G		G					

\*See pages 10–11 for more details.

NOTE: The letters in the chart represent load ranges.

# LONG HAUL TIRES



**KLHA®**

## Steer Tire.

- Tough super tensile steel belts help resist punctures and tears for enhanced retreadability.
- 18/32" tread depth helps enhance miles to removal.
- Robust casing and unique tread pattern help improve treadwear and retreadability.
- Mold shape, shoulder rib design, position-specific compounds and uniform belt area components enhance treadwear and weight distribution as well as help reduce cupping wear.
- Lateral cross slots and sipes enhance traction.

Size	Load Range	Single Load (Lbs)	Single Inflation (PSI)	Dual Load (Lbs)	Dual Inflation (PSI)	Rim Width (In)	Overall Width (In)	Overall Diameter (In)	Tread Depth (In)	Speed Rating (MPH)
<b>Tubeless</b>										
<b>11R22.5</b>	<b>G</b>	<b>6,175</b>	<b>105</b>	<b>5,840</b>	<b>105</b>	<b>8.25</b>	<b>11.2</b>	<b>41.4</b>	<b>18</b>	<b>75</b>
<b>11R24.5</b>	<b>G</b>	<b>6,610</b>	<b>105</b>	<b>6,005</b>	<b>105</b>	<b>8.25</b>	<b>11.2</b>	<b>43.4</b>	<b>18</b>	<b>75</b>
<b>295/75R22.5</b>	<b>G</b>	<b>6,175</b>	<b>110</b>	<b>5,675</b>	<b>100</b>	<b>8.25</b>	<b>11.2</b>	<b>40.2</b>	<b>18</b>	<b>75</b>
<b>285/75R24.5</b>	<b>G</b>	<b>6,175</b>	<b>110</b>	<b>5,675</b>	<b>100</b>	<b>8.25</b>	<b>11.1</b>	<b>41.4</b>	<b>18</b>	<b>75</b>



**KDA®**

## Drive Tire.

- Unique shoulder design helps promote traction and uniform treadwear.
- Deep 28/32" tread depth helps provide long original tread life.
- Tread radius helps distribute pressure evenly over the footprint for uniform treadwear and long tread life.
- Stone ejectors help resist casing damage.
- Unique blading pattern enhances the performance and appearance as the tire begins to wear.
- All-steel casing and belts enhance toughness and help increase casing life.

Size	Load Range	Single Load (Lbs)	Single Inflation (PSI)	Dual Load (Lbs)	Dual Inflation (PSI)	Rim Width (In)	Overall Width (In)	Overall Diameter (In)	Tread Depth (In)	Speed Rating (MPH)
<b>Tubeless</b>										
<b>11R22.5</b>	<b>G</b>	<b>6,175</b>	<b>105</b>	<b>5,840</b>	<b>105</b>	<b>8.25</b>	<b>10.9</b>	<b>42.0</b>	<b>28</b>	<b>75</b>
<b>11R24.5</b>	<b>G</b>	<b>6,610</b>	<b>105</b>	<b>6,005</b>	<b>105</b>	<b>8.25</b>	<b>10.9</b>	<b>44.1</b>	<b>28</b>	<b>75</b>
<b>295/75R22.5</b>	<b>G</b>	<b>6,175</b>	<b>110</b>	<b>5,675</b>	<b>100</b>	<b>8.25</b>	<b>11.1</b>	<b>40.8</b>	<b>28</b>	<b>75</b>
<b>285/75R24.5</b>	<b>G</b>	<b>6,175</b>	<b>110</b>	<b>5,675</b>	<b>100</b>	<b>8.25</b>	<b>11.0</b>	<b>42.0</b>	<b>28</b>	<b>75</b>

Tubeless - For 15° drop center rims

# LONG HAUL TIRES



## KTSA®

### Trailer Tire.

- Mono-groove tread design helps promote even wear and helps evacuate water from the tread for enhanced wet traction.
- Unique center groove design helps resist stone drilling and cracking.
- Low tread void helps provide long mileage, enhanced braking and even wear.
- Decoupling groove helps minimize shoulder wear for many miles to removal.
- Penetration protectors help resist cuts and punctures to enhance retreadability.

Size	Load Range	Single Load (Lbs)	Single Inflation (PSI)	Dual Load (Lbs)	Dual Inflation (PSI)	Rim Width (In)	Overall Width (In)	Overall Diameter (In)	Tread Depth (In)	Speed Rating (MPH)
<b>Tubeless</b>										
11R22.5	G	6,175	105	5,840	105	8.25	10.9	41.1	13	75
11R24.5	G	6,610	105	6,005	105	8.25	10.9	43.1	13	75
295/75R22.5	G	6,175	110	5,675	100	8.25	11.2	39.8	13	75
285/75R24.5	G	6,175	110	5,675	100	8.25	11.0	40.9	13	75
255/70R22.5	H	5,510	120	5,070	120	7.50	10.0	36.3	13	75

# REGIONAL TIRES



## KDM® I

### Drive Tire.

- Aggressive tread design and deep tread depth help provide even treadwear.
- Isolated-element tread pattern helps promote excellent traction.
- Unique blading pattern enhances the performance and appearance as the tire begins to wear.
- Tread radius helps distribute pressure evenly over the footprint for uniform treadwear and long tread life.
- All-steel casing and belts enhance toughness and help increase casing life.

Size	Load Range	Single Load (Lbs)	Single Inflation (PSI)	Dual Load (Lbs)	Dual Inflation (PSI)	Rim Width (In)	Overall Width (In)	Overall Diameter (In)	Tread Depth (In)	Speed Rating (MPH)
<b>Tubeless</b>										
11R22.5	G	6,610	120	6,005	120	8.25	11.1	42.0	26	75
11R22.5	H	6,610	120	6,005	120	8.25	11.1	42.0	26	75
11R24.5	G	7,160	120	6,610	120	8.25	11.1	44.2	26	75
11R24.5	H	7,160	120	6,610	120	8.25	11.1	44.2	26	75
295/75R22.5	G	6,175	110	5,675	100	8.25	10.9	41.0	26	75
285/75R24.5	G	6,175	110	5,675	100	8.25	10.6	42.3	26	75

Tubeless - For 15° drop center rims



## KELLY® KRH™

### All-Position Rib Tire.

- Deep 20/32" tread helps provide long original tread life.
- Tread pattern enhances traction on wet and dry roads.
- Belt package offers even wear with less scrub.
- Rib pattern helps promote uniform wear.

Size	Load Range	Single Load (Lbs)	Single Inflation (PSI)	Dual Load (Lbs)	Dual Inflation (PSI)	Rim Width (In)	Overall Width (In)	Overall Diameter (In)	Tread Depth (In)	Speed Rating (MPH)
<b>Tubeless</b>										
11R22.5	H	6,610	120	6,005	120	8.25	10.9	41.5	20	75
11R24.5	H	7,160	120	6,610	120	8.25	11.0	43.6	20	75
295/75R22.5	G	6,175	110	5,675	100	8.25	11.1	40.5	20	75



## KSE®

### All-Position Rib Tire.

- Five full-depth grooves help provide excellent wet and dry traction.
- Tread compound helps resist cuts and tears.
- 16/32" tread depth and low column rib height help promote even treadwear in steer, drive and trailer positions.

Size	Load Range	Single Load (Lbs)	Single Inflation (PSI)	Dual Load (Lbs)	Dual Inflation (PSI)	Rim Width (In)	Overall Width (In)	Overall Diameter (In)	Tread Depth (In)	Speed Rating (MPH)
<b>Tubeless</b>										
11R22.5	G	6,175	105	5,840	105	8.25	10.9	41.2	16	75
11R24.5	G	6,610	105	6,005	105	8.25	10.9	43.2	16	75
295/75R22.5	G	6,175	110	5,675	100	8.25	11.2	40.1	16	75
285/75R24.5	G	6,175	110	5,675	100	8.25	11.0	41.1	16	75

Tubeless - For 15° drop center rims

# REGIONAL TIRES



## KSR™ I

### All-Position Rib Tire.

- Five-rib design and lateral blades enhance traction and appearance when the tire begins to wear.
- Optimized tread void and tread depth help enhance mileage.
- Tread compound helps resist cuts and tears.
- Solid shoulder design helps resist curb damage.

Size	Load Range	Single Load (Lbs)	Single Inflation (PSI)**	Dual Load (Lbs)	Dual Inflation (PSI)**	Rim Width (In)	Overall Width (In)	Overall Diameter (In)	Tread Depth (In)	Speed Rating (MPH)
<b>Tubeless</b>										
<b>215/75R17.5</b>	<b>H</b>	<b>4,805</b>	<b>125</b>	<b>4,540</b>	<b>125</b>	<b>6.00HC*</b>	<b>8.3</b>	<b>30.6</b>	<b>15</b>	<b>75</b>
<b>245/70R19.5</b>	<b>G</b>	<b>4,540</b>	<b>110</b>	<b>4,410</b>	<b>110</b>	<b>7.50</b>	<b>10.0</b>	<b>33.2</b>	<b>16</b>	<b>75</b>
<b>255/70R22.5</b>	<b>H</b>	<b>5,510</b>	<b>120</b>	<b>5,070</b>	<b>120</b>	<b>7.50</b>	<b>10.0</b>	<b>36.6</b>	<b>18</b>	<b>81</b>

\* Requires the use of HC or High Capacity rims.

\*\* Inflatons listed are those necessary to carry the maximum load at normal speeds from Kelly tires. When loads are less than the maximum, inflations should be reduced accordingly. Consult the tire manufacturer or refer to the Tire and Rim Association recommendations (pages 3-4) for special load/inflation conditions.



## KELLY® KRP®

### All-Position Rib Tire.

- Tread design helps promote rib stability and reduced squirm.
- Special buttressed sidewall helps extend casing life.
- Excellent tread life in fast rate-of-wear metro service.

Size	Load Range	Single Load (Lbs)	Single Inflation (PSI)	Dual Load (Lbs)	Dual Inflation (PSI)	Rim Width (In)	Overall Width (In)	Overall Diameter (In)	Tread Depth (In)	Speed Rating (MPH)
<b>Tubeless</b>										
<b>225/70R19.5</b>	<b>G</b>	<b>3,970</b>	<b>110</b>	<b>3,750</b>	<b>110</b>	<b>6.75</b>	<b>8.8</b>	<b>32.0</b>	<b>15</b>	<b>75</b>

Tubeless - For 15° drop center rims

# MIXED-SERVICE TIRES



## KRM™

### All-Position Rib Tire.

- Wide ribs and deep tread depth help provide long, even wear.
- Tread compound helps resist chipping, chunking and tearing.
- Wide grooves help provide excellent wet traction.
- Four-rib bladeless tread and steel belts help resist snags and tearing, and help provide toughness.
- Application-specific casing helps resist punctures for toughness and retreadability.

Size	Load Range	Single Load (Lbs)	Single Inflation (PSI)	Dual Load (Lbs)	Dual Inflation (PSI)	Rim Width (In)	Overall Width (In)	Overall Diameter (In)	Tread Depth (In)	Speed Rating (MPH)
<b>Tubeless</b>										
<b>12R22.5</b>	<b>H</b>	<b>7,390</b>	<b>120</b>	<b>6,780</b>	<b>120</b>	<b>9.00</b>	<b>11.4</b>	<b>43</b>	<b>23</b>	<b>68</b>



## KRM™ I

### All-Position Rib Tire.

- Tread compound helps resist chipping, chunking and tearing.
- 22/32" tread depth helps provide long original tire life.
- Wide ribs and tread radius help promote long, even wear.
- Stone ejectors in each groove help resist casing damage.
- All-steel casing and belts help provide tough performance and long casing life.
- For steer axle weights up to 18,000 pounds in on-/off-road applications such as waste haul.

Size	Load Range	Single Load (Lbs)	Single Inflation (PSI)*	Dual Load (Lbs)	Dual Inflation (PSI)*	Rim Width (In)	Overall Width (In)	Overall Diameter (In)	Tread Depth (In)	Speed Rating (MPH)
<b>Tubeless</b>										
<b>315/80R22.5</b>	<b>L</b>	<b>9,090</b>	<b>130</b>	<b>8,270</b>	<b>130</b>	<b>9.00</b>	<b>12.4</b>	<b>42.6</b>	<b>22</b>	<b>68</b>

\* Listed pressures are minimums required to carry maximum loads at highway speeds. To obtain optimum service from Kelly tires when loads are less than maximum allowable, inflations should be reduced accordingly. Consult the tire manufacturer or refer to the Tire and Rim Association recommendations (pages 3-4) for special load/inflation conditions.

# MIXED-SERVICE TIRES



## KRM™ I SS

### All-Position Rib Tire.

- Wide ribs and deep tread depth help provide long, even wear.
- Tread compound helps resist chipping, chunking and tearing.
- Wide grooves help provide excellent wet traction.
- Four-rib bladeless tread and steel belts help resist snags and tearing, and help provide toughness.
- Application-specific casing helps resist punctures for toughness and retreadability.

Size	Load Range	Single Load (Lbs)	Single Inflation (PSI)*	Dual Load (Lbs)	Dual Inflation (PSI)*	Rim Width (In)	Overall Width (In)	Overall Diameter (In)	Tread Depth (In)	Speed Rating (MPH)
<b>Tubeless</b>										
<b>385/65R22.5</b>	<b>J</b>	<b>9,370</b>	<b>120</b>	<b>--</b>	<b>--</b>	<b>11.75</b>	<b>14.9</b>	<b>42.4</b>	<b>18</b>	<b>65</b>
<b>425/65R22.5</b>	<b>L</b>	<b>11,400</b>	<b>120</b>	<b>--</b>	<b>--</b>	<b>12.25</b>	<b>16.1</b>	<b>44.2</b>	<b>20</b>	<b>65</b>

\* Listed pressures are minimums required to carry maximum loads at highway speeds. To obtain optimum service from Kelly tires when loads are less than maximum allowable, inflations should be reduced accordingly. Consult the tire manufacturer or refer to the Tire and Rim Association recommendations (pages 3-4) for special load/inflation conditions.



# LIMITED WARRANTY

## United States and Canada

### WHO IS ELIGIBLE FOR WARRANTY COVERAGE?

You are eligible for the benefits of this limited warranty if you meet all of the following criteria:

- You are the owner or authorized agent of the owner of new Kelly medium radial truck tires.
- Your tires bear Department of Transportation (DOT) prescribed tire identification numbers and are not branded "NA" (Not Adjustable).
- Your Kelly medium radial truck tires have been used only on the vehicle on which they were originally installed according to the vehicle manufacturer's or Kelly's recommendations.
- Your tires were purchased on or after March 1, 2009.

### WHAT IS COVERED AND FOR HOW LONG?

**1. FREE TIRE REPLACEMENT** – Kelly medium radial truck tires covered by this warranty that become unserviceable due to a covered warranty condition during the first 2/32" (inch) treadwear or 12 months from date of purchase, whichever comes first, will be replaced with a comparable new Kelly medium radial truck tire without charge. You pay only for the mounting and balancing. (Without proof of purchase, date of manufacture will be used to determine eligibility.)

**2. PRORATED TIRE REPLACEMENT** – Tires worn beyond the first 2/32" (inch) treadwear that become unserviceable due to a covered warranty condition will be replaced on a prorated basis. You are responsible for mounting, balancing and any additional services you order at the time of adjustment, as well as any taxes and government-mandated charges.

### HOW WILL THE PRORATED CHARGES BE CALCULATED?

The replacement price will be calculated by multiplying the current Kelly advertised selling price, at the adjustment location, by the percentage of usable original tread that has been worn off at the time of adjustment. You pay for mounting, balancing, an amount equal to the full current Federal Excise Tax (U.S. only) and any other applicable taxes for the comparable new Kelly replacement tire as well as any government-mandated charges.

### EXAMPLE:

If your disabled tire had an original 16/32" (inch) of usable tread depth and is worn to 8/32" (inch) of usable tread remaining, you have used 50% and therefore must pay 50% of the advertised selling price of a comparable tire, plus an amount equal to the full current Federal Excise Tax (U.S. only) applicable to the comparable new replacement tire at the time of adjustment. If the price of the comparable tire is \$400.00, the cost to you would be \$200.00, plus Federal Excise Tax (U.S. only), mounting, balancing, any other applicable taxes and government-mandated charges.

$$\frac{\text{Amount Of Tread Used}}{\text{Original Tread}} \times \text{Value Of Comparable Tire} = \text{Prorated Price Of New Tire}$$

(Plus FET [U.S. only], other applicable taxes, government mandated charges and mounting and balancing.)

### WHAT IS A COMPARABLE TIRE?

A "comparable" new Kelly medium radial truck tire may either be the same line of tire or, in the event that the same tire is not available, a tire of the same basic construction and quality with a different sidewall or tread configuration. If a higher priced tire is accepted as replacement, the difference in price will be at an additional charge to you.

Any replacement tire provided pursuant to this warranty will be covered by the Kelly warranty in effect at the time of replacement.

### WHAT IS NOT COVERED UNDER THIS LIMITED WARRANTY?

- Wear conditions or tire damage due to: road hazards (including punctures, cuts, snags, impact breaks, etc.), wreck, collision, fire, fast wear, irregular wear, heel and toe wear or other wear conditions.
- Improper inflation, overloading, high-speed spinup, misapplication, misuse, negligence, racing, chain damage or improper mounting or demounting.
- Mechanical condition of the vehicle.
- Chip/chunk conditions on tires intended for highway service.
- Ride disturbance after the first 2/32" (inch) treadwear or due to damaged wheels or any vehicle condition.
- Any tire intentionally altered after leaving a factory producing Kelly tires to change its appearance (example: white inlay on a black tire).
- Tires with weather cracking which were purchased more than four (4) years prior to presentation for adjustment. If you have no proof of purchase date, tires manufactured four (4) or more years prior to presentation are not covered.
- Material added to a tire after leaving a factory producing Kelly tires (examples: tire fillers, sealants or balancing substances). If the added material is the cause of the tire being removed from service, the tire will not be adjusted.
- Tires removed from service due to improper repairs.
- Loss of time, inconvenience, loss of use of vehicle, incidental or consequential damage.

Note: Some states or provinces do not allow the exclusion or limitation of incidental or consequential damages, so the above limitations or exclusions may not apply to you.

This limited warranty is applicable only in the U.S. and Canada.

### WHAT IS THE RADIAL MEDIUM TRUCK TIRE CASING PROVISION?

Kelly® medium radial truck tires will be warranted for covered conditions through the first retread for a period of four (4) years from the date of the casing DOT serial number or proof of purchase if available.

If retreaded by a Goodyear Authorized Retreader, casings will be warranted for covered conditions for an unlimited number of retreads for a period of four (4) years from the date of the casing DOT serial number or proof of purchase, if available.

Casing values are based on the predetermined casing value at the time of adjustment. See your servicing Dealer for these values.

### HOW DO YOU KNOW WHEN YOUR TIRES WERE MANUFACTURED?

Tires with a DOT number ending with 0909 or greater were manufactured after 03/01/2009 (0909 refers to the 1st week of March 2009). These tires are covered under the provisions of this warranty coverage.

### WHEN DOES THE WARRANTY END?

Kelly medium radial truck tires have delivered the full original tread life and the new tire coverage of this warranty ends when the treadwear indicators become visible or four (4) years from the date of original tire manufacture or new tire purchase date (whichever occurs first). Without proof of purchase, date of manufacture will be used to determine eligibility. Casings may continue to be warranted beyond the new tire coverage. Please refer to the "WHAT IS THE RADIAL MEDIUM TRUCK TIRE CASING PROVISION?" section for warranty details on casings.

### HOW DO YOU OBTAIN AN ADJUSTMENT?

- A. You must present the tire to be adjusted to an authorized Kelly Commercial Tire Retailer. Please consult your telephone directory for locations. Tires replaced on an adjustment basis become the property of The Goodyear Tire & Rubber Company or Goodyear Canada Inc.
- B. You must pay for taxes or any additional service you order at the time of adjustment.
- C. No claim will be recognized unless submitted on a Kelly claim form (supplied by a Kelly Commercial Tire Retailer) that is completely filled out and signed by you, the owner of the tire presented for adjustment, or your authorized agent.

### WHAT ARE YOUR LEGAL RIGHTS?

This warranty gives you specific legal rights, and you may also have other rights that vary from state to state and province to province.

Note: No Representative or Dealer has authority to make any representation, promise or agreement on behalf of Kelly except as stated herein.

Any tire, no matter how well constructed, may fail in service or otherwise become unserviceable due to conditions beyond the control of the manufacturer. Under no circumstances is this warranty a representation that a tire failure cannot occur.

### SAFETY WARNINGS

Property damage, serious injury or death may result from:

- **TIRE FAILURE DUE TO UNDERINFLATION/OVERLOADING/MISAPPLICATION.** Follow the vehicle owner's manual or tire placard in the vehicle.
- **TIRE FAILURE DUE TO IMPACT DAMAGE/IMPROPER MAINTENANCE.** Tires should be inspected regularly by a qualified technician for signs of damage, such as punctures or impacts.
- **TIRE FAILURE DUE TO IMPROPER REPAIRS.** See Rubber Manufacturers Association (RMA) established repair procedures at [www.rma.org](http://www.rma.org) and/or go to [www.goodyear.com/truck](http://www.goodyear.com/truck) for information on proper repair procedures.
- **EXPLOSION OF TIRE/RIM ASSEMBLY DUE TO IMPROPER MOUNTING.** Only specially trained persons should mount tires. When mounting tires, use safety cage and clip-on extension air hose to inflate.
- **FAILURE TO MOUNT RADIAL TIRES ON APPROVED RIMS.**
- **FAILURE TO DEFLATE SINGLE OR DUAL ASSEMBLIES COMPLETELY BEFORE DEMOUNTING.**
- **TIRE SPINNING.** On slippery surfaces such as snow, mud, ice, etc., do not spin tires in excess of 35 mph (55 kph), as indicated on the speedometer.
- **EXCESSIVE WHEEL SPINNING.** This can also result in tire disintegration or axle failure.

### FOR SERVICE ASSISTANCE OR INFORMATION:

1. First contact the nearest Authorized Kelly Commercial Tire Retailer.
2. If additional assistance is required:

- In the U.S., write to –  
Kelly Customer Assistance Center  
Department 728  
1144 East Market St.  
Akron, OH 44316

- In Canada, write to –  
Kelly Customer Assistance Center  
450 Kipling Avenue  
Toronto, Ont. M8Z 5E1





### **National Account Status**

- Trusted Tire Brands
- National Pricing
- Consistent Nationwide Service
- 24-Hour Customer Support
- Emergency Roadside Tire Service
- Tire Evaluation Tools
- Online Information
- Consolidated Billing
- Manage Your Fleet, Not Your Tires -  
With fleetHQ<sup>SM</sup>

Contact your local Kelly Dealer to  
establish your program today.



**KELLY TIRES 1144 East Market Street, Akron, OH 46356-0001**  
**[www.kellytires.com/commercial](http://www.kellytires.com/commercial)**