

RACO® Specialty Switches



Applications

- Industrial
- Electronic instruments
- Automotive/marine equipment
- Power tools
- Home appliances
- Emergency lighting
- Vending machines

Pull-Chain Switch**Product Features**

- Plastic body and nipple
- Nipple 3/8" – UNS 27 x 5/16" long
- Aluminum knurled nut, brass or nickel finish

Variable-Speed Pull-Chain Switch**Product Features**

- Plastic body and nipple
- Brass knurled nut
- Nipple 3/8" – UNS 27 x 3/8" long

All-Angle Pull-Chain**Product Features**

- Plastic body and metal nipple
- Nipple 15/32" – UNS 32
- Steel lockout

**Pull-Chain and Variable-Speed
Pull-Chain Switches and All-Angle
Pull-Chain Switches Compliances**

- 
- 

Snap-In Rocker Switches**Product Features**

- Nylon body and rocker
- Polycarbonate rocker (#6437)
- Contacts – silver-plated copper-alloy
- .250 quick connect tabs
- Fits cutout 17/32" x 1-1/8"

**Snap in Rocker Switches
Compliances**

- 
- 



6401, 6354



6402, 6355



6403, 6404



6405



6436



6437

ORDERING INFORMATION - DIMENSIONS**PULL-CHAIN SWITCHES – FOR LAMPS AND CEILING FIXTURES**

CATALOG NUMBER	DESCRIPTION	ELECTRICAL RATINGS	STD. PKG.	UPC BAR CODE
6401	SPST, on-off 6" leads, brass finish Carded	6 amp, 125V AC 3 amp, 250V AC 6 amp, 125V L	5	
6354	SPST, on-off 6" leads, brass finish Bulk Poly Bag	6 amp, 125V AC 3 amp, 250V AC 6 amp, 125V L	25	
6402	SPST, on-off 6" leads, nickel finish Carded	6 amp, 125V AC 3 amp, 250V AC 6 amp, 125V L	5	
6355	SPST, on-off 6" leads, nickel finish Bulk Poly Bag	6 amp, 125V AC 3 amp, 250V AC 6 amp, 125V L	25	

VARIABLE-SPEED PULL-CHAIN SWITCHES – FOR CEILING FANS

CATALOG NUMBER	DESCRIPTION	ELECTRICAL RATINGS	STD. PKG.	UPC BAR CODE
6403	2-speed, off-on-on Stab connections, brass finish Carded	6 amp, 125V AC 3 amp, 250V AC 6 amp, 125V L	5	
6404	3-speed, off-on-on-on, Stab connections, brass finish, Carded	6 amp, 125V AC 3 amp, 250V AC	5	

ALL-ANGLE PULL-CHAIN – FOR CEILING FIXTURES

CATALOG NUMBER	DESCRIPTION	ELECTRICAL RATINGS	STD. PKG.	UPC BAR CODE
6405	All angle, on-off 3" leads, SPST, Carded	6 amp, 125V AC 3 amp, 250V AC	5	

SNAP-IN ROCKER SWITCHES – FOR RANGE HOOD AND APPLIANCES

CATALOG NUMBER	DESCRIPTION	ELECTRICAL RATINGS	STD. PKG.	UPC BAR CODE
6436	Rocker, SPST, on-off Opening 17/32" x 1-1/8" Carded	16 amp, 250V AC 1 HP, 250V AC 1/2 HP, 125V AC	5	
6437	Lighted rocker SPST, on-off Opening 17/32" x 1-1/8" Carded	110V Lamp 16 amp, 250V AC 15 amp, 1 HP, 250V AC 1/2 HP, 125V AC	5	

**RACO**

SPECIALTY TYPE SWITCHES

Applications

- Industrial
- Electronic instruments
- Automotive/marine equipment
- Power tools
- Home appliances
- Emergency lighting
- Vending machines

Canopy Switch Compliances

- 
- 



6445



6446



6356, 6357



6447



6448RAC



6424, 6352



6425, 6353

ORDERING INFORMATION - DIMENSIONS

ROTARY CANOPY SWITCH - FOR LAMPS AND APPLIANCES

CATALOG NUMBER	DESCRIPTION	ELECTRICAL RATINGS	STD. PKG.	UPC BAR CODE
6445	Rotary, canopy, SPST, Off-on-on-on plastic knob Carded	2 amp, 250V AC 4 amp, 125V AC 1 amp, 125V DC	5	
6446	Rotary, canopy, SPST, On-off, 6" leads, plastic knob Carded	1 amp, 250V AC 3 amp, 120V AC 1 amp, 125V ACL	5	
6356	Rotary, canopy, SPST, On-off, 6" leads, plastic knob Bulk Poly Bag	1 amp, 250V AC 3 amp, 120V AC 1 amp, 125V ACL	25	
6447	Rotary, canopy, SPST, On-off, 6" leads, brass knob Carded	1 amp, 250V AC 3 amp, 120V AC 1 amp, 125V ACL	5	
6448RAC	Rotary, canopy, 2-circuit, Off-on-on-on, 6" leads Brass knob, carded	1 amp, 250V AC 3 amp, 125V ACL	5	
6357	Rotary, canopy, 2-circuit, Off-on-on-on, 6" leads Brass knob, Bulk Poly Bag	1 amp, 250V AC 3 amp, 125V ACL	25	

MAINTAINED CONTACT PUSH-BUTTON CANOPY SWITCH - FOR LAMPS AND APPLIANCES

CATALOG NUMBER	DESCRIPTION	ELECTRICAL RATINGS	STD. PKG.	UPC BAR CODE
6424	Push, canopy, SPST On-off, 6" leads, brass Carded	1 amp, 250V AC 2 amp, 125V ACL 3 amp, 120V AC	5	
6352	Push, canopy, SPST On-off, 6" leads, brass Bulk Poly Bag	1 amp, 250V AC 2 amp, 125V ACL 3 amp, 120V AC	25	
6425	Push, canopy, SPST On-off, 6" leads, nickel Carded	1 amp, 250V AC 2 amp, 125V ACL 3 amp, 120V AC	5	
6353	Push, canopy, SPST On-off, 6" leads, nickel Bulk Poly Bag	1 amp, 250V AC 2 amp, 125V ACL 3 amp, 120V AC	25	

Push-Button Switch Product Features

- Plastic case
- Nickel-plated brass nipple, knurled nut, hex nut
- Nipple 15/32" – 32 x 1/2" long

Compliances

- 
- 



6431



6426



6428



6427



6358

ORDERING INFORMATION - DIMENSIONS

MAINTAINED CONTACT SLIDE SWITCH – FOR LAMPS AND APPLIANCES

CATALOG NUMBER	DESCRIPTION	ELECTRICAL RATINGS	STD. PKG.	UPC BAR CODE
6431	Slide, SPST, on-off Opening 9/16" x 7/8", Carded	5 amp, 250V AC 11 amp, 125V AC	5	

CONTACT PUSH-BUTTON SWITCHES – FOR BELLS AND BUZZERS

CATALOG NUMBER	DESCRIPTION	ELECTRICAL RATINGS	STD. PKG.	UPC BAR CODE
6426	SPST Off-on, normally off, push on, Black, screw terminals, Carded	3 amp, 240V AC 6 amp, 120V AC	5	
6428	SPST Off-on, normally on, push off Red, screw terminals, Carded	1.5 amp, 277V AC 3 amp, 120V AC	5	

PUSH BUTTON SWITCH - FOR LAMPS AND APPLIANCES

CATALOG NUMBER	DESCRIPTION	ELECTRICAL RATINGS	STD. PKG.	UPC BAR CODE
6358	Double Insulated, SPST, on-off 6" wire leds, Bulk Poly Bag	2 amp, 125V ACL 3 amp, 120V AC 1 amp, 250V AC	25	
6427	Push button SPST, on-off, 6" leads Carded	10 amp, 125V AC 8 amp, 125V AC 4 amp, 250V 1/3 HP, 125V AC	5	

SPECIALTY TYPE SWITCHES

Product Features

- Impact-resistant thermoplastic body
- Silver cadmium oxide contacts
- Knurled nut, hex and strap all nickel-plated
- Keyed brass bushing
- #6-32 screw-type terminals
- Nickel-plated brass toggle
- Suitable for 12V DC use at rated amperage

Compliances

- 
- 



ORDERING INFORMATION - DIMENSIONS

EXTRA HEAVY-DUTY BAT HANDLE TOGGLE SWITCH				
CATALOG NUMBER	DESCRIPTION	ELECTRICAL RATINGS	STD. PKG.	UPC BAR CODE
6415	DPST, on-off, Screw terminals, Carded	10 amp, 277V AC, 20 amp, 125V AC 1-1/2 HP, 125V/250V AC	5	
6419	DPDT, on-on, Screw terminals, Carded	10 amp, 277V AC, 20 amp, 125V AC 1-1/2 HP, 125V/250V AC	5	
6416	DPDT, on-off-on, Screw terminals, Carded	20 amp, 125V AC 1-1/2 HP, 125V/250V AC	5	

HEAVY-DUTY BAT HANDLE TOGGLE SWITCH				
CATALOG NUMBER	DESCRIPTION	ELECTRICAL RATINGS	STD. PKG.	UPC BAR CODE
6410RAC	SPST, on-off Screw terminals Carded	12 amp, 250V AC 20 amp, 125V AC 1 HP, 120V/240V AC	5	
6413	SPDT, on-on Screw terminals Carded	10 amp, 250V AC 20 amp, 125V AC 3/4 HP, 125V/250V AC	5	
6411	SPDT, on-off-on Screw terminals	10 amp, 250V AC 20 amp, 125V AC 3/4 HP, 125V AC	5	
6420	SPST, on-off Screw terminals Carded	10 amp, 250V AC 20 amp, 125V AC 3/4 HP, 125V/250V AC	5	

EXTRA HEAVY-DUTY BAT HANDLE TOGGLE SWITCH				
CATALOG NUMBER	DESCRIPTION	ELECTRICAL RATINGS	STD. PKG.	UPC BAR CODE
6417	SPST, on-off Screw terminals Nonmetallic, Carded	20 amp, 125V/277V AC 1-1/2 HP, 125V AC 2 HP, 250V AC	5	
6418	DPDT, on-off-on Screw terminals Nonmetallic, Carded	20 amp, 125V/277V AC 2 HP, 250V AC 1-1/2 HP, 125V AC	5	

MEDIUM-DUTY BAT HANDLE TOGGLE SWITCH				
CATALOG NUMBER	DESCRIPTION	ELECTRICAL RATINGS	STD. PKG.	UPC BAR CODE
6414	SPST, on-off Screw terminals Carded	15 amp, 120V AC 10 amp, 240V AC	5	

Product Features

- Impact-resistant thermoplastic body
- Silver cadmium oxide contacts
- Knurled nut, hex and strap all nickel-plated
- Keyed brass bushing
- #6-32 screw-type terminals
- Nickel-plated brass toggle
- Suitable for 12V DC use at rated amperage

Toggle Boot Product Features

- Fits standard bat handle toggle switches
- Made of silicone rubber
- Fits nipples with 15/32" – 32 thread
- Packed two per card

Compliances

- 
- 



6412



6351



6409RAC



6441

ORDERING INFORMATION - DIMENSIONS**MEDIUM-DUTY BAT HANDLE TOGGLE SWITCH WITH WIRE LEADS**

CATALOG NUMBER	DESCRIPTION	ELECTRICAL RATINGS	STD. PKG.	UPC BAR CODE
6412	SPST, on-off, 6" leads Carded	4 amp, 250V 8 amp, 125V 10 amp, 125V AC 1/3 HP, 125V AC	5	

MEDIUM-DUTY BALL HANDLE TOGGLE SWITCH WITH WIRE LEADS

CATALOG NUMBER	DESCRIPTION	ELECTRICAL RATINGS	STD. PKG.	UPC BAR CODE
6351	SPST, on-off, Ball handle Toggle for power tools & appliances, Nonmetallic with 6" wire leads, Bulk Poly Bag	6 amp, 125V AC 3 amp, 250V AC 3 amp, 125V ACL	25	

MEDIUM-DUTY BALL TOGGLE

CATALOG NUMBER	DESCRIPTION	ELECTRICAL RATINGS	STD. PKG.	UPC BAR CODE
6409RAC	SPST, on-off Screw terminals, Carded	6 amp, 120V AC 3 amp, 240V AC	5	

TOGGLE BOOT

CATALOG NUMBER	DESCRIPTION	ELECTRICAL RATINGS	STD. PKG.	UPC BAR CODE
6441	Rubber cover & nut for toggle switch, Carded	—	5	

SPECIALTY TYPE SWITCHES

Switch Assortment Product Features

- All cards are 2-7/8" wide x 5" high
- One carton of five fits on hook
- Hooks and pegboard are not included
- Blisters are 1" deep

RACO PACKAGING PRODUCES SALES!

Basic description
and characteristics

Typical applications
for the switch

Visible packaging
lets the customer
see the switch details

Reorder number




All electrical data –
amps, volts and
horsepower ratings
included.

It is easy to match the
rating with the switch

Easy-to-follow
wiring diagram

Clear instructions for
safe replacement

UPC bar code



Polybagged
Packaging



6395

ORDERING INFORMATION - DIMENSIONS

ASSORTMENT

CATALOG NUMBER	DESCRIPTION	ELECTRICAL RATINGS	STD. PKG.	UPC BAR CODE
6150	5-pack each of 30 switches	—	1	

SPECIALTY SWITCH ASSORTMENT

NO. 6150 SPECIALTY SWITCH ASSORTMENT INCLUDES 5 EACH OF THE FOLLOWING SWITCHES:					
6401	6409RAC	6414	6419	6427	6441
6402	6410RAC	6415	6420	6428	6445
6403	6411	6416	6424	6431	6446
6404	6412	6417	6425	6436	6447
6405	6413	6418	6426	6437	6448RAC

DISPLAY

CATALOG NUMBER	DESCRIPTION	STD. PKG.	UPC BAR CODE
6395	Plexiglass counter display	1	—

