


ANGLE ANGLE SEAT VALVE VALVE



 **ROTEX**


Engineering For The Future



ANGLE SEAT VALVE - DOUBLE ACTING

FEATURES

- NC/ NO/ Bi-Directional
- Can be easily converted from NC to NO/ Double Acting to Single Acting
- Operator with threaded/ NAMUR ports
- Lubricated pilot air not necessary
- Ideally suited for vacuum service
- Fast acting up to 1000 cycles/ hour
- Wetted parts : CF3M (SS 316L cast), SS 316L
- Life > 10 million cycles
- Modular design




- Floating plug for longer life



- Smooth profile with lower bend for higher flow



- Burnished piston shaft and PTFE gland packing for lower friction, smoother operations and longer life




- Longer sleeve accommodating large number of gland packings for better leak tightness and longer life, avoiding metal to metal contacts


ANGLE SEAT VALVE - SINGLE ACTING

FEATURES


- NC/ NO/ Bi-Directional
- Can be easily converted from NC to NO/ Single Acting to Double Acting
- Operator with threaded/ NAMUR ports
- Lubricated pilot air not required
- Ideally suited for vacuum service
- Fast acting up to 500 cycles/ hour
- Wetted parts : CF3M (SS 316L cast), SS 316L
- Life > 10 million cycles
- Modular design



- Aluminium hard anodized piston



- 360° Rotatable operator
- NAMUR/ Threaded port operator
- Operator having threaded ports is ideally suited for area in which contamination due to exhaust air and sedimentation of particles in the operator crevices are not desired
- Corrosion resistive glass filled Nylon operator
- SS inserts for operator ports



- Open/ Closed indicator




SPECIFICATION

- Valve type : Angle Seated Valve
- Action : Normally Closed/ Normally Open/ Bi-Directional
- Operating Pressure : 0 - 16 bar/ 0 - 25 bar
- Size : 1/2" 3/4", 1", 1 1/4", 1 1/2", 2", 2 1/2", 3"
- Body, Sleeve material : CF3M (SS 316L Cast) (1.4435)
- Seat, Seal : PTFE, PEEK
- Shaft/ Seat Material : SS 316L (1.4404)
- Port Connection : Threaded/ Weld end/ Triclamp/ ANSI Flange/ Pipe weld
- Media : Steam, Air, Oil, Water, Fuel Gas and Liquid, Vacuum
- Fluid temperature : -10 °C to +180 °C
- Operator Material : Nylon Glass Filled
- Seal/ O Ring : Viton
- Pilot Pressure : 0.8 - 10 bar (Refer Pages 6 to 10)
- Ambient temperature : -10 °C to +60 °C
- Pilot Fluid : Air, Inert Gas filtered to 50 micron

APPLICATION

Air Drying Equipment, Autoclave, Bottling and Dispensing Equipment, Chemical and Petrochemical Industries, Coolant Control for Machine Tool, Fuel, Ink and Paint Dispensing, Industrial Compressor, Laundry Equipment, Nuclear Energy, Pollution Control Equipment, Process Control Application, Power Generation, Paper and Pulp Industries, PSA Plants, Pharmaceutical, Steam, Sterilizer, Textile Dyeing and Drying.

RECOMANDED : INSTALLATION



PRESSURE TEMPERATURE CHART

Angle seat valve intended to be installed in an area where PED is applicable, the valve should be connected to a fluid pressure as indicated in the table hereunder or as mentioned in the operating parameter on page 5 whichever is lower.

DN	Class	Maximum Pressure kg/cm ²					PED Applicable
		-10 °C To Room Temp.	50 °C	100 °C	150 °C	200 °C	
12	B40	≤25	≤25	≤25	≤25	≤25	Not Applicable
20	B40	≤25	≤25	≤25	≤25	≤25	Not Applicable
25	B40	≤25	≤25	≤25	≤25	≤25	Not Applicable
32	B25	24.5	23.2	20.8	19.0	17.6	Yes
40	B20	19.6	19.0	16.7	15.2	14.1	Yes
50	B25	24.5	23.7	20.8	19.6	17.6	Yes
65	B40	≤25	≤25	≤25	≤25	≤25	Yes
80	B40	≤15	≤15	≤15	≤15	≤15	Yes

Refer to operating parameter on page 5 for maximum permissible pressure based on the function type

OPERATING PARAMETERS

OPERATING PARAMETER AT ROOM TEMPERATURE REFER FOR (AV, AW, AP & AF-(CLASS 300))

TYPE	DN	Actuator Ø	Connection	Kv m³/h	Single Acting										Double Acting			
					Normally Closed, Pr. above plug		Normally Closed, Pr. above plug operated by 5/2 Pilot Valve		Normally Closed, Pr. below plug		Normally Closed, Bi-directional				Normally Open Pr. below plug		Normally Closed/ Open Bi-directional	
					F1		F5		F6		F3		F3		F2		F4	
					Pilot Pr. (bar)	Fluid Pr. (bar)	Pilot Pr. (bar)	Fluid Pr. (bar)	Pilot Pr. (bar)	Fluid Pr. (bar)	Pilot Pr. (bar)	Fluid Pr. (bar)	Pilot Pr. (bar)	Fluid Pr. (bar)	Pilot Pr. (bar)	Fluid Pr. (bar)	Pilot Pr. (bar)	Fluid Pr. (bar)
12040	12	40	1/2"	5.8	4.4-10	16	4.4-10	16			7.5-10	10	7.5-10	12	4.4-10	25	0.8-10	25
12050	12	50	1/2"	5.8	2.8-10	16	2.8-10	16			7-10	14	7-10	16	2.8-10	25	0.8-10	25
12063	12	63	1/2"	5.8					4.5-10	0-25								
20050	20	50	3/4"	10.8	2.5-10	16	2.5-10	16			7-10	12	7-10	16	2.5-10	25	0.8-10	25
20063	20	63	3/4"	10.8	2.2-10	16	2.2-10	16	4.5-10	0-16	7.5-10	14	7.5-10	16	2.2-10	25	0.6-10	25
25050	25	50	1"	21	2.8-10	16	2.8-10	16			7-10	10	7-10	14	2.8-10	25	0.8-10	25
25063	25	63	1"	21	2.5-10	16	2.5-10	16	4.5-10	0-12	7.5-10	12	7.5-10	16	2.5-10	25	0.6-10	25
32063	32	63	1 1/4"	31	2.8-10	16	2.8-10	16	4.5-10	0-8	7.5-10	5	7.5-10	10	2.8-10	24.5	0.6-10	24.5
32090	32	90	1 1/4"	31	1.8-10	16	1.8-10	16			6-10	14	6-10	16	1.8-10	24.5	0.3-10	24.5
40063	40	63	1 1/2"	49	2.8-10	16	2.8-10	16	4.5-10	0-5	-	-	-	-	2.8-10	16	0.6-10	19.6
40090	40	90	1 1/2"	49	1.8-10	16	1.8-10	16			6-10	10	6-10	16	1.8-10	19.6	0.2-10	19.6
40110	40	110	1 1/2"	49	1.2-10	16	1.2-10	16			4.8-10	15	4.8-10	16	1.2-10	19.6	0.6-10	19.6
50063	50	63	2"	68	2.7-10	16	2.7-10	16	4.5-10	0-3	-	-	-	-	2.7-10	13	0.3-10	24.5
50090	50	90	2"	68	1.8-10	16	1.8-10	16			6-10	6	6-10	13	1.8-10	24.5	0.2-10	24.5
50110	50	110	2"	68	1.2-10	16	1.2-10	16			1.3-10	10	4.8-10	16	1.2-10	16	0.2-10	24.5
65090	65	90	2 1/2"	120	1.8-10	12	1.8-10	12							1.8-10	16	0.3-10	16
65110	65	110	2 1/2"	120	1.2-10	16	1.2-10	16							1.2-10	25	0.2-10	25
80110	80	110	3"	185	1.2-10	12	1.2-10	12							1.2-10	15	0.2-10	15

Note : Models in bold prints are preferred valve size, operator combination

OPERATING PARAMETERS

OPERATING PARAMETER AT ROOM TEMPERATURE REFER FOR AF-CLASS 150

TYPE	DN	Actuator Ø	Connection	Kv m³/h	Single Acting										Double Acting			
					Normally Closed, Pr. above plug			Normally Closed, Pr. below plug			Normally Closed, Bi-directional Pr. below plug			Normally Open Pr. below plug			Normally Closed/ Open Bi-directional	
					F1		F5		F6		F3		F2		F4		Pilot Pr. (bar)	Fluid Pr. (bar)
					Pilot Pr. (bar)	Fluid Pr. (bar)	Pilot Pr. (bar)	Fluid Pr. (bar)	Pilot Pr. (bar)	Fluid Pr. (bar)	Pilot Pr. (bar)	Fluid Pr. (bar)	Pilot Pr. (bar)	Fluid Pr. (bar)	Pilot Pr. (bar)	Fluid Pr. (bar)		
12040	12	40	1/2"	5.8	4.4-10	16	4.4-10	16			7.5-10	10	7.5-10	12	4.4-10	19	0.8-10	19
12050	12	50	1/2"	5.8	2.8-10	16	2.8-10	16			7-10	14	7-10	16	2.8-10	19	0.8-10	19
12063	12	63	1/2"	5.8					4.5-10	0-19								
20050	20	50	3/4"	10.8	2.5-10	16	2.5-10	16			7-10	12	7-10	16	2.5-10	19	0.8-10	19
20063	20	63	3/4"	10.8	2.2-10	16	2.2-10	16	4.5-10	0-16	7.5-10	14	7.5-10	16	2.2-10	19	0.6-10	19
25050	25	50	1"	21	2.8-10	16	2.8-10	16			7-10	10	7-10	14	2.8-10	19	0.8-10	19
25063	25	63	1"	21	2.5-10	16	2.5-10	16	4.5-10	0-12	7.5-10	12	7.5-10	16	2.5-10	19	0.6-10	19
32063	32	63	1 1/4"	31	2.8-10	16	2.8-10	16	4.5-10	0-8	7.5-10	5	7.5-10	10	2.8-10	19	0.6-10	19
32090	32	90	1 1/4"	31	1.8-10	16	1.8-10	16			6-10	14	6-10	16	1.8-10	19	0.3-10	19
40063	40	63	1 1/2"	49	2.8-10	16	2.8-10	16	4.5-10	0-5	-	-	-	-	2.8-10	16	0.6-10	19
40090	40	90	1 1/2"	49	1.8-10	16	1.8-10	16			6-10	10	6-10	16	1.8-10	19	0.2-10	19
40110	40	110	1 1/2"	49	1.2-10	16	1.2-10	16			4.8-10	15	4.8-10	16	1.2-10	19	0.6-10	19
50063	50	63	2"	68	2.7-10	16	2.7-10	16	4.5-10	0-3	-	-	-	-	2.7-10	13	0.3-10	19
50090	50	90	2"	68	1.8-10	16	1.8-10	16			6-10	6	6-10	13	1.8-10	19	0.2-10	19
50110	50	110	2"	68	1.2-10	16	1.2-10	16			1.3-10	10	4.8-10	16	1.2-10	16	0.2-10	19
65090	65	90	2 1/2"	120	1.8-10	12	1.8-10	12							1.8-10	16	0.3-10	16
65110	65	110	2 1/2"	120	1.2-10	16	1.2-10	16							1.2-10	19	0.2-10	19
80110	80	110	3"	185	1.2-10	12	1.2-10	12							1.2-10	15	0.2-10	15

Note : Models in bold prints are preferred valve size, operator combination



OPERATING PARAMETERS









OPERATING PARAMETER AT ROOM TEMPERATURE REFER FOR AK

TYPE	DN	Actuator Ø	Connection	Kv m ³ /h	Single Acting										Double Acting			
					Normally Closed, Pr. above plug		Normally Closed, Pr. above plug operated by 5/2 Pilot Valve		Normally Closed, Pr. below plug		Normally Closed, Bi-directional				Normally Open Pr. below plug		Normally Closed/ Open Bi-directional	
					F1		F5		F6		F3		F3		F2		F4	
					Pilot Pr. (bar)	Fluid Pr. (bar)	Pilot Pr. (bar)	Fluid Pr. (bar)	Pilot Pr. (bar)	Fluid Pr. (bar)	Pilot Pr. (bar)	Fluid Pr. (bar)	Pilot Pr. (bar)	Fluid Pr. (bar)	Pilot Pr. (bar)	Fluid Pr. (bar)	Pilot Pr. (bar)	Fluid Pr. (bar)
12040	12	40	1/2"	5.8	4.4-10	13	4.4-10	13			7.5-10	10	7.5-10	12	4.4-10	13	0.8-10	13
12050	12	50	1/2"	5.8	2.8-10	13	2.8-10	13			7-10	13	7-10	13	2.8-10	13	0.8-10	13
12063	12	63	1/2"	5.8					4.5-10	0-13								
20050	20	50	3/4"	10.8	2.5-10	13	2.5-10	13			7-10	12	7-10	13	2.5-10	13	0.8-10	13
20063	20	63	3/4"	10.8	2.2-10	13	2.2-10	13	4.5-10	0-13	7.5-10	13	7.5-10	13	2.2-10	13	0.6-10	13
25050	25	50	1"	21	2.8-10	13	2.8-10	13			7-10	10	7-10	13	2.8-10	13	0.8-10	13
25063	25	63	1"	21	2.5-10	13	2.5-10	13	4.5-10	0-12	7.5-10	12	7.5-10	13	2.5-10	13	0.6-10	13
32063	32	63	1 1/4"	31	2.8-10	13	2.8-10	13	4.5-10	0-8	7.5-10	5	7.5-10	10	2.8-10	13	0.6-10	13
32090	32	90	1 1/4"	31	1.8-10	13	1.8-10	13			6-10	13	6-10	13	1.8-10	13	0.3-10	13
40063	40	63	1 1/2"	49	2.8-10	13	2.8-10	13	4.5-10	0-5	-	-	-	-	2.8-10	13	0.6-10	13
40090	40	90	1 1/2"	49	1.8-10	13	1.8-10	13			6-10	10	6-10	13	1.8-10	13	0.2-10	13
40110	40	110	1 1/2"	49	1.2-10	13	1.2-10	13			4.8-10	13	4.8-10	13	1.2-10	13	0.6-10	13
50063	50	63	2"	68	2.7-10	13	2.7-10	13	4.5-10	0-3	-	-	-	-	2.7-10	13	0.3-10	13
50090	50	90	2"	68	1.8-10	13	1.8-10	13			6-10	6	6-10	13	1.8-10	13	0.2-10	13
50110	50	110	2"	68	1.2-10	13	1.2-10	13			1.3-10	10	4.8-10	13	1.2-10	13	0.2-10	13
65090	65	90	2 1/2"	120	1.8-10	12	1.8-10	12							1.8-10	13	0.3-10	13
65110	65	110	2 1/2"	120	1.2-10	13	1.2-10	13							1.2-10	13	0.2-10	13
80110	80	110	3"	185	1.2-10	12	1.2-10	12							1.2-10	13	0.2-10	13

Note : Models in bold prints are preferred valve size, operator combination



OPERATING PARAMETERS









	SINGLE ACTING, NORMALLY CLOSED, PRESSURE ABOVE PLUG Application : Ideally suited for condensable media (Steam) Media : Air, Oil, Steam, Water, Liquid, Fuel, Gases, Vacuum		
		F1	F5



Note : 1 Models in bold prints are preferred valve size, operator combination
 2 Angle Seat Valve function type F1 when opted to be operated by 5/2 Solenoid Valve, specify function type as F5



OPERATING PARAMETERS









	SINGLE ACTING, NORMALLY CLOSED, PRESSURE BELOW PLUG		
	Application : Ideally suited for condensable media (Steam) Media : Air, Oil, Steam, Water, Liquid, Fuel, Gases, Vacuum		F6



Note : Models in bold prints are preferred valve size, operator combination

OPERATING PARAMETERS

	SINGLE ACTING, NORMALLY CLOSED, BI-DIRECTIONAL	
	Application : For incompressible media. To avoid water hammer connect inlet below plug and for condensable media (steam) connect inlet above plug Media : Air, Oil, Steam, Water, Liquid, Fuel, Gases, Vacuum	F3











Note :

- Follow 'BP' when inlet connected to port '2'. i.e. pressure below plug
- Follow 'AP' when inlet connected to port '1'. i.e. pressure above plug

Note : Models in bold prints are preferred valve size, operator combination



OPERATING PARAMETERS









	SINGLE ACTING, NORMALLY OPEN, PRESSURE BELOW PLUG		
	Application : Ideally suited for incompressible media (Liquid) Media : Air, Oil, Steam, Water, Liquid, Fuel, Gases, Vacuum		F2



Note : Models in bold prints are preferred valve size, operator combination

OPERATING PARAMETERS


	DOUBLE ACTING, NORMALLY CLOSED/ NORMALLY OPEN, BI-DIRECTIONAL	
	Application : For incompressible media. To avoid water hammer connect inlet below plug and for condensable media (Steam) connect inlet above plug Media : Air, Oil, Steam, Water, Liquid, Fuel, Gases, Vacuum	F4



Note : Models in bold prints are preferred valve size, operator combination

DIMENSIONS

TYPE 'AV' : Threaded ports as per ISO 228/1 and ISO 7/1




(All dimensions are in mm)

Model	DN	Actuator Ø	A	B BSP/ NPT	E	F	G	ØJ	I	Weight kg. (appx.)
AV12040-X-X	12	40	65	1/2"	189	180	167	65	38	1
AV12050-X-X	12	50	65	1/2"	187	178	166	75	42	1
AV20050-X-X	20	50	75	3/4"	191	181	165	75	42	1.1
AV20063-X-X	20	63	75	3/4"	205	194	178	93	49	1.3
AV25050-X-X	25	50	90	1"	197	185	165	75	42	1.4
AV25063-X-X	25	63	90	1"	210	199	178	93	49	1.6
AV32063-X-X	32	63	110	1 1/4"	220	208	182	93	49	2.1
AV32090-X-X	32	90	110	1 1/4"	253	240	216	124	67	3.2
AV40063-X-X	40	63	120	1 1/2"	225	219	189	93	49	2.9
AV40090-X-X	40	90	120	1 1/2"	255	249	219	124	67	3.9
AV40110-X-X	40	110	120	1 1/2"	274	268	238	148	75	4.1
AV50063-X-X	50	63	150	2"	253	238	203	93	49	4.1
AV50090-X-X	50	90	150	2"	283	268	233	124	67	5.2
AV50110-X-X	50	110	150	2"	303	291	252	148	75	6.3
AV65090-X-X	65	90	180	2 1/2"	308	298	253	124	67	7.6
AV65110-X-X	65	110	180	2 1/2"	329	319	274	148	75	8.7
AV80110-X-X	80	110	210	3"	352	340	287	148	75	11

Note : Models in bold prints are preferred valve size, operator combination

DIMENSIONS

TYPE 'AW' : Weldneck type ports as per ISO 4200




(All dimensions are in mm)

Model	DN	Actuator Ø	A	E	F	G	ØJ	I	ØH	ØL	K	Weight kg. (appx.)
AW-12040-X-X	12	40	100	189	180	167	65	38	28.4	21.8	12	1
AW12050-X-X	12	50	100	188	178	166	75	42	28.4	21.8	12	1
AW20050-X-X	20	50	115	194	181	165	75	42	34.4	27.2	14	1.1
AW20063-X-X	20	63	115	213	194	178	93	49	34.4	27.2	14	1.3
AW25050-X-X	25	50	130	197	185	165	75	42	41.5	33.9	14	1.4
AW25063-X-X	25	63	130	217	199	178	93	49	41.5	33.9	14	1.6
AW32063-X-X	32	63	145	225	208	182	93	49	50.3	42.7	14	2.1
AW32090-X-X	32	90	145	268	240	216	124	67	50.3	42.7	14	4
AW40063-X-X	40	63	160	232	219	189	93	49	57	48.8	14	2.9
AW40090-X-X	40	90	160	270	249	219	124	67	57	48.8	14	4.3
AW40110-X-X	40	110	160	298	268	238	148	75	57	48.8	14	5.5
AW50063-X-X	50	63	175	260	238	203	93	49	70.4	61.2	16	4.1
AW50090-X-X	50	90	175	298	272	233	124	67	70.4	61.2	16	5.5
AW50110-X-X	50	110	175	326	291	252	148	75	70.4	61.2	16	6.7
AW65090X-X	65	90	210	319	299	253	124	67	87	73.9	16	6.9
AW65110-X-X	65	110	210	340	320	274	148	75	87	73.9	16	8.1
AW80110-X-X	80	110	250	352	340	287	148	75	101.2	89.2	16	9.9

Note : Models in bold prints are preferred valve size, operator combination

DIMENSIONS

TYPE 'AP'




(All dimensions are in mm)

Model	DN	Actuator Ø	A	E	F	G	ØJ	I	ØH	ØL	ØK	ØM	Weight kg. (appx.)
AP12040-X-X	12	40	115	214	180	167	65	38	26	25.4	25	18.8	1
AP12050-X-X	12	50	115	212	178	166	75	42	26	25.4	22	18.8	1
AP20050-X-X	20	50	125	216	181	165	75	42	32	31.2	28	24	1.2
AP20063-X-X	20	63	125	230	194	178	93	49	32	31.2	28	24	1.5
AP25050-X-X	25	50	140	222	185	165	75	42	40	39.4	35	28.7	1.6
AP25063-X-X	25	63	140	235	199	178	93	49	40	39.4	35	28.7	1.8
AP32063-X-X	32	63	160	245	208	182	93	49	49	47.6	44	38.1	2.3
AP32090-X-X	32	90	160	278	240	216	124	67	49	47.6	44	38.1	3.3
AP40063-X-X	40	63	170	250	219	189	93	49	57.8	53.8	50	44	3
AP40090-X-X	40	90	170	280	249	219	124	67	57.8	53.8	50	44	3.2
AP40110-X-X	40	110	170	299	268	238	148	75	57.8	53.8	50	44	4.3
AP50063-X-X	50	63	200	278	238	203	93	49	70	66.4	62	55.5	3.4
AP50090-X-X	50	90	200	308	268	233	124	67	70	66.4	62	55.5	4.5
AP50110-X-X	50	110	200	328	291	252	148	75	70	66.4	62	55.5	6.6
AP65090-X-X	65	90	230	333	298	253	124	67	89	81	77	65.7	8.3
AP65110-X-X	65	110	230	354	319	274	148	75	89	81	77	65.7	8.4
AP80110-X-X	80	110	260	377	340	287	148	75	104.2	96.1	91	81	11.8

Note : Models in bold prints are preferred valve size, operator combination

DIMENSIONS

TYPE 'AK' : Triclamp end as per ISO 2852




(All dimensions are in mm)

Model	DN	Actuator Ø	A	E	F	G	ØJ	I	ØL	ØH	ØK	Weight kg. (appx.)
AK12040-X-X	12	40	100	189	184	167	65	38	18.1	21.6	34.0	1.3
AK12050-X-X	12	50	100	188	183	166	75	42	18.1	21.6	34.0	1
AK20050-X-X	20	50	115	194	191	165	75	42	23.7	26.9	50.5	1.3
AK20063-X-X	20	63	115	213	204	178	93	49	23.7	26.9	50.5	1.4
AK25050-X-X	25	50	130	197	191	165	75	42	29.7	33.7	50.5	1.5
AK25063-X-X	25	63	130	217	204	178	93	49	29.7	33.7	50.5	1.7
AK32063-X-X	32	63	145	225	208	182	93	49	38.4	42.4	50.5	2.1
AK32090-X-X	32	90	145	268	242	216	124	67	38.4	42.4	50.5	3.2
AK40063-X-X	40	63	160	232	221	189	93	49	44.3	48.3	64.0	3
AK40090-X-X	40	90	160	270	251	219	124	67	44.3	48.3	64.0	4.1
AK40110-X-X	40	110	160	298	270	238	148	75	44.3	48.3	64.0	5.2
AK50063-X-X	50	63	190	260	242	203	93	49	55.7	60.3	77.5	4.3
AK50090-X-X	50	90	190	298	272	233	124	67	55.7	60.3	77.5	5.3
AK50110-X-X	50	110	190	326	291	252	148	75	55.7	60.3	77.5	6.5
AK65090-X-X	65	90	220	319	299	253	124	67	72.1	76.1	91	8
AK65110-X-X	65	110	220	340	320	274	148	75	72.1	76.1	91	9.2
AK80110-X-X	80	110	250	347	340	287	148	75	84.9	88.9	106	11.4

Note : Models in bold prints are preferred valve size, operator combination

DIMENSIONS

TYPE 'AF' : Flanged connection as per ASME 16.5 (Class150-RF)
Face to Face distance as per ASME B16.10




(All dimensions are in mm)

Model	DN	Actuator Q	A	E	F	G	ØJ	I	ØM	ØN	ØP	L	H	ØQ	ØR	Weight kg. (appx.)
AF12040-X-X	12	40	140	195	218	167	65	38	15.8	34.9	90	9.6	11.6	60.3	15.8	1
AF12050-X-X	12	50	140	198	221	166	75	42	15.8	34.9	90	9.6	11.6	60.3	15.8	1.8
AF20050-X-X	20	50	152	204	227	165	75	42	20.9	42.9	100	11.2	13.2	69.8	15.8	3
AF20063-X-X	20	63	152	216	239	178	93	49	20.9	42.9	100	11.2	13.2	69.8	15.8	2.9
AF25050-X-X	25	50	165	208	230	165	75	42	26.6	50.8	110	12.7	14.7	79.4	15.8	3
AF25063-X-X	25	63	165	220	242	178	93	49	26.6	50.8	110	12.7	14.7	79.4	15.8	4.2
AF32063-X-X	32	63	184	225	212	182	93	49	35	63.5	118	14.3	16.3	88.9	15.8	4.7
AF32090-X-X	32	90	184	266	288	216	124	67	35	63.5	118	14.3	16.3	88.9	15.8	5.8
AF40063-X-X	40	63	203	257	226	189	93	49	40.9	73	127	15.9	17.9	98.4	15.8	5.5
AF40090-X-X	40	90	203	288	327	219	124	67	40.9	73	127	15.9	17.9	98.4	15.8	6.5
AF40110-X-X	40	110	203	307	339	238	148	75	40.9	73	127	15.9	17.9	98.4	15.8	7.6
AF50063-X-X	50	63	229	280	245	203	93	49	52.5	92.1	152	17.5	19.5	120.6	19	8
AF50090-X-X	50	90	229	308	323	233	124	67	52.5	92.1	152	17.5	19.5	120.6	19	9.1
AF50110-X-X	50	110	229	327	365	252	148	75	52.5	92.1	152	17.5	19.5	120.6	19	10.1
AF65090-X-X	65	90	279	304	342	253	124	67	62.7	104.8	180	20.7	22.7	139.7	19	14
AF65110-X-X	65	110	279	325	363	274	148	75	62.7	104.8	180	20.7	22.7	139.7	19	15.2
AF80110-X-X	80	110	318	340	382	287	148	75	77.9	127	190	22.3	24.3	152.4	19	18.6


Note : Models in bold prints are preferred valve size, operator combination

DIMENSIONS


TYPE 'AF' : Flanged connection as per ASME 16.5 (Class300-RF)
Face to Face distance as per ASME B16.10



VIEW 'X'
NAMUR PORT



VIEW 'X'
STANDARD PORT



(All dimensions are in mm)

Model	DN	Actuator Ø	A	E	F	G	ØJ	I	ØM	ØN	ØP	L	H	ØQ	ØR()	Weight kg. (appx.)
AF12040-X-X	12	40	152	195	218	167	65	38	15.8	34.9	95	12.7	14.7	66.7	15.8(4)	1
AF12050-X-X	12	50	152	211	213	166	75	42	15.8	34.9	95	12.7	14.7	66.7	15.8(4)	1.8
AF20050-X-X	20	50	178	202	224	165	75	42	20.9	42.9	117	14.3	16.3	82.6	19(4)	3
AF20063-X-X	20	63	178	216	237	178	93	49	20.9	42.9	117	14.3	16.3	82.6	19(4)	2.9
AF25050-X-X	25	50	203	201	230	165	75	42	26.6	50.8	125	15.9	17.9	88.9	19(4)	3
AF25063-X-X	25	63	203	215	240	178	93	49	26.6	50.8	125	15.9	17.9	88.9	19(4)	4.2
AF32063-X-X	32	63	216	220	249	182	93	49	35	63.5	135	17.5	19.5	98.4	19(4)	4.7
AF32090-X-X	32	90	216	254	283	216	124	67	35	63.5	135	17.5	19.5	98.4	19(4)	5.8
AF40063-X-X	40	63	240*	231	267	189	93	49	40.9	73	156	19.1	21.1	114.3	22.2(4)	5.5
AF40090-X-X	40	90	240*	260	298	219	124	67	40.9	73	156	19.1	21.1	114.3	22.2(4)	6.5
AF40110-X-X	40	110	240*	280	316	238	148	75	40.9	73	156	19.1	21.1	114.3	22.2(4)	7.6
AF50063-X-X	50	63	267	260	286	203	93	49	52.5	92.1	165	20.7	22.7	127	19(8)	8
AF50090-X-X	50	90	267	289	316	233	124	67	52.5	92.1	165	20.7	22.7	127	19(8)	9.1
AF50110-X-X	50	110	267	307	335	252	148	75	52.5	92.1	165	20.7	22.7	127	19(8)	10.1
AF65090-X-X	65	90	292	311	348	253	124	67	62.7	104.8	190	23.9	25.9	149.2	22.2(8)	14
AF65110-X-X	65	110	292	331	369	274	148	75	62.7	104.8	190	23.9	25.9	149.2	22.2(8)	15.2
AF80110-X-X	80	110	318	311	392	287	148	75	77.9	127	210	27	29	168.3	22.2(8)	18.6

- Specify port connection 300 when opted for class 300RF flange connection

Note : Models in bold prints are preferred valve size, operator combination

*Mark dimension not as per ASME B16.10

ACCESSORIES

PORT CONNECTIONS



DUST CAP

SIZE	MODEL NO
1/8" BSP	DC-01
1/4" BSP	DC-02



BUG SCREEN

SIZE	MODEL NO
1/8" BSP	BS-01
1/4" BSP	BS-02



SINTERED BRONZE MUFFLER

SIZE	MODEL NO
1/8" BSP	S-01
1/4" BSP	S-02



TRICLAMP

SIZE	MODEL NO
DN 12	TC-01
DN 20/25/32	TC 02
DN 40	TC 03
DN 50	TC 04
DN 65	TC 05
DN 80	TC 06

SOLENOID VALVES



3/2 DIRECT MOUNT

Type : 304 3/2 Direct mount
The valve can be directly mounted on single acting operator having threaded/ NAMUR pilot port connections.

Solenoid Enclosure

Weatherproof : DIN plug

Application : Indoor



3/2 SOLENOID VALVE

Type : 30125 3/2 Body ported
30106 3/2 NAMUR


Ideally suited for outdoor application for operating single acting operator having threaded/ NAMUR pilot port connection

Solenoid Enclosure

Weatherproof : DIN plug, terminal box

Explosion proof : Ex d, Ex ia

Application : Indoor and Outdoor



5/2 SOLENOID VALVE

Type : 51400 Single Solenoid body ported
57400 Double Solenoid body

ported 51424/ 51450 Single Solenoid NAMUR 57450 Double Solenoid NAMUR

Ideally suited for outdoor application for operating double acting operator having threaded/ NAMUR pilot port connection

Solenoid Enclosure

Weatherproof : DIN plug, terminal box

Explosion proof : Ex d, Ex ia

Application : Indoor and Outdoor

Note :Contact Rotex for Solenoid Valve code

VALVE TYPE	 PLUGIN-I 22	 TERMINAL BOX 16/ 19	 FPJB Ex d 37/ 39	 Ex ia 63/ 64	 PLUGIN-III 25
30106	✓	✓	✓	✓	
30125	✓	✓	✓	✓	
304	✓				
51424	✓	✓	✓	✓	✓
57450	✓	✓	✓		
51440	✓	✓	✓	✓	✓
57440	✓	✓	✓	✓	✓
57450LW		✓	✓		✓
51450LW		✓	✓		✓
51440LW		✓	✓		✓
57440LW		✓	✓		✓

TYPE OF COIL	COIL CODE	
	CABLE ENTRY	
	1/2" NPT	M20X1.5
Terminal Box	16	19
FPJB Ex d	37	39
Ex ia	63	64

ORDERING CODE VALVE

a			b			c			d		
CONNECTION TYPE			DN-OPERATOR			FUNCTION			PILOT CONNECTION		
Ported	AV		12040			Normally Closed, Pressure			F1		
Weld end	AW		12050			above plug, Single acting					
Triclamp	AK		12063			Normally Open, Pressure			F2		
Flange end	AF		20050			below plug, Single acting					
Pipe Weld	AP		20063			Normally Closed,			F3		
			25050			BI-Directional, Single acting					
			25063			Normally Closed/ Normally Open,			F4		
			32063			BI-Directional, Double acting					
			32090			Normally Closed, Pressure above			F5		
			40063			plug, Single acting, Spring to close					
			40090			Normally Closed, Pressure below			F6		
			40110			plug, Single acting					
			50063								
			50090								
			50110								
			65090								
			65110								
			80110								

e			f			g		h			
SEAL	SEAT		PORT CONNECTION			BODY		PILOT VALVE		TYPE	CODE
Viton	PTFE	※	SIZE	BSP	NPT	CF3M	※	NIL	-	※	
EPDM	PTFE	S1	1/2"	4G	4R			3/2 NAMUR	30106	01	
Viton	PEEK	S17	3/4"	6G	6R			5/2 NAMUR Single Solenoid	51424	02	
			1"	8G	8R			5/2 NAMUR Double Solenoid	57450	03	
			1 1/4"	10G	10R			3/2 Body ported	30125	04	
			1 1/2"	12G	12R			3/2 Direct mount valve	304	05	
			2"	16G	16R			5/2 Body ported Single Solenoid	51440	06	
			2 1/2"	20G	20R			5/2 Body ported Double Solenoid	57440	07	
			3"	24G	24R						

Note : Port connection should be selected only for valve type 'AV'

- × Do not specify when opted for
- Pilot valve optional 01,02 or 03 should be opted for operator with NAMUR port connection (P2)
- Model in bold prints are preferred valve - operator combination
- 5/2 Body ported Single/ Double Solenoid valve shall be supplied loose
- Kindly specify operating voltage, current and Solenoid enclosure when opted for pilot valve
- Select PEEK SEAT for media temperature up to 220 °C
- Specify port connection '300' when opted for class 300RF flange connection

ORDERING EXAMPLE

AV25050-F2-P2-S1-8G

25 NB Angle Seat, Normally Open, pressure below Plug Single Acting Valve, having 1" BSP (f) threaded port Connections, Operated with 50 Ø operator having NAMUR pilot ports, EPDM O rings and Seals.

AV40090-F1-P1-12G-04-24VDC-16

40 NB Angle Seat, Normally Closed pressure above Plug Single Acting Valve, having 11/2" BSP (f) threaded port connections, Operated with 90 Ø operator having threaded pilot ports, Viton O rings and Seals, fitted with 3/2 body ported pilot valve Type 30125, with 24 VDC Terminal Box solenoid having cable entry 1/2" NPT

AF40090-F1-P1-300


40 NB Angle Seat Valve, Normally Closed, Pressure above Plug, Single Acting Valve, having 40 NB, Class 300RF flange connection operated with 90 Ø operator having threaded pilot ports and having Viton O rings and seals.

Note : Models in bold prints are preferred valve size, operator combination



Select 5/2 solenoid valve type 02, 03, 06 or 07 when function type F5 is opted.

ORDERING CODE



Pos. No.	Description	Material
1	Indicator Dome	PC
2	Operator Cover	Nylon Glass Filled
3	Closed Indicator	ABS
4	Open Indicator	ABS
5	Piston Seal	Viton / EPDM
6	Insert	SS 316
7	Piston	Aluminium
*8	Piston Spring	Carbon Steel (IS 4454 GR II)
*8a	Piston Inner Spring	Carbon Steel (IS 4454 GR II)
9	Operator	Nylon Glass Filled
10	Shaft Seal	Viton/ EPDM

Pos. No.	Description	Material
11	Hex	Brass
12	Shaft Bearing	PTFE/ PEEK
13	Gland Packing	PTFE
14	Gland Spring	SS
15	Sleeve	CF3M (SS 316L Cast), (1.4435)
16	Body Seal	Graphoil
17	Shaft	SS 316L (1.4404)
18	Plug	SS 316L (1.4404)
19	Seat Seal	PTFE/ PEEK
20	Pressure Disc	SS 316L (1.4404)
21	Body	CF3M (SS 316L Cast), (1.4435)

*(Where applicable)

ORDERING CODE SPARES, TOOLS

DESCRIPTION OF SPARES

- **Operator Assembly** : Consists of Indicator Dome(1), Operator Cover (2), Closed Indicator (3), Open Indicator (4), Operator (9), Piston (7), Piston Spring (8 and 8a)*, Hex (11), Shaft Seal (10) All O rings of the Operator
- **Piston Seal and O Ring set** : Consists of Piston Seal (5), Shaft Seal (10) and all O rings of the Operator Piston Spring Set consists of Piston Spring (8 and 8a)*
- **Repair Kit** : Consists of all O ring of the Operator and Sleeve, Piston Seal (5), Shaft (10) and all Gland Packings (13), Body Seal (16), Shaft Bearing (12), Gland Spring (14), Shaft (17), and Seat (18) duly assembled and Piston Spring (8 and 8a)*
- **Seat Assembly** : Consists of seat (18) duly assembled with seat seal (19) and pressure disc(20), Shaft (17) and Body Seal (16)

Note : Replace body seal (part no.16), in case if sleeve (part no.15) is opened

Refer to construction on page 18

*where applicable

a	b	c	d	e	f
SPARE KIT	DN-OPERATOR	FUNCTION		SEAL SEAT	BODY
Operator Assembly 99	12040	Normally Closed, Pressure above plug, Single acting F1		Viton PTFE *	CF3M *
Piston seal and O ring Set 98	12050	Normally Open, Pressure below plug, Single acting F2		EPDM PTFE S1	
Repair Kit 97	12063	Normally Closed, BI-Directional, Single acting F3		Viton PEEK S17	
Seat Assembly 96	20050	Normally Closed, BI-Directional, Double acting F4			
	20063	Normally Closed, Pressure above plug, Single acting, Spring to close F5			
	25050	Normally Closed, Pressure below plug, Single acting F6			
	25063				
	32063				
	32090				
	40063				
	40090				
	40110				
	50063				
	50090				
	50110				
	65090				
	65110				
	80110				
			PILOT CONNECTION		
			THREADED P1		
			NAMUR P2		

Note : * Do not specify when opted for

ORDERING EXAMPLE

99-32090-F1-P1

90 Ø Operator Assembly having threaded pilot ports, viton seals and O rings suitable for 32 NB Angle Seat Normally Closed, pressure above Plug Single Acting Valve.

TOOL KIT



PHOTO - 1



PHOTO - 2

CODE	TOOL (Refer Photo - 1)
T40	For opening Ø40 operator
T50	For opening Ø50 operator
T63	For opening Ø63 operator
T90	For opening Ø90 operator
T110	For opening Ø110 operator

Note : For opening cover of the operator use special tool to avoid damage, ensure that operator is held in the soft JAW vice (Refer photo 2)

ORDERING EXAMPLE

T50

Cover opening tool for operator Ø50

Note : Models in bold prints are preferred valve size, operator combination



Engineering For The Future

0111-M2 DESIGN AND PRODUCTION BY : MEDIA INC. PH. +91 265 2422835

**ROTEX MANUFACTURERS &
ENGINEERS PRIVATE LIMITED**
Manpada Road, Dombivli (E) - 421204
Maharashtra, INDIA.
Ph. : +91 251 2871033/ 2871390/ 2871196/
2871989/ 2870890/ 2870663
Fax : +91 251 2871191
E-mail : rotexdbi@rotexindia.com

ROTEX AUTOMATION LIMITED
UNIT 1
987/11, GIDC Makarpura,
Vadodara - 390010, Gujarat, INDIA.
Ph. : +91 265 2638136/ 2638795/ 46
Fax : +91 265 2638130
Email : rotexbrd@rotexindia.com

UNIT 2
C - 1 B/ 1501, 4 & 5, GIDC
Vithal Udyognagar - 388121,
Gujarat, INDIA.
Ph. : +91 2692 236224/ 236292/ 236399
Fax : +91 2692 236442
Email : rotexvun@rotexindia.com

www.rotexindia.com