



Shin-Etsu Silicone

Silicone Products for Personal Care

Shin-Etsu Unique Materials

Silicone Gels

KSG-Z Series

Emulsifiers

Silicone Gels

KSG Series

Silicone Acrylates

KP Series

Hybrid Silicone Powders

KSP Series

Inorganic Powder Dispersions

SPD Series


7.2009

Shin-Etsu materials enable the personal care industry to develop products with greater functionality and diversity than ever before.

Our silicone materials have the basic properties required for personal care products in general, and also provide the functionality and diversity required for special applications including skin care, make up, and sun care products. Shin-Etsu develops a range of original, innovative materials including silicone-based emulsifiers — essential to basic processing — and silicone gels, silicone acrylates and silicone powders, products that impart unique features to end-products. Our materials make it possible for manufacturers to develop unique, high-quality personal care products with greater functionality.

Contents

Formulation Design	2
Silicone Gels for Personal Care KSG-Z Series	3
Emulsifiers for Personal Care	4
Silicone Gels for Personal Care KSG Series	8
Silicone Acrylates for Personal Care KP Series	12
Hybrid Silicone Powders for Personal Care KSP Series	14
Inorganic Powder Dispersions for Personal Care SPD Series	16
Handling precautions	17
Applications	18-19



KSG-Z Series

Silicone Gels for Personal Care

The three-dimensionally crosslinked fine particles used for the KSG-Z series differ from those of our earlier KSG series; they contain two types of branches – silicone chains and alkyl chains – that are not involved in crosslinking. The result is gels that exhibit high swelling ability in both silicone fluids and organic oils.

Silicone crosslinked polymers

KSG-042Z and KSG-045Z improve the quality attributes of personal care products in various ways, such as imparting a smooth, silky feel and providing a matting effect to inhibit oil sheen.

Product name	INCI	Component A Component B	Appearance	Penetration (worked) 25°C	Refractive- Index 25°C
KSG-042Z	LAURYL POLYDIMETHYLSILOXYETHYL DIMETHICONE/BIS-VINYL DIMETHICONE CROSSPOLYMER	15-25%	Colorless transparent paste	330	1.418
	ISODODECANE	75-85%			
KSG-045Z	LAURYL POLYDIMETHYLSILOXYETHYL DIMETHICONE/BIS-VINYL DIMETHICONE CROSSPOLYMER	15-25%	Colorless translucent paste	350	1.401
	CYCLOPENTASILOXANE	75-85%			

Polyether-modified silicone crosslinked polymers

KSG-320Z and KSG-350Z are emulsifying agents with a smooth feel that can be used to produce unique water-in-silicone and water-in-oil products.

Product name	INCI	Component A Component B	Appearance	Penetration (worked) 25°C	Refractive- Index 25°C
KSG-320Z	PEG-15/LAULYL POLYDIMETHYLSILOXYETHYL DIMETHICONE CROSSPOLYMER	20-30%	Colorless milky white paste	360	1.420
	ISODODECANE	70-80%			
KSG-350Z	PEG-15/LAULYL POLYDIMETHYLSILOXYETHYL DIMETHICONE CROSSPOLYMER	20-30%	Colorless milky white paste	370	1.404
	CYCLOPENTASILOXANE	70-80%			

Polyglycerin-modified silicone crosslinked polymers

KSG-820Z and KSG-850Z are emulsifying agents that can be used to produce unique water-in-silicone and water-in-oil products with high moisture retentivity, and are soft, moist, and spread easily on the skin.


Product name	INCI	Component A Component B	Appearance	Penetration (worked) 25°C	Refractive- Index 25°C
KSG-820Z	POLYGLYCERYL-3/LAURYL POLYDIMETHYLSILOXYETHYL DIMETHICONE CROSSPOLYMER	20-30%	Colorless milky white paste	360	1.420
	ISODODECANE	70-80%			
KSG-850Z	POLYGLYCERYL-3/LAURYL POLYDIMETHYLSILOXYETHYL DIMETHICONE CROSSPOLYMER	20-30%	Colorless milky white paste	360	1.404
	CYCLOPENTASILOXANE	70-80%			

* These documents are not a certification of quality. For documentation of quality assurance and standards, please contact our Sales Department.

* INCI names are subject to change without notice.

Compatibility with Base Oils

Emulsifier Linear/Branched type	Emulsifier & Elastomer Gel Cross-linked type	Elastomer Gel Cross-linked type
Silicone Fluids Light Esters KF-6017 KF-6028 KF-6104 KF-6038 KF-6105	KSG-210, 240 KSG-710 KSG-350Z KSG-850Z KSG-310, 320 KSG-810, 820 330, 340 830, 840	KSG-15, 16, 1610 KSG-18A KSG-045Z KSG-41, 42 43, 44



Emulsifiers






The two main classes of emulsifiers are polyether modified silicones and polyglycerin modified silicones.

Polyether modified silicones include linear types, branched types and cross-linked polymer types, while polyglycerin modified silicones include branched types and cross-linked polymer types.

We also offer distinctive alkyl co-modified emulsifiers.

Applying these products enables the development of diverse cosmetic formulations.

Product Classification

Type		Product	Model
Linear Type	Polyether modified	KF-6011 KF-6011P KF-6012 KF-6013 KF-6015 KF-6016 KF-6017 KF-6017P KF-6043	
Branched Type	Polyether modified	KF-6028 KF-6028P	
	Polyglycerin modified	KF-6100 KF-6104	
	Polyether / alkyl co-modified	KF-6038	
	Polyglycerin / alkyl co-modified	KF-6105	
Cross-linked polymer Type	Polyether modified	KSG-210 KSG-240	
	Polyglycerin modified	KSG-710	
	Polyether / alkyl co-modified	KSG-310 KSG-320 KSG-330 KSG-340	
	Polyglycerin / alkyl co-modified	KSG-810 KSG-820 KSG-830 KSG-840	

Cross-linked polymer Type: Please refer to KSG Series (page 8-11) .

Polyether modified silicones [Linear Type]

We offer numerous polyether modified silicone emulsifiers with varying HLB values, meaning these products can be used as either Si/W or W/Si emulsifiers.

Product name	INCI	Viscosity 25°C mm ² /s	Specific Gravity 25°C	Refractive Index 25°C	Calculated HLB wt % EO/5	Cloud Point °C
KF-6011	PEG-11 METHYL ETHER DIMETHICONE	130	1.07	1.450	14.5	65
KF-6011P	PEG-11 METHYL ETHER DIMETHICONE	130	1.07	1.450	14.5	65
KF-6012	PEG/PPG-20/22 BUTYL ETHER DIMETHICONE	1,600	1.03	1.446	7.0	35
KF-6013	PEG-9 DIMETHICONE	400	1.03	1.436	10.0	—
KF-6015	PEG-3 DIMETHICONE	150	1.00	1.420	4.5	—
KF-6016	PEG-9 METHYL ETHER DIMETHICONE	150	1.01	1.417	4.5	—
KF-6017	PEG-10 DIMETHICONE	600	1.01	1.420	4.5	—
KF-6017P	PEG-10 DIMETHICONE	850	1.01	1.420	4.5	—
KF-6043	PEG-10 DIMETHICONE	400	1.09	1.454	14.5	71

● P Grade: odorless versions created using an improved deodorization process.

* This document is not a certification of quality. For documentation of quality assurance and standards, please contact our Sales Department.

* INCI names are subject to change without notice.

Polyether modified silicones [Branched Type]

The silicone component has a branched structure, providing unique solubility, superior to that of linear structures.

These emulsifiers enable creation of distinctive products in terms of the viscosity and stability of the emulsions.

KF-6038 has good solubility in both silicone fluid and organic oils.

Product name	INCI	Viscosity 25°C mm ² /s	Specific Gravity 25°C	Refractive Index 25°C	Calculated HLB wt % EO/5
KF-6028	PEG-9 POLYDIMETHYLSILOXYETHYL DIMETHICONE	900	1.00	1.420	4.0
KF-6028P	PEG-9 POLYDIMETHYLSILOXYETHYL DIMETHICONE	900	1.00	1.420	4.0
Alkyl co-modified type					
KF-6038	LAURYL PEG-9 POLYDIMETHYLSILOXYETHYL DIMETHICONE	700	0.96	1.430	3.0

● P Grade: odorless versions created using an improved deodorization process.

* This document is not a certification of quality. For documentation of quality assurance and standards, please contact our Sales Department.

* INCI names are subject to change without notice.

Polyglycerin modified silicones [Branched Type]

These silicone emulsifiers feature polyglycerin as the hydrophilic component.

These emulsifiers hold moisture well, so emulsions agree with skin and impart a distinctly soft and moist feel.

KF-6105 is a W/O emulsifier that is co-modified with alkyl chains.

Product name	INCI	Viscosity 25°C mPa·s	Specific Gravity 25°C	Refractive Index 25°C	Estimated HLB
KF-6100	POLYGLYCERYL-3 DISILOXANE DIMETHICONE	40,000	1.08	1.458	Medium
KF-6104	POLYGLYCERYL-3 POLYDIMETHYLSILOXYETHYL DIMETHICONE	4,000	1.00	1.409	Low
Alkyl co-modified type					
KF-6105	LAURYL POLYGLYCERYL-3 POLYDIMETHYLSILOXYETHYL DIMETHICONE	4,000	0.95	1.426	Low

* This document is not a certification of quality. For documentation of quality assurance and standards, please contact our Sales Department.


* INCI names are subject to change without notice.

Compatibility (concentration 20%)

	KF-6011 KF-6011P	KF-6012	KF-6013	KF-6015	KF-6016	KF-6017 KF-6017P	KF-6028 KF-6028P	KF-6038	KF-6043	KF-6100	KF-6104	KF-6105
DM-FLUID A-6cs (Dimethicone)	I	I	PS	I	S	S	S	S	I	PS	S	S
TMF-1.5 (Methyl Trimethicone)	I	I	I	S	S	S	S	S	I	PS	S	S
KF-995 (Cyclopentasiloxane)	I	I	I	S	S	S	S	S	I	PS	S	S
KF-56A (Diphenylsiloxy Phenyl Trimethicone)	S	S	PS	S	S	S	S	S	I	I	S	S
Mineral Oil	I	PS	I	I	PS	PS	PS	S	I	I	I	S
Isotridecyl Isononanoate	I	S	S	S	S	S	S	S	I	PS	S	S
Triethylhexanoin	S	S	S	S	S	S	S	S	S	PS	PS	S
Ethyl Alcohol	S	S	S	S	S	S	S	PS	S	S	PS	PS
Isopropyl Alcohol	S	S	S	S	S	S	S	S	S	S	S	S
Propylene Glycol	S	I	S	I	I	S	I	PS	S	S	I	I
1,3-Butylene Glycol	S	I	S	I	I	S	I	PS	S	S	PS	PS
Glycerin	I	I	I	I	I	I	I	PS	I	S	PS	PS
Water	S	S	I	I	I	I	I	I	S	G	I	I

S: Soluble PS: Partially Soluble I: Insoluble G: Gel

Surface tension

* Measured using a "fully automated interfacial tensiometer
(model PD-W, KYOWA INTERFACE SCIENCE CO., LTD.)"

KSG Series

Silicone Gels for Personal Care

Commonly known thickening agents have never been compatible with silicone systems and have left a heavy, draggy feel on the skin. The KSG series was developed to solve these problems.

Silicone Cross-linked polymers

Because of their 3-dimensional network structure, the KSG series products silicone systems, improve formulation stability, and provide a smooth, silky and luxurious feel to products.

Product name	INCI	Component A	Appearance	Penetration (worked) 25°C	Refractive- Index 25°C	Heavy Metal	Arsenic
		Component B					
KSG-15	DIMETHICONE/VINYL DIMETHICONE CROSSPOLYMER	4-10%	Colorless transparent paste	420	1.397	< 20ppm	< 2ppm
	CYCLOPENTASILOXANE	90-96%					
USG-103	DIMETHICONE/VINYL DIMETHICONE CROSSPOLYMER	8-12%	Colorless transparent paste	350	1.398	< 20ppm	< 2ppm
	CYCLOPENTASILOXANE	88-92%					
KSG-16	DIMETHICONE/VINYL DIMETHICONE CROSSPOLYMER	20-30%	Colorless translucent paste	330	1.400	< 20ppm	< 2ppm
	DIMETHICONE	70-80%					
KSG-1610	DIMETHICONE/VINYL DIMETHICONE CROSSPOLYMER	15-20%	Colorless translucent paste	380	1.389	< 20ppm	< 2ppm
	METHYL TRIMETHICONE	80-85%					
USG-106	DIMETHICONE/VINYL DIMETHICONE CROSSPOLYMER	8-12%	Colorless transparent paste	420	1.418	< 20ppm	< 2ppm
	ISODODECANE	88-92%					
KSG-18A	DIMETHICONE/PHENYL VINYL DIMETHICONE CROSSPOLYMER	10-20%	Colorless translucent paste	330	1.495	< 20ppm	< 2ppm
	DIPHENYLSILOXY PHENYL TRIMETHICONE	80-90%					
KSG-41	VINYL DIMETHICONE/LAURYL DIMETHICONE CROSSPOLYMER	25-35%	Colorless translucent paste	360	1.455	< 20ppm	< 2ppm
	MINERAL OIL	65-75%					
KSG-42	VINYL DIMETHICONE/LAURYL DIMETHICONE CROSSPOLYMER	20-30%	Colorless translucent paste	380	1.422	< 20ppm	< 2ppm
	ISODODECANE	70-80%					
KSG-43	VINYL DIMETHICONE/LAURYL DIMETHICONE CROSSPOLYMER	25-35%	Colorless translucent paste	400	1.442	< 20ppm	< 2ppm
	TRIETHYLHEXANOIN	65-75%					
KSG-44	VINYL DIMETHICONE/LAURYL DIMETHICONE CROSSPOLYMER	25-35%	Colorless translucent paste	380	1.451	< 20ppm	< 2ppm
	SQUALANE	65-75%					

* This document is not a certification of quality. For documentation of quality assurance and standards, please contact our Sales Department.

* INCI names are subject to change without notice.

Polyether modified Silicone Cross-linked polymers

KSG-210, 240, 310, 320, 330, 340 are polyether modified self-emulsifying systems allowing for easy formulation of unique W/Si and W/O products, and provide a smooth and silky feel to them.

Product name	INCI	Component A	Appearance	Penetration (worked) 25°C	Refractive- Index 25°C	Heavy Metal	Arsenic
		Component B					
KSG-210	DIMETHICONE/PEG-10/15 CROSSPOLYMER 20-30%		Colorless milky white paste	400	1.403	< 20ppm	< 2ppm
	DIMETHICONE 70-80%						
KSG-240	DIMETHICONE/PEG-10/15 CROSSPOLYMER 15-25%		Colorless milky white paste	400	1.400	< 20ppm	< 2ppm
	CYCLOPENTASILOXANE 75-85%						
Alkyl co-modified type							
KSG-310	PEG-15/LAURYL DIMETHICONE CROSSPOLYMER 25-35%		Colorless milky white paste	400	1.450	< 20ppm	< 2ppm
	MINERAL OIL 65-75%						
KSG-320	PEG-15/LAURYL DIMETHICONE CROSSPOLYMER 20-30%		Colorless milky white paste	400	1.420	< 20ppm	< 2ppm
	ISODODECANE 70-80%						
KSG-330	PEG-15/LAURYL DIMETHICONE CROSSPOLYMER 15-25%		Colorless milky white paste	395	1.442	< 20ppm	< 2ppm
	TRIETHYLHEXANOIN 75-85%						
KSG-340	PEG-10/LAURYL DIMETHICONE CROSSPOLYMER PEG-15/LAURYL DIMETHICONE CROSSPOLYMER 25-35%		Colorless milky white paste	410	1.452	< 20ppm	< 2ppm
	SQUALANE 65-75%						

* This document is not a certification of quality. For documentation of quality assurance and standards, please contact our Sales Department.

* INCI names are subject to change without notice.

Polyglycerin modified Silicone Cross-linked polymers

KSG-710, 810, 820, 830, 840 contain a hydrophilic polyglycerin group, which acts as a moisturizer. These products allow for easy formulation of unique W/Si and W/O products.

Product name	INCI	Component A	Appearance	Penetration (worked) 25°C	Refractive- Index 25°C	Heavy Metal	Arsenic
		Component B					
KSG-710	DIMETHICONE/POLYGLYCERIN-3 CROSSPOLYMER 20-30%		Colorless milky white paste	400	1.400	< 20ppm	< 2ppm
	DIMETHICONE 70-80%						

Product name	INCI	Component A	Appearance	Penetration (worked) 25°C	Refractive- Index 25°C	Heavy Metal	Arsenic	
		Component B						
Alkyl co-modified type								
KSG-810	LAURYL DIMETHICONE/POLYGLYCERIN-3 CROSSPOLYMER		25-35%	Colorless milky white paste	380	1.450	< 20ppm	< 2ppm
	MINERAL OIL		65-75%					
KSG-820	LAURYL DIMETHICONE/POLYGLYCERIN-3 CROSSPOLYMER		20-30%	Colorless milky white paste	340	1.420	< 20ppm	< 2ppm
	ISODODECANE		70-80%					
KSG-830	LAURYL DIMETHICONE/POLYGLYCERIN-3 CROSSPOLYMER		15-25%	Colorless milky white paste	400	1.442	< 20ppm	< 2ppm
	TRIETHYLHEXANOIN		75-85%					
KSG-840	LAURYL DIMETHICONE/POLYGLYCERIN-3 CROSSPOLYMER		25-35%	Colorless milky white paste	400	1.445	< 20ppm	< 2ppm
	SQUALANE		65-75%					

* This document is not a certification of quality. For documentation of quality assurance and standards, please contact our Sales Department.


* INCI names are subject to change without notice.

	Elastomer Gel										Emulsifier & Elastomer Gel														
	KSG-15	KSG-16	KSG-1610	KSG-18A	KSG-41	KSG-42	KSG-43	KSG-44	KSG-042Z	KSG-045Z	KSG-210	KSG-240	KSG-310	KSG-320	KSG-330	KSG-340	KSG-320Z	KSG-350Z	KSG-710	KSG-810	KSG-820	KSG-830	KSG-840	KSG-820Z	KSG-850Z
Swelling ability of KSG series with cosmetic oils																									
TMF-1.5 (Methyl Trimethicone)	O	O	B	O	R	R	R	R	O	O	O	O	R	R	R	R	O	O	O	R	R	R	R	O	O
KF-995 (Cyclopentasiloxane)	B	O	O	O	R	R	R	R	O	B	O	B	R	R	R	R	O	B	O	R	R	R	R	O	B
DM-FLUID A-6cs (Dimethicone)	O	B	O	O	R	R	R	R	O	O	B	O	R	R	R	R	O	O	B	R	R	R	R	O	O
DM-FLUID A-20cs (Dimethicone)	O	O	O	R	R	R	R	R	O	O	O	O	R	R	R	R	O	O	O	R	R	R	R	O	O
DM-FLUID A-100cs (Dimethicone)	R	R	R	R	R	R	R	R	R	R	R	R	R	R	R	R	R	R	R	R	R	R	R	R	R
KF-56A (Diphenylsiloxy Phenyl Trimethicone)	O	O	O	B	R	R	R	R	O	O	O	O	R	R	R	R	O	O	O	R	R	R	R	O	O
Isododecane	O	O	O	R	O	B	O	O	B	O	O	O	B	O	O	B	O	O	O	B	O	O	B	O	
Mineral Oil	R	R	R	R	B	O	O	O	O	R	R	B	O	O	O	O	O	R	B	O	O	O	O	O	
Squalane	R	R	R	R	R	R	R	B	O	O	R	R	R	R	R	B	O	O	R	R	R	R	B	O	O
Isotridecyl Isononanoate	R	R	R	O	O	O	O	O	O	O	R	R	O	O	O	O	O	O	R	O	O	O	O	O	O
Cetyl Caprylate	R	R	R	O	O	O	O	O	O	R	R	O	O	O	O	O	O	R	O	O	O	O	O	O	O
Jojoba (Buxus Chinensis) Oil	R	R	R	R	R	R	R	R	R	R	R	R	R	R	R	R	R	R	R	R	R	R	R	R	R
Triethylhexanoin	O	O	O	O	O	O	B	O	O	O	O	O	O	O	B	O	O	O	O	O	B	O	O	O	
Triisostearin	R	R	R	R	O	O	O	O	O	O	R	R	O	O	O	O	O	R	O	O	O	O	O	O	O
Macadamia Ternifolia Nut Oil	R	R	R	R	R	R	R	R	R	R	R	R	R	R	R	R	R	R	R	R	R	R	R	R	R

B: Base Oil O: Optional Amount R: Restrictive Use


Viscosity vs. Cross-linked polymer content

KSG-10 series enables us to make gel-like products from low viscosity silicone fluids. This is accomplished by combining a silicone cross-linked polymer with a silicone fluid. The viscosity of the final product depends upon the concentration of cross-linked polymer as illustrated in this graph. The viscosity curve is different for each KSG-10 series due to the type of silicone fluid and the ability of the cross-linked polymer to thicken that particular silicone fluid. Note that KSG-15 requires much less cross-linked polymer to reach a particular viscosity than does KSG-16. As a result, the cross-linked polymer film formed by KSG-15 is thinner than that of KSG-16.



Viscosity vs. Shear rate

The viscosity of KSG products remains constant over time when the products are in a still, unagitated condition. However, the materials are shear sensitive and the viscosity will decrease upon the application of shear. This is illustrated for each KSG product in the accompanying graph. When formulating, this can be advantageous to facilitate the dispersion of cosmetic ingredients, such as pigments. Once formulated, the dispersions demonstrate excellent stability.



Formulating W/O creams with KSG-210, KSG-310, KSG-710 or KSG-810


KSG-210 and KSG-710 are self-emulsifying paste which can be used to formulate stable W/Si creams without the addition of an emulsifying agent. This graph illustrates formulation ratios of KSG-210 or KSG-710, DM-FLUID A-6cs and water (and also ratios of KSG-310 or KSG-810, Mineral Oil and water). W/O emulsions can be produced in the area marked W/O area illustrating the formulation latitude of KSG-210, KSG-310, KSG-710 or KSG-810. Stable W/O emulsions can be obtained using the formulation area indicated in green.

W/O emulsion with KSG-310 (x200 **A** point)



100µm

A Component of Emulsion
KSG-310 5wt %
Mineral Oil 5wt %
Water 90wt %



The **A** point

This diagram illustrates a formulation containing 90 % water, 5 % DM-FLUID A-6cs and 5 % KSG-210 or KSG-710 (90 % water, 5 % mineral oil and 5 % KSG-310 or KSG-810). This example illustrates the ability of KSG-210, KSG-310, KSG-710 or KSG-810 to form stable W/O creams with extremely high water content.

KP Series

Silicone Acrylates for Personal Care

KP products combine the benefits of acrylic resins with silicones.

They are graft copolymers with an acrylic polymer backbone and dimethylpolysiloxane side chains.

Silicone acrylates dissolved in volatile silicone or hydrocarbon carriers to form soft flexible films with excellent water and oil repellency.

Powder treatment

Product name	INCI	Component A	Appearance	Viscosity 25°C mPa.s	pH	Heavy Metal	Arsenic
		Component B					
KP-541	ACRYLATES/DIMETHICONE COPOLYMER 60%		Colorless transparent- light yellow hazy fluid	500- 10,000	Neutral	< 20ppm	< 2ppm
	ISOPROPYL ALCOHOL 40%						

Dispersant

Product name	INCI	Component A	Appearance	Viscosity 25°C mm²/s	pH	Heavy Metal	Arsenic
		Component B					
KP-575	ACRYLATES/ETHYLHEXYL ACRYLATE/DIMETHICONE METHACRYLATE COPOLYMER 30%		Colorless transparent- light yellow hazy fluid	10-50	Neutral	< 20ppm	< 2ppm
	CYCLOPENTASILOXANE 70%						

Film former

Product name	INCI	Component A	Appearance	Viscosity 25°C mm²/s	pH	Heavy Metal	Arsenic
		Component B					
KP-543	ACRYLATES/DIMETHICONE COPOLYMER 50%		Colorless transparent- light yellow hazy fluid	100- 1,000	Neutral	< 20ppm	< 2ppm
	BUTYL ACETATE 50%						
KP-545	ACRYLATES/DIMETHICONE COPOLYMER 30%		Colorless transparent- light yellow hazy fluid	100- 500	Neutral	< 20ppm	< 2ppm
	CYCLOPENTASILOXANE 70%						
KP-549	ACRYLATES/DIMETHICONE COPOLYMER 40%		Colorless transparent- light yellow hazy fluid	500- 5,000	Neutral	< 20ppm	< 2ppm
	METHYL TRIMETHICONE 60%						
KP-550	ACRYLATES/DIMETHICONE COPOLYMER 40%		Colorless transparent- light yellow hazy fluid	100- 3,000	Neutral	< 20ppm	< 2ppm
	ISODODECANE 60%						

Silicone wax

Product name	INCI	Appearance	Melting Point °C	pH	Heavy Metal	Arsenic
KP-561P	ACRYLATES/STEARYL ACRYLATE/DIMETHICONE METHACRYLATE COPOLYMER	Colorless-light yellow hazy solid	25-35	Neutral	< 20ppm	< 2ppm
KP-562P	ACRYLATES/BEHENYL ACRYLATE/DIMETHICONE METHACRYLATE COPOLYMER	Colorless-light yellow hazy solid	45-55	Neutral	< 20ppm	< 2ppm

* This document is not a certification of quality. For documentation of quality assurance and standards, please contact our Sales Department.

* INCI names are subject to change without notice.

The physical properties of silicone acrylate film

		KP-541	KP-543	KP-545
Contact Angle	degree	103	98	103
Glass Transition Point	°C	50	20	50
Softening Point	°C	90	80	90

Performance of nail enamel* containing KP-543

Testing sample:

KP-543 and other raw materials are combined at 1 %, 3 %, 5 % of KP-543.
Each enamel is painted on a glass plate by wire bar (#20).

* Main component is Nitrocellulose.

Tack free time

KP-543 wt %	Tack free time (min)
0	11
1	9
3	9
5	9

* Tack free time of each sample is measured by touching with cotton every one minute.

Water repellency

KP-543 wt %	Contact angle degree (°)
0	70
1	99
3	100
5	100

* Measure the contact angle of water on each sample.

Lubricity

KP-543 wt %	COF (μk)
0	0.48
1	0.25
3	0.24
5	0.21

* Measure the COF (Coefficient of friction) of each sample. (PET, 150 mm/min, 200 g pressure)

Gloss degree of lipstick containing KP-561P

		Sample A	Sample B	Sample C
Testing sample formulations	Candelilla Wax	8.0 wt %	8.0 wt %	8.0 wt %
	Polyethylene	8.0 wt %	8.0 wt %	8.0 wt %
	KP-561P	15.0 wt %	—	—
	Polyol Ester	—	15.0 wt %	—
	Rosin Ester	—	—	15.0 wt %
	KF-54	3.0 wt %	3.0 wt %	3.0 wt %
	Isotridecyl Isononanoate	20.0 wt %	20.0 wt %	20.0 wt %
	Glyceryl Isostearate	16.0 wt %	16.0 wt %	16.0 wt %
	Polyglyceryl-2 Triisostearate	30.0 wt %	30.0 wt %	30.0 wt %
	Pigment	q.s.	q.s.	q.s.
Test results	Gloss degree	47	39	21

* Testing method

Measure the gloss degree of each sample above painted on test paper by Gloss Meter VG-2000.
(Gloss Meter VG-2000, Nippon Denshoku Co., Ltd.)

Dispersibility of titanium dioxide

Powder: Fine grain titanium dioxide

Solvent: Cyclopentasiloxane (KF-995)


Dispersing agent: KP-545

Test method: Mix KF-995 with KP-545, add 2 g of titanium dioxide, then put in a 30 ml sedimentary tube, disperse by ultrasound, observe without disturbing.

Test results

The resin portion of KP-545*	Sedimentary capacity (ml)	
	After 4 hours	After 68 hours
0	18.7	18.3
5	16.5	11.9
7.5	9.2	6.4
10	0	3.3
12.5	0	2.3
25	0	2.1
37.5	0	1.7
50	0	2

* 100 powder weight: KP-545 resin weight



Compatibility in cosmetic ingredients

Cosmetic Ingredients	KP-541	KP-543	KP-545	KP-561P	KP-562P
Water	I	I	I	I	I
Ethanol	S	P	S	I	I
Isopropyl Alcohol	S	S	S	I	I
Glycerin	I	P	I	I	I
C13-16 Isoparaffin	S	I	S	S	S
Liquid Isoparaffin	I	I	I	S	S
Squalane	I	I	I	S	S
Cetyl Isooctanoate	S	I	S	S	S
Triethylhexanooin	S	I	S	S	S
Jojoba Oil	I	I	I	P	P
Oleic Acid	I	I	I	S	S
KF-995	S	I	S	S	S
DM-FLUID A-6cs	S	I	S	S	S
DM-FLUID A-10cs	I	I	I	S	S
KF-54	P	I	P	I	I

S: soluble P: partially soluble I: insoluble

KP series/Cosmetic ingredients = 1/10 (weight ratio)

(at room temperature)

KSP Series

Hybrid Silicone Powders for Personal Care


The KSP series is a new generation of "hybrid" silicone powders.

The structure consists of silicone rubber coated with silicone resin.

The KSP series provides a uniquely soft, silky feel and good dispersibility with reduced agglomeration.

Hybrid silicone powders combine the features of rubber and resin powders

■ Molecular structure of KSP Series



KSP series powders consist of a spherical silicone rubber core chemically bonded to an outer shell of silicone resin. KSP-100 powders will swell in silicone fluids such as cyclomethicone and dimethicone. Therefore, KSP-300 was developed for applications where swelling is undesirable.

KSP-300 is a hybrid silicone powder functionalized with phenyl groups. The phenyl groups prevent swelling in low viscosity dimethicone fluids.

The physical properties



Product name	INCI	Appearance	Volatile Content 105°C/3h %	Heavy Metal	Arsenic	True Specific Gravity	Average Particle- Size μ	Hardness Durometer A
KSP-100	VINYL DIMETHICONE/METHICONE SILSESQUIOXANE CROSSPOLYMER	White spherical powder	0.1	< 20ppm	< 2ppm	1.00	5	30
KSP-101	VINYL DIMETHICONE/METHICONE SILSESQUIOXANE CROSSPOLYMER	White spherical powder	0.1	< 20ppm	< 2ppm	0.98	12	30
KSP-102	VINYL DIMETHICONE/METHICONE SILSESQUIOXANE CROSSPOLYMER	White spherical powder	0.1	< 20ppm	< 2ppm	0.98	30	30
KSP-105	VINYL DIMETHICONE/METHICONE SILSESQUIOXANE CROSSPOLYMER	White spherical powder	0.1	< 20ppm	< 2ppm	0.99	2	75
KSP-300	DIPHENYL DIMETHICONE/VINYL DIPHENYL DIMETHICONE/SILSESQUIOXANE CROSSPOLYMER	White spherical powder	0.1	< 20ppm	< 2ppm	1.11	5	40

* This document is not a certification of quality. For documentation of quality assurance and standards, please contact our Sales Department.



* INCI names are subject to change without notice.

Scanning electron micrographs and particle size distributions


KSP-100





KSP-101




KSP-105



KSP-300



Swelling properties of silicone powder



* Swelling weight = A - Original weight (5.0 g)

* 'A' value is the filtered cake weight (g) of powder after shaking for 3 days in silicone fluid (50 g).

SPD Series

Inorganic Powder Dispersions for Personal Care

The SPD series is a dispersion of fine TiO_2/ZnO in Volatile silicone designed for use in sunscreens as well as other skincare and make-up products.

The SPD products offer performance enhancements due to the use of high performance dispersant.

Features

- High Solids Dispersions that are Stable and have Very Low Viscosity
- Excellent Stability
- High Transparency that facilitates transparent formulations without the use of organic UV absorbers
- High SPF
- Enhanced Water Resistance
- Smooth, Non-Tacky Skin Feel

The physical properties

Product name	Composition	Appearance	Viscosity 25°C mPa·s	Specific Gravity 25°C	Powder Content wt %	Transmissivity* %
SPD-T5	CYCLOPENTASILOXANE TITANIUM DIOXIDE POLYGLYCERYL-3 POLYDIMETHYLSILOXYETHYL DIMETHICONE ALUMINUM HYDROXIDE STEARIC ACID	White- light gray	< 4,000	1.3	40	> 65
SPD-Z5	ZINC OXIDE CYCLOPENTASILOXANE POLYGLYCERYL-3 POLYDIMETHYLSILOXYETHYL DIMETHICONE TRIETHOXYSILOXYETHYL POLYDIMETHYLSILOXYETHYL HEXYL DIMETHICONE	White- light yellow	< 4,000	1.7	60	> 65

* Percent transmission at 400nm by using spectrophotometer.

* This document is not a certification of quality. For documentation of quality assurance and standards, please contact our Sales Department.

* INCI names are subject to change without notice.

SPD-T5



Composition

Fine Titanium Dioxide (coated) 40 wt %
Cyclopentasiloxane 50 wt %
Silicone Dispersant 10 wt %



Composition


Fine Zinc Oxide (coated) 60 wt %
Cyclopentasiloxane 35 wt %
Silicone Dispersant 5 wt %

SPD-Z5



* Photographs taken through a glass plate coated with SPD-T5/Z5 (Thickness ; 6 µm).

Water resistance of SPD-T5, SPD-Z5



* Test method

A sample was coated on a quartz plate with thickness of 6 µm by wire bar. Percent transmission was measured by a spectrophotometer after the plate was immersed in water for 24 hours at room temperature.

* Result

The same spectrum was got after immersed in water.

Quality, Storage and Handling

- Since changes in quality may occur due to exposure to heat, humidity, light or acidic or alkaline environments, be sure to close tightly and store in a cool, dark location.
- Do not leave products in an open state while working.
- Please read the Material Safety Data Sheet (MSDS) before use. MSDS can be obtained from our Sales Department.

Si/W Cream

1. KSG-15*1	8.0 wt %
2. KSG-16*1	30.0 wt %
3. KF-995*1	10.0 wt %
4. 1,3-Butylene Glycol	3.0 wt %
5. KF-6100*1	0.6 wt %
6. KF-6104*1	0.3 wt %
7. SIMULGEL 600*2	0.6 wt %
8. Ammonium Acryloyldimethyltauræ/ vp copolymer (5% aq)	13.0 wt %
9. Sodium Chloride (1% aq)	8.0 wt %
10. Water	26.5 wt %

A. Combine 1, 2 and 3 with stirring.
 B. Combine 4 - 9 and 10 with stirring.
 C. Add A to B with stirring.
 *1: Shin-Etsu *2: SEPPIC

W/Si Cream

1. KSG-210*1	4.0 wt %
2. KF-6017*1	0.3 wt %
3. KSG-15*1	3.0 wt %
4. DM-FLUID A-6cs*1	10.7 wt %
5. 1,3-Butylene Glycol	8.0 wt %
6. Sodium Citrate	0.2 wt %
7. Sodium Chloride	0.5 wt %
8. Ethyl Alcohol	5.0 wt %
9. Water	68.3 wt %

A. Combine 1 - 3 and 4 with stirring.
 B. Combine 5 - 8 and 9 with stirring.
 C. Add B to A with stirring.
 *1: Shin-Etsu

O/W Cream

1. KSG-43*1	25.0 wt %
2. Isotridecyl Isononanoate	20.0 wt %
3. Glycerin	5.0 wt %
4. 1,3-Butylene Glycol	7.0 wt %
5. KF-6100*1	0.7 wt %
6. PEG-60 Hydrogenated Caster Oil	0.5 wt %
7. SIMULGEL EG*2	0.8 wt %
8. Ammonium Acryloyldimethyltauræ/ vp copolymer (5% aq)	10.0 wt %
9. Sodium Chloride	0.1 wt %
10. Water	30.9 wt %

A. Combine 1 and 2 with stirring.
 B. Combine 3 - 9 and 10 with stirring.
 C. Add A to B with stirring.
 *1: Shin-Etsu *2: SEPPIC

W/O Cream

1. KSG-310*1	4.0 wt %
2. KSG-41*1	6.0 wt %
3. KF-6038*1	0.5 wt %
4. Mineral Oil	12.0 wt %
5. Neopentyl Glycol Diethylhexanoate	5.0 wt %
6. KSP-100*1	1.5 wt %
7. Glycerin	3.0 wt %
8. 1,3-Butylene Glycol	7.0 wt %
9. Sodium Citrate	0.2 wt %
10. Sodium Chloride	0.5 wt %
11. Water	60.3 wt %

A. Combine 1 - 5 and 6 with stirring.
 B. Combine 7 - 10 and 11 with stirring.
 C. Add B to A with stirring.
 *1: Shin-Etsu

W/O Liquid foundation

1. KSG-210*1	3.5 wt %
2. KSG-15*1	5.0 wt %
3. KF-6028*1	2.0 wt %
4. Quaternium-18 Hectorite	1.2 wt %
5. Triethylhexanoin	5.0 wt %
6. DM-FLUID A-6cs*1	6.5 wt %
7. KF-995*1	21.6 wt %
8. KP-575*1 (KP-545*1)	1.5 wt %
9. Pigment (Treated with KF-9909)	10.0 wt %
10. Dipropylene Glycol	5.0 wt %
11. Sodium Citrate	0.2 wt %
12. Water	38.5 wt %

A. Combine 1 - 5, a part of 6 and a part of 7 until uniformly dispersed.

B. Add 9 to the rest of 6, the rest of 7 and 8, and mix with roller.

C. Combine 10, 11 and 12 mix until dissolved

D. Add C to A with Stirring.

E. Add B to D with Stirring.

*1: Shin-Etsu

Sunscreen lotion (SPF: 50+, PA++*2)

1. KSG-210*1	3.0 wt %
2. KSG-15*1	2.0 wt %
3. DM-FLUID A-6cs*1	5.0 wt %
4. KF-995*1	5.0 wt %
5. KF-6028*1	1.0 wt %
6. Isotridecyl Isononanoate	4.0 wt %
7. SPD-T5*1	25.0 wt %
8. SPD-Z5*1	35.0 wt %
9. Dipropylene Glycol	2.0 wt %
10. Sodium Citrate	0.2 wt %
11. Sodium Chloride	1.0 wt %
12. Water	16.8 wt %

A. Combine 1 - 5 and 6 with stirring.

B. Combine 9 - 11 and 12 with stirring.

C. Add B to A. with stirring.

D. Add 7, 8 to C with stirring.

*1: Shin-Etsu

*2: By Consumer Product Testing Co.

W/O Cream foundation

1. KSG-310*1	2.0 wt %
2. KSG-41*1	2.0 wt %
3. KF-6038*1	1.0 wt %
4. Mineral Oil	2.0 wt %
5. Triethylhexanoin	5.0 wt %
6. Isotridecyl Isononanoate	9.0 wt %
7. Lecithin	0.2 wt %
8. Polysorbate 80	0.5 wt %
9. 1,3-Butylene Glycol	5.0 wt %
10. KSP-100*1	2.0 wt %
11. Pigment (Treated Pigment)	10.0 wt %
12. Sodium Citrate	0.2 wt %
13. Sodium Chloride	0.5 wt %
14. Water	60.6 wt %

A. Combine 1 - 5 and 6 until uniformly dispersed.

B. Combine 7 - 10 and 11 mix with roller.

C. Combine 12, 13 and a part of 14 mix until dissolved.

D. Add B to the rest of 14, and until uniformly dispersed.

E. Add C to A with Stirring.

F. Add D to E with Stirring.

*1: Shin-Etsu

Lip Stick

1. Candelilla Wax	4.0 wt %
2. Polyethylene	2.0 wt %
3. Microcrystalline Wax	3.0 wt %
4. Ceresin	7.0 wt %
5. KP-561P*1	15.0 wt %
6. KF-6105*1	3.0 wt %
7. Macadamia Ternifolia Nut Oil	28.0 wt %
8. Diisostearyl Malate	10.0 wt %
9. Hydrogenated Polyisobutene	10.0 wt %
10. Isotridecyl Isononanoate	18.0 wt %
11. Pigment Base*2	q.s
12. Mica	q.s

A. Combine 1 - 9 and 10 with stirring (90°C).

B. Add 11, 12 to A with stirring.

*1: Shin-Etsu

*2: Polyglyceryl-2 Triisostearate 60 % Base

Silicone Division Sales and Marketing Department I

6-1, Ohtemachi 2-chome, Chiyoda-ku, Tokyo, Japan

Phone : +81-(0)3-3246-5132 Fax : +81-(0)3-3246-5361

Shin-Etsu Silicones of America, Inc.

1150 Damar Drive, Akron, OH 44305, U.S.A.

Phone : +1-330-630-9860 Fax : +1-330-630-9855

Shin-Etsu Silicones Europe B. V.

Bolderweg 32, 1332 AV, Almere, The Netherlands

Phone : +31-(0)36-5493170 Fax : +31-(0)36-5326459

Shin-Etsu Silicone Taiwan Co., Ltd.

Hung Kuo Bldg. 11F-D, No. 167, Tun Hua N. Rd.,

Taipei, 10549 Taiwan, R.O.C.

Phone : +886-(0)2-2715-0055 Fax : +886-(0)2-2715-0066

Shin-Etsu Silicone Korea Co., Ltd.

Danam Bldg., 9F, 120, Namdaemunno5(o)-ga,

Jung-gu, Seoul 100-704, Korea

Phone : +82-(0)2-775-9691 Fax : +82-(0)2-775-9690

Shin-Etsu Singapore Pte. Ltd.

4 Shenton Way, #10-03/06, SGX Centre II, Singapore 068807

Phone : +65-6743-7277 Fax : +65-6743-7477

Shin-Etsu Silicones (Thailand) Ltd.

7th Floor, Harindhorn Tower, 54 North Sathorn Road,

Bangkok 10500, Thailand

Phone : +66-(0)2-632-2941 Fax : +66-(0)2-632-2945

Shin-Etsu Silicone International Trading (Shanghai) Co., Ltd.

29F Junyao International Plaza, No.789,

Zhao Jia Bang Road, Shanghai

Phone : +86-(0)21-6443-5550 Fax : +86-(0)21-6443-5868

- The data and information presented in this catalog may not be relied upon to represent standard values. Shin-Etsu reserves the right to change such data and information, in whole or in part, in this catalog, including product performance standards and specifications without notice.
- Users are solely responsible for making preliminary tests to determine the suitability of products for their intended use. Statements concerning possible or suggested uses made herein may not be relied upon, or be construed, as a guaranty of no patent infringement.
- The silicone products described herein have been designed, manufactured and developed solely for general industrial use only; such silicone products are not designed for, intended for use as, or suitable for, medical, surgical or other particular purposes. Users have the sole responsibility and obligation to determine the suitability of the silicone products described herein for any application, to make preliminary tests, and to confirm the safety of such products for their use.
- Users must never use the silicone products described herein for the purpose of implantation into the human body and/or injection into humans.
- Users are solely responsible for exporting or importing the silicone products described herein, and complying with all applicable laws, regulations, and rules relating to the use of such products. Shin-Etsu recommends checking each pertinent country's laws, regulations, and rules in advance, when exporting or importing, and before using, the products.
- Please contact Shin-Etsu before reproducing any part of this catalog.
Copyright belongs to Shin-Etsu Chemical Co., Ltd.



The Development and Manufacture of Shin-Etsu Silicones are based on the following registered international quality and environmental management standards.

Gunma Complex ISO 9001 ISO 14001
(JCQA-0004 JCQA-E-0002)

Naoetsu Plant ISO 9001 ISO 14001
(JCQA-0018 JCQA-E-0064)

Takefu Plant ISO 9001 ISO 14001
(JQA-0479 JQA-EM0298)

<http://www.silicone.jp/>