

# Gas Torches



## Quality

High-grade quality materials and state-of-the-art design backed by the STEINEL quality guarantee.

## Value

Heavy-duty professional tools at an attractive price point.

## Versatility

Completely portable, multi-function tools for a wide variety of applications.

## Performance

Power and durability that gets the job done in industrial applications.



## Applications

- Automotive and truck repairs
- Solder/desolder circuit boards
- TV, meter and switchboard repairs
- Activate potting compounds and soften caulk
- Industrial cable repairs and installation
- Loosen rusted nuts and bolts
- Aviation service and repairs
- Environmental splicing
- Shrink tubing
- Jewelry, eye glasses and dental work

Precision Hot Air Tools

Professional Heat Blowers

Industrial Heat Guns

Professional Heat Guns

Gas Torches

Adhesive Systems

## Gas Torches



- Shrink tubing
- Installing connectors
- Desoldering
- Soldering
- Cutting, cauterizing
- Welding
- Light brazing
- Loosening rusted bolts
- Thawing frozen locks
- Electronic repair

### The Ultimate Butane Kit

The Ultimate Butane Kit includes tools and accessories needed for a variety of applications. ThermaSolder™ butane powered soldering irons are cordless. Multi-functional tools may be used as soldering irons, convenient portable torches and flameless heat blowers. The tools heat up in 20 seconds or less and are safe and simple to use under most any condition.



## Applications




Shrink Tube Wires



Aircraft Maintenance



Desolder / Solder Circuit Boards



Loosen Rusted Bolt



Solder to shrink in minutes with just one tool using a variety of nozzles.

## The Ultimate Butane Kit



### The Ultimate Butane Kit

|                  |                                                                                                                                                                                                         |
|------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Item No.         | 77000                                                                                                                                                                                                   |
| Accessories      | 70001 BT 01 - 1 oz butane                                                                                                                                                                               |
| Temperature      | TS 550 480°F - 1000°F (250°C - 550°C) soldering tip<br>2400°F (1316°C) torch<br>1400°F (750°C) flameless heat<br>TH 310 Catalytic Tip 1400°F (750°C)<br>TT 175 2400°F (1316°C)<br>TT 30 2400°F (1316°C) |
| Operation Time   | TS 550 160 min<br>TT 175 120 min<br>TT 30 30 min                                                                                                                                                        |
| Fuel Capacity    | TS 550 25 ml<br>TT 175 60 ml refillable fuel tank<br>TT 30 5 ml refillable see-through fuel tank                                                                                                        |
| Fuel Type        | Standard butane fuel                                                                                                                                                                                    |
| Dimensions       | 12.60" x 4.20" x 12.30" (l x w x h)                                                                                                                                                                     |
| Net Weight       | 4.80 lbs (76.80 oz)                                                                                                                                                                                     |
| Single Sell Pack | Dimensions: 12.60" x 4.20" x 12.30"<br>Weight: 4.80 lbs (76.80 oz)                                                                                                                                      |
| Warranty         | One year limited                                                                                                                                                                                        |



## Kit Tools & Accessories

- TT 175 Torch
- TT 30 Mini Torch
- TS 550 Soldering Iron
- TS 21 Conical Tip (installed)
- 2 - 1oz Butane Canisters
- TH 310 Flameless Catalytic Tip
- TS 20 Deflector
- TS 25 Hot Knife
- TS 23 Chisel
- TS 27 Heat Blower
- TS 29 Spare Orifice
- Hands-Free Stand
- Tip Cleaning Sponge
- Solder Dispenser
- Shrink Tube Assortment
- Silver Case



Cut Foam



Heat Chemicals



Ignite Charcoal



Thaw Locks



Caramelise Creme Brulee

Precision Hot Air Tools

Professional Heat Blowers

Industrial Heat Guns

Professional Heat Guns

Gas Torches

Adhesive Systems

# TT 270, TT 175 & TT 151

## Gas Torches



TT 270

TT 175

TT 151

- Quality
- Performance
- Durable

ThermaTorch™ 270 high output butane torch provides the most powerful and stable butane flame available for demanding jobs.

ThermaTorch™ 175 has adjustable airflow and flame control. It incorporates a high capacity 60ml refillable fuel tank for up to 220 minutes of continuous use.

ThermaTorch™ 151 general purpose butane torch provides adjustable flame. features a compact size, ergonomic grip and stable base.



### TT 270 / TT 175 / TT 151

|                  |                                                                                                                                                                                                        |
|------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Item No.         | TT 270 71270<br>TT 175 71175<br>TT 151 71151                                                                                                                                                           |
| Temperature      | TT 270 2500°F (1300°C)<br>TT 175 / TT 151 2400°F (1316°C)                                                                                                                                              |
| Fuel Capacity    | TT 270 / TT 175 60 ml refillable fuel tank<br>TT 151 20 ml refillable fuel tank                                                                                                                        |
| Operating Time   | TT 270 Up to 120 min (90 min at mid setting)<br>TT 175 120 min continuous use<br>TT 151 60 min at mid setting                                                                                          |
| Fuel Type        | Standard butane fuel                                                                                                                                                                                   |
| Ignition         | Water proof piezo electronic system                                                                                                                                                                    |
| Safety           | TT 151 Child resistant, compliant with CPSC                                                                                                                                                            |
| Nozzle Diameter  | TT 270 0.87" (22.1 mm)<br>TT 175 0.78" (19.8 mm)<br>TT 151 0.79" (20.0 mm)                                                                                                                             |
| Dimensions       | TT 270 6.25" x 4.70" x 2.50" (l x w x h)<br>TT 175 5.25" x 4.00" x 1.50"<br>TT 151 5.50" x 4.00" x 2.50"                                                                                               |
| Net Weight       | TT 270 0.64 lb (10.24 oz)<br>TT 175 0.59 lb (9.44 oz)<br>TT 151 0.31 lb (4.96 oz)                                                                                                                      |
| Single Sell Pack | Dimensions: TT 270 9.50" x 5.60" x 3.00"<br>TT 175 7.40" x 5.50" x 1.75"<br>TT 151 8.00" x 4.88" x 2.63"<br>Weight: TT 270 0.87 lb (13.92 oz)<br>TT 175 0.78 lb (12.48 oz)<br>TT 151 0.50 lb (8.00 oz) |
| Warranty         | One year limited                                                                                                                                                                                       |

## Applications



Carmelize Creme Brulee



Plumbing



Braze



Prosthetics



Solder and Desolder

Gas Torches



TT 30

|                  |                                                                |
|------------------|----------------------------------------------------------------|
| Item No.         | 71030                                                          |
| Accessories      | 70001 BT 01 - 1 oz Butane<br>70005 BT 05 - 5 oz Butane         |
| Feature          | Windproof and waterproof                                       |
| Temperature      | 2400°F (1316°C)                                                |
| Operation Time   | 30 min                                                         |
| Fuel Capacity    | 5 ml refillable see-through fuel tank                          |
| Fuel Type        | Standard butane fuel                                           |
| Nozzle Diameter  | 0.66" (16.75 mm)                                               |
| Dimensions       | 0.88" x 0.63" x 1.50" (l x w x h)                              |
| Net Weight       | 0.11 lb (1.76 oz)                                              |
| Single Sell Pack | Dimensions: 6.00" x 4.00" x 1.63"<br>Weight: 0.15 lb (2.40 oz) |
| Warranty         | One year limited                                               |

- Windproof
- Compact, lightweight construction
- Exceptional value

ThermaTorch™ 30 windproof lighter with waterproof automatic ignition system features simple twist flame adjustment and protective auto-flip cap.



Triple Filtered Butane  
BT 01 - 1 oz (28.4 gm) No. 70001  
BT 05 - 5 oz (142 gm) No. 70005



Fireworks



Light Cigars



Thaw Locks



Camping



Start Camp Fires

Precision Hot Air Tools  
Professional Heat Blowers  
Industrial Heat Guns  
Professional Heat Guns  
Gas Torches  
Adhesive Systems

# TS 600 & TS 600 K

## Gas Torches



TS 600 / TS 600 K

|                     |                                                                                                                                                                                     |
|---------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Item No.            | TS 600 72600<br>TS 600 K 72601                                                                                                                                                      |
| Accessories         | Soldering Tip and Protective Cap                                                                                                                                                    |
| Soldering Iron Tip  | 480°F - 1000°F (250°C - 550°C)                                                                                                                                                      |
| Torch               | 2400°F (1316°C)                                                                                                                                                                     |
| Flameless Heat      | 1400°F (750°C) with available hot air blower tip                                                                                                                                    |
| Electric Equivalent | 30 - 125 watts                                                                                                                                                                      |
| Fuel Capacity       | 38 ml (200 min)                                                                                                                                                                     |
| Fuel Type           | Standard Butane Fuel                                                                                                                                                                |
| Ignition            | Piezo Electronic System with 15 sec. heat-up                                                                                                                                        |
| Kit Contents        | TS 600 Soldering Iron, Heat Blower Tip, Reflector Tip, Hot Knife Tip, Chisel Tip, Soldering Tip, Spare Orifice, Solder with Dispenser, Tip Cleaning Sponge, Protective Cap and Case |
| Tip Dimensions      | 0.06" (1.52 mm)                                                                                                                                                                     |
| Dimensions          | TS 600 9.75" x 1.20" x 1.25" (l x w x h)<br>TS 600 K 12.00" x 6.60" x 2.00"                                                                                                         |
| Net Weight          | TS 600 0.34 lb (5.44 oz)<br>TS 600 K 1.47 lbs (23.52 oz)                                                                                                                            |
| Single Sell Pack    | Dimensions: TS 600 12.00" x 4.00" x 1.25"<br>TS 600 K 12.00" x 6.60" x 2.00"<br>Weight: TS 600 0.50 lbs (8.00 oz)<br>TS 600 K 1.47 lbs (23.52 oz)                                   |
| Warranty            | One year limited                                                                                                                                                                    |

### ThermaSolder™ 600 K Contents:

- TS 600 Soldering Iron
- Heat Blower Tip
- Reflector Tip
- Hot Knife Tip
- Chisel Tip
- Soldering Tip
- Spare Orifice
- Solder with Dispenser
- Tip Cleaning Sponge
- Protective Cap
- Case

High capacity soldering iron offers auto ignition, powerful 30W - 125W output, and a refillable 38 ml tank for 200 minutes of continuous use.



Metal glasses can be soldered to form a more solid joint.

### Applications



Solder Circuit Board



Solder Sleeves



Wood Repair



Water Heater Installation

# TS 550 & TS 550 K


## Gas Torches



### ThermaSolder™ 550 K Contents:

- TS 550 Soldering Iron
- Heat Blower Tip
- Reflector Tip
- Hot Knife Tip
- Chisel Tip
- Soldering Tip
- Spare Orifice
- Solder with Dispenser
- Tip Cleaning Sponge
- Protective Cap
- Case

Butane soldering iron provides auto ignition, 30W - 125W power range and refillable 25ml tank for 160 minutes of continuous use.



### TS 550 / TS 550 K

|                     |                                                                                                                                                                                     |
|---------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Item No.            | <b>TS 550 72550</b><br><b>TS 550 K 72551</b>                                                                                                                                        |
| Accessories         | Soldering Tip and Protective Cap                                                                                                                                                    |
| Soldering Iron Tip  | 480°F - 1000°F (250°C - 550°C)                                                                                                                                                      |
| Torch               | 2400°F (1316°C)                                                                                                                                                                     |
| Flameless Heat      | 1400°F (750°C) with available hot air blower tip                                                                                                                                    |
| Electric Equivalent | 30 - 125 watts                                                                                                                                                                      |
| Fuel Capacity       | 25 ml (160 min)                                                                                                                                                                     |
| Fuel Type           | Standard Butane Fuel                                                                                                                                                                |
| Ignition            | Piezo Electronic System with 15 sec. heat-up                                                                                                                                        |
| Kit Contents        | TS 550 Soldering Iron, Heat Blower Tip, Reflector Tip, Hot Knife Tip, Chisel Tip, Soldering Tip, Spare Orifice, Solder with Dispenser, Tip Cleaning Sponge, Protective Cap and Case |
| Tip Dimensions      | 0.06" (1.52 mm)                                                                                                                                                                     |
| Dimensions          | TS 550 9.00" x 1.20" x 1.22" (l x w x h)<br>TS 550 K 13.50" x 5.70" x 2.10"                                                                                                         |
| Net Weight          | TS 550 0.20 lb (3.20 oz)<br>TS 550 K 1.41 lbs (22.56 oz)                                                                                                                            |
| Single Sell Pack    | Dimensions: TS 550 12.00" x 4.00" x 1.35"<br>TS 550 K 13.50" x 5.70" x 2.10"<br>Weight: TS 550 0.35 lb (5.60 oz)<br>TS 550 K 1.41 lbs (22.56 oz)                                    |
| Warranty            | One year limited                                                                                                                                                                    |

Precision Hot Air Tools

Professional Heat Blowers

Industrial Heat Guns

Professional Heat Guns

Gas Torches

Adhesive Systems



Cut Foam



Jewelry Repair



Light Maintenance



Handy Man



Electrical Work

# TS 500 & TS 500 K

## Gas Torches



### TS 500 / TS 500 K

|                     |                                                                                                                                                   |
|---------------------|---------------------------------------------------------------------------------------------------------------------------------------------------|
| Item No.            | <b>TS 500 72500</b><br><b>TS 500 K 72501</b>                                                                                                      |
| Accessories         | Soldering Tip and Protective Cap                                                                                                                  |
| Soldering Iron Tip  | 410°F - 850°F (210°C - 450°C)                                                                                                                     |
| Torch               | 2400°F (1316°C)                                                                                                                                   |
| Flameless Heat      | 1400°F (750°C) with available hot air blower tip                                                                                                  |
| Electric Equivalent | 25 - 80 watts                                                                                                                                     |
| Fuel Capacity       | 20 ml (120 min)                                                                                                                                   |
| Fuel Type           | Standard butane fuel                                                                                                                              |
| Ignition            | Manual ignition                                                                                                                                   |
| Kit Contents        | TS 500 Soldering Iron, Soldering Tip, Reflector Tip, Hot Knife Tip, Heat Blower Tip, Blow Torch Tip, Tip Cleaning Sponge, Protective Cap and Case |
| Nozzle Diameter     | 0.06" (1.50 mm)                                                                                                                                   |
| Dimensions          | TS 500 8.50" x 1.00" x 1.00"<br>TS 500 K 10.75" x 10.40" x 1.90"                                                                                  |
| Net Weight          | TS 500 0.14 lb (2.24 oz)<br>TS 500 K 0.87 lb (13.92 oz)                                                                                           |
| Single Sell Pack    | Dimensions: TS 500 10.00" x 4.00" x 1.10"<br>TS 500 K 10.75" x 10.40" x 1.90"<br>Weight: TS 500 0.23 lb (3.68 oz)<br>TS 500 K 0.87 lb (13.92 oz)  |
| Warranty            | One year limited                                                                                                                                  |

### ThermoSolder™ 500 K Contents:

- TS 500 Soldering Iron
- Heat Blower Tip
- Reflector Tip
- Hot Knife Tip
- Soldering Tip
- Solder with Dispenser
- Tip Cleaning Sponge
- Protective Cap
- Case

Butane soldering iron provides 25W - 80W power range. It is cordless and ready to use in 20 seconds and contains a refillable 20ml tank for 120 minutes of continuous use.



Solder/desolder circuit boards with STEINEL's portable precise soldering iron

## Applications




Plastic Molding



Cut Foam



Desolder



Install Connectors

## Gas Torches



**TH 310**

|                  |                                                                 |
|------------------|-----------------------------------------------------------------|
| Item No.         | 73310                                                           |
| Included Nozzle  | Deflector                                                       |
| Flameless Heat   | 1400°F (750°C)                                                  |
| Fuel Capacity    | 38 ml                                                           |
| Fuel Type        | Standard Butane Fuel                                            |
| Operating Time   | Up to 120 min continuous use                                    |
| Ignition         | Piezo Electronic System with 15 sec. heat-up                    |
| Nozzle Diameter  | 0.78" (19.9 mm)                                                 |
| Dimensions       | 8.75" x 1.20" x 1.25" (l x w x h)                               |
| Net Weight       | 0.23 lb (3.68 oz)                                               |
| Single Sell Pack | Dimensions: 12.00" x 4.00" x 1.50"<br>Weight: 0.30 lb (4.80 oz) |
| Warranty         | One year limited                                                |

- High-grade quality materials
- Professional tools at an attractive price point
- Completely portable

The ThermoHeat™ 310 is a high output flameless heat tool that offers rapid heat-up for immediate use. The tool is completely cordless and features adjustable heat output up to 1400°F (750°C) and a removable deflector for shrink tube installation.



Repair, bend and mold prosthetics with portable STEINEL ThermoHeat™



Electrical Work



Cable Installation



Automotive Repair



Shrink Tubes



Dental Work

Precision Hot Air Tools

Professional Heat Blowers

Industrial Heat Guns

Professional Heat Guns

Gas Torches

Adhesive Systems

# Hot-Melt Adhesive Systems



## Keeping it Together with Hot-Melt Adhesives

Cord-free operation and virtually unlimited flow of adhesive when and where you want it makes the HiPURformer™ a truly a convenient and efficient tool. Elimination of clamping, bracing and nailing saves time and avoids touch-ups. Heavy-duty housing and mechanical parts are designed to withstand the demands of professional use.



## Applications

- Installing crown and base molding
- Cabinet and counter top repair
- Pottery, stonework and ceramic repair
- Household projects
- Anchoring floor boards and paneling
- Crafts and modeling
- Securing fasteners and cables
- Packaging

Precision Hot Air Tools

Professional Heat Blowers

Industrial Heat Guns

Professional Heat Guns

Gas Torches

Adhesive Systems

# HiPURformer™

## Hot-Melt Adhesive Systems



- FLX-Valve Technology™ permits easy, controlled extrusion and protection for the adhesive from air and moisture. This ensures initial and repeat use while preventing adhesive drool.
- Durable components provide reliability and long life even under the most rigorous conditions
- Specially designed trigger handle provides refined adhesive control
- 20 minutes of cord-free operation makes it easy to take directly to the project regardless of location
- Indicator lights on the base indicate when the applicator is ready for use
- Quick 10-12 minute heat up

### HiPURformer Applicator

The HiPURformer™ Advanced Bonding System is the perfect solution for virtually all your bonding needs. It combines the highest quality Polyurethane Reactive (PUR) Hot-Melt adhesives with the most easy to use, cost-effective PUR application system.

All HiPURformer™ adhesives provide strong permanent waterproof bonds, for both interior and exterior use. Quick set times reduce the need for clamping or bracing, and in many applications can eliminate the use of nails or staples. This saves time and money spent on filling, sanding and staining repair marks.

Extremely convenient and easy to use, the HiPURformer applicator provides up to 20 minutes of cord-free gluing after a quick 10-12 minute heat up. The charging station includes a green diode to indicate when “ready”.

HiPURformer adhesives are available in handy 50 gm “no-drip” cartridges.

## Features



Insert Cartridge



Push Heating Head Onto  
Handle



Heat Up Adhesive



Remove Cap



Store Cap in Handle



Indicator Light Indicates  
Ready for Use



#### HiPURformer Kit

- One HiPURformer™ Adhesive Applicator with Base Charger
  - One Cartridge WW30
  - One Cartridge WW60
  - One Cartridge MP75
  - Waterproof Carry Case
- No. 31134



#### HiPURformer™

|                              |                                                                   |
|------------------------------|-------------------------------------------------------------------|
| Item No.                     | 31331                                                             |
| Accessories                  | 50 g cartridge                                                    |
| Glue                         | Available in 50gm "no-drip" cartridges                            |
| Glue Application Temperature | 212°F - 284°F (100°C - 140°C)                                     |
| Open Time                    | 60 sec +/- 15 sec                                                 |
| Warm Up Time                 | Quick 10 - 12 minutes                                             |
| Max. Application Time        | 15-20 min (cordless gluing)                                       |
| Final Strength               | 1 - 5 days (depending on material)                                |
| Voltage                      | 120 VAC                                                           |
| Nozzle Diameter              | 0.87" (22.20 mm)                                                  |
| Dimensions                   | 6.75" x 9.50" x 1.80" (l x w x h)                                 |
| Net Weight                   | 0.78 lb (12.48 oz)                                                |
| Single Sell Pack             | Dimensions: 12.00" x 8.00" x 2.90"<br>Weight: 1.92 lbs (30.70 oz) |
| Warranty                     | One year limited                                                  |

Precision Hot Air Tools

Professional Heat Blowers

Industrial Heat Guns

Professional Heat Guns

Gas Torches

Adhesive Systems

## Polyurethane Hot-Melt Adhesives

**Faster** - Shorter set time than "yellow" glues

**Stronger** - More permanent, less brittle bond than "super" glues

**Better** - Outperforms traditional hot-melts: won't foam like other polyurethanes



#### MP75

- Multi-purpose formula with 75 second set time
- Bonds most common materials including ceramics, metal, most plastics, marble, glass, FRP, brick, wood and more

No. 31132



#### MP300

- Multi-purpose formula with 1 minute set time
- Longest set time
- Ideal for face framing and construction
- Bonds most common materials including ceramics, metal, most plastics, marble, glass, FRP, brick, wood, and more

No. 31135



#### WW30

- Wood to wood formula with 30 second set time
- Designed for quick assembly projects to reduce clamping

No. 31130



#### WW60

- Wood to wood formula with 60 second set time
- Higher viscosity fills gaps and irregularities with no shrinkage

No. 31131

HiPURformer polyurethane reactive hot-melt adhesives are manufactured by Franklin International, the makers of Titebond® Glues and Adhesives. For additional information call (800) 347-GLUE or visit [www.titebond.com](http://www.titebond.com).

## Applications

Made in E.U.



ISO 9001:2001



Home Repair



Wood Working



Door and Glass Repair



Ceramic Soap Dish



Adhere to Brick



Kitchen Furnishings

# TM 6000

## Hot-Melt Adhesive Systems



**TM 6000**

|                  |                                                         |
|------------------|---------------------------------------------------------|
| Item No.         | <b>76000</b>                                            |
| Accessories      | Sturdy metal stand included                             |
| Melt Temperature | 320°F - 464°F (160 - 240°C)                             |
| Operating Time   | 100 min                                                 |
| Fuel Type        | Standard butane fuel                                    |
| Ignition         | Piezo Electronic System                                 |
| Nozzle Diameter  | 0.08" (2 mm)                                            |
| Dimensions       | 9.00" x 7.50" x 2.00" (l x w x h)                       |
| Net Weight       | 0.75 lb (12.00 oz)                                      |
| Single Sell Pack | Dimensions: 12.50" x 12.50" x 2.20"<br>Weight: 1.30 lbs |
| Warranty         | One year limited                                        |

- Cordless butane powered glue gun
- Rapid 3 minute heat up
- Features removable LEC™ technology fuel cells for quick refueling and safe air travel
- Instant glue flow cut off reducing dripping

Portable butane powered hot-melt glue gun allows users to work almost anywhere. The ThermaMelt™ 6000 features the power and durability to get the job done in industry applications. It runs continuously for up to 100 minutes on the easily refillable LEC™ and provides fast even adhesive flow with 1/2" diameter glue sticks.

**STEINEL offers premium quality glue that creates a strong bond on a multitude of surfaces.**



**G200C**  
Clear Glue Sticks  
No. 04080 - 1 lb  
04801 - 1 kg



**GF 14**  
Carton Glue Stick  
No. 04040 - 1 lb  
04041 - 11 lbs



**GF 23**  
Wood Glue Stick  
No. 04034 - 1 lb  
04035 - 11 lbs



**GF 213**  
Laminate Glue Stick  
No. 04037 - 1 lb  
04038 - 11 lbs



**GF 232**  
General Purpose Glue Stick  
No. 04031 - 1 lb  
04032 - 11 lbs




**GF 260**  
High Strength Glue Stick  
No. 04043 - 1 lb  
04044 - 11 lbs

### Features



Instant Glue Flow Cut-Off



Sturdy Metal Stand



LEC™ Fuel Cell



Ignition Button

## Hot-Melt Adhesive Systems



Double Insulated



### GF 3002

|                  |                                                                   |
|------------------|-------------------------------------------------------------------|
| Item No.         | 33241                                                             |
| Accessories      | Sturdy metal stand included                                       |
| Glue             | Accepts 1/2" & 7/16" dia. glue sticks within temp range.          |
| Operating Temp.  | 400°F (204°C)                                                     |
| Melting Capacity | High 7.5 gm / minute                                              |
| Warm Up Time     | Quick 7 minutes                                                   |
| Nozzle Diameter  | 0.08" (2 mm)                                                      |
| Dimensions       | 8.00" x 7.00" x 1.85" (l x w x h)                                 |
| Net Weight       | 0.71 lb (11.36 oz)                                                |
| Single Sell Pack | Dimensions: 10.25" x 6.75" x 1.75"<br>Weight: 1.10 lbs (17.60 oz) |
| Warranty         | One year limited                                                  |

Precision Hot Air Tools

Professional Heat Blowers

### Application Glue Guide

- Easy to use, mechanical glue stick feeding system for consistent flow
- Die cast aluminum heating chamber retains heat for increased volume
- No-drip nozzle won't ooze hot glue
- Lightweight 11.4 oz construction for comfortable long term use

STEINEL's GlueFix™ 3002 represents the state-of-the-art in hot-melt adhesive application. The exclusive PTC (positive temperature control) electronic heating system ensures the ideal bonding temperature for extended periods of time, providing precise, continuous glue output. Industrial users and trades professionals alike count on STEINEL glue guns for consistent high performance and reliability.

| Name               | Open Time | ABS     | PP / PC / HDPE / LDPE | Polystyrene    | PVC | Glass Reinforced Plastic | Aluminum / Stainless S. | EPS Foam | Wood | Sand Mold | Glass | Cardboard |
|--------------------|-----------|---------|-----------------------|----------------|-----|--------------------------|-------------------------|----------|------|-----------|-------|-----------|
| GF 232 General     | Medium    | •       | •                     | •••            | •   | •                        | •                       | ••••     | •    | ••••      | •     | ••••      |
| GF 14 Carton       | Fast      | •       | •                     | •              | •   | •                        | •                       | •••      | •    | ••••      | •     | ••••      |
| GF 23 Wood         | Long      | •       | •                     | •••            | •   | •                        | •                       | ••••     | •••• | ••••      | •     | ••••      |
| GF 213 Laminate    | Long      | •       | •                     | •••            | •   | •                        | •                       | •••      | •    | •••       | •     | •••       |
| GF 260 Hi Strength | Long      | •••     | •                     | •••            | •   | •••                      | •••                     | •        | •••• | •         | •••   | •••       |
| Key                | • Poor    | •• Fair | ••• Good              | •••• Very Good |     |                          |                         |          |      |           |       |           |

Industrial Heat Guns

Professional Heat Guns



**2 mm Nozzle**  
1.30" x 0.81" x 0.81"  
No. 01247



**2.8 mm Fine Tip Nozzle**  
1.90" x 0.81" x 0.81"  
No. 01245



**1 mm Nozzle**  
1.90" x 0.81" x 1.81"  
No. 01243



**12 mm Spreader Nozzle**  
1.40" x 0.75" x 0.50"  
No. 01241

Gas Torches

### Applications

Made in E.U.



ISO 9001:2001



Construction



Packaging



Pipe Insulation



Hobbies



Circuit Board Sealing



Paintless Dent Removal

Adhesive Systems



STEINEL  
9051 Lyndale Avenue South  
Bloomington, MN 55420

Support: (800) 852-4343  
Office: (952) 888-5950  
Fax: (952) 888-5132

[sales@steinel.net](mailto:sales@steinel.net)  
[www.steinel.net](http://www.steinel.net)