



STENTOFON BI-WAY

TALK THROUGH GLASS



TALK THROUGH GLASS

- COMPACT AND EASY TO INSTALL, ONE PERSON INSTALLATION
- NO HOLES REQUIRED IN THE SECURITY GLASS
- FIELD OF VISION NOT OBSTRUCTED
- WIDE FREQUENCY RANGE FOR OPTIMAL SOUND QUALITY
- DESIGN SUITS ALL DECORS

The Bi-Way system solves the communication problem between people on both sides of security glass partitions.

The built-in duplex controller switches the speech direction to permit natural two-way conversation in varying noise levels, on either side of the counter, without push buttons.

The system provides a safe, hygienic, efficient and comfortable working environment for counter personnel.

Bi-Way makes normal conversation and personal service possible, while maintaining security.

Bi-Way two-way conversation is suitable for communicating with callers, visitors or customers, and prevents employees being put at risk.

The system is renowned for its excellent sound quality.

3007250003

BI-WAY STARTER KIT

- This kit consists of an 3007250002 Operator's unit, the 3007250006 External microphone, the 3007250007 Loudspeaker kit and the 3007250014 Power supply
- The Operator's unit includes a microphone select button for switching to an optional microphone, stand-by button to set the system in reduced volume listening mode, push-to-talk button and an ON/OFF button



3007250002

BI-WAY OPERATORS UNIT

- This unit contains all the electronics for one counter position including microphone and loudspeaker
- The unit is designed for desk or flush mounting



Size (WxHxD): 93 x 224 x 65 mm Wt: 0.3 kg

Accessories: LBB 3007250012 Flush Mount Frame to Operator's Unit

3007250007

BI-WAY LOUDSPEAKER KIT

- 2 loudspeaker cabinets with self-adhesive tape and 10 m flexible loudspeaker cable
- Includes alco-pad for screen cleaning



Size (WxHxD): 105 x 106 x 72 mm Wt: 0.2 kg

Accessories: 3007250002 Bi-Way Operator's Unit

3007250005

BI-WAY EXTERNAL MICROPHONE

- Unidirectional and noise cancelling microphone for connection to the operator's unit to improve flexibility



Wt: 0.1 kg

Accessories: 3007250002 Bi-Way Operator's Unit

3007250004

BI-WAY GOOSENECK MICROPHONE

- Optional directional microphone for extreme noise conditions
- Frequency range: 100 - 10,000 Hz, impedance 1,000 Ohms



Size (LxD): 320 x 12 mm Wt: 0.1 kg

Accessories: 3007250002 Bi-Way Operator's Unit

3007250010

BI-WAY HEADSET

- Headset with microphone for connecting to the Bi-Way Operator's Unit
- Supplied headset may have a slight different design



Wt: 0.1 kg

Accessories: 3007250002 Bi-Way Operator's Unit

3007250008

BI-WAY FLUSH-MOUNT LOUDSPEAKER KIT

- Optional 6W loudspeakers for flush-mount applications in desk or wall
- Impedance: 20 Ohms



Size (Diam x D): 160 x 58 mm Wt: 0.7 kg

Accessories: 3007250002 Bi-Way Operator's Unit

3007250009

BI-WAY HEARING AID KIT

- Hearing aid loop antenna and amplifier
- To be used with 230 V/12 V AC, 8W power supply



Wt: 0.5 kg

Accessories: 3007250015 PSU, Hearing Aid Unit 12V AV Euro Connector, 3007250016 PSU

3007250014

POWER SUPPLY 12V/8W

- 230V AC, +6/-10%
- 50/60 Hz
- Double insulated and thermal fused



Size (WxHxD): 100 x 51 x 63 mm Wt: 0.5 kg

Accessories: 3007250002 Bi-Way Operator's Unit

3007320011

HANDSET WITH CRADLE

- Optional handset for wall mounting in difficult noisy conditions or for situations where confidentiality is required



Wt: 0.4 kg

Accessories: 3007250002 Bi-Way Operator's Unit

3007250012

FLUSH MOUNT FRAME TO OPERATORS UNIT

- Flush-mount frame for Operator's Unit
- Desk or wall mounting



Size (WxHxD): 130 x 265 x 18 mm

Accessories: 3007250002 Bi-Way Operator's Unit

3007250011

FLUSH-MOUNT BACK BOX - 60MM

- For flush mounting of the Bi-Way Operator's Unit, station cord and termination included
- The Bi-Way Operator's Unit needs a flush mount frame



Size (WxHxD): 120 x 254 x 60 mm

Accessories: 3007250002 Bi-Way Operator's Unit, 3007250012 Flush Mount Frame to Operator's Unit

3007250015

PSU, HEARING AID UNIT 12V AC EURO CONNECTOR

- 230 V/12 V AC
- 8W power supply with Euro-connector



Size (WxHxD): 100 x 51 x 63 mm Wt: 0.5 kg

Accessories: 3007250009 Bi-Way Hearing Aid Kit

3007250013

CRADLE BRACKET

- For table-top use of the Bi-Way operator's unit



Wt: 0.3 kg

Accessories: LBB 7026/60 Bi-Way Operator's Unit, 3007250012 Flush Mount Frame to Operator's Unit

3007250015

PSU, HEARING AID UNIT 12V AC UK CONNECTOR

- 240 V/12 V AC 8W power supply with UK connector
- Available until stock is depleted



Size (WxHxD): 100 x 51 x 63 mm Wt: 0.5 kg

Accessories: 3007250009 Bi-Way Hearing Aid Kit

